Ellis Playbook

How to run Ellis today: which command answers which question, what to give it, how to read what comes back, and what to do next. Everything here works now; the agent stages still planned are named at the end.

As of 10 Nov 2026 **For** K.D. and whoever operates Ellis **Prepared by** Quincy Nkwain Ninying, Forward Deployed Engineer

Repository `github.com/qninying/platform-reliability-agent`

41	16	3	4	0
commands that answer a reliability question	sandbox rehearsals, one per rung built	kinds of input: a platform checkout, a dated export, a sandbox fixture	verdicts, each with its own next step	commands that can write to the platform

BEFORE YOU RUN ANYTHING

Set up once, then give each command the input it reads

```
git clone https://github.com/qninying/platform-reliability-agent
cd platform-reliability-agent
npm ci          # Node 23.6 or later; no runtime dependencies
npm test        # 913 tests; every one should pass before you trust an answer
```

A platform checkout

`--source <folder>`

A read-only clone of the platform repository. Ellis reads its code and never changes it. Note the commit you cloned at: answers name it.

A dated export

`--snapshot <file.json>`

Records a person with admin access pulls from the platform's admin endpoints, stamped with when and by whom. Ellis has no production access; an answer is about that export, at that time.

A sandbox fixture

`--fixture`, `--sandbox`

For rehearsals only. Point `--sandbox` at an empty folder; nothing outside it is written. The rungs started by a person also need `--operator <name>`.

Each command prints what it needs at the top of its file in `src/cli/`, and refuses with exit 1 and the missing piece if you leave one out. Run any of them as `npm run <command> -- <arguments>`.

WHICH COMMAND ANSWERS WHICH QUESTION

Start from the question, not the tool

Each command is one capability's check. Its document in `docs/capabilities/` says what it reads, what it cannot see, and its exit codes.

WHEN THE QUESTION IS	RUN
Is anything broken right now?	`cron-health` `agent-health` `orchestration-health` `scheduler-liveness` `dead-letters` `stale-actions`
What ran, when, and did it fail?	`cron-runs` `incident-trace` `error-class-coverage` `dead-letter-triage` `replay-harness`
Is the registry telling the truth?	`registry-reconcile` `registry-ask` `timer-inventory` `default-on-timers` `schedule-governance` `overlap-guard`
Who can do what, and is it safe?	`security-posture` `access-watch` `behavior-watch` `security-rollup` `manager-access` `autonomy-authority`
Can we recover, and is the data kept as promised?	`backup-position` `schema-drift` `retention-sweep` `preview-reaping` `resilience-posture`
Is this change ready, and what should be done about an agent?	`deploy-readiness` `release-evidence` `promotion-evidence` `bug-baseline` `disable-recommendation` `ticket-resolution` `orchestration-repair`
What does K.D. need to see or decide?	`reliability-report` `reliability-thresholds` `evolution-proposals` `technology-direction` `prompt-performance` `shadow-evaluation`

The briefing, `reliability-report`, composes several of these into one text a person can read with no login, the unmeasured section first.

READING AN ANSWER

Two layers: the command's own answer, and one shared envelope

On the command line, each command prints its own answer in its own words (`healthy`, `alerting`, `traced` and so on): a statement, the records it read, and what it cannot say. Every check also has an adapter to one shared envelope in `src/output/`, the shape the broker will call. Its fields:

FIELD	WHAT IT TELLS YOU
`verdict`	**ok**, **problem**, **partly_unknown** or **unknown**. Read it first; the next section says what to do with each.
`evidence`	The row ids the verdict rests on. A problem or an ok with none cannot leave the command.
`blind_spots`	What the command could not see. Read these before you trust an ok.
`severity, severity_rule`	Set only from K.D.'s table. Until it has rules, every severity is unassigned, and the rule field says why.
`platform_signal`	A severity or alert the platform itself raised, shown as evidence, never used as Ellis's severity.
`as_of`	When the input was captured and by whom, or the sandbox fixture's name, marked "not production".

Exit codes: **0** means the command answered, and for most commands that there is nothing to act on; **1** is always bad input, with an error class (`SourceUnavailable` when a file could not be read, `ContractViolation` when its shape is wrong). Other codes are per command and listed in its document.

WHAT TO DO ON EACH VERDICT

Four verdicts, four next steps

Whatever words a command uses, its answer maps to one of these four, and the next step is the same.

ok

1. Check the blind spots are empty.
2. Record it with its `as_of`: it is true of those rows, at that time.
3. Do not stretch it to rows or days it did not read.

partly_unknown

1. Read each blind spot.
2. Decide whether what was seen is enough for the question.
3. If not, get the missing export and run again.

unknown

1. Never read it as clean.
2. Fix the input: re-export, or re-clone the checkout.
3. If the record does not exist on the platform, that absence is the finding: take it to K.D.

problem

1. Take it to K.D. with the row ids and the command's statement.
2. K.D. judges severity until the table has rules.
3. Do not change the platform yourself: a fix ships through a reviewed deploy by a person.

RUNNING A SANDBOX REHEARSAL

Prove a mechanism on a copy, never on the platform

The 16 rehearsals end in `-sandbox`. Each runs a mechanism beside a control that must fail, and says whether every check held.

```
npm run restore-sandbox -- --fixture examples/backup/restore.fixture.json \
  --sandbox "$(mktemp -d)" --operator "<your name>"
```

Exit 0: verified

Every check held, including the control. The statement ends "Sandbox only; nothing ran on the platform."

Exit 3: not verified

The statement names the checks that failed. Read them: a rehearsal that fails is telling you something about the fixture or the mechanism.

What it does not prove

Each answer lists its limits. A verified rehearsal is a proposal for K.D. and A.M., not a change to the platform.

WHO TO TAKE WHAT TO

Ellis reports; people decide

TAKE THIS	TO
A problem verdict, a severity question, a threshold, a decision on a timer or a scoring model, or a rung from R0 to R2	K.D.
A governance question, a rung from R3 up, the gate and broker, or a change to the platform's plan	A.M.
A fix to the platform's code, data or timers	a person, through a reviewed deploy

Stop and report, never work around:

- a command that tries to write outside its sandbox folder, or to the platform
- a test that fails after `npm ci`: do not trust any answer until it passes
- a check pointed at a production database: none is built to accept one, and production access is default-denied

WHEN THE AGENT STAGES LAND

What changes, and what stays

Changes

Cases start on their own: a job out of retries, a scheduled sweep, or K.D.'s question. The gate decides whether one may run, and the broker calls these same commands as the agent's tools.

Stays

The envelope, the four verdicts and what to do on each; verdicts and severity from code and K.D.'s table, never from the model; nothing written to the platform.

Not yet built

The entry points, gate, agent core, broker, report and audit log. Who builds them is open with A.M. This playbook gains a section when they land.

Sources: `package.json` (the 57 commands); the usage line at the top of each file in `src/cli/`; the output contract in `src/output/toolOutput.ts` and decision record 006; the capability documents in `docs/capabilities/`. Companion documents: Ellis Workflow, Ellis Architecture, Ellis Executive Brief.