Specification

Technical Field

The present invention belongs to the technical fields of distributed artificial intelligence, smart contracts, service gateway load routing and digital currency clearing and settlement. Specifically, it relates to a method and system based on result validation, featuring three-tier price gateway state machine transition, automatic validation by logic actor sandboxes, saturated routing diversion of human service capacity, and direct clearing of digital Renminbi via smart contracts.

Background Art

With the popularization of large language models and multi-agent technologies, human-machine collaborative services have evolved from simple pay-per-use billing to complex pay-by-result billing. However, existing billing and traffic scheduling networks have the following objective technical defects in engineering:

1. **Rigid pricing mechanism failing to match the hybrid cost of human-machine collaboration**: Most existing multi-agent platform billing charges by invocation times or fixed subscriptions. However, in actual industrial scenarios, services include two stages: pure AI guidance (low cost, high concurrency) and human Chuan Guang Shi services (high cost, limited bandwidth). There is a lack of control protocol and gateway that can automatically implement dynamic transition of a three-tier gradient price state machine (free trial, low-cost AI, high-priced human services with pay-by-result billing) at the system gateway layer.

2. **Black-box result determination with coexisting free-riding and fraud**: The core of pay-by-result is to charge only when quantifiable results are generated. However, if the determination right is fully handed over to users, users may falsely claim no effect and refuse to pay after obtaining and implementing the solution; if the determination right is handed over to service providers, providers may forge data to claim compliance and force deductions. The industry lacks a validation system that performs automatic determination combined with protocol assertions in a local hardware security isolation zone and outputs tamper-proof determination proofs.

3. **Systemic congestion caused by Chuan Guang Shi capacity limits**: The service time and energy of human Chuan Guang Shis are physically limited (i.e., there is a service saturation capacity bottleneck). When a large amount of user traffic flocks to a leading Chuan Guang Shi, it will cause system congestion and response timeout. Existing network load balancing can only

perform undifferentiated server diversion, cannot identify the homology of knowledge pedigrees and automatically route traffic to the Chuan Guang Shi's homologous sub-protocols (operated by their successors), nor can it automatically pass benefits upward on the ledger through multi-generation fingerprints.

4. **Asynchronous double spending and deadlock in fund clearing**: When a blockchain ledger system is connected to an external programmable fiat currency payment network (such as the e-CNY interface), the second-level communication delay of the external clearing gateway has serious asynchronous interaction conflicts with the on-chain smart contract execution environment. If the clearing and settlement logic is not equipped with lockstep control, concurrent transactions are prone to double spending vulnerabilities or asynchronous deadlock risks caused by "external fiat currency transfer completed but contract status not deducted in time".

Therefore, designing a pricing and verification settlement system that can match the hybrid cost of human-machine collaboration, provide neutral and credible result determination, identify knowledge pedigree homologous diversion, and has state lockstep to prevent double spending and reentrancy is an urgent technical problem to be solved in the field of multi-agent collaboration and pay-by-result settlement.

Summary of the Invention

Technical Problems to Be Solved

To overcome the defects of existing billing networks such as rigid pricing, inability to provide neutral and credible result determination, vulnerability to malicious order evasion, easy saturation and congestion of human Chuan Guang Shis, and double spending and deadlock easily caused by heterogeneous asynchronous clearing interfaces, the present invention proposes a method and system featuring three-tier price gateway transition, local isolation verification, real-time session activity overflow diversion, and state-lockstep programmable e-CNY clearing and settlement.

Technical Solutions

To solve the above technical problems, the present invention provides a dynamic pricing and verification system based on result validation.

Aspect 1: A dynamic pricing and verification system based on result validation, the system comprising:

1. A **Price Limitation Gateway**: deployed in an edge reverse proxy server at the network access layer, configured to maintain a **three-tier gradient price gateway state machine** including a Trial Tier, a Paid LLM Service Tier and a Human Pay-by-Result Tier; it controls forced transition and interception of billing modes among the three-tier state machine through a cumulative invocation counter at the hardware socket level; when the Human Pay-by-Result Tier is triggered, it forces user nodes to send settlement pre-authorized escrow funds to the on-chain escrow account for locking;
2. A **Result Self-Discipline Validation Sandbox**: deployed in a local hardware trusted execution environment (TEE), configured to securely read unredacted private interaction slice feature vectors from a local database through a unidirectional physical tunnel when a session invocation occurs, and run **quantitative result assertion determination rules** encapsulated in a standardized protocol container to perform causal projection comparison on the feature vectors, so as to calculate quantitative result indicators; if and only if the result indicators reach the preset mathematical boundary threshold, it physically purges raw data including privacy details inside the isolated execution environment and generates a **desensitized Boolean assertion proof** that only indicates result achievement, and invokes the unique hardware-protected private key of the isolated execution environment to generate and output a cryptographic digital signature for the Boolean assertion proof;
3. A **Clearing Routing Contract**: deployed on a decentralized ledger, comprising a capacity monitoring module, a traffic shunt router and a settlement module; wherein the capacity monitoring module is configured to count the number of concurrent active human service sessions of each service Chuan Guang Shi in real time within the ledger execution context; when the number of concurrent active human service sessions of the target Chuan Guang Shi is greater than or equal to the preset service saturation capacity limit, it automatically triggers the traffic shunt router to pull a list of homologous sub-protocols with multi-generation fingerprint alignment, and shunts and routes the current session invocation traffic to the selected sub-protocol service node via a gateway redirection instruction; the settlement module receives the desensitized Boolean assertion proof broadcast by the Result Self-Discipline Validation Sandbox and verifies the signature using the corresponding public key; upon successful signature verification and a determination of result achievement, it triggers programmable payment directly connected to multi-party digital wallets; upon a determination of unachieved result, it triggers a fee exemption state machine transition and transfers the locked escrow fund balance in the escrow account back to the user's address.

Preferably, the settlement module adopts a **pull-based withdrawal topology** during clearing and settlement; after calculating the allocated funds for each participant, the settlement module only updates the pending withdrawal balance state mapping variables corresponding to each participant on the ledger, without executing proactive fund pushes. Each participant node triggers fund withdrawal by sending an external withdrawal transaction, so as to physically block contract concurrent reentrancy and abnormal Gas overflow from the system architecture level.

Preferably, after the traffic shunt router redirects invocation traffic to the homologous sub-protocol service node, if the sub-protocol triggers pay-by-result payment, the settlement module automatically allocates a fixed proportion of the transaction revenue to the account address of the owner of the main value protocol as royalty compensation for copyright authorization.

Aspect 2: A dynamic pricing and verification method based on result validation, characterized in that, executed by a computer processor, the method comprises the following steps:

1. **Price gateway transition control**: A Price Limitation Gateway deployed in an edge reverse proxy server at the network access layer maintains a three-tier gradient price gateway state machine including a Trial Tier, a Paid LLM Service Tier and a Human Pay-by-Result Tier, and controls forced transition and interception of billing modes among the three-tier state machine through a cumulative invocation counter at the hardware socket level; when the Human Pay-by-Result Tier is triggered, it forces user nodes to send settlement pre-authorized escrow funds to the on-chain escrow account for locking;
2. **Human service saturation traffic routing**: A Clearing Routing Contract monitors the number of concurrent active human service sessions within the ledger execution context; when the number of concurrent active human service sessions of the target Chuan Guang Shi is greater than or equal to the preset service saturation capacity limit, it automatically triggers the traffic shunt router to pull a list of homologous sub-protocols with multi-generation fingerprint alignment, and shunts and routes the current session invocation traffic to the selected sub-protocol service node via a gateway redirection instruction;
3. **Sandbox quantitative result validation**: A Result Self-Discipline Validation Sandbox deployed in a local hardware trusted execution environment securely reads unredacted private interaction slice feature vectors from a local database through a unidirectional physical tunnel when a session invocation occurs, and runs quantitative result assertion determination rules to perform causal projection comparison on the feature vectors to calculate quantitative result

indicators; if and only if the result indicators reach the preset mathematical boundary threshold, it physically purges raw plaintext data inside the isolated execution environment, generates a desensitized Boolean assertion proof, and outputs it after signing with a hardware private key;

4. **Clearing execution and exemption**: The on-chain contract receives and verifies the digital signature proof to confirm it originates from an authorized sandbox; upon successful signature verification and a determination of result achievement, it triggers programmable payment directly connected to multi-party digital wallets; upon a determination of unachieved result, it triggers a fee exemption state machine transition and transfers the locked escrow fund balance in the escrow account back to the user's address.

Preferably, in the price gateway transition control step, the gradient transition is specifically as follows: when the cumulative free trial count **C_trial** exceeds the free quota limit and $1 \leq C_trial \leq 3$, the state machine transitions from the Trial Tier to the Paid AI Service Tier; when the cumulative paid AI service count **C_paid** exceeds the limit of 3, the state machine forcibly transitions from the Paid AI Service Tier to the Human Pay-by-Result Tier, mandating the user to send settlement pre-authorized pledge funds to the clearing contract.

Preferably, in the clearing execution and exemption step, the execution mechanism of direct e-CNY programmable payment includes: the on-chain settlement module first locks the current session's ledger pending withdrawal balance mapping state, invokes the programmable payment API interface connected to systems of secondary operating institutions of the central bank through a distributed secure socket, and triggers peer-to-peer clearing and transfer between the personal or enterprise digital fiat currency wallets bound to both transaction parties; if and only if a transaction success receipt signal returned by the secondary operating institution system is received, it releases the lock on the ledger state and clears the corresponding escrow pre-authorization counter within constant time complexity, so as to block asynchronous concurrent reentrancy between heterogeneous clearing gateways through a state lockstep mechanism.

Aspect 3: A decentralized clearing contract-side operation method in the dynamic pricing and verification settlement method based on result validation, characterized in that, executed by a clearing routing contract deployed on a decentralized clearing and settlement ledger, the method comprises the following steps:

1. **Session gateway transition control**: Monitor the establishment of invocation sessions and changes of the Price Limitation Gateway counter, implement three-tier state transition

control of trial, paid AI and human services through hardware socket interception, and receive and lock the user's pre-authorized escrow funds;

2. **Session activity saturation monitoring**: Monitor the number of active service sessions of the target Chuan Guang Shi; when it is greater than or equal to the preset service saturation capacity limit, trigger a traffic shunt mechanism to redirect and shunt the current session traffic to its registered homologous sub-protocol service nodes;
3. **Desensitized assertion signature verification and settlement**: Receive the cryptographic result assertion signature proof broadcast by the external sandbox and verify the signature using a public key; when the signature verification passes and the assertion is true, lock the ledger mapping state, trigger the programmable API interface connected to the e-CNY system to execute transfer, and clear the escrow pre-authorization counter to release the lock after receiving a success receipt;
4. **Result non-compliance exemption and refund**: When the signature verification passes and the assertion is false, determine that the service fails to meet the standard, release the frozen escrow funds and transfer the balance back to the user's address.

Preferably, the session gateway transition control step further includes a temporal random number and digital signature verification sub-step to prevent replay attacks; and in the desensitized assertion signature verification and settlement step, when locking the ledger mapping state, a concurrency control state identifier based on optimistic locking and concurrent version control is added to handle multi-party concurrent settlement requests.

Aspect 4: A local result validation sandbox-side operation method in the dynamic pricing and verification settlement method based on result validation, characterized in that, executed by a result self-discipline validation sandbox deployed in a local hardware trusted isolation zone, the method comprises the following steps:

1. **Local data reading and loading**: When a session invocation occurs, securely read unredacted private interaction slice feature vectors from a local database through a unidirectional physical channel, and read and load the quantitative result assertion determination rules encapsulated in a standardized protocol container;
2. **Result indicator projection comparison**: Run the assertion determination rules to perform causal projection comparison on the feature vectors in a hardware-level physical memory isolation space, and calculate quantitative result indicators;

3. **Desensitized Boolean proof generation**: If the calculated quantitative result indicators reach the mathematical boundary threshold, physically purge raw plaintext data including privacy details inside the isolation space, and only generate desensitized Boolean assertion data indicating result achievement;
4. **Sandbox private key digital signature**: Apply cryptographic digital signature to the Boolean assertion data using the unique hardware-protected private key of the isolation space, generate an encrypted proof file and broadcast it to the decentralized ledger to trigger clearing and settlement.

Preferably, in the sandbox private key digital signature step, the latest block hash of the current session or a one-time random Nonce is mixed in when performing digital signature with the private key, so as to realize signature anti-replay; and before the encrypted proof file is sent to the decentralized ledger, physical transmission encryption is performed through an asymmetric public key encryption channel to prevent man-in-the-middle interference and interception snooping.

Aspect 5: A computer-readable storage medium having a computer program stored thereon, characterized in that the program, when executed by a processor, implements the method according to any one of Claim 4 to Claim 10.

Beneficial Effects

The beneficial effects brought by the present invention include the following:
1. **Realizing refined gradient pricing based on results**: Through forced transition of dynamic counting at the socket layer of the reverse proxy gateway, the present invention limits the allocation of service resources in the trial and AI stages, and implements escrow locking in the human service stage to prevent order evasion.
2. **Balancing data privacy sovereignty and neutral validation**: Using a local trusted isolation sandbox to perform projection causal determination on feature vectors and purge plaintext locally, only desensitized Boolean proofs and cryptographic hardware signatures are broadcast, ensuring that user sovereignty is not infringed.
3. **Dynamic traffic diversion and benefit backfeed**: When leading Chuan Guang Shi sessions are saturated, the system intelligently routes overflow traffic to homologous sub-protocol nodes according to the protocol fingerprint pedigree tree, and automatically allocates 10% of the profit to the main owner's account on the ledger, realizing self-balance of network traffic load and ecological benefits.
4. **Atomic lockstep for anti-reentrancy and anti-double-spending**: When connecting to

the programmable fiat currency API, it adopts ledger pending withdrawal balance state lockstep and optimistic lock control mechanisms, and releases the lock and clears the pre-authorization only after receiving a successful receipt from the clearing network, preventing asynchronous reentrancy double spending vulnerabilities.

5. **Pure software distribution and medium-level anti-avoidance protection**: By adding an independent claim for computer-readable storage media, contract code deployment packages, sandbox-side determination SDKs and billing gateway suites encapsulating the result validation and dynamic clearing program are included in the direct protection scope of the patent, preventing competing products from evading infringement determination through pure code distribution.

Brief Description of the Drawings

Figure 1 shows the physical topology diagram of the dynamic pricing, result validation and saturation diversion system of the present invention;

Figure 2 shows the transition control flowchart of the three-tier gradient price state machine;

Figure 3 shows the routing control flowchart of human service bandwidth saturation determination and homologous sub-protocol redirection.

Detailed Description of the Embodiments

5.0 Terminology Definition and Term Generalization

This section establishes consistent definitions for core assets and technical concepts of the present invention.

1. Value protocol encapsulation gateway: represents the web validation entry and result tracking gateway, carries the execution of validation sandboxes and distributes clearing instructions, functionally corresponding to a standardized protocol encapsulation gateway.

2. Value protocol assertion logic: represents the standard protocol specification encapsulating quantitative result calculation formulas and validation assertions.

3. Distributed clearing and settlement ledger: also referred to as "distributed incremental right confirmation ledger", represents the smart contract ledger that records three-tier gradient state machine transitions and executes programmable payments, functionally corresponding to a decentralized trust accounting network.

4. Ecological Targeted Backfeed Pool: represents the destination of shares allocated to the owners of public open source meta-protocols, corresponding to the public backfeed settlement account.

As an ecological integration description of the system, the system can be seamlessly deployed in a three-layer separated multi-agent system operating architecture composed of a Rule Cognition Layer, an Isolated Asset Layer and a Computing Execution Layer (i.e., a Rule Cognition Layer, an Isolated Asset Layer and a Computing Execution Layer physically isolated from one another), and performs ecological integration and business linkage with the smart contract-based multi-level automatic revenue allocation system for cognitive assets (i.e., Patent No.4) and the logical continuity-based multi-agent interaction sincerity audit system (i.e., Patent No.5). Among them, the Price Limitation Gateway of the system is deployed at the network access layer, providing traffic restriction and pricing billing for access of the entire multi-agent system; the Result Self-Discipline Validation Sandbox, as a logic actor sandbox, is physically deployed in a local trusted execution environment for local desensitized determination of execution effects; the Clearing Routing Contract runs in the distributed incremental right confirmation ledger. The sincerity audit score output by the audit system determines the access conditions and free quotas of the user's LLM billing tier and human billing tier. When the audit system determines that logical disconnection or fraud occurs, the escrow fund balance locked by the clearing routing contract will be automatically forcibly cleared or redirected to the Ecological Targeted Backfeed Pool, realizing an integrated closed loop of pricing, audit and clearing settlement in the multi-agent collaboration network.

5.1 Three-Tier Gradient Price Gateway State Machine Transition Logic

The Price Limitation Gateway is deployed in the edge reverse proxy server at the network access layer, and controls the billing tier to flow among FreeTrial, PaidAI and ResultHuman according to the invocation counter.

1. **Trial Tier**: When the cumulative trial counter satisfies $C_{trial} < N_{free}$ (the trial count limit is $1 \le N_{free} \le 3$), the gateway grants access for free without audit.
2. **Low-cost Paid AI Tier**: When the trial quota is exceeded, it transitions to Paid AI. The system requires the user to prepay a small fee, and limits the service count $C_{paid} < N_{paid}$ (count limit ≤ 3); no sincerity audit is performed at this stage.
3. **Human Pay-by-Result Tier**: When the AI service count exceeds the limit, the edge gateway state machine forces a transition. The system requires the user to send settlement pre-authorized escrow funds to the clearing and settlement ledger for escrow freezing, and Chuan Guang Shi human intervention services are provided. At this time, two-way sincerity audit linkage is enabled: if the user fails to submit the local execution action hash, it is determined as action disconnection, and the contract automatically deducts fees; if the user executes the solution and the action hash matches, but the local sandbox detects that the effect does not meet the standard, it is determined

as effect disconnection, the contract triggers fee exemption, and the escrow funds are returned in the original way.

5.2 Logic Actor Sandbox Operation Mechanism and Data Erasure

To protect the user's data sovereignty, the system designs a local result validation sandbox (i.e., logic actor sandbox):

- **Local calculation and self-inspection**: When a session is invoked, unredacted private interaction slice feature vectors are securely read from the local database through a unidirectional physical channel, the quantitative result assertion determination rules encapsulated in the standardized protocol container are loaded, and the assertion determination rules are run in the hardware-level physical memory isolation space (TEE enclave memory page) to perform causal projection comparison on the feature vectors and calculate quantitative result indicators.
- **Desensitized assertion and physical purging**: If and only if the quantitative result indicators reach the mathematical boundary threshold, raw plaintext data including privacy details are physically purged inside the isolation space (physical memory zeroing and erasure), and only desensitized Boolean assertion data indicating result achievement is generated. The sandbox signs the assertion with a built-in hardware-protected private key, mixes the latest block hash of the current session and a one-time random Nonce during signing, generates a desensitized validation proof file, performs physical transmission encryption using an asymmetric public key encryption channel, and broadcasts it to the distributed ledger.

5.3 Chuan Guang Shi Service Capacity Saturation Diversion and Homologous Sub-Protocol Routing Algorithm

To prevent session congestion caused by the service bandwidth bottleneck of Chuan Guang Shis, the system monitors the number of active service sessions S_{active} of the Chuan Guang Shi in real time on the decentralized ledger:

- **Overflow diversion**: When the number of active sessions is greater than or equal to the preset service saturation capacity limit C_{limit} (e.g., a maximum of 20 real-time channels), the routing gateway pulls a list of homologous sub-protocols with multi-generation fingerprint alignment (tracking the dependency chain via hash fingerprints), and redirects subsequent session traffic to its registered and bound homologous sub-protocol nodes through a gateway redirection instruction.
- **Sub-protocol backfeed**: After the sub-protocol obtains the service fee, the clearing contract

automatically returns a fixed ratio (e.g., 10%) as copyright to the account address of the main protocol owner, ensuring multi-generation collaborative ecological backfeed.

5.4 Digital Fiat Currency Direct-Connected Programmable Interface and Atomic Lockstep Clearing Algorithm

The settlement module adopts a pull-based withdrawal topology during clearing and settlement to defend against reentrancy attacks. When clearing human service result fees and invoking external payment channels, to solve the asynchronous interaction deadlock and double spending risks between the ledger system and the external banking system, the following lockstep and optimistic lock control mechanisms are implemented:

1. **State locking**: The on-chain settlement module first locks the current session's ledger pending withdrawal balance mapping state, and adds an optimistic lock concurrent state identifier with version control to it.
2. **Asynchronous invocation**: Send an invocation request through a distributed secure socket, directly connecting to the digital fiat currency (which can be e-CNY or other legal digital currencies) programmable payment API of the secondary operating institution system of the central bank.
3. **Wallet transfer**: After receiving the instruction, the digital fiat currency system triggers peer-to-peer clearing and transfer between the personal or enterprise digital fiat currency wallets bound to both transaction parties.
4. **Receipt release**: The clearing contract monitors the transaction receipt returned from the secondary operating institution system and verifies the anti-replay identifier. If and only if a success receipt signal is received, the contract clears the corresponding escrow pre-authorization counter and releases the lock on the ledger mapping state within O(1) constant time complexity. If a failure signal is returned, the state lock is rolled back to prevent concurrent double spending.

The programmable digital fiat currency direct connection interface of the system is connected to the secondary institution clearing module, so that the clearing delay is controlled within 150 milliseconds, which greatly ensures the security of fund circulation.

5.5 Vertical Industry Application Scenarios and Embodiments

The validation and settlement system can be widely deployed in human-machine collaboration and pay-by-result scenarios in actual deployment. Typical deployment embodiments are listed below.

1. **Industrial manufacturing scenario**: Process optimization services are billed based on the effect of defect reduction rate. The factory introduces an external process Chuan Guang Shi agent

for equipment debugging. The edge reverse proxy gateway controls the billing tier to transition from free trial to AI tier and human tier according to the invocation counter. When the human tier service is executed, unredacted private interaction slices (such as defect detection image features) are loaded into the local result validation sandbox (i.e., logic actor sandbox) to determine whether the defect reduction rate reaches the boundary threshold (e.g., $\theta \geq 5\%$). If it does not meet the standard, the fee exemption state machine is automatically activated to return the escrow funds. When the Chuan Guang Shi's concurrent active sessions are saturated, the traffic shunt router tracks the dependency chain according to hash fingerprints (i.e., action execution hash fingerprints) and diverts traffic to sub-process agent nodes. This scenario operates on a three-layer separated multi-agent system operating architecture, and is implemented based on any one of the methods according to Claims 4 to 10 of the present invention.

2. **Government confidential scenario**: Government consultation services are settled based on the effect of handling satisfaction. In cross-department government agent collaboration, user agents initiate official document approval consultations. When the concurrent channels of human government Chuan Guang Shis are saturated ($S_{active} \geq 20$), the gateway automatically diverts traffic to its homologous government sub-nodes, and returns 10% of the profit compensation to the main creator's account on the ledger. Service result validation is completed in the local sandbox, which determines the satisfaction feature vector, physically erases raw plaintext data containing government sensitive privacy, and only signs and uploads desensitized Boolean assertions on-chain to trigger digital fiat currency direct clearing. This scenario operates on a three-layer separated multi-agent system operating architecture, and is implemented based on any one of the methods according to Claims 4 to 10 of the present invention.

3. **Financial data scenario**: Risk control consulting services are billed based on the improvement effect of bad debt rate. Financial institutions introduce credit risk control rating. The initial trial tier is free; after transitioning to the AI tier and human billing tier, the system forcibly intercepts invocation requests at the edge reverse proxy layer and locks settlement funds. The local sandbox reads desensitized credit slice feature vectors through a unidirectional physical channel, verifies the bad debt rate reduction effect and physically purges sensitive details. The clearing contract updates the pending withdrawal balance after receiving the receipt from the digital fiat currency programmable interface, and uses optimistic lock version control and Nonce anti-replay signature to protect peer-to-peer transactions of heterogeneous wallets, eliminating concurrent double spending. This scenario operates on a three-layer separated multi-agent system operating architecture, and is implemented based on any one of the methods according to Claims 4 to 10 of the present invention.

5.6 Description of Anti-Evasion Features

As a critical anti-evasion design of the present invention, if the technical solution of "reverse proxy price gateway + local isolation sandbox validation + fingerprint homologous diversion + state lockstep programmable clearing" disclosed in the present invention is not adopted during actual deployment, and traditional business layer billing, manual subjective result evaluation or conventional server load balancing solutions are directly used, the following technical and system defects will arise:

(1) Pricing rules can be easily cracked by bypassing the edge gateway and directly connecting to internal services, and it is impossible to implement three-tier transition control of trial, paid AI and human services for human-machine collaboration through underlying socket interception;

(2) Result validation lacks neutral and isolated hardware determination, and users and service providers are prone to trust games over "whether the payment standard is met", or sensitive process and financial privacy data is forced to be leaked to the public network for audit purposes;

(3) Undifferentiated server diversion when Chuan Guang Shi capacity is reached.