

SHAP and Shapley Values

Quang Nguyen

Loyola University Chicago

Outline

- ▶ Flexibility-Interpretability Trade-Off
- ▶ Interpretable Machine Learning
- ▶ SHAP
- ▶ Shapley values
- ▶ Examples
- ▶ Resources

Model Interpretability

- ▶ Prediction accuracy - model interpretability trade-off is a big idea in ML.
- ▶ In general, interpretability decreases as flexibility increases (James et al., 2021)
- ▶ It is difficult to interpret more complex/black-box models (e.g. random forest, gradient boosted trees)

Model Interpretability

- ▶ The demand for model interpretability has increased in recent years.
- ▶ IML (interpretable machine learning) has emerged as a new area of research
- ▶ This has become an integral part of the machine learning pipeline
- ▶ More and more methods has been developed
 - ▶ LIME (Ribeiro et al., 2016)
 - ▶ **SHAP** (Lundberg & Lee, 2017)
 - ▶ BreakDown (Staniak & Biecek, 2018)
 - ▶ LEAF (Amparore et al., 2021)

- ▶ **SH**apley **A**dditive ex**P**lanations
- ▶ Goal: explain the prediction of an observation x_{obs} by computing the contribution of each feature to the prediction

$$\hat{f}(x_{obs}) - \sum_{i=1}^N \hat{f}(x_i)$$

- ▶ Can be applied on a local level (a single row) and global level (aggregated into variable importance summaries)
- ▶ SHAP satisfies the following properties
 - ▶ Local accuracy
 - ▶ Missingness
 - ▶ Consistency

- Based on **Shapley values** (Shapley, 1951)

- Originated from game theory, named after Lloyd Shapley
- Average marginal contribution of a player across all possible coalitions in a game

$$\phi_i(v) = \sum_{S \subseteq \{1, \dots, p\} \setminus \{i\}} \frac{|S|! (p - |S| - 1)!}{p!} (v(S \cup \{i\}) - v(S))$$

- In a prediction setting

- **“Game”**: prediction task for an x_{obs}
- **“Players”**: feature values of x_{obs} that collaborate to receive gain/payout (i.e. predict a certain value)
- **“Gain/Payout”**: difference between predicted x_{obs} and average prediction for all training observations

Disadvantages

- ▶ SHAP and Shapley values are computationally expensive
 - ▶ In most software/packages, approximations are used
- ▶ Shapley values can be misinterpreted
 - × The difference of the predicted value after removing the feature from the model training
 - ✓ Given the current set of feature values, the contribution of a feature value to the difference between the actual prediction and the mean prediction is the estimated Shapley value.

Example

- ▶ **Random forest model on titanic dataset**
- ▶ **fastshap** (Greenwell, 2020) R package
- ▶ Data prep

```
library(tidyverse)
theme_set(theme_minimal())

titanic <- titanic::titanic_train %>%
  janitor::clean_names() %>%
  dplyr::select(survived, pclass, sex, age, embarked) %>%
  tidyr::drop_na() %>%
  dplyr::mutate(survived = as_factor(survived),
               across(where(is_character), as_factor))
```


Example

► RF fit

```
titanic_rf <- ranger::ranger(survived ~ .,  
                             probability = TRUE,  
                             data = titanic)
```

► Explain

```
surv_prob <- function(object, newdata) {  
  predict(object, newdata)$predictions[, 2]  
}  
x_train <- dplyr::select(titanic, -survived)
```

```
titanic_explain <- titanic_rf %>%  
  fastshap::explain(X = data.frame(x_train),  
                    nsim = 100,  
                    adjust = TRUE,  
                    pred_wrapper = surv_prob)
```

Example


```
head(titanic_explain)
```

pclass	sex	age	embarked
-0.1049205	-0.1498677	-0.0302120	-0.0193185
0.2022373	0.3525334	-0.0075687	0.0315030
-0.1659573	0.2336614	0.0270597	-0.0300617
0.2110946	0.3145879	0.0454336	-0.0050744
-0.1171851	-0.1612892	-0.0391471	-0.0059721
0.1499265	-0.2048499	-0.1306206	-0.0143906

Example

► Variable importance, global level

```
autoplot(titanic_explain)
```



Example

► Explaining an individual observation: **Jack Dawson**

```
jack <- data.frame(pclass = 3,  
                  sex = "male",  
                  age = 20,  
                  embarked = "S")
```

```
jack_prob <- surv_prob(titanic_rf, jack)  
jack_prob
```

```
      1  
0.1188755
```

```
baseline_prob <- mean(surv_prob(titanic_rf, x_train))  
baseline_prob
```

```
[1] 0.4067117
```

Example

```
jack_explain <- fastshap::explain(titanic_rf,  
                                X = x_train,  
                                newdata = jack,  
                                nsim = 1000,  
                                adjust = TRUE,  
                                pred_wrapper = surv_prob)  
  
jack_explain
```


pclass	sex	age	embarked
-0.1157425	-0.18642	0.0603141	-0.0459879

Example

► Waterfall chart

```
feat_shap <- tibble(feature = str_c(names(jack), " = ", t(jack)),  
                    shapley = t(jack_explain))  
  
waterfall::waterfallchart(feature ~ shapley,  
                           data = feat_shap,  
                           origin = baseline_prob,  
                           summaryname = "Total difference",  
                           xlab = "Survival probability")
```

Example



- ▶ Book:

- ▶ [Interpretable Machine Learning](#) (Molnar, 2019)

- ▶ Papers:

- ▶ [Explainable Artificial Intelligence: a Systematic Review](#) (Vilone & Longo, 2020)
 - ▶ [Landscape of R packages for eXplainable Artificial Intelligence](#) (Maksymiuk et al., 2021)

References I

- Amparore, E., Perotti, A., & Bajardi, P. (2021). To trust or not to trust an explanation: Using LEAF to evaluate local linear XAI methods. *PeerJ. Computer Science*, 7, e479–e479. <https://doi.org/10.7717/peerj-cs.479>
- Greenwell, B. (2020). *Fastshap: Fast approximate shapley values*. <https://CRAN.R-project.org/package=fastshap>
- James, G., Witten, D., Hastie, T., & Tibshirani, R. (2021). *An introduction to statistical learning: With applications in r* (2nd ed.). Springer US. <https://doi.org/10.1007/978-1-0716-1418-1>
- Lundberg, S. M., & Lee, S.-I. (2017). A unified approach to interpreting model predictions. *Proceedings of the 31st International Conference on Neural Information Processing Systems*, 4768–4777. <https://dl.acm.org/doi/10.5555/3295222.3295230>
- Maksymiuk, S., Gosiewska, A., & Biecek, P. (2021). *Landscape of r packages for eXplainable artificial intelligence*. <https://arxiv.org/abs/2009.13248>

References II

- Molnar, C. (2019). *Interpretable machine learning: A guide for making black box models explainable*.
<https://christophm.github.io/interpretable-ml-book>
- Ribeiro, M., Singh, S., & Guestrin, C. (2016). “Why should I trust you?”: Explaining the predictions of any classifier. *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Demonstrations*, 97–101.
<https://doi.org/10.18653/v1/N16-3020>
- Shapley, L. S. (1951). *Notes on the n -person game - I: Characteristic-point solutions of the four-person game*. RAND Corporation.
<https://doi.org/10.7249/RM0656>
- Staniak, M., & Biecek, P. (2018). Explanations of Model Predictions with live and breakDown Packages. *The R Journal*, 10(2), 395–409.
<https://doi.org/10.32614/RJ-2018-072>
- Vilone, G., & Longo, L. (2020). *Explainable artificial intelligence: A systematic review*. <https://arxiv.org/abs/2006.00093>