

Analysis of CSV File Reading in R

Quang Nguyen* and Robert Tedesco*

* Loyola University Chicago

STAT 407 Fall 2021

Outline

- ▶ Background
- ▶ Experiment
- ▶ ANOVA
- ▶ Additional Analysis
- ▶ Discussion

Background


- ▶ Statisticians struggle with reading in large dataset (Matthews, 2021)
- ▶ `read.csv`, part of base R (R Core Team, 2021), is old and slow.
- ▶ There are better and more efficient data I/O algorithms in R (Gillespie & Lovelace, 2021)
 - ▶ `rio::import()` (Chan et al., 2021)
 - ▶ `readr::read_csv()` (Wickham & Hester, 2021) - part of `tidyverse` (Wickham et al., 2019)
 - ▶ `data.table::fread()` (Dowle & Srinivasan, 2021)

Experiment


- ▶ 3^3 factorial design (Montgomery, 2012)
 - ▶ File size: low ($\sim 0.5\text{GB}$), medium ($\sim 1.2\text{GB}$), high ($\sim 2\text{GB}$)
 - ▶ Computer: Lenovo, Dell, MacBook
 - ▶ Function: `rio::import()`, `readr::read_csv()`,
`data.table::fread()`
- ▶ Model: insert formula
- ▶ $n = 20$ replicates
- ▶ How were the data generated?

Data Understanding


► Interaction plots



package — fread — import — readr



computer — dell — lenovo — mac



computer — dell — lenovo — mac

ANOVA



- All model terms are significant. . .

Term	df	SS	MS	F	p-value
computer	2	118.6155	59.3078	12.8017	0.0000
size	2	908.9852	454.4926	98.1034	0.0000
package	2	38.4974	19.2487	4.1549	0.0162
computer:size	4	136.3553	34.0888	7.3582	0.0000
computer:package	4	114.5762	28.6441	6.1829	0.0001
size:package	4	87.9878	21.9970	4.7481	0.0009
computer:size:package	8	144.3655	18.0457	3.8952	0.0002
Residuals	513	2376.6214	4.6328	NA	NA

- However . . .

ANOVA

- There are issues with both **normality** and **homoscedasticity**



- Confirmed by Shapiro-Wilk and Levene tests (both with p -value ≈ 0)

- ▶ Transforming the data (log, Box-Cox) did not fix issues with model assumptions
- ▶ This leads us to consider a nonparametric approach,
 - ▶ No distribution assumption about the data
 - ▶ Permutation test for a three way factorial designs
 - ▶ `asbio::perm.fact.test()` (Aho, 2021)

ANOVA


- A permutation test gives significant results

Term	Initial F	df	p-value
size	98.1034	2	0.0001
computer	12.8017	2	0.0001
package	4.1549	2	0.0123
size:computer	7.3582	4	0.0001
size:package	4.7481	4	0.0007
computer:package	6.1829	4	0.0002
size:computer:package	3.8952	8	0.0003
Residual	NA	513	NA

- ▶ Post-hoc analysis: pairwise permutation tests
- ▶ Use False Discovery Rate (Benjamini & Hochberg, 1995) as p -value adjustment method
- ▶ Which pairs differ in mean reading time?
 - ▶ Speed: all pairs
 - ▶ Computer: Lenovo-Dell, Lenovo-Mac
 - ▶ Package/Function: `data.table::fread()` - `rio::import()`,
`rio::import()` - `readr::read_csv()`


ANOVA

► Univariate effects plot of the factors



Additional Analysis

- Investigate reading method (package/function) for MacBook only



Additional Analysis

- ▶ A simulation study
- ▶ Simulate more data, in addition to the existing 3 data files
- ▶ Consider 10 file sizes (in GB)
 - ▶ **0.49, 1.22**, 1.51, 1.73, **1.96**, 2.16, 2.36, 2.61, 2.94, 3.32
- ▶ Use MacBook to read in each file using the 3 functions, and record the time elapsed

Additional Analysis

► ANCOVA

- Response: time elapsed (in seconds)
- Treatment: function (3 levels)
- Covariate: file size (in GB)

Term	SS	df	F	p-value
(Intercept)	10.5154	1	8.4657	0.0073
meth	187.3580	2	75.4188	0.0000
size	192.4662	1	154.9502	0.0000
Residuals	32.2950	26	NA	NA

Additional Analysis

- Model assumptions are met.

statistic	p.value	method
0.9732	0.6286	Shapiro-Wilk normality test

statistic	p.value	df	df.residual	method
2.3633	0.1133	2	27	Levene test

Additional Analysis

► Multiple comparisons - Tukey contrasts

contrast	estimate	se	statistic	adj p-value
import - fread	-0.2873	0.4984	-0.5764	0.8338
readr - fread	-5.4391	0.4984	-10.9127	0.0000
readr - import	-5.1518	0.4984	-10.3362	0.0000

► readr significantly differs from the other 2 methods when using Mac.

Cheers.

- ▶ Acknowledgments
 - ▶ Lance Davis
 - ▶ Mike Perry
 - ▶ Greg Matthews
- ▶ Take advantage of more efficient algorithms!!!
- ▶ Greg's YouTube video: youtu.be/E5KJkooW4RY
- ▶ GitHub: github.com/qntkhvn/read_speed
- ▶ Question?

References I

- Aho, K. (2021). *Asbio: A collection of statistical tools for biologists*.
<https://CRAN.R-project.org/package=asbio>
- Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society. Series B (Methodological)*, 57(1), 289–300.
<http://www.jstor.org/stable/2346101>
- Chan, C., Chan, G. C., Leeper, T. J., & Becker, J. (2021). *Rio: A swiss-army knife for data file i/o*.
<https://CRAN.R-project.org/package=rio>
- Dowle, M., & Srinivasan, A. (2021). *Data.table: Extension of 'data.frame'*.
<https://CRAN.R-project.org/package=data.table>
- Gillespie, C., & Lovelace, R. (2021). *Efficient r programming*.
<https://csgillespie.github.io/efficientR>
- Matthews, G. (2021). *Old dog (statistician) learns new trick (read_csv)*.
<https://youtu.be/E5KJkooW4RY>.

References II

- Montgomery, D. C. (2012). *Design and analysis of experiments, 8th edition*. John Wiley & Sons.
- R Core Team. (2021). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing.
<https://www.R-project.org/>
- Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L. D., François, R., Grolemund, G., Hayes, A., Henry, L., Hester, J., Kuhn, M., Pedersen, T. L., Miller, E., Bache, S. M., Müller, K., Ooms, J., Robinson, D., Seidel, D. P., Spinu, V., ... Yutani, H. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686.
<https://doi.org/10.21105/joss.01686>
- Wickham, H., & Hester, J. (2021). *Readr: Read rectangular text data*.
<https://CRAN.R-project.org/package=readr>