

Contents

Qompass AI Hyprland Graphics Config

Aquamarine (aq.conf/aq.lua) ·

Electron (electron.conf/electron.lua) ·

Google (google.conf) ·

GTK (gtk.conf) ·

Hypr Graphics (hypr__graphics.conf) ·

Intel / oneAPI (intel.conf) ·

Mesa / OpenGL (mesa.conf) ·

NVIDIA (nvidia.conf) ·

Proton / DXVK-NVAPI (proton.conf) ·

Qt (qt.conf) ·

SDL (sdl.conf) ·

Unreal Engine (unreal.conf) ·

Vulkan (vulkan.conf) ·

X11 / Xwayland (x11.conf)

Config File

Purpose

Key Areas

aq.conf

Aquamarine(AQ) renderer + multi-GPU routing for Hyprland

AQ_DRM_DEVICES, AQ_RENDER_BACKEND, AQ_MGPU_NO_EXPLICIT

electron.conf

Electron apps on Wayland with Ozone + IME support

ELECTRON_ENABLE_WAYLAND, ELECTRON_FLAGS, Ozone platform
hints

google.conf

TensorFlow / Google ML threading and logging

TF_* threading, logging, oneDNN toggles

gtk.conf

Gnome ToolKit (GTK) 2/3/4 graphics backend

GDK_BACKEND, GSK_RENDERER, GTK_THEME, GTK_IM_MODULE

hypr_graphics.conf

Global Hyprland graphics + browser/toolkit Wayland flags

CLUTTER_BACKEND, MOZ_ENABLE_WAYLAND, GBM/EGL, WEBKIT_FORCE_WAYLAND

intel.conf

Intel GPU / oneAPI SYCL runtime tuning

ONEAPI_DEVICE_SELECTOR, SYCL_* cache, Level Zero + CUDA/HIP knobs

mesa.conf

Mesa OpenGL / Vulkan drivers, shader cache, video accel

MESA_* cache + drivers, LIBVA/VDPAU, Rusticl OpenCL, Zink settings

nvidia.conf

NVIDIA GBM backend, VRR, OpenGL/Vulkan behavior

GBM_BACKEND, performance flags, CUDA_VISIBLE_DEVICES, NVD_BACKEND

proton.conf

Proton / DXVK-NVAPI / DLSS / Reflex for games

DXVK_NVAPI_, PROTON_ENABLE_, NGX / DLSS overrides

qt.conf

Qt 6 high-DPI and Wayland graphics configuration

QT_QPA_PLATFORM, QT_SCALE_FACTOR, QT_WAYLAND_DISABLE_WINDOWDECORATION, QML_IMPORT_PATH

sdl.conf

SDL 3 audio/video backends and rendering under Wayland

SDL_VIDEODRIVER, SDL_AUDIO_DRIVER, SDL_RENDER_DRIVER, Wayland / KMSDRM options

unreal.conf

Unreal Engine Wayland forcing

UNREAL_FORCE_WAYLAND

vulkan.conf

Vulkan loader, WSI, and toolkit Vulkan integration

MESA_VK_WSI_LIST, VK_PRESENT_MODE, VK_WSI_MODE,
Qt/SDL Vulkan hints

x11.conf

Xwayland compatibility and legacy X11 behavior

WLR_EGL_NO_X11, XWAYLAND_NO_GLAMOR, xwayland{...} block

Aquamarine (aq.conf)

Aquamarine (aq.conf)

AQ_DRM_DEVICES – colon-separated list of DRM nodes in priority order
(e.g. /dev/dri/card2:/dev/dri/card1 or /dev/dri/by-path/...).

AQ_MGPU_NO_EXPLICIT – disable explicit multi-GPU management (0 /
1).

AQ_NO_MODIFIERS – disable dma-buf modifiers if set (0 / 1).

AQ_RENDER_BACKEND – Aquamarine renderer (gl, potentially others as
backends evolve).

Electron (electron.conf)

Electron (electron.conf)

ELECTRON_ENABLE_LOGGING – enable Chromium/Electron logging (0 /
1).

ELECTRON_ENABLE_WAYLAND – prefer Wayland compositor integration
(0 / 1).

ELECTRON_FLAGS – extra Chromium flags (e.g. IME and text-input version
arguments).

ELECTRON_OZONE_PLATFORM – Ozone backend (wayland, x11).

ELECTRON_ENABLE_FEATURES – Chromium feature list (comma-separated
flags like UseOzonePlatform).

ELECTRON_OZONE_PLATFORM_HINT – hint for Ozone platform
selection; typically auto or wayland (ignored on newer Electron but harm-
less).[web:81]

Google (google.conf)

Google / TensorFlow (google.conf)

ANGLE_CAPTURE_SERIALIZE_STATE – enable ANGLE state capture (0
/ 1).

TENSORFLOW_DELEGATE – delegate backend (none, platform-specific delegate names).

TF_CPP_MIN_LOG_LEVEL – log level (0=all, 1=INFO, 2=WARNING, 3=ERROR).

TF_ENABLE_ONEDNN_OPTS – enable oneDNN optimizations (0 / 1).

TF_INTRA_OP_PARALLELISM_THREADS – per-op parallel threads (integer).

TF_INTER_OP_PARALLELISM_THREADS – inter-op parallel threads (integer).

GTK (gtk.conf)

GTK (gtk.conf)

GDK_BACKEND – ordered list of backends (e.g. wayland,x11,*); valid names include wayland, x11, broadway, etc.[web:71][web:82]

GDK_PIXBUF_MODULE_FILE – path to GdkPixbuf loaders cache file.

GDK_RENDERING – GTK 3 rendering mode (e.g. similar or image).[web:72]

GDK_SCALE – integer scaling factor for GTK (e.g. 1, 2).[web:72]

GSK_CACHE_TIMEOUT – GTK 4 scene graph cache timeout in seconds.

GSK_RENDERER – GTK 4 renderer (vulkan, gl, cairo depending on build).[web:74]

GTK_APPLICATION_PREFERS_NON_DEFAULT_THEME – whether apps prefer system theme (0 / 1).[web:72]

GTK_CSD – client-side decorations (0 / 1).

GTK_IM_MODULE – IM module name (fcitx5, ibus, etc.).[web:72]

GTK_MEDIA – GTK 4 media backend (e.g. gstreamer).[web:74]

GTK_THEME – GTK theme (e.g. Adwaita:dark).

GTK_USE_PORTAL – use XDG portals where possible (0 / 1).[web:72]

GTK_VIDEOSINK – video sink element for GTK media (waylandsink, xvimagesink, etc.).

XDG_DATA_DIRS – search path for data files (colon-separated directories).

Commented options like GDK_DISABLE, GDK_GL_DISABLE, GDK_WAYLAND_DISABLE, GSK_GPU_DISABLE selectively disable features for debugging.

Hypr Graphics (hypr_graphics.conf)

Hypr Graphics (hypr_graphics.conf)

CLUTTER_BACKEND – Clutter backend (wayland, x11).

DISCORD_ENABLE_WAYLAND – enable Discord Wayland mode (0 / 1).

EGL_PLATFORM – EGL platform hint (wayland, x11, drm, etc.).[web:76]

GST_PLUGIN_PATH – additional GStreamer plugin directories.

HYPRCURSOR_FORCE_SOFTWARE – force software cursor rendering (0 / 1).

HYPRCURSOR_THEME – cursor theme name.

HYPRCURSOR_SIZE – cursor size in pixels.

MOZ_DBUS_REMOTE – enable Firefox/Thunderbird remote via D-Bus (0 / 1).

MOZ_ENABLE_WAYLAND – enable Wayland backend in Mozilla apps (0 / 1).[web:46]

MOZ_WEBRENDER – enable WebRender compositor (0 / 1).

NIXOS_OZONE_WL – hint for Ozone Wayland usage in NixOS environments (0 / 1).

OZONE_PLATFORM – global Ozone platform (auto, wayland, x11).

WEBKIT_FORCE_WAYLAND – prefer Wayland backend in WebKit-GTK (0 / 1).

WEBVIEW_FORCE_WAYLAND – similar, for webview wrappers (0 / 1).

Commented WLR_* options can pin DRM devices, renderer, and software allowance for wlroots.

Intel / oneAPI (intel.conf)

Intel / oneAPI (intel.conf)

ONEAPI_DEVICE_SELECTOR – complex selector for SYCL/oneAPI devices (e.g. level_zero:gpu;!:cpu;!!vmpipe:); supports backend and device type filters.[web:79]

SYCL_CACHE_DIR – directory for JIT/cache artifacts.

SYCL_CACHE_IN_MEM – enable in-memory cache (0 / 1).

SYCL_CACHE_MAX_DEVICE_IMAGE_SIZE, SYCL_CACHE_MIN_DEVICE_IMAGE_SIZE, SYCL_CACHE_MAX_SIZE, SYCL_CACHE_THRESHOLD – cache size and thresholds (integers in bytes or MB-ish units, per docs).[web:79]

SYCL_CACHE_PERSISTENT – keep cache across runs (0 / 1).

SYCL_DISABLE_EXECUTION_GRAPH_CLEANUP – keep execution graphs (0 / 1).

SYCL_DISABLE_PARALLEL_FOR_RANGE_ROUNDING – disable rounding optimizations (0 / 1).

SYCL_DUMP_IMAGES – dump device images for debugging (0 / 1).

SYCL_EAGER_INIT – pre-initialize backends (0 / 1).

SYCL_HOST_UNIFIED_MEMORY – enable host unified memory (0 / 1).

SYCL_IN_MEM_CACHE_EVICTION_THRESHOLD – eviction threshold in bytes.

SYCL_JIT_AMDGCN_PTX_KERNELS – enable JIT for AMDGCN/PTX kernels (0 / 1).

SYCL_PARALLEL_FOR_RANGE_ROUNDING_TRACE – trace range rounding (0 / 1).

SYCL_PI_HIP_MAX_LOCAL_MEM_SIZE, SYCL_PI_CUDA_MAX_LOCAL_MEM_SIZE – max local mem for HIP/CUDA backends (bytes).

SYCL_PI_LEVEL_ZERO_* – various Level Zero tuning knobs (batch size, cleanup thresholds, copy engine usage, USM behavior, etc.).

SYCL_PRINT_EXECUTION_GRAPH – when to print graphs (never, on_error, always).

SYCL_PROGRAM_*_OPTIONS – append or override compile/link options for device programs.

SYCL_QUEUE_THREAD_POOL_SIZE – size of SYCL queue thread pool (integer).

SYCL_REDUCTION_PREFERRED_WORKGROUP_SIZE – hint like gpu:128 for reduction kernels.

SYCL_UR_USE_LEVEL_ZERO_V2 – opt-in to newer Level Zero UR (0 / 1).

SYCL_USM_HOSTPTR_IMPORT – enable host pointer import (0 / 1).

SYCL_UR_CUDA_ENABLE_IMAGE_SUPPORT – enable CUDA image support (0 / 1).

Mesa / OpenGL (mesa.conf)

Mesa (mesa.conf)

EGL_DRIVER – Mesa EGL driver (e.g. iris, radeonsi, zink).[web:32]

EGL_PLATFORM – platform for EGL (wayland, x11, surfaceless, etc.).[web:76]

GST_VAAPI_ALL_DRIVERS – VAAPI driver discovery for GStreamer (0 / 1).

LIBGL_ALWAYS_SOFTWARE – force software GL if 1; GPU if 0.[web:32]

LIBVA_DRIVERS_PATH – search path for VA-API drivers.

`LP_NUM_THREADS` – number of llvmpipe threads (integer).[web:32]
`MESA_DISK_CACHE_DATABASE`, `MESA_DISK_CACHE_SINGLE_FILE`,
`MESA_DISK_CACHE_MULTI_FILE` – choose cache backend layout (0 / 1).[web:32]
`MESA_GLSL_CACHE_ENABLE` – enable GLSL shader cache (true / false).[web:32]
`MESA_GLSL_CACHE_DIR`, `MESA_SHADER_CACHE_DIR` – directories for caches.
`MESA_GLSL_CACHE_MAX_SIZE`, `MESA_SHADER_CACHE_MAX_SIZE` – max cache size (e.g. 32G).[web:32]
`MESA_LOADER_DRIVER_OVERRIDE` – override Mesa driver name (e.g. iris, zink).[web:32]
`MESA_NO_ERROR` – disable error checking for perf (0 / 1).[web:32]
`OCL_ICD_VENDORS` – path to OpenCL ICD vendor file (Rusticl here).[web:32]
`OPENCV_OPENCL_DEVICE` – selects OpenCV OpenCL device (e.g. NVIDIA CUDA:GPU:0).
`RUSTICL_DEVICE_TYPE` – Rusticl device type (gpu, cpu, etc.).[web:32]
`RUSTICL_ENABLE` – list of drivers to enable (e.g. iris, llvmpipe).[web:32]
`RUSTICL_FEATURES` – features like fp16, fp64, intel.[web:32]
`RUSTICL_MAX_WORK_GROUPS` – max work-groups hint.
`VAAPI_COMPAT`, `VAAPI_MPEG4_ENABLED` – VAAPI compatibility and codec support toggles.
`VDPAU_DRIVER` – VDPAU driver name (e.g. va_gl, nvidia).
`ZINK_BATCH_COUNT` – batch count for Zink driver.
`ZINK_SHADER_CACHE_DIR` – directory for Zink shader cache.
NVIDIA (nvidia.conf)
NVIDIA (nvidia.conf)
`CUDA_VISIBLE_DEVICES` – list of visible CUDA devices by index (e.g. 0,1,2).
`GBM_BACKEND` – GBM backend library (nvidia-drm, nvidia, etc.).
`VK_LAYER_NV_optimus` – toggle Vulkan Optimus layer via env-based enable flag. (Layer JSON uses its own `enable_environment` / `disable_environment` keys; here you're simply setting a flag consumed by that stack.)
Proton / DXVK-NVAPI (proton.conf)

Proton / DXVK-NVAPI (proton.conf)

DXVK_ENABLE_NVAPI – enable DXVK-NVAPI integration (0 / 1).

DXVK_NVAPI_ALLOW_OTHER_DRIVERS – allow non-NVIDIA Vulkan drivers (0 / 1).

DXVK_NVAPI_DISABLE_ENTRYPOINTS – disable specific NVAPI entry-points (comma-separated, or empty for none).

DXVK_NVAPI_DRIVER_VERSION – spoofed driver version (integer, optional).

DXVK_NVAPI_DRS_SETTINGS – raw DRS settings, see DXVK-NVAPI docs.

DXVK_NVAPI_DRS NGX_DLSS_*_OVERRIDE* – override DLSS/NGX presets and modes (e.g. on, off, quality, performance).

DXVK_NVAPI_GPU_ARCH – GPU architecture string (e.g. AD100).

DXVK_NVAPI_VKREFLEX_INJECT_PRESENT_FRAME_IDS /
DXVK_NVAPI_VKREFLEX_INJECT_SUBMIT_FRAME_IDS – inject specific frame IDs (0 / 1).

DXVK_NVAPI_VKREFLEX_LAYER_LOG_LEVEL – Reflex logging level (trace, debug, info, etc.).

PROTON_ENABLE NGX_UPDATER, PROTON_ENABLE_NVAPI,
PROTON_ENABLE_WAYLAND, PROTON_USE_WAYLAND – Proton feature toggles (0 / 1).

DXVK_NVAPI_VKREFLEX_ALLOW_FALLBACK_TO_OOB_FRAME_ID,
DXVK_NVAPI_VKREFLEX_ALLOW_FALLBACK_TO_PRESENT_FRAME_ID,
DXVK_NVAPI_VKREFLEX_ALLOW_FALLBACK_TO_SIMULATION_FRAME_ID
– control Reflex frame-ID fallbacks (0 / 1).

DXVK_NVAPI_LOG_PATH – directory for DXVK-NVAPI logs.

DXVK_NVAPI_VKREFLEX – enable Reflex layer (0 / 1).

PROTON_FORCE_LARGE_ADDRESS_AWARE – force LAA flag in games (0 / 1).

PROTON_NO_ESYNC – disable esync (0 / 1).

PROTON_USE_NTDLL_HAVE_THREAD – tweak NTDLL threading behavior (0 / 1).

DXVK_NVAPI_DRS NGX_DLSS_OVERRIDE_OPTIMAL_SETTINGS – DLSS preset override (e.g. perf_to_9x).

DXVK_NVAPI_ENABLE, DXVK_NVAPI_VKREFLEX at bottom – additional on/off switches (0 / 1).

Qt (qt.conf)

Qt (qt.conf)

QML_IMPORT_PATH, QML2_IMPORT_PATH – search paths for QML modules (colon-separated directories).

QT_AUTO_SCREEN_SCALE_FACTOR – enable auto DPI scaling (0 / 1).

QT_ENABLE_HIGHDPI_SCALING – high-DPI behavior toggle (0 / 1).

QT_FONT_DPI – font DPI value (integer, e.g. 144).[web:85]

QT_IM_MODULE – IM module (fcitx5, ibus, etc.).

QT_QPA_PLATFORM – platform plugin (wayland, wayland:xcb, xcb).[web:82]

QT_QPA_PLATFORMTHEME – platform theme plugin (e.g. hyprqt6engine, qt6ct).

QT_QUICK_CONTROLS_CONF – path to Qt Quick Controls 2 config file.

QT_QUICK_CONTROLS_* – styling (Material / Universal themes, colors, variants, etc.).

QT_SCALE_FACTOR – global scale factor (float, e.g. 1.0, 1.5).[web:85]

QT_SCALE_FACTOR_ROUNDING_POLICY – rounding mode (Round, Ceil, Floor, PassThrough).[web:85]

QT_WAYLAND_DISABLE_WINDOWDECORATION – disable server-side decorations (0 / 1).[web:85]

QT_XCB_GL_INTEGRATION – XCB GL integration plugin (xcb_egl, xcb_glx).

Commented QT_SCREEN_SCALE_FACTORS and QT_USE_PHYSICAL_DPI give per-screen and physical DPI control.

SDL (sdl.conf)

SDL (sdl.conf)

SDL_AUDIO_DRIVER – preferred audio backend (e.g. pipewire, pulseaudio, alsa).

SDL_AUDIO_FREQUENCY – output sample rate in Hz, 0 = system default.

SDL_DYNAMIC_API_ALL – enable dynamic API loading (0 / 1).

SDL3_DYNAMIC_API – path to libSDL3.so for dynamic API.

SDL_IM_MODULE – input method module (e.g. fcitx5, ibus).

SDL_VIDEODRIVER – video drivers search order (e.g. wayland,x11).

SDL_VIDEO_YUV_HWACCEL – enable YUV hardware accel (0 / 1).

SDL_VIDEO_X11_DGAMOUSE – DGA mouse on X11 (0 / 1).

SDL_FRAMEBUFFER_ACCELERATION – framebuffer accel hint (0=off, 1=hint, 2=force).

SDL_INVALID_PARAM_CHECKS – runtime argument checks (0 / 1).

SDL_KEYCODE_OPTIONS – keycode mapping mode (e.g. scancode).

SDL_KMSDRM_ATOMIC – require atomic KMS (0 / 1).

SDL_KMSDRM_DEVICE_INDEX – KMS/DRM card index (integer, usually 0).

SDL_KMSDRM_REQUIRE_DRM_MASTER – require DRM master (0 / 1).

SDL_LOGGING – log level (trace, debug, info, warn, error, critical).

SDL_NO_SIGNAL_HANDLERS – disable SDL signal handlers (0 / 1).

SDL_OPENGL_ES_DRIVER – GLES driver hint (e.g. default).

SDL_OPENGL_LIBRARY – OpenGL library (e.g. libGL.so.1).

SDL_QUIT_ON_LAST_WINDOW_CLOSE – auto-quit when last window closes (0 / 1).

SDL_RENDER_DRIVER – renderer backend (opengl, vulkan, software, etc.).

SDL_RENDER_GPU_LOW_POWER – prefer low-power GPU (0 / 1).

SDL_RENDER_LINE_METHOD – line rendering mode (integer, driver-specific).

SDL_RENDER_VSYNC – vsync on/off/late (0, 1, or driver-specific values).

SDL_SCREENSAVER_INHIBIT_ACTIVITY_NAME – name used to inhibit screensaver.

SDL_THREAD_FORCE_REALTIME_TIME_CRITICAL – force RT priority (0 / 1).

SDL_THREAD_PRIORITY_POLICY – thread priority policy (normal, time_critical, etc.).

SDL_TIMER_RESOLUTION – requested timer resolution in ms.

SDL_VIDEO_ALLOW_SCREENSAVER – allow screensaver during apps (0 / 1).

SDL_VIDEO_DISPLAY_PRIORITY – prefer specific display (empty or name-based hint).

SDL_VIDEO_DOUBLE_BUFFER – double buffering hint (0 / 1).

SDL_VIDEO_MINIMIZE_ON_FOCUS_LOSS – minimize on focus loss (0 / 1).

SDL_VIDEO_OFFSCREEN_SAVE_FRAMES – keep offscreen frames (0 / 1).

SDL_VIDEO_SYNC_WINDOW_OPERATIONS – sync window ops with display (0 / 1).

SDL_VIDEO_WAYLAND_ALLOW_LIBDECOR – allow libdecor decorations (0 / 1).

SDL_VIDEO_WAYLAND_MODE_EMULATION – mode emulation (0 / 1).

SDL_VIDEO_WAYLAND_MODE_SCALING – scaling mode (stretch, center, etc.).

SDL_VIDEO_WAYLAND_PREFER_LIBDECOR – prefer libdecor (0 / 1).

SDL_VIDEO_WAYLAND_SCALE_TO_DISPLAY – scale surface to display (0 / 1).

SDL_WAVE_CHUNK_LIMIT – max WAVE chunk size (bytes, 0 = unlimited).

SDL_WAVE_FACT_CHUNK – how to handle FACT chunks (strict, ignore).

SDL_WAVE_RIFF_CHUNK_SIZE – RIFF size handling (strict, ignore).

SDL_WAVE_TRUNCATION – truncated file handling (strict, ignore).

Unreal Engine (unreal.conf)

Unreal Engine (unreal.conf)

UNREAL_FORCE_WAYLAND – force Unreal Engine to prefer Wayland surfaces (0 / 1).

Vulkan (vulkan.conf)

Vulkan (vulkan.conf)

DISABLE_LAYER_AMD_SWITCHABLE_GRAPHICS_1 – disable AMD switchable graphics layer (0 / 1).

MESA_VK_WSI_LIST – allowed WSI backends (e.g. wayland, x11, comma-separated).

QSG_RHI_BACKEND – Qt scene graph backend (vulkan, opengl, metal, etc.).

QT_VK_DISPLAY_INDEX – display index for Qt Vulkan (integer).

QT_VK_MODE_INDEX – mode index for Qt Vulkan (integer).

QT_VK_PHYSICAL_DEVICE_INDEX – Vulkan physical device index for Qt (integer).

SDL_VULKAN_DISPLAY – SDL display index for Vulkan surfaces (integer).

SDL_VULKAN_LIBRARY – Vulkan loader library (e.g. libvulkan.so.1).

VK_ADD_LAYER_PATH – additional directory for Vulkan implicit layer JSONs.
 VK_KHR_PRESENT_WAIT_ENABLED – enable VK_KHR_present_wait usage (0 / 1).
 VK_PRESENT_MODE – preferred present mode (mailbox, fifo, immediate, etc.).
 VK_WSI_MODE – preferred WSI integration (wayland, xcb, xlib).
 ANGLE_DEFAULT_PLATFORM – vulkan, opengl, etc.
 ANGLE_FEATURE_OVERRIDES_ENABLED – e.g. prefer_vulkan.
 ANGLE_PLATFORM / ANGLE_PLATFORM_FEATURES – ANGLE back-end + features.
 GDK_DISABLE / GDK_VULKAN_DISABLE – disable specific GTK graphics features.
 VK_ICD_FILENAMES – explicit driver JSONs list.
 __VK_LAYER_NV_optimus – e.g. NVIDIA_only for Optimus routing.
 VK_LAYER_PATH / VK_LOADER_DISABLE_LAYER_MESA / VK_LOADER_LAYERS_DISABLE – loader layer control.
 MESA_VK_DEVICE_SELECT – force specific GPU (e.g. pci:10de:2820).
 VK_INSTANCE_LAYERS – explicit layers list (e.g. VK_LAYER_MESA_device_select).
 X11 / Xwayland (x11.conf)
 X11 / Xwayland (x11.conf)
 WLR_EGL_NO_X11 – disable using X11 for EGL (0 / 1).
 WLR_X11_NO_ATOMS – avoid querying X11 atoms (0 / 1).
 XCURSOR_SIZE – cursor size in pixels (integer).
 XWAYLAND_NO_GLAMOR – disable glamor acceleration in Xwayland (0 / 1).