

Lecture 4

Regular Expressions/ Classes

Lecturer: Pieter De Bleser
Bioinformatics Core Facility, IRC




Regular Expressions

Introduction to regular expressions

- In bioinformatics we often work with strings
- Regex: highly specialized “language” for matching strings
- In python: the re module
- Perl-style regular expressions
- Useful for scripts, shell scripts and command line
- In unix: “grep -P” uses similar commands
- In R: grepl, grep: set perl=TRUE

Why?



/([li]f[and])* [AC]+.(and)?/

"...might," the candid hero admitted; "though such obtuseness could certainly be phenomenal. Still, the event is *possible*. So I must ask you to grant one more Hypothetical."

"Very good. I'm quite willing to grant it, as soon as you've written it down. We will call it

(D) If A and B and C are true, Z must be true.

"Have you entered that in your note-book?"

"I have!" Achilles joyfully exclaimed, as he ran the pencil into its sheath. "And at last we've got to the end of the ideal race-course! Now that you accept A and B and C and D, of course you accept Z."

"Do I?" said the Tortoise innocently. "Let's make that quite clear. I accept A and B and C and D. Suppose I *still* refuse to accept Z?"

"Then Logic would take you by the throat, and force you to do it!"

Achilles triumphantly replied. "Logic would tell you 'You can't help yourself. Now that you've accepted A and B and C and D, you must accept Z!' So you've no choice, you see."

```
<div class="PopUpBody">
<p>Our price is below the manufacturer's suggested price and at
<p>Please click <strong>Keep in Cart</strong> to purchase this i
<div style="border-top:1px solid #CCC;border-bottom:1px solid #C

<div class="Price4XL">$599.00</div>
<div style="margin-top:5px">List Price: <span style="text-decora
<div class="BodyMBold">You Save: $100.00  (14%)</div>
</div>
<div class="BodyMBold" style="margin:0 190px 0 110px">Nikon D310
<p class="clear"><!-- --></p>
</div>
<div style="text-align:right">
<a href="javascript:window.close();"><
<a href="JavaScript:handlePCStuff();"></a>
</div>
```


Simple example

- The simple way: use `re.search()`
- `re.search(pattern, string, flags=0)`
- Scan through *string* looking for a location where *pattern* produces a match, and return a corresponding **'Match object'** instance.
- Returns `None` if no position in the string matches the pattern

```
>>> import re
>>> re.search("hello", "oh, hello") != None
True
>>> re.search("hello", "oh, hwello") != None
False
>>> re.search("hello", "oh, Hello") != None
False
```

Outline

- Simple matching: basic rules
 - Some python issues
- Compiling expressions
- Additional methods
- The returned object
 - Getting more than one match
- Advanced stuff
 - Grouping options
 - Modifying strings



<https://xkcd.com/208/>

Metacharacters

- Character class: a set of characters we want to match
- Specified by writing in []
- Examples:
 - [abc], the same as [a-c]

```
>>> re.match('[abcd]', "d") != None
True
>>> re.match('[a-d]', "d") != None
True
```

- Use completing set:
 - [^5] – match everything but 5

```
>>> re.match('[^abcd]', "d") != None
False
>>> re.match('[^abcd]', "e") != None
True
```

The backslash \

- Regex:
 - Specifies defined classes
- In standard python:
 - Specifies escape characters (agreed patterns e.g. “\n”)
 - “\n”, “\t”, ...
- “Problems”
 - When we want to match metacharacters
 - Clashes between Python and re definitions
 - Let’s ignore these problems for now

Escape Sequence	Meaning
<code>\\</code>	Backslash (\)
<code>\'</code>	Single quote (')
<code>\"</code>	Double quote (")
<code>\a</code>	ASCII Bell (BEL)
<code>\b</code>	ASCII Backspace (BS)
<code>\f</code>	ASCII Form feed (FF)
<code>\n</code>	ASCII Linefeed (LF)
<code>\N{name}</code>	Character named <i>name</i> in the Unicode database (Unicode only)
<code>\r</code>	ASCII Carriage Return (CR)
<code>\t</code>	ASCII Horizontal Tab (TAB)
<code>\uxxxx</code>	Character with 16-bit hex value <i>xxxx</i> (Unicode only)
<code>\Uxxxxxxxx</code>	Character with 32-bit hex value <i>xxxxxxxx</i> (Unicode only)
<code>\v</code>	ASCII Vertical Tab (VT)
<code>\ooo</code>	Character with octal value <i>ooo</i>
<code>\xhh</code>	Character with hex value <i>hh</i>

Python built-in use: escape characters

These are standard strings identifiers, used by standard C

Backslash example:

```
>>> x = "aabb"
      File "<stdin>", line 1
        x = "aabb"
              ^
SyntaxError: invalid syntax
>>> x = "aabb"
>>> x
'aabb'
>>> x = "\"aabb\""
>>> x
'"aabb"'
```

Regex use: predefined classes

String	Class	Equivalent
\d	Decimal digit	[0-9]
\D	Non-digit	[^0-9]
\s	Any whitespace	[\t\n\r\f\v]
\S	Non-whitespace	[^ \t\n\r\f\v]
\w	Any alphanumeric	[a-zA-Z0-9_]
\W	Non alphanumeric	[^a-zA-Z0-9_]

These sequences can be included inside a character class. For example, `[\s,.]` is a character class that will match any whitespace character, or ',' or '.'.

Question

- Does a given DNA string contain a TATA-box-like pattern?
 - Define a TATA-box-like pattern as “TATAA” followed by 3 nucleotides and ends with “TT”

```
>>> import re
>>> def hasTataLike(string):
...     if (re.search("TATAA[ACGT][ACGT][ACGT]TT", string)):
...         return True
...     return False
...
>>> s = "ACGACGTTTACACGGATATAAGGGTTACGCGCTGTATAATGTGATCAGCTGATTCGAA"
>>> print (hasTataLike(s))
True
>>> s = "ACGACGTTTACACGGAAATAAGGGTTACGCGCTGTATAATGTGATCAGCTGATTCGAA"
>>> print (hasTataLike(s))
False
```

Matching any character

- The metacharacter “.” matches any character but newline.

```
>>> re.search("...", "ab\t") != None
True
>>> re.search("...", "ab\n") != None
False
>>> # Match two digits then any character then two non digits
>>> re.search("\d\d.\D\D", "98\tAD") != None
True
```

Repeats

- Character quantifiers:
 - “*” : the regex before can be matched zero or more times
 - `ca*t` matches `ct`, `cat`, `caat`, `caaaaaaat` ...
 - Matching is “greedy”: python searches for the largest match
 - “+” : one or more times
 - `ca+t` matches `cat` but not `ct`
 - “?” once or zero times
- Specifying a range:
 - `{m,n}`: at least `m`, at most `n`
 - “`a/{1,3}b`” will match `a/b`, `a//b`, and `a///b`. It won’t match `ab`.
 - Omitting `m` is interpreted as a lower limit of 0, while omitting `n` results in an upper bound of infinity

Examples

- **.** – any single character except a newline
 - **bet.y** would match “betty”, “betsy” but not “bety”
 - **3\1415** if the dot is what you’re after
- ***** - match the preceding character 0 or more times.
 - **fred\t*barney** matches fred, then any number of tabs, then barney. “fredbarney” is also matched
 - **.*** matches any character (other than newline) any number of times

Examples

- **+** is another **quantifier**, same as *****, but the preceding items has to be matched **>0** times
 - **fred +barney** - arbitrary number of spaces between fred and barney, but at least one
- **?** is another quantifier, this time meaning that zero or one matches are needed
 - **bamm-?bamm** will match “bamm**bamm**” and “bamm-bamm”, but only those two
 - Useful for optional prefix or suffix

Question

- Does a given DNA string contain a TATA-box-like pattern?
 - Define a TATA-box-like pattern as “TATAA” followed by 3 nucleotides and ends with “TT”

```
>>> import re
>>> def hasTataLike(string):
...     if (re.search("TATAA[ACGT]{3}TT", string)):
...         return True
...     return False
...
>>> s = "ACGACGTTTACACGGATATAAGGGTTACGCGCTGTATAATGTGATCAGCTGATTCGAA"
>>> print (hasTataLike(s))
True
>>> s = "ACGACGTTTACACGGAAATAAGGGTTACGCGCTGTATAATGTGATCAGCTGATTCGAA"
>>> print (hasTataLike(s))
False
```


Grouping patterns

- () are a grouping meta-character
 - **fred+** matches freddddddd
 - **(fred)+** matches fredfredfredfred
 - **(fred)***
 - matches “Hello world” (or anything)

Question

At least two TATA like patterns?

```
>>> def multipleTataLike(string):  
...     if (re.search("(TATAA[ACGT]{3}TT).*(TATAA[ACGT]{3}TT)", string)):  
...         return True  
...     return False  
...  
>>>  
>>> s = "GATATAAGGGTTACGCGCTATAAGGGTTTTTTTTGTATAATGTGATCAGCTGATTTCGAA"  
>>> print (multipleTataLike(s))  
True  
>>> s = "ACGACGTTTACACGGAAATAAGGGTTACGCGCTGTATAATGTGATCAGCTGATTTCGAA"  
>>> print (multipleTataLike(s))  
False
```

Alternatives

- **|** allows to separate between options
- **fred|barney|betty** means that the matched string must contain fred **or** barney **or** betty
- **fred(|\t)+barney** matches fred and barney separated by one or more space/tab
 - **fred(+|\t+)barney (?)**
 - Similar, but either all spaces or all tabs
 - **fred (and|or) barney (?)**
 - Matches “fred and barney” and “fred or barney”

Anchors

- \A
 - Match from the beginning of the string

```
>>> re.search('\AProsper', 'Prosper and live well') != None
True
>>> re.search('\AProsper', 'Party and live well') != None
False
>>> re.search('\APros', 'Pro') != None
False
>>> re.search('\APros', 'Prospe') != None
True
>>> re.search('\APros.+', 'Prosper and') != None
True
```

Anchors

- `\Z`
 - Match from the end of the string

```
>>> re.search('}\Z', '{block}') != None
True
>>> re.search('}\Z', '{block} ') != None
False
>>> re.search('}\Z', '{block}\n') != None
False
```

More anchors

- `^`
 - Match the beginning of lines
- `$`
 - Match the end of lines
- Don't forget to set the MULTILINE flag (more on flags later)

`findall()` matches *all* occurrences of a pattern, not just the first one as `search()` does

```
>>> gene_scores = "AT5G42600\t12.254\nAT1G08200\t302.1\n"
>>> print (gene_scores)
AT5G42600 12.254
AT1G08200 302.1

>>> re.findall("(\d+)$", gene_scores, re.MULTILINE)
['254', '1']
>>> re.findall("(\d)$", gene_scores)
['1']
```

Matching metacharacters

- Say we want to match the regex: (...\${2,5}...)

```
>>> re.search("(...${2,5}...)", "(ACG$$$$GCT)")
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "/home/pieterdb/anaconda3/lib/python3.7/re.py", line 183, in search
    ...
  File "/home/pieterdb/anaconda3/lib/python3.7/sre_parse.py", line 651, in
_parse
    source.tell() - here + len(this))
re.error: nothing to repeat at position 5
```

Use “\” before each metacharacter

Matching metacharacters

- Say we want to match the regex: (...\${2,5}...)

```
>>> re.search("\(...\${2,5}...\)", "(ACG$$$$GCT)") != None
True
>>> re.search("(...\${2,5}...)", "ACG$$$$GCT") != None
True
>>> re.search("\(...\${2,5}...\)", "ACG$$$$GCT") != None
False
```


The backspace plague

- “\” has a special use also in Python (not the re module)

```
>>> x="\\"
      File "<stdin>", line 1
        x="\\"
            ^
SyntaxError: EOL while scanning string literal
>>> x = "\\\"
>>> x
'\\'
>>> print (x)
\
```

The backspace plague

- Regular expressions use the backslash character ('\') to indicate special cases.
- This conflicts with Python's usage of the same character for the same purpose in string literals.

```
>>> y = "\section"  
>>> y  
'\\section'  
>>> print(y)  
\\section
```

The backspace plague

- Say we want to match “\section”

```
>>> re.search("\section", "\section") != None
False
>>> re.search("\\section", "\ section") != None
True
>>> re.search("\\section", "\section") != None
False
>>> re.search("\\\\section", "\section") != None
True
```

- One has to write '\\\\' as the RE string, because the regular expression must be \\, and each backslash must be expressed as \\ inside a regular Python string literal.



Using raw strings

- In Python, strings that start with r are raw, and “\” is not treated as a special character

```
>>> l = "\n"
>>> l
'\n'
>>> print(l)
```

```
>>> l=r"\n"
>>> l
'\\n'
>>> print(l)
\n
```

Using raw strings

- In Python, strings that start with `r` are raw, and “\” is not treated as a special character

```
>>> re.search(r"\\section","\section") != None
False
>>> re.search(r"\section","\section") != None
False
>>> re.search(r"\\section","\section") != None
True
```

When you really need “\” in your strings work with raw strings!

Compiling expressions

- Create an object that represents a specific regex and use it later on strings.

```
>>> p = re.compile('[a-z]+')
>>> p
re.compile('[a-z]+')
>>> print(p.match(""))
None
>>> m = p.match('tempo')
>>> m
<re.Match object; span=(0, 5), match='tempo'>
```

Compile vs. Static use

- Same rules for matching.
- The static use: Python actually compiles the expression and uses the result
 - When are going to the same expression many times compile once.
 - Running time difference is usually minor.
- Safer and more readable code
 - A good habit: compile all expression once in the same place, and use them later.
 - Reusable code, reduce typos.

Additional methods

Method/ Attribute	Purpose
match()	Determine if the RE matches at the beginning of the string.
search()	Scan through a string, looking for any location where this RE matches.
findall()	Find all substrings where the RE matches, and returns them as a list.
finditer()	Find all substrings where the RE matches, and returns them as an <u>iterator</u> .

The match object

- Both `re.search` and `p.search` (or `match`) return a match object.
 - Always has a `True` boolean value
 - The method `re.finditer` returns an iterable datastructure of match objects.
 - Useful methods:

Method/Attribute	Purpose
<code>group()</code>	Return the (sub)string matched by the RE
<code>start()</code>	Return the starting position of the match
<code>end()</code>	Return the ending position of the match
<code>span()</code>	Return a tuple containing the (start, end) positions of the match

Getting many matches

```
>>> p = re.compile('\d+')
>>> p.findall('12 drummers drumming, 11 pipers piping, 10 lords a-leaping')
['12', '11', '10']
>>> iterator = p.finditer('12 drummers drumming, 11 ... 10 ...')
>>> iterator
<callable_iterator object at 0x7f0c754d5d68>
>>> for match in iterator:
...     print (match.span())
...
(0, 2)
(22, 24)
(29, 31)
```

Compilation flags

- Add flexibility in the regex definition (at compilation time)
- Using more than one flag: add or between them
- Ignore case:
- Using re

```
>>> re.search("he", "Hello", re.IGNORECASE)
<re.Match object; span=(0, 2), match='He'>
>>> p = re.compile("he", re.IGNORECASE)
>>> p
```

- Using compilation

```
re.compile('he', re.IGNORECASE)
>>> p.search("Hello")
<re.Match object; span=(0, 2), match='He'>
```

Compilation flags

- Locale:
 - Used for non-English chars (not relevant for this course)
- Multiline (re.MULTILINE)
 - When this flag is specified, ^ matches at the beginning of the string and at the beginning of each line within the string, immediately following each newline.
 - Similarly, the \$ metacharacter matches either at the end of the string and at the end of each line (immediately preceding each newline).
- DOTALL
 - Makes the '.' special character match any character at all, **including a newline**

Grouping: getting sub-expressions

- Groups indicated with '(', ')' also capture the starting and ending index of the text that they match.
- This can be retrieved by passing an argument to `group()`, `start()`, `end()`, and `span()`.
- Groups are numbered starting with 0. Group 0 is always present; it's the whole RE.
- Subgroups are numbered from left to right, from 1 upward.
- Groups can be nested; to determine the number, just count the opening parenthesis characters, going from left to right.

Example 1

What will span(X) return here?

```
>>> print (re.search("(ab)*AAA(cd)*", "ababAAAc").span())
(0, 9)
>>> print (re.search("(ab)*AAA(cd)*", "ababAAAc").group(0))
ababAAAc
>>> print (re.search("(ab)*AAA(cd)*", "ababAAAc").group(1))
ab
>>> print (re.search("(ab)*AAA(cd)*", "ababAAAc").group(2))
cd
>>> print (re.search("(ab)*AAA(cd)*", "ababAAAc").group(3))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
IndexError: no such group
```

Example 2

```
>>> p = re.compile('(a(b)c)d')
>>> m = p.match('abcd')
>>> m.group(0)
'abcd'
>>> m.group(1)
'abc'
>>> m.group(2)
'b'
```

- `group()` can be passed multiple group numbers at a time, in which case it will return a tuple containing the corresponding values for those groups.

```
>>> m.group(2,1,2)
('b', 'abc', 'b')
```

Example 3

- The groups() method returns a tuple containing the strings for all the subgroups, from 1 up to however many there are.

```
>>> m.groups()  
('abc', 'b')  
>>> len (m.groups())  
2
```


Example 4

- The `groups()` method returns a tuple containing the strings for all the subgroups, from 1 up to however many there are.

```
>>> re.match("A(B+)C", "ABBBBBC").groups()  
( 'BBBBB', )  
>>> re.match("A(B+)C", "ABBBBBC").span(1)  
(1, 6)
```

Modifying strings

Method/ Attribute	Purpose
split()	Split the string into a list, splitting it wherever the RE matches
sub()	Find all substrings where the RE matches, and replace them with a different string

Split

- Parameter: `maxsplit`
 - When *maxsplit* is nonzero, at most *maxsplit* splits will be made.
- Use `re.split` or `p.split` (`p` is a compiled object)

```
>>> p = re.compile(r'\W+')
>>> p.split('This is a test, short and sweet, of split().')
['This', 'is', 'a', 'test', 'short', 'and', 'sweet', 'of',
'split', '']
>>> p.split('This is a test, short and sweet, of split().', 3)
['This', 'is', 'a', 'test, short and sweet, of split().']
```

String	Class	Equivalent
<code>\d</code>	Decimal digit	<code>[0-9]</code>
<code>\D</code>	Non-digit	<code>[^0-9]</code>
<code>\s</code>	Any whitespace	<code>[\t\n\r\f\v]</code>
<code>\S</code>	Non-whitespace	<code>[^\t\n\r\f\v]</code>
<code>\w</code>	Any alphanumeric	<code>[a-zA-Z0-9_]</code>
<code>\W</code>	Non alphanumeric	<code>[^a-zA-Z0-9_]</code>

Split

- Sometimes we also need to know the delimiters.
- Add parentheses in the RE!
- Compare the following calls:

```
>>> p = re.compile('\W+')
>>> p.split('This... is a test.')
['This', 'is', 'a', 'test', '']
>>> p2 = re.compile('(\W+)')
>>> p2.split('This... is a test.')
['This', '...', 'is', ' ', 'a', ' ', 'test', '.', '']
```

Search and replace

- Find matches and replace them.
- Usage: `.sub(replacement, string[, count=0])`
- Returns a new string.
 - If the pattern is not found string is return unchanged
 - count: optional
 - Specifies the maximal number of replacements (when it is positive)

Search and replace - examples

```
>>> p = re.compile( '(blue|white|red)')
>>> p.sub( 'color', 'blue socks and red shoes')
'color socks and color shoes'
>>> p.sub( 'color', 'blue socks and red shoes', count=1)
'color socks and red shoes'

>>> p = re.compile('x*')
>>> p.sub( '- ', 'abxd')
'-a-b--d-'
```

Empty matches are replaced only when they're not adjacent to a previous match:

```
>>> re.sub("a|x*", '- ', 'abcd')
'- -b-c-d-'
```

Naming groups

- Sometimes we use many groups
- Some of them should have meaningful names
- Syntax: (?P<name>...)
 - The '...' is where you need to write the actual regex

```
>>> p = re.compile(r'\W*(?P<word>\w+)\W*')
>>> m = p.search( '(((( Lots of punctuation )))' )
>>> m.group('word')
'Lots'
>>> m.group(1)
'Lots'
>>> m = p.finditer('(((( Lots of punctuation )))')
>>> for match in m:
...     print(match.group('word'))
...
Lots
of
punctuation
```

Backreferences

- Regex within regex
- Specify that the contents of an **earlier capturing group** must\can also be found at the current location in the string.
- \1 will succeed if the exact contents of group 1 can be found at the current position, and fails otherwise.
- Remember that Python's string literals also use a backslash followed by numbers to allow including arbitrary characters in a string
 - **Be sure to use a raw strings!**

Example

- Explain this:

```
>>> p = re.compile(r'\W+(\w+)\W+\1')  
>>> p.search('Paris in the the spring').group()  
' the the'
```

Backreferences with names

- Syntax: use (?P=name) instead of \number
- In one regex do not use both numbered and named backreferences!

```
>>> p = re.compile(r'\W+(\w+)\W+\1')
>>> p.search('Paris in the the spring').group()
'the the'
>>> p = re.compile(r'(?P<word>\b\w+)\s+(?P=word)')
>>> p.search('Paris in the the spring').group()
'the the'
```

Pattern matching

A very sophisticated kind of logical test is to ask whether a string contains a ***pattern***
e.g. does a yeast promoter sequence contain the MCB binding site, ACGCGT?

```
name = 'YBR007C'  
dna = 'TAATAAAAAACGCGTTGTCG'  
if 'ACGCGT' in dna:  
    print('%s has MCB!' % name)
```

20 bases upstream of the yeast gene YBR007C

YBR007C has
MCB!

The membership operator **in**

The pattern for the MCB binding site

Regular expressions

We already defined a simple pattern: `ACGCGT`

What if we don't care about the 3rd position?

`ACGCGT` `ACCGGT` `ACACGT` `ACTCGT`

- Python provides a pattern-matching engine
- Patterns are called regular expressions
- They are extremely powerful
- Often called "regexps" for short
- module `re`

Motivation: N-glycosylation motif

- Common post-translational modification
- Attachment of a sugar group
- Occurs at asparagine residues with the consensus sequence NX1X2, where
 - X1 can be anything (but proline inhibits)
 - X2 is serine or threonine
- Can we detect potential N-glycosylation sites in a protein sequence?

Building regexps I: Character Groups

- In general square brackets denote a set of alternative possibilities
 - E.g. **[abc]** -> matches a,b, or c
- Use - to match a range of characters: **[A-Z]**
- Negation : **[^X]** matches anything but X
- **.** matches anything

Building regexps II: Abbreviations

- **\d** matches any decimal digits [0-9]
- **\D** matches any non-digit [^0-9]
- Equivalent syntax for ...
 - whitespaces (**\s** and **\S**)
 - alphanumeric (**\w** and **\W**)

Building regexps III: Repetitions

- Use `*` to match none or any number of times
 - E.g. `ca*t` matches: `ct`, `cat`, `caat`, `caaat`, `caaaat`, ...
- Use `+` to match one or any number of times
 - E.g. `ca+t` matches `cat`, `caat`, `caaat`, `caaaat`, ...
- Use `?` to match none or once
 - E.g. `bio-?info` matches `bioinfo` and `bio-info`
- Use `{m, n}` to specifically set the number of repetitions (min `m`, max `n`)
 - E.g. `ab{1, 3}c` will match `abc`, `abbc`, `abbbc`

Using regular expressions

- Compile a regular expression object (pattern) using `re.compile`
- pattern has a number of methods
 - `match` (in case of success returns a Match object, otherwise None)
 - `search` (scans through a string looking for a match)
 - `findall` (returns a list of all matches)

```
>>> import re
>>> pattern = re.compile('[ACGT]')
>>> if pattern.match("A"): print("Matched")
Matched
>>> if pattern.match("a"): print("Matched")
>>>
```


successful match

unsuccessful, returns None
by def. case sensitive

Matching alternative strings

- `/(this|that)/` matches "this" or "that"
- ...and is equivalent to: `/th(is|at)/`

case insensitive search pattern



```
>>> import re
>>> pattern=re.compile("(this|that|other)", re.IGNORECASE)
>>> pattern.search("Will match THIS") ## success
<re.Match object; span=(11, 15), match='THIS'>
>>> pattern.search("Will also match THat") ## success
<re.Match object; span=(16, 20), match='THat'>
>>> pattern.search("Will not match ot-her") ## will return None
>>>
```

Python returns a description of the match object

Word and string boundaries

`^` matches the start of a string

`$` matches the end of a string

`\b` matches word boundaries

“Escaping” special characters

- `\` is used to "escape" characters that otherwise have meaning in a regexp
- so `\[` matches the character "["
 - if not escaped, "[" signifies the start of a list of alternative characters, as in `[ACGT]`
 - All special characters: `. ^ $ * + ? { [] \ | ()`

Substitutions/Match Retrieval

- regexp methods can be used without compiling (less efficient but easier to use)

→ Example `re.sub` (substitution):

```
>>> re.sub("(red|blue|green)", "color", "blue socks and red shoes")  
'color socks and color shoes'
```

```
>>> e,raw,frm,to = re.findall("\d+", \  
... "E-value: 4, \  
... Raw Bit Score: 165, \  
... Match position: 362-419")  
>>> print(e, raw, frm, to)  
4 165 362 419
```

matches one or more digits

The result, a list of 4 strings,
is assigned to 4 variables

`\` allows multiple line commands
alternatively, construct multi-line
strings using triple quotes `""" ... """`

N-glycosylation site detector

```
import re

protein="MGMFFNLRSNIAKKKAMDNGLSLPISRNGSSNNIKDKRSEHNSNSLKGKYRYQPRSTPSKFQLTVSITSLI \
IIAVLSLYLFISFLSGMGIGVSTQNGRSLLGSSKSSSENYKTIDLEDEEYYDYDFEDIDPEVISKFDDGVQ \
HYLISQFGSEVLTPKDDEKYQRELNMLFDSTVEEYDLSNFEGAPNGLETRDHILLCIPLRNAADVLPMLF \
KHLMNLTYPHELIDLAFLVSDCSEGDTTLDALIAYSRHLQNGTLSQIFQEIDAVIDSQTKGTDKLYLKYM \
DEGYINRVHQAFSPPFHENYDKPFRSVQIFQKDFGQVIGQGFSRHAVKVQGIRRKLMGRARNWLTANAL \
KPYHSWVYWRDADVELCPGSVIQDLMSKNYDVI".upper().replace("\n", "")

for match in re.finditer("N[^P][ST]" + protein):
    print(match.group(), match.span())
```

`re.finditer`
provides an iterator
over match-objects

`N[^P][ST]`
- the main regular
expression

`> python3 nglycosylation.py`
NGS (26, 29)
NLT (217, 220)
NGT (253, 256)

`match.group` and `match.span` print the actual matched string and the position-tuple.

Exercise

Modify the previous script such that it accepts a Fasta-formatted sequence via the CLI and returns location(s) and sequence(s) of putative N-glycosylation sites in this sequence. Use subroutines.


Desired behaviour:

```
> python3 nglycosylation.py P18892.fasta
>sp|P18892|BT1A1_BOVIN Butyrophilin subfamily 1 member A1 OS=Bos taurus GN=BTN1A1 PE=1
SV=2; length:526 bp
MAVFPNSCLAGCLLIFILLQLPKLDSAPFDVIGPQEPILAVVGEDAELPCRLSPNVSAKGMELRWFREKVSPAVFVSREGQEQEGEEMAE
YRGRVSLVEDHIAEGSVAVRIQEVKASDDGEYRCFFRQDENYEEAIVHLKVAALGSDPHISMKVQESGEIQLECTSVGWYPEPQVQWRTH
RGEEFPSMSERNPDDEGLFTVRASVIIRDSSMKNVSCCIRNLLLGQEKEVEVSIPASFFPRLTPWMVAVAVILVVLGLLTIGSIFFTWR
LYKERSRQRRNEFSSKEKLLEELKWKRATLHAVDVTLPDPTAHPHLFLYEDSKSVRLEDSRQKLPEKPERFDSWPCVMGREAFTSGRHYW
EVEVGDRTDWAIGVCRENVMKKGFDPMPENGFWAVELYGNGYWALTPLRTPPLAGPPRRVGVFLDYESGDIFFYNMTDGSHIYTFSKA
SFSGPLRPFFCLWSCGKKPLTICPVTGLEGVMVADAKDISKEIPLSPMGEDSASGDIETLHSKLIPLQPSQGVP
Potential N-glycosylation sequence NVS at residue 55
Potential N-glycosylation sequence NVS at residue 215
Potential N-glycosylation sequence NMT at residue 437
```

Test your Regular Expressions

www.pythex.org

- Develop regular expressions
- Test them on examples of your choice



2REG
10sn
1VSN
9ins

PDB IDs

`([1-9][A-Za-z0-9]{3})`

Summary

- **Regular expression** as powerful tools to match patterns
- Allow matching of character groups, repetitions, alternatives, etc.
- Learn the meaning of special characters: . ^ \$ * + ? { [] \ | ()
- Python offers **regex** functions in the **re** module: match, search, findall, compile, etc.
- Regular expressions can be used to find motifs in sequences


Dictionaries (hashes)

- Hash tables are efficient data structures for looking up values of specific entries
- Conveniently, Python provides this type of array called a dictionary
- A dictionary is a set of key:value pairs
 - like in a phone book

Squared brackets [] are used to index a dictionary

phone_book["Donald Trump"] = "666-666666"

How does a dictionary work?



Keys and Values

- `keys` returns the list of keys in the hash
 - e.g. `names`, in the `name2seq` hash
- `values` returns the list of values
 - e.g. `sequences`, in the `name2seq` hash

Getting familiar with hashes

```
>>> phones={"Adrian":9063,\
... "Barry":9065,\
... "Theresa":9090 }
>>> phones.keys()
dict_keys(['Adrian', 'Barry', 'Theresa'])
>>> phones.values()
dict_values([9063, 9065, 9090])
>>> phones["Adrian"]
9063
>>> "Jeff" in phones
False
>>> phones["Jeff"] = 9999
>>> "Jeff" in phones
True
```

- ← Creating an initial phone book
- ← Asking for all keys
- ← Asking for all values
- ← Asking for a value, given a key
- ← Checking whether a key is in the list
- ← Inserting a single key:value pair
- ← Checking whether a key is in the list

Looping through the dictionary

```
>>> for name in phones.keys():
...     print(name, phones[name])
...
```

Adrian 9063
Barry 9065
Theresa 9090
Jeff 9999

Application: read csv file into a hash

list.csv

Julian	Alaphilippe	100
Kasper	Asgreen	101
Dries	Devenyns	102
Yves	Lampaert	103
Enric	Mas	104
Michael	Mørkøv	105
Maximilian	Richeze	106
Elia	Viviani	107

read_file_to_hash.py

```
def read_file(filename):  
    phonebook = {}  
    with open(filename, "r") as f:  
        for line in f.readlines()[1:]:  
            name, lastname, number=line.strip().split("\t")  
            phonebook[name]=number  
    return phonebook  
  
print( read_file("list.csv") )
```

```
> python3 read_file_to_hash.py  
{'Kasper': '101', 'Dries': '102', 'Yves': '103', 'Enric': '104', 'Michael': '105', 'Maximilian': '106',  
'Elia': '107'}
```

The genetic code as a hash

```
aa = {'ttt':'F', 'tct':'S', 'tat':'Y', 'tgt':'C',  
      'ttc':'F', 'tcc':'S', 'tac':'Y', 'tgc':'C',  
      'tta':'L', 'tca':'S', 'taa':'!', 'tga':'!',  
      'ttg':'L', 'tcg':'S', 'tag':'!', 'tgg':'W',  
  
      'ctt':'L', 'cct':'P', 'cat':'H', 'cgt':'R',  
      'ctc':'L', 'ccc':'P', 'cac':'H', 'cgc':'R',  
      'cta':'L', 'cca':'P', 'caa':'Q', 'cga':'R',  
      'ctg':'L', 'ccg':'P', 'cag':'Q', 'cgg':'R',  
  
      'att':'I', 'act':'T', 'aat':'N', 'agt':'S',  
      'atc':'I', 'acc':'T', 'aac':'N', 'agc':'S',  
      'ata':'I', 'aca':'T', 'aaa':'K', 'aga':'R',  
      'atg':'M', 'acg':'T', 'aag':'K', 'agg':'R',  
  
      'gtt':'V', 'gct':'A', 'gat':'D', 'ggt':'G',  
      'gtc':'V', 'gcc':'A', 'gac':'D', 'ggc':'G',  
      'gta':'V', 'gca':'A', 'gaa':'E', 'gga':'G',  
      'gtg':'V', 'gcg':'A', 'gag':'E', 'ggg':'G' }
```

Application: Translating DNA into protein

dna_to_protein.py

```
import sys

def translate(dna):
    length = len(dna)
    if len(dna) % 3 != 0:
        print( "Warning: Length is not a multiple of 3!" )
        sys.exit()
    protein = ""
    i = 0
    while i < length:
        codon = dna[i:i+3]
        #print( codon )
        if not codon in aa:
            print( "Codon ",codon," is illegal" )
            sys.exit()
        protein += aa[codon]
        i+=3
    return protein

print( translate("gatgacgaaagttgt") )
#print( translate("gatgacgaaagttgta") )
print( translate("gatgacgiaagttgt") )
```




```
> python3 dna_to_protein.py
DDESC
Codon  gia  is illegal
```

Application: Counting residue frequencies

count_residues.py

```
def count_residues(seq):
    freq={}
    seq = seq.lower()
    for res in seq:
        if res in freq:
            freq[res]+=1
        else:
            freq[res]=1
    return freq


freq =
count_residues("gatgacgaaagtgt")
for residue in freq.keys():
    print(residue,":", freq[residue])
```



```
> python3 count_residues.py
g : 5
a : 5
t : 4
c : 1
```


Application: Counting N-mer frequencies

```
def count_nmers(seq, n):  
    freq={}  
    seq = seq.lower()  
    for i in range(len(seq)-n+1):  
        nmer=seq[i : i+n]  
        if nmer in freq:  
            freq[nmer]+=1 # incr. counter  
        else: freq[nmer]=1 # first  
occurrence  
    return freq  
  
freq = count_nmers("gatgacgaaagttgt", 2)  
for residue in freq.keys():  
    print(residue,":", freq[residue])
```




```
> python3 count_nmers.py  
ga : 3  
at : 1  
tg : 2  
ac : 1  
cg : 1  
aa : 2  
ag : 1  
gt : 2  
tt : 1
```

Classes

- A class is a collection of related variables and functions
- Object-oriented programming
- A class is a blueprint for objects
- E.g. a class for cars
 - Properties: color, transmission, gears, type
 - Methods: start, break, open_trunk, etc.

Objects => “Real World” Instances



https://cgfrog.com/wp-content/uploads/2015/11/Audi-A3-2013-cgfrog_com_2.png

Class => “Blueprint” / Specifications

Properties

num_of_wheels
manufacturer
color
size
age

Functions

run()
stop()



https://upload.wikimedia.org/wikipedia/commons/thumb/5/59/2013_Volkswagen_Golf_SE_BlueMotion_Technology_1.4_Front.jpg/2560px-2013_Volkswagen_Golf_SE_BlueMotion_Technology_1.4_Front.jpg

num_of_wheels = 4
manufacturer = “Volkswagen”
color = “grey”
size = “medium”
Age = 3

run()
stop()



[https://en.wikipedia.org/wiki/File:2018_Ford_Escape_\(ZG\)_Trend_AWD_wagon_\(2018-10-29\)_01.jpg](https://en.wikipedia.org/wiki/File:2018_Ford_Escape_(ZG)_Trend_AWD_wagon_(2018-10-29)_01.jpg)

num_of_wheels = 4
manufacturer = “Ford”
color = “white”
size = “medium”
Age = 3

run()
stop()



https://upload.wikimedia.org/wikipedia/commons/thumb/d/d6/2017_Alfa_Romeo_Stelvio_Milano_Edizione_TD_Automatic_2.1.jpg/420px-2017_Alfa_Romeo_Stelvio_Milano_Edizione_TD_Automatic_2.1.jpg

num_of_wheels = 4
manufacturer = “Alfa Romeo”
color = “red”
size = “big”
Age = 1

run()
stop()

Properties

Functions

Properties

Functions

Properties

Functions

Syntax

car_class.py

```
# class definition
class Car:
    def __init__(self, manufacturer, color, size, age):
        num_of_wheels = 4
        self.manufacturer = manufacturer
        self.color = color
        self.size = size
        self.age = age

    def run(self):
        print("Brummmmm!")

    def stop(self):
        print("Eeeeeek!")

# class instances
alfa = Car("Alfa Romeo", "red", "medium", None)
mini = Car("Ford", "blue", "small", 3)

mini.run()
print(mini.color)
mini.age += 1
print(mini.age)
```



```
> python3 car_class.py
Brummmmm!
blue
4
```

Classes

```
class <classname>:  
statement_1  
.  
.  
statement_n
```

The methods of a class get the instance as the first parameter traditionally named **self**

The method **__init__** is called upon object construction (if available)

Classes

- Reminder: ***type*** = **data** representation + behaviour
- **Classes are user-defined types.**

```
class <classname>:  
statement_1  
.  
.  
statement_n
```

- **Objects** of a class are called **class instances**.

Example – multi_map

- A dictionary with more than one value for each key
- We could use something like:

```
>>> lst = d.get(key, [ ])
>>> lst.append(value)
>>> d[key] = lst
```

- We will now write a new **class** that will be a **wrapper** around a **dict**
- The class will have **methods** that allow us to keep **multiple values for each key**

multi_map.py

```
class multi_map:
    def __init__(self):
        '''Create an empty Multimap'''
        self.inner = dict()

    def get(self, key):
        '''Return list of values associated with key'''
        return self.inner.get(key, [])

    def put(self, key, value):
        '''Adds value to the list of values associated with key'''
        value_list = self.get(key)
        if value not in value_list:
            value_list.append(value)
            self.inner[key] = value_list

    def put_all(self, key, values):
        for v in values:
            self.put(key, v)

    def remove(self, key, value):
        value_list = self.get(key)
        if value in value_list:
            value_list.remove(value)
            self.inner[key] = value_list
            return True
        return False
```

```
m = multi_map()
m.put('Belgium', 'Brussels')
m.put('Belgium', 'Ghent')
m.put('Belgium', 'Antwerp')
m.put('Belgium', 'Bruges')
m.put('France', 'Paris')
m.put('France', 'Tours')
m.put_all('England', ('London', 'Manchester', 'Moscow'))
m.remove('England', 'Moscow')
print(m.get('Belgium'))
print(m.get('England'))
```

```
> python multi_map.py
['Brussels', 'Ghent', 'Antwerp', 'Bruges']
['London', 'Manchester']
```


Example: Reverse complement


[a:b:c] “Count in increment of **c** starting at **a** inclusive up to **b** exclusive”

reverse_comp.py

```
import string

def revcomp(seq):
    translation = str.maketrans("agct", "tcga")
    comp = seq.translate(translation)
    rcomp = comp[::-1] # reversing comp
    return rcomp

dna = "cggcgt"
rev = revcomp(dna)
print("Revcomp of %s is %s"%(dna, rev))
```



```
> python3 reverse_comp.py
Revcomp of cggcgt is acgccg
```



string formatted with place holders

Revcomp in a DNA class

`self` refers to the current object, gives access to all its variables

reverse_comp_class.py

```
import string

class DNA:
    def __init__(self, sequence):
        self.seq = sequence.lower()

    def revcomp(self):
        translation = str.maketrans("agct", "tcga")
        comp = self.seq.translate(translation)
        self.revcomp = comp[::-1]


    def report(self):
        print ("Revcomp of %s is %s"% (self.seq,self.revcomp))

dna = DNA("accggcatg")# Creating a DNA object
dna.revcomp()
dna.report()
```

Class
Constructor
saves input
sequence
as object
variable in
lower case



Method
Calls



Useful to structure code :

add additional DNA sequence functionality to this class

-> e.g. a function that calculates GC-contents, translation to protein etc.

Everything is an object

- Instances of lists, strings, etc. are objects with built-in methods
- Explore available methods using `dir`:

```
>>> dir("hello")
['__add__', '__class__', '__contains__', '__delattr__', '__dir__', '__doc__', '__eq__', '__format__',
 '__ge__', '__getattribute__', '__getitem__', '__getnewargs__', '__gt__', '__hash__', '__init__',
 '__init_subclass__', '__iter__', '__le__', '__len__', '__lt__', '__mod__', '__mul__', '__ne__', '__new__',
 '__reduce__', '__reduce_ex__', '__repr__', '__rmod__', '__rmul__', '__setattr__', '__sizeof__', '__str__',
 '__subclasshook__', 'capitalize', 'casefold', 'center', 'count', 'encode', 'endswith', 'expandtabs', 'find',
 'format', 'format_map', 'index', 'isalnum', 'isalpha', 'isascii', 'isdecimal', 'isdigit', 'isidentifier',
 'islower', 'isnumeric', 'isprintable', 'isspace', 'istitle', 'isupper', 'join', 'ljust', 'lower', 'lstrip',
 'maketrans', 'partition', 'replace', 'rfind', 'rindex', 'rjust', 'rpartition', 'rsplit', 'rstrip', 'split',
 'splitlines', 'startswith', 'strip', 'swapcase', 'title', 'translate', 'upper', 'zfill']
>>> help("hello".count)
Help on built-in function count:

count(...) method of builtins.str instance
    S.count(sub[, start[, end]]) -> int

    Return the number of non-overlapping occurrences of substring sub in
    string S[start:end]. Optional arguments start and end are
    interpreted as in slice notation.
>>> "hello".count("l")
2
```

String object Method

. (dot) applies method to object

Summary

- Use dictionaries if you need to lookup your values frequently in a program
- Dictionaries can store key-value pairs in a very efficient way using hash tables
- Use classes to organize related variables and methods into a shared structure
- Classes are blueprints for objects
- Everything in Python is an object