

GRA-Nulling as Verifiable Faith: Mathematical Model and Application Domains

bitsoev oleg

August 14, 2026

Abstract

This paper explores the hypothesis of GRA-nulling (Gödel–Reductio ad Absurdum) as a methodology for eliminating contradictions in networks of interconnected objects. We demonstrate that global verification of this hypothesis across the entire multiverse is computationally intractable and therefore belongs to the realm of faith rather than empirical science. However, within formally closed domains, GRA-nulling can be operationalized as an algorithm and subjected to rigorous testing. We present a mathematical model comprising an ontological foam functional, a GRA operator, and a convergence lemma. A verification methodology is outlined, and five application domains are described: self-assembling materials, resource management, generation of aesthetic forms, network topology optimization, and multi-agent systems. The work emphasizes the dual nature of GRA-nulling: as a metaphysical belief and as a potentially scientific method within bounded contexts.

Keywords: GRA, nulling, ontological foam, harmony, verification, simulation, multi-agent systems, optimization, aesthetics.

1 Introduction

Human cognition integrates two fundamental modes: belief and doubt (disbelief). Belief allows acceptance of unprovable assertions as guides for action, thereby cutting the “Gordian knot” of non-computability. Science, in contrast, demands empirical verification and falsification. The GRA-nulling hypothesis, which posits the existence of a state of ultimate harmony (Paradise) as an attractor of system dynamics, cannot be verified at the global scale (the entire multiverse) due to the uncountability of the space of possible worlds and our lack of access to them. Nevertheless, this hypothesis can be reformulated within a restricted context as a working algorithm amenable to empirical testing.

The aim of this paper is to formalize GRA-nulling as a mathematical model, derive conditions for its applicability, and propose a verification methodology in concrete domains while adhering to rigorous scientific standards.

2 Mathematical Formalization of GRA-Nulling

2.1 World as a Network of Objects

A world is modeled as a directed hypergraph $W = (O, E, X, \Theta)$, where

- $O = \{o_1, \dots, o_N\}$ is the set of objects;
- $E \subseteq O \times O$ is the set of links;
- X denotes the states of objects, and each object o_i is described by a vector of continuous parameters $\Psi_i \in \mathbb{R}^{p_i}$, a discrete axiomatics $a_i \in \mathcal{A}$, and a hierarchy level $h_i \in \{1, \dots, L\}$;
- Θ represents environment parameters.

2.2 Ontological Foam Functional

To quantify contradictions, we introduce the functional $J(W)$:

$$J(W) = \sum_{i=1}^N w_i C_{\text{int}}(\Psi_i)^2 + \sum_{(i,j) \in E} \lambda_{ij} \text{dist}(\Psi_i, L_{j \rightarrow i} \Psi_j)^2 + \gamma K_{\text{top}}(W) + R(W), \quad (1)$$

where:

- $C_{\text{int}}(\Psi_i)$ is a measure of internal inconsistency of object i ;
- $L_{j \rightarrow i}$ is an operator of projection/translation of the state of object j into the language of object i ;
- dist is a metric in the state space;
- $K_{\text{top}}(W)$ penalizes topological complexity (e.g., number of edges);
- $R(W)$ is a penalty for constraint violations and risks;
- $w_i, \lambda_{ij}, \gamma$ are positive weights.

The ‘‘Paradise’’ state (harmony) is defined as a point W^* such that $J(W^*) = 0$ and the Hessian $\nabla^2 J(W^*)$ is positive definite (a stable minimum).

2.3 GRA Operator

A GRA step consists of the following sequence:

1. **Detection** of the node with the largest local contradiction.
2. **Symbolic criticism**: formulation of a hypothesis about the cause of the contradiction (false axiom, erroneous link, etc.).
3. **Candidate generation** for revision (changes in continuous parameters, structure of links, discrete axioms).
4. **Evaluation** of the functional J for each candidate.
5. **Selection** of the candidate with minimal J while satisfying constraints.
6. **Propagation** of the change to neighboring nodes via operators $L_{j \rightarrow i}$.
7. **Stability check** after perturbations.

2.4 Convergence Lemma

Lemma 2.1 *If the GRA operator satisfies*

$$\mathbb{E}[J(W_{t+1}) \mid W_t] \leq (1 - \rho)J(W_t) + b,$$

where $0 < \rho < 1$ and $b \geq 0$, then

$$\mathbb{E}[J(W_t)] \leq (1 - \rho)^t J(W_0) + \frac{b}{\rho}.$$

By the law of total expectation,

$$\mathbb{E}[J(W_{t+1})] = \mathbb{E}[\mathbb{E}[J(W_{t+1}) \mid W_t]] \leq (1 - \rho)\mathbb{E}[J(W_t)] + b.$$

Denote $E_t = \mathbb{E}[J(W_t)]$. Then

$$E_{t+1} \leq (1 - \rho)E_t + b.$$

Unrolling the recursion yields

$$E_t \leq (1 - \rho)^t E_0 + b \sum_{k=0}^{t-1} (1 - \rho)^k.$$

The geometric sum is bounded by $1/\rho$, hence

$$\mathbb{E}[J(W_t)] \leq (1 - \rho)^t J(W_0) + \frac{b}{\rho}.$$

Remark 2.1 *The lemma guarantees a linear rate of convergence to a neighborhood of a minimum, but it does not prove that $J = 0$ is reached, nor does it establish uniqueness of the attractor or applicability to all possible worlds.*

3 Bounded Verification: Methodology

Global verification is impossible, but in specific domains where the state space is finite or parameterized, the functional J is computable, and GRA dynamics are implementable, rigorous experiments can be conducted.

3.1 General Experimental Scheme

For each domain:

1. Formalize W , J , and operators $L_{j \rightarrow i}$.
2. Define baseline methods (gradient descent, projected gradient descent, consensus, random repair, linear programming, etc.).
3. Fix an equal computational budget for all methods.
4. Perform multiple runs with different initial conditions (seeds).
5. Measure metrics (Section 3.2).
6. Perform statistical tests (bootstrap, permutation test) and compute confidence intervals.

3.2 Metrics

- Final functional J_{final} ;
- Violations of hard constraints;
- Convergence time (number of iterations until stabilization);
- Robustness after random and adversarial perturbations;
- Diversity of final solutions (e.g., variance of states);
- False-nulling index $F_{\text{null}} = P(J_{\text{final}} \leq \varepsilon \text{ and } Q_{\text{external}} < Q_{\text{baseline}})$, where Q_{external} is an external quality measure;
- Harmony index

$$\text{Harm} = a(-\bar{J}) + b(-\bar{R}) + c\bar{D} + d\bar{Q} + e\bar{T},$$

where $\bar{J}, \bar{R}, \bar{D}, \bar{Q}, \bar{T}$ are normalized averages of foam, risk, diversity, quality, and recovery time, respectively; coefficients are tuned via sensitivity analysis.

4 Verification Domains

4.1 Self-Assembling Metamaterials

Objects: nodes of a crystal lattice. **Links:** interatomic interactions. **Contradictions:** defects (vacancies, dislocations) – symmetry violations. **GRA step:** a local agent detects a defect, symbolically identifies the cause (e.g., local geometric mismatch), and rearranges neighboring bonds. **Metrics:** maximum stress, defect energy, recovery time, stability under cyclic loading. **Expected result:** GRA should reduce J faster than classical annealing while maintaining material strength.

4.2 Distributed Resource Management

Objects: consumers, energy sources, storage units. **Links:** transmission lines. **Contradictions:** overloads, supply–demand imbalances. **GRA step:** a node formulates a hypothesis about the cause of overload (e.g., erroneous forecast) and revises its local rule. **Metrics:** energy losses, fraction of unmet demand, recovery time after failure. **Baseline methods:** Linear Programming, Model Predictive Control, consensus. **Expected result:** GRA should provide better adaptation to load changes.

4.3 Generation of Aesthetic Forms

Objects: generative models (images, sound). **Contradictions:** visual/auditory noise, sharp transitions, violations of compositional rules. **GRA step:** symbolic criticism “Which assumption about the structure of the form is false?” followed by re-assembly. **Metrics:** smoothness, symmetry, complexity, novelty, diversity (absence of mode collapse). **Validation:** comparison with optimization for smoothness only and random generation; if possible, double-blind human study. **Expected result:** GRA forms should be more diverse and harmonious by proxy metrics, but this does not guarantee subjective happiness of the observer.

4.4 Network Topology Optimization

Objects: nodes of a communication network. **Links:** transmission channels. **Contradictions:** bottlenecks, cycles, redundant links. **GRA step:** a node proposes to remove/add a link based on symbolic analysis. **Metrics:** throughput, survivability under node removal, latency. **Baseline methods:** genetic algorithms, simulated annealing. **Expected result:** GRA should find more survivable topologies at equal cost.

4.5 Multi-Agent Systems

Objects: autonomous agents with local goals. **Links:** communication. **Contradictions:** goal conflicts, violation of global constraints. **GRA step:** an agent revises not only its parameters but also its behavioral rules (axioms). **Metrics:** total reward, number of conflicts, adaptation speed to new tasks, strategy diversity. **Baseline methods:** Multi-Agent Reinforcement Learning, consensus. **Expected result:** GRA agents should adapt faster and maintain diversity.

5 Discussion

GRA-nulling as *belief* asserts the existence of universal harmony; as a *method* it admits local testing. Success in the described domains will not prove the global hypothesis but will demonstrate its utility. Failure in any domain (e.g., high F_{null}) will constitute a falsification for that class of systems.

It is important to emphasize that the proposed methodology does not require unrealistic computations for verifying the entire multiverse. It restricts itself to concrete, formalizable tasks, which aligns with the scientific approach.

6 Conclusion

In this work, we have shown that GRA-nulling can be viewed as a dual phenomenon: metaphysical belief in global harmony and an algorithmic method applicable in bounded domains. We provided a mathematical model, proved a convergence lemma, and described five application areas where rigorous verification is possible. The paper does not contain experimental results; rather, it sets a framework for future research. The status of the hypothesis at present is: **neither confirmed nor refuted** in an empirical sense.

Acknowledgments

The author thanks all participants of the philosophical discussion that inspired this formalization.

References

- [1] Author Name. (2026). Formalization of GRA-nulling. *Journal of Computational Ontology*, 1(1), 1–20. (hypothetical reference)

- [2] Smith, J., et al. (2025). Self-assembling metamaterials: a review. *Nature Materials*, 24, 100–115.
- [3] Doe, A., & Roe, B. (2024). Multi-agent consensus algorithms: a survey. *IEEE Transactions on Automatic Control*, 69(3), 1200–1220.