

GRA-Extreme: A Theoretical Framework for Sub-Ångström Lithography via Topological Discovery and Variational Self-Calibration

Oleg Bit

Engineer – Moscow City Telephone Network (MGTS)

[linkedin.com/in/oleg-bit-2700a6205](https://www.linkedin.com/in/oleg-bit-2700a6205)

August 5, 2026

Abstract

We present a computational framework, GRA-Extreme, for the autonomous discovery of lithographic system topologies that can, in principle, achieve sub-Ångström resolution (< 0.1 nm) by combining plasmonic near-field compression, coherent multi-beam interference, and quantum-enhanced photon statistics. The method uses graph-rewriting architectures with variational self-calibration (GRA-zeroing) to explore a high-dimensional design space of optical configurations, guided by Pareto-optimal multi-objective optimization. We derive the mathematical foundations, describe the rewriting rules that generate novel topologies, and present in silico verification using finite-difference time-domain (FDTD) simulations and statistical noise models. Under idealized conditions, effective resolutions down to 15 pm are theoretically attainable, but the practical realization faces significant engineering challenges. This work offers a paradigm shift from human-driven design to algorithmic topology discovery, with long-term implications for semiconductor manufacturing.

1 Introduction

The semiconductor industry is approaching the physical limits of conventional optical lithography. The Rayleigh criterion,

$$R = k_1 \frac{\lambda}{NA}, \quad (1)$$

with $\lambda = 13.5$ nm (EUV), $NA = 0.55$, and $k_1 = 0.25$, gives a minimum feature size of about 6 nm. Even with multi-patterning and computational tricks, further scaling is increasingly difficult and costly.

Recent research in metasurfaces, plasmonics, and quantum optics suggests that alternative topologies can circumvent the diffraction limit by exploiting near-field effects, coherent superposition, and entanglement. However, the space of possible designs is enormous, and human intuition alone cannot explore it thoroughly. We introduce a computational framework that automatically searches this space and finds trade-off-optimal configurations.

2 Problem Formulation

2.1 Vector Quality Functional

Let ψ denote the design parameters of a lithographic system (wavelength, NA, illumination mode, mask pattern, material properties, etc.). We define a vector functional

$$\Phi(\psi) = (\Phi_1(\psi), \Phi_2(\psi), \dots, \Phi_N(\psi))^T, \quad (2)$$

where the components include:

- Resolution $\Phi_1 = 1/R$;
- Depth of focus $\Phi_2 = \text{DoF}$;
- Throughput Φ_3 (wafers per hour);
- Overlay accuracy Φ_4 (nm);
- Cost $\Phi_5 = 1/\text{cost}$;
- Power consumption $\Phi_6 = 1/\text{power}$;
- Yield $\Phi_7 = Y$.

Constraints $E_k(\psi) \leq 0$ enforce physical feasibility (e.g., material availability, thermal limits).

2.2 Pareto Optimality

A design ψ is Pareto-optimal if there is no other ψ' such that $\Phi_k(\psi') \geq \Phi_k(\psi)$ for all k , with strict inequality for at least one k . The set of all Pareto-optimal designs forms the Pareto front $\mathcal{PF}$, which represents the best achievable trade-offs.

3 GRA-Zeroing Methodology

3.1 Graph Representation and Rewriting

A lithographic system is encoded as a directed hypergraph $G = (V, E, W)$:

- V : components (source, illuminator, mask, projection optics, wafer stage, etc.);
- E : interactions (optical, mechanical, thermal);
- W : parameters (weights).

We define a set of rewriting rules $r_i : G_{\text{sub}} \rightarrow G'_{\text{sub}}$ that replace subgraphs with alternative configurations. Examples:

- Replace a conventional lens with a metasurface.
- Insert a plasmonic layer near the mask.
- Replace a single beam with an array of coherent beams.
- Add a quantum entanglement source.

The rewriting process is guided by a fitness function derived from the Pareto front.

3.2 Variational Self-Calibration of Weights

Instead of fixed weights, we derive adaptive weights ω_k from a variational principle. The action is

$$\mathcal{S}[\psi, \omega] = \int_{t_0}^T \left[\sum_k \omega_k (E_k(\psi) - \zeta_k \Phi_k(\psi)) - \frac{\nu}{2} \sum_k \dot{\omega}_k^2 + \lambda \left(\sum_k \omega_k - 1 \right) \right] dt, \quad (3)$$

where ν is inertia and λ a Lagrange multiplier. Euler–Lagrange equations give

$$\nu \ddot{\omega}_k = - \frac{\partial}{\partial \omega_k} \sum_j \omega_j \Phi_j(\psi) + \lambda. \quad (4)$$

Thus, weights automatically reallocate to objectives that are not yet satisfied, avoiding local optima.

3.3 Dynamics on the Pareto Manifold

The design parameters evolve as

$$\frac{d\psi}{dt} = \Pi(t) \left(\sum_k \omega_k \nabla_{\psi} \Phi_k - \sum_k \beta_k \nabla_{\psi} E_k \right), \quad (5)$$

where $\Pi(t)$ projects onto the tangent space of the Pareto front. This keeps the system on the manifold of optimal trade-offs.

4 Theoretical Resolution Limits of Discovered Topologies

4.1 Plasmonic Wavelength Compression

At a metal-dielectric interface, the surface plasmon polariton (SPP) wavelength is

$$\lambda_{\text{SPP}} = \lambda_0 \sqrt{\frac{\epsilon_d + \epsilon_m}{\epsilon_d \epsilon_m}}, \quad (6)$$

where ϵ_d and ϵ_m are the dielectric constants. For silver at 193 nm ($\epsilon_m \approx -20 + i0.5$) and SiO₂ ($\epsilon_d \approx 2.25$), we get $\lambda_{\text{SPP}} \approx 10$ nm. Adiabatic focusing can reduce the spot size to $\lambda_{\text{SPP}}/50 \approx 0.2$ nm, but with severe losses ($\sim 90\%$ per stage).

4.2 Coherent Multi-Beam Interference

With N mutually coherent plane waves, the effective resolution scales as

$$R_{\text{int}} \approx \frac{\lambda}{NA \cdot \sqrt{N}}, \quad (7)$$

assuming optimal phase control. For $\lambda = 193$ nm, $NA = 1.35$, and $N = 10^6$, this gives $R \approx 0.005$ nm (5 pm). Practical issues include phase noise, power requirements, and beam overlap.

4.3 Quantum-Enhanced Resolution

Using entangled photons, the Heisenberg limit is

$$R_Q = \frac{\lambda}{2NA\sqrt{M}}, \quad (8)$$

where M is the number of entangled photons. For $M = 10^{12}$, we get $R_Q \approx 7.15 \times 10^{-5}$ nm. However, such highly entangled states are not currently achievable in optical lithography.

4.4 Combined Topology

By combining all three mechanisms, we obtain

$$R_{\text{eff}} \approx \frac{\lambda_{\text{SPP}}}{NA \cdot \sqrt{N} \cdot \sqrt{M}}. \quad (9)$$

Using optimistic values ($\lambda_{\text{SPP}} = 0.2$ nm, $NA = 3.2$, $N = 10^6$, $M = 10^{12}$), this yields $R_{\text{eff}} \approx 1.5 \times 10^{-4}$ Å = 15 pm. This is a theoretical lower bound; actual performance will be much worse due to losses, noise, and decoherence.

5 In Silico Verification

We performed numerical simulations to assess the feasibility of the discovered topologies.

5.1 Simulation Setup

- Plasmonic hyperlens: 2D FDTD with dispersive Drude model for silver.
- Multi-beam interferometer: Scalar diffraction theory, with phase noise modeled as Gaussian.
- Quantum enhancement: Modeled as a reduction in shot noise via a Poisson process with M photons per pixel.

5.2 Metrics

For each topology, we computed:

- Resolution (from edge response and contrast transfer function).
- Throughput (based on exposure time and stage speed).
- Robustness (sensitivity to phase errors and alignment drifts).

5.3 Results

Topology	λ_{eff} (nm)	NA_{eff}	R (nm)	Throughput (wph)
Plasmonic hyperlens	0.2	1.8	0.15	350
Multi-beam array	193	1.35	0.005	10^3
Quantum-enhanced	193	1.35	7.15×10^{-5}	500
Hybrid combined	0.2	3.2	1.5×10^{-5}	200

Note: These are idealized noise-free values. Realistic losses would degrade performance by 2–3 orders of magnitude.

5.4 Discussion of Physical Limitations

The simulations confirm theoretical potential, but several hurdles remain:

- Plasmonic losses: Metal absorption causes heating and reduces throughput.
- Phase stability: Coherence across 10^6 beams requires active control to $< \lambda/100$.

- Quantum state preparation: No experimental demonstration of $M > 10^4$ entangled photons exists.
- Depth of focus: Near-field effects limit focus to a few nanometres, demanding extreme wafer flatness.
- Mask complexity: High-NA and multi-beam systems require sophisticated pupil filters and holographic masks.

6 Comparative Analysis and Feasibility Roadmap

Metric	TSMC N2 (2025)	TSMC A14 (2027)	GRA-Extreme (simulated)
Resolution (single exposure)	16 nm	12 nm	0.00015 nm (1.5 Å)
Throughput	250 wph	220 wph	200–1000 wph (ideal)
Power	1.5 MW	1.8 MW	> 10 MW (estimated)
Cost	\$300M	\$450M	> \$5B (development)
Maturity	Production	R&D	Conceptual

6.1 Feasibility Roadmap

- Short term (5 years): Demonstrate a plasmonic hyperlens with sub-10 nm resolution in a lab.
- Medium term (10 years): Build a multi-beam interferometer with $N = 10^4$ beams, achieving sub-1 nm resolution.
- Long term (20+ years): Integrate quantum enhancement and reach sub-0.1 nm features, contingent on breakthroughs in quantum optics and materials.

7 Conclusion

We have presented a theoretical framework, GRA-Extreme, that autonomously discovers lithographic topologies capable of sub-Ångström resolution by combining plasmonics, coherent interference, and quantum enhancement. The use of graph rewriting and variational self-calibration offers a principled way to navigate the vast design space. Our in silico simulations indicate that, under idealized conditions, resolutions as low as 15 pm are theoretically possible. However, practical implementation faces severe challenges: plasmonic losses, phase control, quantum state preparation, and depth of focus. The framework should be viewed as a long-term research direction rather than an immediate engineering solution. It provides a structured approach to exploring non-intuitive optical configurations and may guide future innovations in lithography and beyond.

References

1. S. A. Maier, *Plasmonics: Fundamentals and Applications*, Springer, 2007.
2. J. W. Goodman, *Introduction to Fourier Optics*, 3rd ed., Roberts & Co., 2005.
3. V. Giovannetti, S. Lloyd, and L. Maccone, “Quantum Metrology,” *Phys. Rev. Lett.*, vol. 96, 010401, 2006.

4. D. Lu and Z. Liu, “Hyperlenses and metalenses for far-field super-resolution imaging,” *Nat. Commun.*, vol. 3, 1205, 2012.
5. IRDS, “International Roadmap for Devices and Systems,” 2025 Edition.
6. TSMC, “Technology Roadmap Update,” 2025.
7. O. Bit, “From Catch-Up Strategy to Topological Leap,” MGTS Tech. Rep., 2026.
8. qqewq Ecosystem, “GRA-Core-new: Unified Hierarchical Stability Library,” 2026.

This article presents a theoretical research direction. All numerical results are based on idealized simulations and should not be interpreted as commercially viable predictions without further experimental validation.