

LECTURE 08 — DYNAMIC PROGRAMMING (PART 2)

COMPSCI 308 — DESIGN AND ANALYSIS OF ALGORITHMS

Xing Shi Cai <https://newptcai.gitlab.io>

Duke Kunshan University, Kunshan, China

Jan-Mar 2026

SUMMARY

ITA 15.2 Matrix-Chain Multiplication

ITA 15.3 Elements of Dynamic Programming

More Examples in Dynamic Programming

The Change-Making Problem

Even More Examples

ASSIGNMENTS¹



Practice makes perfect!

Introduction to Algorithms (ITA)

Required Readings:

- Section 15.2.
- Section 15.3.

Required Exercises:

- Exercises 15.2 – 1–6. Exercises 15.3 – 1–5.

¹ ⚪ Assignments will not be collected; however, quiz problems will be selected from them. (This includes both Readings and Exercises.)

ITA 15.2 MATRIX-CHAIN MULTIPLICATION



Product of more than 2
matrices.

REVIEW — MATRIX MULTIPLICATION

Let A and B be two matrices.


Let a_{ij} and b_{ij} be the entries of A and B respectively.

Let $C = A \cdot B$ and c_{ij} be the entries of C .

Then

$$c_{ij} = \sum_{k=1}^n a_{ik} \cdot b_{kj}$$

This is called the **row-column rule**.



THE ROW AND COLUMN RULES

Given matrices A of size $m \times n$ and B of size $n \times p$,

$$A = \begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1n} \\ a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1} & a_{m2} & \cdots & a_{mn} \end{bmatrix}, \quad m$$
$$B = \begin{bmatrix} b_{11} & b_{12} & \cdots & b_{1p} \\ b_{21} & b_{22} & \cdots & b_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ b_{n1} & b_{n2} & \cdots & b_{np} \end{bmatrix}, \quad n$$

The product $C = A \times B$ is a matrix of size $m \times p$

$$C = \begin{bmatrix} c_{11} & c_{12} & \cdots & c_{1p} \\ c_{21} & c_{22} & \cdots & c_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ c_{m1} & c_{m2} & \cdots & c_{mp} \end{bmatrix}$$

The total # of
X is
 $m \cdot n \cdot p$

where

$$c_{ij} = \sum_{k=1}^n a_{ik} \times b_{kj}$$

THE PSEUDOCODE

🍰 If A is of size $m \times n$ and B is of size $n \times p$, how many \times do we need to compute AB ?

```
1: Matrix-Multiply( $A, B$ )
2: let  $C$  be a new  $A.\text{rows} \times B.\text{columns}$  matrix
3: for  $i = 1$  to  $A.\text{rows}$  do  $m$ 
4:   for  $j = 1$  to  $B.\text{columns}$  do  $P$ 
5:      $C_{ij} = 0$ 
6:     for  $k = 1$  to  $A.\text{columns}$  do  $k$ .
7:        $C_{ij} = C_{ij} + A_{ik} \times B_{kj}$ 
8: return  $C$ 
```

$m \times P \times k$ times.

ASSOCIATIVE LAW OF MULTIPLICATION

Let (2×2)

$$A = \begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix}, \quad \underbrace{\}_{2 \times 2}}$$

$$B = \begin{bmatrix} 0 \\ 2 \end{bmatrix}, \quad \underbrace{\}_{1 \times 2}} \quad C = [2 \ 4]$$

- We have —

$$AB = \underbrace{\begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix} \begin{bmatrix} 0 \\ 2 \end{bmatrix}}_{2 \times 2} = \begin{bmatrix} 0 \\ 8 \end{bmatrix}$$

$$(AB)C = \begin{bmatrix} 0 \\ 8 \end{bmatrix} \begin{bmatrix} 2 & 4 \end{bmatrix} = \begin{bmatrix} 0 \cdot 2 + 0 \cdot 4 \\ 8 \cdot 2 + 8 \cdot 4 \end{bmatrix} \underbrace{\}_{2 \times 2}} = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$

row: 行

column: 列

ASSOCIATIVE LAW OF MULTIPLICATION

Let

$$A = \begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix}, \quad B = \begin{bmatrix} 0 \\ 2 \end{bmatrix}, \quad C = \begin{bmatrix} 2 & 4 \end{bmatrix}$$

- We have —

$$AB = \begin{bmatrix} 0 \\ 8 \end{bmatrix} \quad (AB)C = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$


ASSOCIATIVE LAW OF MULTIPLICATION

Let

$$A = \begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix}, \quad B = \begin{bmatrix} 0 \\ 2 \end{bmatrix}, \quad C = \begin{bmatrix} 2 & 4 \end{bmatrix}$$

2×1 1×2 .

- We have —

$$AB = \begin{bmatrix} 0 \\ 8 \end{bmatrix} \quad (AB)C = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$


- We also have —

$$BC = \begin{bmatrix} 0 & 0 \\ 4 & 8 \end{bmatrix} \quad A(BC) = \begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix} \begin{bmatrix} 0 & 0 \\ 4 & 8 \end{bmatrix} = \begin{bmatrix} \underline{3.0 + 0.4} & \underline{3.0 + 8} \\ \underline{5.0 + 4.4} & \underline{5.0 + 4.8} \end{bmatrix}$$
$$= \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}.$$

ASSOCIATIVE LAW OF MULTIPLICATION

Let

$$A = \begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix}, \quad B = \begin{bmatrix} 0 \\ 2 \end{bmatrix}, \quad C = \begin{bmatrix} 2 & 4 \end{bmatrix}$$

- We have —

$$AB = \begin{bmatrix} 0 \\ 8 \end{bmatrix} \quad (AB)C = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$

 The same.

- We also have —

$$BC = \begin{bmatrix} 0 & 0 \\ 4 & 8 \end{bmatrix} \quad A(BC) = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$

ASSOCIATIVE LAW OF MULTIPLICATION

Let

$$A = \begin{bmatrix} 3 & 0 \\ 5 & 4 \end{bmatrix}, \quad B = \begin{bmatrix} 0 \\ 2 \end{bmatrix}, \quad C = \begin{bmatrix} 2 & 4 \end{bmatrix}$$

- We have —

$$AB = \begin{bmatrix} 0 \\ 8 \end{bmatrix} \quad (AB)C = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$

- We also have —

$$BC = \begin{bmatrix} 0 & 0 \\ 4 & 8 \end{bmatrix} \quad A(BC) = \begin{bmatrix} 0 & 0 \\ 16 & 32 \end{bmatrix}$$

The Associative Law

Given any matrices A, B, C (of compatible sizes), we have —

$$A(BC) = (AB)C$$

💡 So we often drop the brackets and simply write ABC .

FULLY PARENTHESIZED PRODUCT

When computing a product like $A_1 A_2 \dots A_n$, we must decide the order of the \times .
Parentheses can be used to indicate that order —

$$A_1 A_2 = (A_1 A_2)$$

(1)

FULLY PARENTHESIZED PRODUCT

When computing a product like $A_1 A_2 \dots A_n$, we must decide the order of the \times .

Parentheses can be used to indicate that order —

$$A_1 A_2 = (A_1 A_2)$$

$$A_1 A_2 A_3 = (A_1 (A_2 A_3)) = ((A_1 A_2) A_3).$$

(1)

(2)

FULLY PARENTHESIZED PRODUCT

When computing a product like $A_1 A_2 \dots A_n$, we must decide the order of the \times .

Parentheses can be used to indicate that order —


$$A_1 A_2 = (A_1 A_2)$$

$$A_1 A_2 A_3 = (A_1 (A_2 A_3)) = ((A_1 A_2) A_3).$$

$$\begin{aligned} A_1 A_2 A_3 A_4 &= (A_1 (A_2 (A_3 A_4))) = (A_1 ((A_2 A_3) A_4)) \\ &= ((A_1 A_2) (A_3 A_4)) = ((A_1 (A_2 A_3)) A_4) \\ &= (((A_1 A_2) A_3) A_4). \end{aligned}$$

🧐 In how many ways can we fully parenthesize $A_1 A_2 \dots A_n$?

$$= \frac{1}{n} \cdot \frac{(2(n-1)!)}{(n-1)! (n-1)!}$$

Cartoon number.

(1)

(2)

(5)

$$\frac{1}{n} \binom{2(n-1)}{n-1}$$

WHY DO PARENTHESES MATTER?

Consider three matrices A_1, A_2, A_3 of sizes $10 \times 100, 100 \times 5, 5 \times 50$.

🎂 How many scalar \times do we need to compute

$$(A_1(A_2A_3))$$

10×100 100×5 5×50

100×50

It Takes $100 \times 5 \times 50$ "x"

$$= 25,000$$

+

=

$$75,000$$

It Takes $10 \times 100 \times 50 = 50,000$ "x"

"x"

WHY DO PARENTHESES MATTER?

Consider three matrices A_1, A_2, A_3 of sizes $10 \times 100, 100 \times 5, 5 \times 50$.

🎂 How many scalar \times do we need to compute

🎂 What about

$$(A_1(A_2A_3))$$

$$10 \times \underbrace{5}_{\text{---}} \quad \underbrace{5 \times 50}_{\text{---}}$$

$$((A_1A_2)A_3)$$

+

Take $10 \times 5 \times 50$

$$= 2,500 \text{ "x"}$$

+

Takes. $10 \times 100 \times 5 = 5,000 \text{ "x"}$

= In total.
7,500 "x"

WHY DO PARENTHESES MATTER?

Consider three matrices A_1, A_2, A_3 of sizes $10 \times 100, 100 \times 5, 5 \times 50$.

🎂 How many scalar \times do we need to compute

$$(A_1(A_2A_3))$$

🎂 What about

$$((A_1A_2)A_3)$$

🎂 Can you think of a case when any parenthesization of A_1, A_2, \dots, A_n uses the same amount of \times ?

When A_1, \dots, A_n are all squared.

EXHAUSTIVE SEARCH

Let $P(n)$ be the number of ways to fully parenthesize $A_1 A_2 \dots A_n$. Then

$$P(n) = \begin{cases} 1 & \text{if } n = 1, \\ \sum_{k=1}^{n-1} P(k)P(n-k) & \text{if } n > 1. \end{cases}$$

\downarrow \curvearrowright

$$(A_1 \dots A_k) (A_{k+1} \dots A_n).$$

EXHAUSTIVE SEARCH

Let $P(n)$ be the number of ways to fully parenthesize $A_1 A_2 \dots A_n$. Then

$$P(n) = \begin{cases} 1 & \text{if } n = 1, \\ \sum_{k=1}^{n-1} P(k)P(n-k) & \text{if } n > 1. \end{cases}$$

In COMPSCI 203, we have seen that $P(n)$ is the famous Catalan number –

$$P(n) = \frac{1}{n} \binom{2n-2}{n-1} = \Theta\left(\frac{4^n}{n^{3/2}}\right) \quad (1)$$

There are simply too many ways to check exhaustively.

✳ Try to prove (1).

THE STRUCTURE OF THE OPTIMAL SOLUTION

If the optimal way to parenthesize $A_i A_{i+1} \dots A_j$ is to “break” the chain into two parts between A_k and A_{k+1} , i.e.,

$$((A_i \dots A_k)(A_{k+1} \dots A_j))$$

then the parenthesizations of both

$$A_i \dots A_k$$

and

$$A_{k+1} \dots A_j$$

must both be optimal.

Otherwise we could get even better parenthesization.

A RECURSIVE SOLUTION

Let $m[i, j]$ be the minimum number of \times needed to compute $A_i A_{i+1} \dots A_j$.

Let the size of A_i be $p_{i-1} \times p_i$.

Then by the previous observation

No computation needed.

$$m[i, j] = \begin{cases} 0 & \text{if } i = j, \\ \min_{i \leq k < j} \{m[i, k] + m[k + 1, j] + p_{i-1} p_k p_j\} & \text{if } i < j. \end{cases}$$

Why is $m[i, j] = 0$ when $i = j$?

$$(A_i \dots A_k) \quad (A_{k+1} \dots A_j)$$

$\underbrace{}$

$$p_{i-1} \times p_k$$

$\underbrace{\phantom{A_{k+1} \dots A_j}}$

$$p_k \times p_j$$

DYNAMIC PROGRAMMING TO HELP


To compute $m[i, j]$, we can fill up the optimal cost table and split table as shown below.

$$m[3, 5] = \min \{ m[3, 3] + m[4, 5] + 15 \times 5 \times 20, m[3, 4] + m[5, 5] + 15 \times 10 \times 20 \}$$

\uparrow

$\checkmark (A_3 \cdot A_4) \cdot A_5$.

Bottom $m_{1,1}$ Up



The min "x" needed

for 30×35

$A_1 \cdot A_2$.

$= 30 \times 35 \times 15$

$= 15,750$

$A_3 : 15 \times 5$

$A_4 \cdot A_5 : 5 \times 20$

$A_1, A_2, A_3, A_4, A_5, A_6$

Figure 2: The matrix chain cost table for matrices with $\langle p_0, \dots, p_6 \rangle = \langle 30, 35, 15, 5, 10, 20, 25 \rangle$

THE PSEUDOCODE

Matrix-Chain-Order(p)

Initialize m and s

for $l = 2$ to n do

 for $i = 1$ to $n - l + 1$ do

$j \leftarrow i + l - 1$

$m[i, j] \leftarrow \infty$

 for $k = i$ to $j - 1$ do

$q \leftarrow m[i, k] + m[k + 1, j] + p[i - 1] \times p[k] \times p[j]$

 if $q < m[i, j]$ then

$m[i, j] \leftarrow q$

$s[i, j] \leftarrow k$

return m and s



$(A_1 \cdot \dots \cdot A_k) (A_{k+1} \cdot \dots \cdot A_j)$.

CONSTRUCT THE OPTIMAL PARENTHESIZATION

POP

Print-Optimal-Parens(s, i, j)

if $i = j$ then

 print " A_i "

else

 print "("

 PRINT-OPTIMAL-PARENS($s, i, s[i, j]$)

 PRINT-OPTIMAL-PARENS($s, s[i, j] + 1, j$)

 print ")"

🎂 What is the output when this is applied to the table on the right?




Figure 3: The matrix chain split table for matrices with
 $\langle p_0, \dots, p_6 \rangle = \langle 30, 35, 15, 5, 10, 20, 25 \rangle$

$$(A_1 \left| (A_2 \ A_3)) \quad ((A_4 \ A_5) \right| A_6)$$

Consider matrices A_1, A_2, A_3 whose sizes are given by

$$\langle 4, 5, 7, 3 \rangle$$

$$A_1 \quad \overbrace{A_3}^{A_2}$$

$$m[1, 3]$$

What is $m(1, 3)$?

$$= \min \{ 105 + 60,$$

$$m[40 + 84] \}$$

$$+ 4 \times 5 \times 3,$$

$$m[1, 2] + m[3, 3]$$

$$+ 4 \times 7 \times 3 \}$$

$$(A_1 A_2) \cdot A_3$$

$$m[2, 3] = 5 \times 7 \times 3$$

$$= 105$$

$$m[1, 2]$$

$$= 4 \times 5 \times 7$$




Figure 4: The matrix chain cost table

$A_1 (A_2 A_3)$

ITA 15.3 ELEMENTS OF DYNAMIC PROGRAMMING

★ OPTIMAL STRUCTURE

A pattern in problems suitable for dynamic programming is –

1. A solution entails making a choice, e.g., an initial cut in a rod or a matrix split index. This choice results in subproblems.

★ OPTIMAL STRUCTURE

A pattern in problems suitable for dynamic programming is –

1. A solution entails making a choice, e.g., an initial cut in a rod or a matrix split index. This choice results in subproblems.
2. Assume that you already have the choice leading to an optimal solution.

$$(A_1 \dots A_k) \Big| (A_{k+1} \dots A_j).$$

★ OPTIMAL STRUCTURE

A pattern in problems suitable for dynamic programming is –

1. A solution entails making a choice, e.g., an initial cut in a rod or a matrix split index. This choice results in subproblems.
2. Assume that you already have the choice leading to an optimal solution.
3. Based on this choice, identify the **subproblems** and characterize the resulting space.

★ OPTIMAL STRUCTURE

A pattern in problems suitable for dynamic programming is –

1. A solution entails making a choice, e.g., an initial cut in a rod or a matrix split index. This choice results in subproblems.
2. Assume that you already have the choice leading to an optimal solution.
3. Based on this choice, identify the subproblems and characterize the resulting space.
4. Prove **subproblem solutions** within an **optimal solution** must be **optimal** by contradiction – If a subproblem's solution isn't optimal, by replacing it with the **optimal one**, a **better solution** to the original problem is obtained.

Look OUT FOR PITFALLS

In the directed graph below, the longest simple path from q to t is $q \rightarrow r \rightarrow t$.

🎂 What is the longest simple path from q to r and from r to t ?




Figure 5: A directed graph

Look OUT FOR PITFALLS

In the directed graph below, the longest simple path from q to t is $q \rightarrow r \rightarrow t$.

🎂 What is the longest simple path from q to r and from r to t ?




Figure 5: A directed graph

longest from
a to r is

$q \rightarrow s \rightarrow t \rightarrow r$.

longest path from
r to t is

$r \rightarrow q \rightarrow s \rightarrow t$.

💣 Sometimes the optimal solution does not contain optimal solutions for subproblems.

🎂 Can you think of another problem like this?

OVERLAPPING SUBPROBLEMS

A sign that a problem is suitable for dynamic programming is that there are overlapping subproblems.




Figure 6: Example – The recursion tree for the matrix chain multiplication problem

COMPUTE THE OPTIMAL CHAIN NAIVELY

```
1: Recursive-Matrix-Chain( $p, i, j$ )
2: if  $i = j$  then
3:     return 0
4:  $min \leftarrow \infty$ 
5: for  $k = i$  to  $j - 1$  do
6:
     $c \leftarrow$  RECURSIVE-MATRIX-CHAIN( $p, i, k$ )
        + RECURSIVE-MATRIX-CHAIN( $p, k + 1, j$ )
        +  $p[i - 1] \times p[k] \times p[j]$ 
7:     if  $c < min$  then
8:          $min \leftarrow c$ 
9: return  $min$ 
```

COMPUTE THE OPTIMAL CHAIN NAIVELY

```
1: Recursive-Matrix-Chain( $p, i, j$ )
2: if  $i = j$  then
3:     return 0
4:  $min \leftarrow \infty$ 
5: for  $k = i$  to  $j - 1$  do
6:
     $c \leftarrow \text{RECURSIVE-MATRIX-CHAIN}(p, i, k)$ 
    +  $\text{RECURSIVE-MATRIX-CHAIN}(p, k + 1, j)$ 
    +  $p[i - 1] \times p[k] \times p[j]$ 
7: if  $c < min$  then
8:      $min \leftarrow c$ 
9: return  $min$ 
```

Let $T(n)$ be the running time of this algorithm. Then we have

$$T(n) \geq 1 + \sum_{k=1}^{n-1} (T(k) + T(n-k) + 1) \quad \text{for } n > 1.$$

+ We can show by induction that

$$T(n) \geq 2^{n-1}.$$

MORE EXAMPLES IN DYNAMIC PROGRAMMING

MORE EXAMPLES IN DYNAMIC PROGRAMMING

THE CHANGE-MAKING PROBLEM

EXAMPLE — BUYING A MAGIC MUSHROOM²

Consider wanting to purchase a magic  priced at \$99.

However, the vendor only accepts  in denominations of

 value
\$5, \$10, \$25, \$50.

Determine the fewest number of  required to make the purchase.



Figure 7: A magic  shop

²This is not in the textbook.

THE CHANGE-MAKING PROBLEM

For a given set of  denominations $D = \{d_1, d_2, \dots, d_n\}$ and a specified amount A –

Determine the minimum count of coins, from the set, that combine to reach the amount A .

Let c_i represent the count of coins of denomination d_i .

Our objective is to minimize –

$$C(A) = \sum_{i=1}^n c_i$$

Subject to the constraint –

$$\sum_{i=1}^n c_i \cdot d_i = A$$

DYNAMIC PROGRAMMING SOLUTION

The following simple algorithm computes the optimal solution.

1: **ChangeMaking**(D, A)

2: Initialize array $M[0 \dots A]$ with values set to ∞

3: $M[0] = 0$

4: **for** $i = 1$ to A **do**

5: **for each** d in D **do**

6: **if** $i - d \geq 0$ and $M[i - d] + 1 < M[i]$ **then**

7: $M[i] = M[i - d] + 1$

8: **return** $M[A]$

min # of coins needed to
pay $i - d$.

🎂 What is the output when $D = \{5, 10, 25, 50\}$ and $A = 99$?

Not possible.

The algorithm returns ∞

multiples of 5

MORE EXAMPLES IN DYNAMIC PROGRAMMING

EVEN MORE EXAMPLES

TREASURE HUNT PROBLEM




Figure 8: A treasure hunt on a grid

TREASURE HUNT PROBLEM

A  starts at coordinate $(0, 0)$ on a $m \times n$ grid.

Each grid cell (i, j) holds a treasure with value t_{ij} .

The  can move either up or right one unit at a time.

 Maximize the total treasure collected.

Let c_{ij} be the maximum treasure collected by the robot starting from coordinate (i, j) .

 Can you find a recursion for c_{ij} ?

 Can you write a dynamic programming algorithm in pseudocode for finding c_{mn} ?

LONGEST PALINDROMIC SUBSTRING

A **palindrome** is a string that reads the same forward and backward.

🤔 Given a string s , how can the longest palindromic substring in s be found? For example,

- $s = \text{"babad"} \Rightarrow \text{"bab" or "aba"}$
- $s = \text{"cbbd"} \Rightarrow \text{"bb"}$
- $s = \text{"a"} \Rightarrow \text{"a"}$

Let

$$P(i, j) = \begin{cases} \text{true}, & i = j, \\ (s_i = s_j), & j = i + 1, \\ (s_i = s_j) \wedge P(i + 1, j - 1), & j > i + 1. \end{cases}$$

$P(i, j)$ indicates whether $s[i \dots j]$ is a palindrome. The longest palindromic substring is the valid (i, j) pair that maximizes $j - i + 1$.

WHAT ARE YOUR MAIN TAKEAWAYS TODAY? ANY QUESTIONS?

