


Time Series and Sequence Learning

Modeling time series with stochastic processes

Fredrik Lindsten, Linköping University

A graphical representation

Classical regression applied to time series data.



$$\mu_t = \theta_0 + \theta_1 u_t, \quad u_t = 1993 \frac{4}{365}, 1993 \frac{14}{365}, \dots, 2020 \frac{20}{365}$$

A fundamental approach to time series analysis is to model the data as a **stochastic process**,


$$\{y_t : t = 1, 2, \dots\}$$

Stochastic process

A fundamental approach to time series analysis is to model the data as a **stochastic process**,

$$\{y_t : t = 1, 2, \dots\}$$

Probabilistic graphical model:



How can we model the stochastic process?

A complete **probabilistic description** is given by the *joint probability density function*

$$p(y_{1:n}) = p(y_1, y_2, \dots, y_n).$$

A model for time series data

How can we model the stochastic process?

A complete **probabilistic description** is given by the *joint probability density function*

$$p(y_{1:n}) = p(y_1, y_2, \dots, y_n).$$

Cumbersome to work with directly:

1. Dimension grows with time horizon n
2. High-dimensional for large n
3. Can not be used to *forecast* values y_t for $t > n$

A model for time series data

$$p(y_{1:n}) = p(y_n | y_{1:n-1}) p(y_{1:n-1})$$

$$= p(y_n | y_{1:n-1}) p(y_{n-1} | y_{1:n-2}) p(y_{1:n-2})$$

$$= p(y_n | y_{1:n-1}) p(y_{n-1} | y_{1:n-2}) \dots p(y_2 | y_1) p(y_1)$$

A model for time series data

Factorize joint pdf as

$$p(y_{1:n}) = \prod_{t=1}^n p(y_t | y_{1:t-1})$$

It is enough to model the **one-step predictive pdf** $p(y_t | y_{1:t-1})$.

[For notational brevity we define $p(y_1 | y_{1:0}) := p(y_1)$]

$y_{1:0}$ is an empty set

First-order auto-regressive model

A model for $p(y_t | y_{1:t-1})$ tells us how the **current value** y_t depends on **the past values** $y_{1:t-1}$.

First-order auto-regressive model

A model for $p(y_t | y_{1:t-1})$ tells us how the **current value** y_t depends on **the past values** $y_{1:t-1}$.

ex) If we believe that y_t is **similar to** y_{t-1} , one possibility is to assume

$$y_t = a y_{t-1} + \varepsilon_t, \quad \varepsilon_t \stackrel{\text{iid}}{\sim} \mathcal{N}(0, \sigma_\varepsilon^2),$$

for some parameter a .

First-order auto-regressive model

A model for $p(y_t | y_{1:t-1})$ tells us how the **current value** y_t depends on **the past values** $y_{1:t-1}$.

ex) If we believe that y_t is **similar to** y_{t-1} , one possibility is to assume

$$y_t = a y_{t-1} + \varepsilon_t, \quad \varepsilon_t \stackrel{\text{iid}}{\sim} \mathcal{N}(0, \sigma_\varepsilon^2),$$

for some parameter a .

This is referred to as a (first-order) **auto-regressive (AR) model**.

First-order auto-regressive model

A model for $p(y_t | y_{1:t-1})$ tells us how the **current value** y_t depends on **the past values** $y_{1:t-1}$.

ex) If we believe that y_t is **similar to** y_{t-1} , one possibility is to assume

$$y_t = a y_{t-1} + \varepsilon_t, \quad \varepsilon_t \stackrel{\text{iid}}{\sim} \mathcal{N}(0, \sigma_\varepsilon^2),$$

for some parameter a .

This is referred to as a (first-order) **auto-regressive (AR) model**.

For a first-order AR model we have,

we only focus on 1 past value here

$$p(y_t | y_{1:t-1}) = p(y_t | y_{t-1}) = \mathcal{N}(y_t | a y_{t-1}, \sigma_\varepsilon^2).$$

First-order auto-regressive model


The dependency structure of the predictive pdf,

$$p(y_t | y_{1:t-1}) = p(y_t | y_{t-1}) = \mathcal{N}(y_t | \textcolor{red}{a}y_{t-1}, \sigma_\epsilon^2).$$


can be illustrated graphically as



Simulation of AR(1)



Simulation of AR(1)



Simulation of AR(1)

