#	Name	Registers							Definition
		param 0	param 1	param 2	param 3	param 4	param 5	param 6	
4000	syscall	-	-	-	-	-	-	-	Not implemented
4001	exit	0xfa1	int error_code	-	-	-	-	-	kernel/exit.c:1095
4002	fork	0xfa2	-	-	-	-	-	-	arch/mips/kernel/syscall.c:93
4003	read	0xfa3	unsigned int fd	char *buf	size_t count	-	-	-	fs/read_write.c:460
4004	write	0xfa4	unsigned int fd	const char *buf	size_t count	-	-	-	fs/read_write.c:477
4005	open	0xfa5	const char *filename	int flags	umode_t mode	-	-	-	fs/open.c:1046
4006	close	0xfa6	unsigned int fd	-	-	-	-	-	fs/open.c:1117
4007	waitpid	0xfa7	pid_t pid	int *stat_addr	int options	-	-	-	kernel/exit.c:1879
4008	creat	0xfa8	const char *pathname	umode_t mode	-	-	-	-	fs/open.c:1079
4009	link	0xfa9	const char *oldname	const char *newname	-	-	-	-	fs/namei.c:3152
4010	unlink	0xfaa	const char *pathname	-	-	-	-	-	fs/namei.c:2979
4011	execve	0xfab	-	-	-	-	-	-	arch/mips/kernel/syscall.c:133
4012	chdir	0xfac	const char *filename	-	-	-	-	-	fs/open.c:375
4013	time	0xfad	time_t *tloc	-	-	-	-	-	kernel/time.c:62
4014	mknod	0xfae	const char *filename	umode_t mode	unsigned dev	-	-	-	fs/namei.c:2693
4015	chmod	0xfaf	const char *filename	umode_t mode	-	-	-	-	fs/open.c:499
4016	lchown	0xfb0	const char *filename	uid_t user	gid_t group	-	-	-	fs/open.c:586
4017	break	-	-	-	-	-	-	-	Not implemented
4018	unused18	-	-	-	-	-	-	-	Not implemented
4019	lseek	0xfb3	unsigned int fd	off_t offset	unsigned int origin	-	-	-	fs/read_write.c:230
4020	getpid	0xfb4	-	-	-	-	-	-	kernel/timer.c:1413
4021	mount	0xfb5	char *dev_name	char *dir_name	char *type	unsigned long flags	void *data	-	fs/namespace.c:2362
4022	umount	0xfb6	char *name	int flags	-	-	-	-	fs/namespace.c:1190
4023	setuid	0xfb7	uid_t uid	-	-	-	-	-	kernel/sys.c:761
4024	getuid	0xfb8	-	-	-	-	-	-	kernel/timer.c:1435
4025	stime	0xfb9	time_t *tptr	-	-	-	-	-	kernel/time.c:81
4026	ptrace	0xfba	long request	long pid	unsigned long addr	unsigned long data	-	-	kernel/ptrace.c:857
4027	alarm	0xfbb	unsigned int seconds	-	-	-	-	-	kernel/timer.c:1390
4028	unused28	-	-	-	-	-	-	-	Not implemented
4029	pause	0xfbd	-	-	-	-	-	-	kernel/signal.c:3245
4030	utime	0xfbe	char *filename	struct utimbuf *times	-	-	-	-	fs/utimes.c:27
4031	stty	-	-	-	-	-	-	-	Not implemented
4032	gtty	-	-	-	-	-	-	-	Not implemented
4033	access	0xfc1	const char *filename	int mode	-	-	-	-	fs/open.c:370
4034	nice	0xfc2	int increment	-	-	-	-	-	kernel/sched/core.c:4119
4035	ftime	-	-	-	-	-	-	-	Not implemented
4036	sync	0xfc4	-	-	-	-	-	-	fs/sync.c:98
4037	kill	0xfc5	pid_t pid	int sig	-	-	-	-	kernel/signal.c:2841
4038	rename	0xfc6	const char *oldname	const char *newname	-	-	-	-	fs/namei.c:3403
4039	mkdir	0xfc7	const char *pathname	umode_t mode	-	-	-	-	fs/namei.c:2751
4040	rmdir	0xfc8	const char *pathname	-	-	-	-	-	fs/namei.c:2870
4041	dup	0xfc9	unsigned int fildes	-	-	-	-	-	fs/fcntl.c:131
4042	pipe	0xfca	int *fildes	-	-	-	-	-	fs/pipe.c:1149
4043	times	0xfcb	struct tms *tbuf	-	-	-	-	-	kernel/sys.c:1058
4044	prof	-	-	-	-	-	-	-	Not implemented
4045	brk	0xfcd	unsigned long brk	-	-	-	-	-	mm/mmap.c:246
4046	setgid	0xfce	gid_t gid	-	-	-	-	-	kernel/sys.c:614
4047	getgid	0xfcf	-	-	-	-	-	-	kernel/timer.c:1447
4048	signal	0xfd0	int sig	__sighandler_t handler	-	-	-	-	kernel/signal.c:3228
4049	geteuid	0xfd1	-	-	-	-	-	-	kernel/timer.c:1441
4050	getegid	0xfd2	-	-	-	-	-	-	kernel/timer.c:1453
4051	acct	0xfd3	const char *name	-	-	-	-	-	kernel/acct.c:255
4052	umount2	0xfd4	char *name	int flags	-	-	-	-	fs/namespace.c:1190
4053	lock	-	-	-	-	-	-	-	Not implemented
4054	ioctl	0xfd6	unsigned int fd	unsigned int cmd	unsigned long arg	-	-	-	fs/ioctl.c:604
4055	fcntl	0xfd7	unsigned int fd	unsigned int cmd	unsigned long arg	-	-	-	fs/fcntl.c:442
4056	mpx	-	-	-	-	-	-	-	Not implemented
4057	setpgid	0xfd9	pid_t pid	pid_t pgid	-	-	-	-	kernel/sys.c:1083
4058	ulimit	-	-	-	-	-	-	-	Not implemented
4059	unused59	-	-	-	-	-	-	-	Not implemented
4060	umask	0xfdc	int mask	-	-	-	-	-	kernel/sys.c:1782
4061	chroot	0xfdd	const char *filename	-	-	-	-	-	fs/open.c:422
4062	ustat	0xfde	unsigned dev	struct ustat *ubuf	-	-	-	-	fs/statfs.c:222
4063	dup2	0xfdf	unsigned int oldfd	unsigned int newfd	-	-	-	-	fs/fcntl.c:116
4064	getppid	0xfe0	-	-	-	-	-	-	kernel/timer.c:1424
4065	getpgrp	0xfe1	-	-	-	-	-	-	kernel/sys.c:1184
4066	setsid	0xfe2	-	-	-	-	-	-	kernel/sys.c:1219

#	Name	param 0	param 1	param 2	param 3	param 4	param 5	param 6	Definition
4067	sigaction	0xfe3	int sig	const struct sigaction *act	struct sigaction *oact	-	-	-	arch/mips/kernel/signal.c:280
4068	sgetmask	0xfe4	-	-	-	-	-	-	kernel/signal.c:3207
4069	ssetmask	0xfe5	int newmask	-	-	-	-	-	kernel/signal.c:3213
4070	setreuid	0xfe6	uid_t ruid	uid_t euid	-	-	-	-	kernel/sys.c:690
4071	setregid	0xfe7	gid_t rgid	gid_t egid	-	-	-	-	kernel/sys.c:557
4072	sigsuspend	0xfe8	-	-	-	-	-	-	arch/mips/kernel/signal.c:250
4073	sigpending	0xfe9	old_sigset_t *set	-	-	-	-	-	kernel/signal.c:3107
4074	sethostname	0xfea	char *name	int len	-	-	-	-	kernel/sys.c:1365
4075	setrlimit	0xfeb	unsigned int resource	struct rlimit *rlim	-	-	-	-	kernel/sys.c:1641
4076	getrlimit	0xfec	unsigned int resource	struct rlimit *rlim	-	-	-	-	kernel/sys.c:1440
4077	getrusage	0xfed	int who	struct rusage *ru	-	-	-	-	kernel/sys.c:1774
4078	gettimeofday	0xfee	struct timeval *tv	struct timezone *tz	-	-	-	-	kernel/time.c:101
4079	settimeofday	0xfef	struct timeval *tv	struct timezone *tz	-	-	-	-	kernel/time.c:179
4080	getgroups	0xff0	int gidsetsize	gid_t *grouplist	-	-	-	-	kernel/groups.c:202
4081	setgroups	0xff1	int gidsetsize	gid_t *grouplist	-	-	-	-	kernel/groups.c:231
4082	reserved82	-	-	-	-	-	-	-	Not implemented
4083	symlink	0xff3	const char *oldname	const char *newname	-	-	-	-	fs/namei.c:3039
4084	unused84	-	-	-	-	-	-	-	Not implemented
4085	readlink	0xff5	const char *path	char *buf	int bufsiz	-	-	-	fs/stat.c:321
4086	uselib	0xff6	const char *library	-	-	-	-	-	fs/exec.c:116
4087	swapon	0xff7	const char *specialfile	int swap_flags	-	-	-	-	mm/swapfile.c:1996
4088	reboot	0xff8	int magic1	int magic2	unsigned int cmd	void *arg	-	-	kernel/sys.c:432
4089	readdir	0xff9	unsigned int fd	struct old_linux_dirent *dirent	unsigned int count	-	-	-	fs/readdir.c:105
4090	mmap	0xffa	struct mmap_arg_struct *arg	-	-	-	-	-	mm/mmap.c:1153
4091	munmap	0xffb	unsigned long addr	size_t len	-	-	-	-	mm/mmap.c:2141
4092	truncate	0xffc	const char *path	long length	-	-	-	-	fs/open.c:128
4093	ftruncate	0xffd	unsigned int fd	unsigned long length	-	-	-	-	fs/open.c:178
4094	fchmod	0xffe	unsigned int fd	umode_t mode	-	-	-	-	fs/open.c:472
4095	fchown	0xfff	unsigned int fd	uid_t user	gid_t group	-	-	-	fs/open.c:605
4096	getpriority	0x1000	int which	int who	-	-	-	-	kernel/sys.c:241
4097	setpriority	0x1001	int which	int who	int niceval	-	-	-	kernel/sys.c:172
4098	profil	-	-	-	-	-	-	-	Not implemented
4099	statfs	0x1003	const char *pathname	struct statfs *buf	-	-	-	-	fs/statfs.c:166
4100	fstatfs	0x1004	unsigned int fd	struct statfs *buf	-	-	-	-	fs/statfs.c:187
4101	ioperm	-	-	-	-	-	-	-	Not implemented
4102	socketcall	0x1006	int call	unsigned long *args	-	-	-	-	net/socket.c:2355
4103	syslog	0x1007	int type	char *buf	int len	-	-	-	kernel/printk.c:1195
4104	setitimer	0x1008	int which	struct itimerval *value	struct itimerval *ovalue	-	-	-	kernel/itimer.c:278
4105	getitimer	0x1009	int which	struct itimerval *value	-	-	-	-	kernel/itimer.c:103
4106	stat	0x100a	const char *filename	struct __old_kernel_stat *statbuf	-	-	-	-	fs/stat.c:155
4107	lstat	0x100b	const char *filename	struct __old_kernel_stat *statbuf	-	-	-	-	fs/stat.c:168
4108	fstat	0x100c	unsigned int fd	struct __old_kernel_stat *statbuf	-	-	-	-	fs/stat.c:181
4109	unused109	-	-	-	-	-	-	-	Not implemented
4110	iopl	-	-	-	-	-	-	-	Not implemented
4111	vhangup	0x100f	-	-	-	-	-	-	fs/open.c:1156
4112	idle	-	-	-	-	-	-	-	Not implemented
4113	vm86	-	-	-	-	-	-	-	Not implemented
4114	wait4	0x1012	pid_t upid	int *stat_addr	int options	struct rusage *ru	-	-	kernel/exit.c:1834
4115	swapoff	0x1013	const char *specialfile	-	-	-	-	-	mm/swapfile.c:1539
4116	sysinfo	0x1014	struct sysinfo *info	-	-	-	-	-	kernel/timer.c:1641
4117	ipc	0x1015	unsigned int call	int first	unsigned long second	unsigned long third	void *ptr	long fifth	ipc/syscall.c:16
4118	fsync	0x1016	unsigned int fd	-	-	-	-	-	fs/sync.c:201
4119	sigreturn	0x1017	-	-	-	-	-	-	arch/mips/kernel/signal.c:330
4120	clone	0x1018	-	-	-	-	-	-	arch/mips/kernel/syscall.c:100
4121	setdomainname	0x1019	char *name	int len	-	-	-	-	kernel/sys.c:1416
4122	uname	0x101a	struct old_utsname *name	-	-	-	-	-	kernel/sys.c:1311
4123	modify_ldt	-	-	-	-	-	-	-	Not implemented
4124	adjtimex	0x101c	struct timex *txc_p	-	-	-	-	-	kernel/time.c:200
4125	mprotect	0x101d	unsigned long start	size_t len	unsigned long prot	-	-	-	mm/mprotect.c:232
4126	sigprocmask	0x101e	int how	old_sigset_t *nset	old_sigset_t *oset	-	-	-	kernel/signal.c:3125
4127	create_module	-	-	-	-	-	-	-	Not implemented
4128	init_module	0x1020	void *umod	unsigned long len	const char *uargs	-	-	-	kernel/module.c:3010
4129	delete_module	0x1021	const char *name_user	unsigned int flags	-	-	-	-	kernel/module.c:768
4130	get_kernel_syms	-	-	-	-	-	-	-	Not implemented
4131	quotactl	0x1023	unsigned int cmd	const char *special	qid_t id	void *addr	-	-	fs/quota/quota.c:346
4132	getpgid	0x1024	pid_t pid	-	-	-	-	-	kernel/sys.c:1154
4133	fchdir	0x1025	unsigned int fd	-	-	-	-	-	fs/open.c:396
4134	bdflush	0x1026	int func	long data	-	-	-	-	fs/buffer.c:3130
4135	sysfs	0x1027	int option	unsigned long arg1	unsigned long arg2	-	-	-	fs/filesystems.c:183

#	Name	param 0	param 1	param 2	param 3	param 4	param 5	param 6	Definition
					Registers				
4136	personality	0x1028	unsigned int personality	-	-	-	-	-	kernel/exec_domain.c:182
4137	afs_syscall	-	-	-	-	-	-	-	Not implemented
4138	setfsuid	0x102a	uid_t uid	-	-	-	-	-	kernel/sys.c:969
4139	setfsgid	0x102b	gid_t gid	-	-	-	-	-	kernel/sys.c:1008
4140	_llseek	0x102c	unsigned int fd	unsigned long offset_high	unsigned long offset_low	loff_t *result	unsigned int origin	-	fs/read_write.c:254
4141	getdents	0x102d	unsigned int fd	struct linux_dirent *dirent	unsigned int count	-	-	-	fs/readdir.c:191
4142	_newselect	0x102e	int n	fd_set *inp	fd_set *outp	fd_set *exp	struct timeval *tvp	-	fs/select.c:593
4143	flock	0x102f	unsigned int fd	unsigned int cmd	-	-	-	-	fs/locks.c:1636
4144	msync	0x1030	unsigned long start	size_t len	int flags	-	-	-	mm/msync.c:31
4145	readv	0x1031	unsigned long fd	const struct iovec *vec	unsigned long vlen	-	-	-	fs/read_write.c:787
4146	writev	0x1032	unsigned long fd	const struct iovec *vec	unsigned long vlen	-	-	-	fs/read_write.c:808
4147	cacheflush	0x1033	unsigned long addr	unsigned long bytes	unsigned int cache	-	-	-	arch/mips/mm/cache.c:67
4148	cachectl	0x1034	char *addr	int nbytes	int op	-	-	-	arch/mips/kernel/syscall.c:303
4149	sysmips	0x1035	-	-	-	-	-	-	arch/mips/kernel/syscall.c:265
4150	unused150	-	-	-	-	-	-	-	Not implemented
4151	getsid	0x1037	pid_t pid	-	-	-	-	-	kernel/sys.c:1191
4152	fdatasync	0x1038	unsigned int fd	-	-	-	-	-	fs/sync.c:206
4153	_sysctl	0x1039	struct __sysctl_args *args	-	-	-	-	-	kernel/sysctl_binary.c:1444
4154	mlock	0x103a	unsigned long start	size_t len	-	-	-	-	mm/mlock.c:482
4155	munlock	0x103b	unsigned long start	size_t len	-	-	-	-	mm/mlock.c:512
4156	mlockall	0x103c	int flags	-	-	-	-	-	mm/mlock.c:549
4157	munlockall	0x103d	-	-	-	-	-	-	mm/mlock.c:582
4158	sched_setparam	0x103e	pid_t pid	struct sched_param *param	-	-	-	-	kernel/sched/core.c:4477
4159	sched_getparam	0x103f	pid_t pid	struct sched_param *param	-	-	-	-	kernel/sched/core.c:4512
4160	sched_setscheduler	0x1040	pid_t pid	int policy	struct sched_param *param	-	-	-	kernel/sched/core.c:4462
4161	sched_getscheduler	0x1041	pid_t pid	-	-	-	-	-	kernel/sched/core.c:4486
4162	sched_yield	0x1042	-	-	-	-	-	-	kernel/sched/core.c:4711
4163	sched_get_priority_max	0x1043	int policy	-	-	-	-	-	kernel/sched/core.c:4935
4164	sched_get_priority_min	0x1044	int policy	-	-	-	-	-	kernel/sched/core.c:4960
4165	sched_rr_get_interval	0x1045	pid_t pid	struct timespec *interval	-	-	-	-	kernel/sched/core.c:4985
4166	nanosleep	0x1046	struct timespec *rqtp	struct timespec *rmtp	-	-	-	-	kernel/hrtimer.c:1621
4167	mremap	0x1047	unsigned long addr	unsigned long old_len	unsigned long new_len	unsigned long flags	unsigned long new_addr	-	mm/mremap.c:431
4168	accept	0x1048	int fd	struct sockaddr *upeer_sockaddr	int *upeer_addrlen	-	-	-	net/socket.c:1582
4169	bind	0x1049	int fd	struct sockaddr *umyaddr	int addrlen	-	-	-	net/socket.c:1446
4170	connect	0x104a	int fd	struct sockaddr *uservaddr	int addrlen	-	-	-	net/socket.c:1600
4171	getpeername	0x104b	int fd	struct sockaddr *usockaddr	int *usockaddr_len	-	-	-	net/socket.c:1663
4172	getsockname	0x104c	int fd	struct sockaddr *usockaddr	int *usockaddr_len	-	-	-	net/socket.c:1632
4173	getsockopt	0x104d	int fd	int level	int optname	char *optval	int *optlen	-	net/socket.c:1844
4174	listen	0x104e	int fd	int backlog	-	-	-	-	net/socket.c:1475
4175	recv	0x104f	int fd	void *ubuf	size_t size	unsigned int flags	-	-	net/socket.c:1799
4176	recvfrom	0x1050	int fd	void *ubuf	size_t size	unsigned int flags	struct sockaddr *addr	int *addr_len	net/socket.c:1754
4177	recvmsg	0x1051	int fd	struct msghdr *msg	unsigned int flags	-	-	-	net/socket.c:2189
4178	send	0x1052	int fd	void *buff	size_t len	unsigned int flags	-	-	net/socket.c:1742
4179	sendmsg	0x1053	int fd	struct msghdr *msg	unsigned int flags	-	-	-	net/socket.c:2016
4180	sendto	0x1054	int fd	void *buff	size_t len	unsigned int flags	struct sockaddr *addr	int addr_len	net/socket.c:1695
4181	setsockopt	0x1055	int fd	int level	int optname	char *optval	int optlen	-	net/socket.c:1810
4182	shutdown	0x1056	int fd	int how	-	-	-	-	net/socket.c:1874
4183	socket	0x1057	int family	int type	int protocol	-	-	-	net/socket.c:1324
4184	socketpair	0x1058	int family	int type	int protocol	int *usockvec	-	-	net/socket.c:1365
4185	setresuid	0x1059	uid_t ruid	uid_t euid	uid_t suid	-	-	-	kernel/sys.c:808
4186	getresuid	0x105a	uid_t *ruidp	uid_t *euidp	uid_t *suidp	-	-	-	kernel/sys.c:873
4187	query_module	-	-	-	-	-	-	-	Not implemented
4188	poll	0x105c	struct pollfd *ufds	unsigned int nfds	int timeout_msecs	-	-	-	fs/select.c:908
4189	nfsservctl	-	-	-	-	-	-	-	Not implemented
4190	setresgid	0x105e	gid_t rgid	gid_t egid	gid_t sgid	-	-	-	kernel/sys.c:893
4191	getresgid	0x105f	gid_t *rgidp	gid_t *egidp	gid_t *sgidp	-	-	-	kernel/sys.c:945
4192	prctl	0x1060	int option	unsigned long arg2	unsigned long arg3	unsigned long arg4	unsigned long arg5	-	kernel/sys.c:1999
4193	rt_sigreturn	0x1061	-	-	-	-	-	-	arch/mips/kernel/signal.c:365
4194	rt_sigaction	0x1062	int sig	const struct sigaction *act	struct sigaction *oact	size_t sigsetsize	-	-	kernel/signal.c:3174
4195	rt_sigprocmask	0x1063	int how	sigset_t *nset	sigset_t *oset	size_t sigsetsize	-	-	kernel/signal.c:2591
4196	rt_sigpending	0x1064	sigset_t *set	size_t sigsetsize	-	-	-	-	kernel/signal.c:2651
4197	rt_sigtimedwait	0x1065	const sigset_t *uthese	siginfo_t *uinfo	const struct timespec *uts	size_t sigsetsize	-	-	kernel/signal.c:2805
4198	rt_sigqueueinfo	0x1066	pid_t pid	int sig	siginfo_t *uinfo	-	-	-	kernel/signal.c:2938
4199	rt_sigsuspend	0x1067	sigset_t *unewset	size_t sigsetsize	-	-	-	-	kernel/signal.c:3274
4200	pread64	0x1068	char *buf size_t count	loff_t pos	-	-	-	-	fs/read_write.c:495
4201	pwrite64	0x1069	const char *buf size_t count	loff_t pos	-	-	-	-	fs/read_write.c:524
4202	chown	0x106a	const char *filename	uid_t user	gid_t group	-	-	-	fs/open.c:540
4203	getcwd	0x106b	char *buf	unsigned long size	-	-	-	-	fs/dcache.c:2885
4204	capget	0x106c	cap_user_header_t header	cap_user_data_t dataptr	-	-	-	-	kernel/capability.c:158

#	Name	Registers							Definition
		param 0	param 1	param 2	param 3	param 4	param 5	param 6	
4205	capset	0x106d	cap_user_header_t header	const cap_user_data_t data	-	-	-	-	kernel/capability.c:232
4206	sigaltstack	0x106e	-	-	-	-	-	-	arch/mips/kernel/signal.c:320
4207	sendfile	0x106f	int out_fd	int in_fd	off_t *offset	size_t count	-	-	fs/read_write.c:973
4208	getpmsg	-	-	-	-	-	-	-	Not implemented
4209	putpmsg	-	-	-	-	-	-	-	Not implemented
4210	mmap2	0x1072	unsigned long addr	unsigned long len	unsigned long prot	unsigned long flags	unsigned long fd	unsigned long pgoff	mm/mmap.c:1105
4211	truncate64	0x1073	loff_t length	-	-	-	-	-	fs/open.c:188
4212	ftruncate64	0x1074	loff_t length	-	-	-	-	-	fs/open.c:200
4213	stat64	0x1075	const char *filename	struct stat64 *statbuf	-	-	-	-	fs/stat.c:372
4214	lstat64	0x1076	const char *filename	struct stat64 *statbuf	-	-	-	-	fs/stat.c:384
4215	fstat64	0x1077	unsigned long fd	struct stat64 *statbuf	-	-	-	-	fs/stat.c:396
4216	pivot_root	0x1078	const char *new_root	const char *put_old	-	-	-	-	fs/namespace.c:2453
4217	mincore	0x1079	unsigned long start	size_t len	unsigned char *vec	-	-	-	mm/mincore.c:266
4218	madvise	0x107a	unsigned long start	size_t len_in	int behavior	-	-	-	mm/madvise.c:362
4219	getdents64	0x107b	unsigned int fd	struct linux_dirent64 *dirent	unsigned int count	-	-	-	fs/readdir.c:272
4220	fcntl64	0x107c	unsigned int fd	unsigned int cmd	unsigned long arg	-	-	-	fs/fcntl.c:468
4221	reserved221	-	-	-	-	-	-	-	Not implemented
4222	gettid	0x107e	-	-	-	-	-	-	kernel/timer.c:1569
4223	readahead	0x107f	loff_t offset size_t count	-	-	-	-	-	mm/readahead.c:579
4224	setxattr	0x1080	const char *pathname	const char *name	const void *value	size_t size	int flags	-	fs/xattr.c:361
4225	lsetxattr	0x1081	const char *pathname	const char *name	const void *value	size_t size	int flags	-	fs/xattr.c:380
4226	fsetxattr	0x1082	int fd	const char *name	const void *value	size_t size	int flags	-	fs/xattr.c:399
4227	getxattr	0x1083	const char *pathname	const char *name	void *value	size_t size	-	-	fs/xattr.c:459
4228	lgetxattr	0x1084	const char *pathname	const char *name	void *value	size_t size	-	-	fs/xattr.c:473
4229	fgetxattr	0x1085	int fd	const char *name	void *value	size_t size	-	-	fs/xattr.c:487
4230	listxattr	0x1086	const char *pathname	char *list	size_t size	-	-	-	fs/xattr.c:541
4231	llistxattr	0x1087	const char *pathname	char *list	size_t size	-	-	-	fs/xattr.c:555
4232	flistxattr	0x1088	int fd	char *list	size_t size	-	-	-	fs/xattr.c:569
4233	removexattr	0x1089	const char *pathname	const char *name	-	-	-	-	fs/xattr.c:602
4234	lremovexattr	0x108a	const char *pathname	const char *name	-	-	-	-	fs/xattr.c:620
4235	fremovexattr	0x108b	int fd	const char *name	-	-	-	-	fs/xattr.c:638
4236	tkill	0x108c	pid_t pid	int sig	-	-	-	-	kernel/signal.c:2923
4237	sendfile64	0x108d	int out_fd	int in_fd	loff_t *offset	size_t count	-	-	fs/read_write.c:992
4238	futex	0x108e	u32 *uaddr	int op	u32 val	struct timespec *utime	u32 *uaddr2	u32 val3	kernel/futex.c:2680
4239	sched_setaffinity	0x108f	pid_t pid	unsigned int len	unsigned long *user_mask_ptr	-	-	-	kernel/sched/core.c:4626
4240	sched_getaffinity	0x1090	pid_t pid	unsigned int len	unsigned long *user_mask_ptr	-	-	-	kernel/sched/core.c:4677
4241	io_setup	0x1091	unsigned nr_events	aio_context_t *ctxp	-	-	-	-	fs/aio.c:1298
4242	io_destroy	0x1092	aio_context_t ctx	-	-	-	-	-	fs/aio.c:1334
4243	io_getevents	0x1093	aio_context_t ctx_id	long min_nr	long nr	struct io_event *events	struct timespec *timeout	-	fs/aio.c:1844
4244	io_submit	0x1094	aio_context_t ctx_id	long nr	struct iocb * *iocbpp	-	-	-	fs/aio.c:1746
4245	io_cancel	0x1095	aio_context_t ctx_id	struct iocb *iocb	struct io_event *result	-	-	-	fs/aio.c:1781
4246	exit_group	0x1096	int error_code	-	-	-	-	-	kernel/exit.c:1136
4247	lookup_dcookie	0x1097	char *buf size_t len	-	-	-	-	-	fs/dcookies.c:148
4248	epoll_create	0x1098	int size	-	-	-	-	-	fs/eventpoll.c:1668
4249	epoll_ctl	0x1099	int epfd	int op	int fd	struct epoll_event *event	-	-	fs/eventpoll.c:1681
4250	epoll_wait	0x109a	int epfd	struct epoll_event *events	int maxevents	int timeout	-	-	fs/eventpoll.c:1809
4251	remap_file_pages	0x109b	unsigned long start	unsigned long size	unsigned long prot	unsigned long pgoff	unsigned long flags	-	mm/fremap.c:122
4252	set_tid_address	0x109c	int *tidptr	-	-	-	-	-	kernel/fork.c:1109
4253	restart_syscall	0x109d	-	-	-	-	-	-	kernel/signal.c:2501
4254	fadvise64	0x109e	loff_t offset size_t len	int advice	-	-	-	-	mm/fadvise.c:148
4255	statfs64	0x109f	const char *pathname	size_t sz	struct statfs64 *buf	-	-	-	fs/statfs.c:175
4256	fstatfs64	0x10a0	unsigned int fd	size_t sz	struct statfs64 *buf	-	-	-	fs/statfs.c:196
4257	timer_create	0x10a1	const clockid_t which_clock	struct sigevent *timer_event_spec	timer_t *created_timer_id	-	-	-	kernel/posix-timers.c:535
4258	timer_settime	0x10a2	timer_t timer_id	int flags	const struct itimerspec *new_setting	struct itimerspec *old_setting	-	-	kernel/posix-timers.c:819
4259	timer_gettime	0x10a3	timer_t timer_id	struct itimerspec *setting	-	-	-	-	kernel/posix-timers.c:715
4260	timer_getoverrun	0x10a4	timer_t timer_id	-	-	-	-	-	kernel/posix-timers.c:751
4261	timer_delete	0x10a5	timer_t timer_id	-	-	-	-	-	kernel/posix-timers.c:882
4262	clock_settime	0x10a6	const clockid_t which_clock	const struct timespec *tp	-	-	-	-	kernel/posix-timers.c:950
4263	clock_gettime	0x10a7	const clockid_t which_clock	struct timespec *tp	-	-	-	-	kernel/posix-timers.c:965
4264	clock_getres	0x10a8	const clockid_t which_clock	struct timespec *tp	-	-	-	-	kernel/posix-timers.c:1006
4265	clock_nanosleep	0x10a9	const clockid_t which_clock	int flags	const struct timespec *rqtp	struct timespec *rmtp	-	-	kernel/posix-timers.c:1035
4266	tgkill	0x10aa	pid_t tgid	pid_t pid	int sig	-	-	-	kernel/signal.c:2907
4267	utimes	0x10ab	char *filename	struct timeval *utimes	-	-	-	-	fs/utimes.c:221
4268	mbind	0x10ac	unsigned long start	unsigned long len	unsigned long mode	unsigned long *nmask	unsigned long maxnode	unsigned flags	mm/mempolicy.c:1263
4269	get_mempolicy	0x10ad	int *policy	unsigned long *nmask	unsigned long maxnode	unsigned long addr	unsigned long flags	-	mm/mempolicy.c:1400
4270	set_mempolicy	0x10ae	int mode	unsigned long *nmask	unsigned long maxnode	-	-	-	mm/mempolicy.c:1285
4271	mq_open	0x10af	const char *u_name	int oflag	umode_t mode	struct mq_attr *u_attr	-	-	ipc/mqueue.c:803
4272	mq_unlink	0x10b0	const char *u_name	-	-	-	-	-	ipc/mqueue.c:876
4273	mq_timedsend	0x10b1	mqd_t mqdes	const char *u_msg_ptr	size_t msg_len	unsigned int msg_prio	const struct timespec *u_abs_timeout	-	ipc/mqueue.c:971

#	Name	param 0	param 1	param 2	param 3	param 4	param 5	param 6	Definition
						Registers			
4274	mq_timedreceive	0x10b2	mqd_t mqdes	char *u_msg_ptr	size_t msg_len	unsigned int *u_msg_prio	const struct timespec *u_abs_timeout	-	ipc/mqueue.c:1092
4275	mq_notify	0x10b3	mqd_t mqdes	const struct sigevent *u_notification	-	-	-	-	ipc/mqueue.c:1201
4276	mq_getsetattr	0x10b4	mqd_t mqdes	const struct mq_attr *u_mqstat	struct mq_attr *u_omqstat	-	-	-	ipc/mqueue.c:1333
4277	vserver	-	-	-	-	-	-	-	Not implemented
4278	waitid	0x10b6	int which	pid_t upid	struct siginfo *infop	int options	struct rusage *ru	-	kernel/exit.c:1763
4280	add_key	0x10b8	const char *_type	const char *_description	const void *_payload	size_t plen	key_serial_t ringid	-	security/keys/keyctl.c:54
4281	request_key	0x10b9	const char *_type	const char *_description	const char *_callout_info	key_serial_t destringid	-	-	security/keys/keyctl.c:147
4282	keyctl	0x10ba	int option	unsigned long arg2	unsigned long arg3	unsigned long arg4	unsigned long arg5	-	security/keys/keyctl.c:1556
4283	set_thread_area	0x10bb	unsigned long addr	-	-	-	-	-	arch/mips/kernel/syscall.c:152
4284	inotify_init	0x10bc	-	-	-	-	-	-	fs/notify/inotify/inotify_user.c:749
4285	inotify_add_watch	0x10bd	int fd	const char *pathname	u32 mask	-	-	-	fs/notify/inotify/inotify_user.c:754
4286	inotify_rm_watch	0x10be	int fd	__s32 wd	-	-	-	-	fs/notify/inotify/inotify_user.c:795
4287	migrate_pages	0x10bf	pid_t pid	unsigned long maxnode	const unsigned long *old_nodes	const unsigned long *new_nodes	-	-	mm/mempolicy.c:1304
4288	openat	0x10c0	int dfd	const char *filename	int flags	umode_t mode	-	-	fs/open.c:1059
4289	mkdirat	0x10c1	int dfd	const char *pathname	umode_t mode	-	-	-	fs/namei.c:2723
4290	mknodat	0x10c2	int dfd	const char *filename	umode_t mode	unsigned dev	-	-	fs/namei.c:2646
4291	fchownat	0x10c3	int dfd	const char *filename	uid_t user	gid_t group	int flag	-	fs/open.c:559
4292	futimesat	0x10c4	int dfd	const char *filename	struct timeval *utimes	-	-	-	fs/utimes.c:193
4293	fstatat64	0x10c5	int dfd	const char *filename	struct stat64 *statbuf	int flag	-	-	fs/stat.c:407
4294	unlinkat	0x10c6	int dfd	const char *pathname	int flag	-	-	-	fs/namei.c:2968
4295	renameat	0x10c7	int olddfd	const char *oldname	int newdfd	const char *newname	-	-	fs/namei.c:3309
4296	linkat	0x10c8	int olddfd	const char *oldname	int newdfd	const char *newname	int flags	-	fs/namei.c:3097
4297	symlinkat	0x10c9	const char *oldname	int newdfd	const char *newname	-	-	-	fs/namei.c:3004
4298	readlinkat	0x10ca	int dfd	const char *pathname	char *buf	int bufsiz	-	-	fs/stat.c:293
4299	fchmodat	0x10cb	int dfd	const char *filename	umode_t mode	-	-	-	fs/open.c:486
4300	faccessat	0x10cc	int dfd	const char *filename	int mode	-	-	-	fs/open.c:299
4301	pselect6	0x10cd	int n	fd_set *inp	fd_set *outp	fd_set *exp	struct timespec *tsp	void *sig	fs/select.c:671
4302	ppoll	0x10ce	struct pollfd *ufds	unsigned int nfds	struct timespec *tsp	const sigset_t *sigmask	size_t sigsetsize	-	fs/select.c:942
4303	unshare	0x10cf	unsigned long unshare_flags	-	-	-	-	-	kernel/fork.c:1778
4304	splice	0x10d0	int fd_in	loff_t *off_in	int fd_out	loff_t *off_out	size_t len	unsigned int flags	fs/splice.c:1689
4305	sync_file_range	0x10d1	loff_t offset loff_t nbytes	unsigned int flags	-	-	-	-	fs/sync.c:275
4306	tee	0x10d2	int fdin	int fdout	size_t len	unsigned int flags	-	-	fs/splice.c:2025
4307	vmsplice	0x10d3	int fd	const struct iovec *iov	unsigned long nr_segs	unsigned int flags	-	-	fs/splice.c:1663
4308	move_pages	0x10d4	pid_t pid	unsigned long nr_pages	const void * *pages	const int *nodes	int *status	int flags	mm/migrate.c:1343
4309	set_robust_list	0x10d5	struct robust_list_head *head	size_t len	-	-	-	-	kernel/futex.c:2422
4310	get_robust_list	0x10d6	int pid	struct robust_list_head * *head_ptr	size_t *len_ptr	-	-	-	kernel/futex.c:2444
4311	kexec_load	0x10d7	unsigned long entry	unsigned long nr_segments	struct kexec_segment *segments	unsigned long flags	-	-	kernel/kexec.c:940
4312	getcpu	0x10d8	unsigned *cpup	unsigned *nodep	struct getcpu_cache *unused	-	-	-	kernel/sys.c:2179
4313	epoll_pwait	0x10d9	int epfd	struct epoll_event *events	int maxevents	int timeout	const sigset_t *sigmask	size_t sigsetsize	fs/eventpoll.c:1860
4314	ioprio_set	0x10da	int which	int who	int ioprio	-	-	-	fs/ioprio.c:61
4315	ioprio_get	0x10db	int which	int who	-	-	-	-	fs/ioprio.c:176
4316	utimensat	0x10dc	int dfd	const char *filename	struct timespec *utimes	int flags	-	-	fs/utimes.c:175
4317	signalfd	0x10dd	int ufd	sigset_t *user_mask	size_t sizemask	-	-	-	fs/signalfd.c:292
4318	timerfd	-	-	-	-	-	-	-	Not implemented
4319	eventfd	0x10df	unsigned int count	-	-	-	-	-	fs/eventfd.c:431
4320	fallocate	0x10e0	int mode loff_t offset	loff_t len	-	-	-	-	fs/open.c:272
4321	timerfd_create	0x10e1	int clockid	int flags	-	-	-	-	fs/timerfd.c:252
4322	timerfd_gettime	0x10e2	int ufd	struct itimerspec *otmr	-	-	-	-	fs/timerfd.c:344
4323	timerfd_settime	0x10e3	int ufd	int flags	const struct itimerspec *utmr	struct itimerspec *otmr	-	-	fs/timerfd.c:283
4324	signalfd4	0x10e4	int ufd	sigset_t *user_mask	size_t sizemask	int flags	-	-	fs/signalfd.c:237
4325	eventfd2	0x10e5	unsigned int count	int flags	-	-	-	-	fs/eventfd.c:406
4326	epoll_create1	0x10e6	int flags	-	-	-	-	-	fs/eventpoll.c:1625
4327	dup3	0x10e7	unsigned int oldfd	unsigned int newfd	int flags	-	-	-	fs/fcntl.c:53
4328	pipe2	0x10e8	int *fildes	int flags	-	-	-	-	fs/pipe.c:1133
4329	inotify_init1	0x10e9	int flags	-	-	-	-	-	fs/notify/inotify/inotify_user.c:724
4330	preadv	0x10ea	unsigned long fd	const struct iovec *vec	unsigned long vlen	unsigned long pos_l	unsigned long pos_h	-	fs/read_write.c:835
4331	pwritev	0x10eb	unsigned long fd	const struct iovec *vec	unsigned long vlen	unsigned long pos_l	unsigned long pos_h	-	fs/read_write.c:860
4332	rt_tgsigqueueinfo	0x10ec	pid_t tgid	pid_t pid	int sig	siginfo_t *uinfo	-	-	kernel/signal.c:2979
4333	perf_event_open	0x10ed	struct perf_event_attr *attr_uptr	pid_t pid	int cpu	int group_fd	unsigned long flags	-	kernel/events/core.c:6186
4334	accept4	0x10ee	int fd	struct sockaddr *upeer_sockaddr	int *upeer_addrlen	int flags	-	-	net/socket.c:1508
4335	recvmmsg	0x10ef	int fd	struct mmsghdr *mmsg	unsigned int vlen	unsigned int flags	struct timespec *timeout	-	net/socket.c:2313
4336	fanotify_init	0x10f0	unsigned int flags	unsigned int event_f_flags	-	-	-	-	fs/notify/fanotify/fanotify_user.c:679
4337	fanotify_mark	0x10f1	unsigned int flags __u64 mask	int dfd const char *pathname	-	-	-	-	fs/notify/fanotify/fanotify_user.c:767
4338	prlimit64	0x10f2	pid_t pid	unsigned int resource	const struct rlimit64 *new_rlim	struct rlimit64 *old_rlim	-	-	kernel/sys.c:1599
4339	name_to_handle_at	0x10f3	int dfd	const char *name	struct file_handle *handle	int *mnt_id	int flag	-	fs/fhandle.c:92
4340	open_by_handle_at	0x10f4	int mountdirfd	struct file_handle *handle	int flags	-	-	-	fs/fhandle.c:257
4341	clock_adjtime	0x10f5	const clockid_t which_clock	struct timex *utx	-	-	-	-	kernel/posix-timers.c:983
4342	syncfs	0x10f6	int fd	-	-	-	-	-	fs/sync.c:134
4343	sendmmsg	0x10f7	int fd	struct mmsghdr *mmsg	unsigned int vlen	unsigned int flags	-	-	net/socket.c:2091

#	Name	param 0	param 1	param 2	param 3	param 4	param 5	param 6	Definition
4344	setns	0x10f8	int fd	int nstype	-	-	-	-	kernel/nsproxy.c:235
4345	process_vm_readv	0x10f9	pid_t pid	const struct iovec *lvec	unsigned long liovcnt	const struct iovec *rvec	unsigned long riovcnt	unsigned long flags	mm/process_vm_access.c:398
4346	process_vm_writev	0x10fa	pid_t pid	const struct iovec *lvec	unsigned long liovcnt	const struct iovec *rvec	unsigned long riovcnt	unsigned long flags	mm/process_vm_access.c:405

Showing 1 to 346 of 346 entries