D

Е

F

G

CONTENTS

PRECAUTIONS	2
Precautions for Supplemental Restraint System	
(SRS) "AIR BAG" and "SEAT BELT PRE-TEN-	
SIONER"	2
Precautions	2
CLIP AND FASTENER	3
List of Table	3
INSTRUMENT PANEL ASSEMBLY	4
Component Parts Location	4
Removal and Installation	5

WORK ITEM TABLE	5
REMOVAL	5
REMOVAL AND INSTALLATION OF INSTRU-	
MENT PAD	9
REMOVAL AND INSTALLATION OF CONSOLE	
BOX	9
CONSOLE BOX	. 10
Disassembly and Assembly	. 11
INSTRUMENT PANEL PAD	. 11
GLOVE BOX COVER ASSEMBLY	. 11

ΙΡ

Н

Κ

L

M

PRECAUTIONS

PRECAUTIONS PFP:00001

Precautions for Supplemental Restraint System (SRS) "AIR BAG" and "SEAT BELT PRE-TENSIONER"

ISONAOW

The Supplemental Restraint System such as "AIR BAG" and "SEAT BELT PRE-TENSIONER", used along with a front seat belt, helps to reduce the risk or severity of injury to the driver and front passenger for certain types of collision. Information necessary to service the system safely is included in the SRS and SB section of this Service Manual.

WARNING:

- To avoid rendering the SRS inoperative, which could increase the risk of personal injury or death in the event of a collision which would result in air bag inflation, all maintenance must be performed by an authorized NISSAN/INFINITI dealer.
- Improper maintenance, including incorrect removal and installation of the SRS, can lead to personal injury caused by unintentional activation of the system. For removal of Spiral Cable and Air Bag Module, see the SRS section.
- Do not use electrical test equipment on any circuit related to the SRS unless instructed to in this Service Manual. SRS wiring harnesses can be identified by yellow and/or orange harnesses or harness connectors.

Precautions EIS0040X

- Disconnect both battery cables in advance.
- Disconnect air bag system line in advance.
- Never tamper with or force air bag lid open, as this may adversely affect air bag performance.
- Be careful not to scratch pad and other parts.
- When removing or disassembling any part, be careful not to damage or deform it. Protect parts, which may get in the way with cloth.
- When removing parts with a screwdriver or other tool, protect parts by wrapping them with vinyl or tape.
- Keep removed parts protected with cloth.
- If a clip is deformed or damaged, replace it.
- If an unreusable part is removed, replace it with a new one.
- Tighten bolts and nuts firmly to the specified torque.
- After re-assembly has been completed, make sure each part functions correctly.
- Remove stains in the following way.

Water-soluble stains:

Dip a soft cloth in warm water, and then squeeze it tightly. After wiping the stain, wipe with a soft dry cloth.

Dissolve a synthetic detergent in warm water (density of 2 to 3% or less), dip the cloth, then clean off the stain with the cloth. Next, dip the cloth in fresh water and squeeze it tightly. Then clean off the detergent completely. Then wipe the area with a soft dry cloth.

• Do not use any organic solvent, such as thinner or benzine.

CLIP AND FASTENER

CLIP AND FASTENER

Symbol No. Shape Removal and installation Removal: 1. Screw out with a Phillips screwdriver. 2. Remove female portion with flat-bladed screwdriver.

ΙP

Н

PFP:76906

MIIB0017E

Α

В

С

D

Е

F

G

J

Κ

L

M


INSTRUMENT PANEL ASSEMBLY

PFP:68200

Component Parts Location

SMA for VIN >SJNxxAK12U1000000

EIS004OI



1.	Passenger air bag module	2.	Instrument mask	3.	Upper instrument panel
4.	Combination meter	5.	Cluster lid "A"	6.	Instrument side mask (RH)
7.	Switch panel finisher	8.	Instrument panel under tray	9.	Side ventilator grille (RH)
10.	Instrument finisher	11.	Fuse block lid	12.	Cluster lid C
13.	Audio	14.	Glove box striker	15.	Instrument side mask (LH)
16.	Side ventilator grille (LH)	17.	Glove box cover assembly	18.	Glove box lid
19.	Tray	20.	Air conditioner finisher	21.	Steering column cover
22.	Steering lock escutcheon	23.	Instrument panel stay cover	24.	Console box
25.	Coin holder	26.	Instrument panel & pad	27.	Steering column protector
28.	Central ventilator grille (LH)	29.	Central ventilator grille (RH)	30.	Console mask

Removal and Installation WORK ITEM TABLE

SMA for VIN >SJNxxAK12U1000000

EIS004OJ

Α

В

С

D

F

F

G

Н

IΡ

M

Component Parts Location		Instrument panel &Brake pad	Instrument pad	Upper instru- ment panel	Combination meter	Audio, Car- Wings unit
A. Front pillar garnish	IP-5	[1]	[1]	[1]	[1]	[1] ^{Note}
B. Upper instrument panel	IP-6	[2]	[2]	[2]	[2]	[2] ^{Note}
C. Steering lock escutcheon	<u>IP-6</u>	[3]	[3]			
D. Instrument panel under tray	<u>IP-6</u>	[4]				
E. Switch panel finisher	<u>IP-6</u>	[5]	[4]			
F. Steering column cover	<u>IP-6</u>	[6]	[5]		[3]	
G. Combination switch	<u>IP-6</u>	[7]	[6]			
H. Cluster lid "A"	<u>IP-7</u>	[8]	[7]		[4]	
I. Combination meter	<u>IP-7</u>	[9]	[8]		[5]	
J. Instrument finisher	<u>IP-7</u>	[10]	[9]			[3]
K. Cluster lid C	<u>IP-7</u>	[11]	[10]			[4]
L. Air conditioner finisher	<u>IP-7</u>	[12]				
M. Instrument panel stay cover	IP-8	[13]				
N. Glove box lid	<u>IP-8</u>	[14]	[11]			
O. Glove box cover assembly	<u>IP-8</u>	[15]	[12]			
P. Side ventilator grille	<u>IP-8</u>	[16]	[13]			
Q. Instrument side mask	<u>IP-8</u>	[17]	[14]			
R. Passenger seat air bag module	<u>IP-8</u>	[18]	[15]			
S. Steering wheel	<u>IP-8</u>	[19]				
T. Instrument panel & pad	<u>IP-9</u>	[20]				
U. Instrument pad	<u>IP-9</u>		[16]			

^{[]:} The number shows the removal order.

CAUTION:

• Only applies to combinations of Car-Wings unit and MD/CD integrated AM/FM electronic tuner radio, and of pocket deck and MD/CD integrated AM/FM electronic tuner radio. Other companies can only be removed using procedures [3] and [4].

REMOVAL

A. Front Pillar Garnish

Refer to EI-19, "BODY SIDE TRIM" in EI section.

B. Upper Instrument Panel

- Insert a screwdriver wrapped with cloth into the instrument mask back notch to remove the instrument mask. When vehicle has sunload sensor, disconnect the sensor harness. Refer to <u>ATC-67</u>, "SUNLOAD SENSOR" in ATC section.
- 2. Insert a screwdriver, etc., wrapped with cloth into the upper instrument panel passenger side back edge and disengage metal clips and lift up panel.
- 3. Hold the lifted up part by hand, remove metal clips engaged in instrument pad, and remove upper instrument panel.

C. Steering Lock Escutcheon


Pull toward vehicle and remove.

CAUTION:

To install, align key cylinder end bottom protrusion with escutcheon inside notch and install.


D. Instrument Panel Under Tray

- 1. Disengage upper metal clips, hold bottom lid by hand, pull panel forward, and disengage metal clips.
- Remove being careful of interference from surrounding metal objects.



E. Switch Panel Finisher

Hold lid side (arrow area) by hand, disengage metal clips, and then pull forward and disengage plastic clips to remove.



F. Steering Column Cover

Upper

- 1. To make it easier to remove lower side, face steering pad top downward. (Tilt right side at about 160°)
- 2. Tilt down steering column and remove screw (1) facing front of vehicle.
- 3. Disengage hooks and remove.

Lower

Remove screws (3).

CAUTION:


Pull out being careful of interference with surrounding objects.

G. Combination Switch

Refer to LT-187, "LIGHTING AND TURN SIGNAL SWITCH" in LT section and WW-46, "Removal and Installation of Front Wiper and Washer Switch" (models without rain sensor) or WW-80, "Removal and Installation of Front Wiper and Washer Switch" (models with rain sensor) and WW-109, "Removal and Installation of Rear Wiper and Washer Switch" in WW section.


H. Cluster lid "A"

- 1. Tilt down steering column.
- 2. Pull cluster lid A forward and remove hooks and mounting clips.
- 3. While being careful of surrounding interference, remove from steering right side.




I. Combination Meter

After removing screws, remove harness connector, and then place combination meter top to the rear and remove.




J. Instrument Finisher

- Insert a screwdriver wrapped with tape into the bottom of instrument finisher, and pull up and remove finisher.
- (Vehicles with pocket decks) Open pocket, insert a screwdriver wrapped with tape into the bottom of the instrument finisher at the top, and remove the finisher.



K. Cluster Lid C

- 1. Remove screws and metal clips, hold lid bottom by hand, and pull straight out.
- 2. Separate and remove audio harness connector.
- 3. After removal, separate the center ventilator grille and audio equipment. Refer to <u>ATC-80, "DUCTS AND GRILLES"</u> in ATC section, <u>MTC-57, "DUCTS AND GRILLES"</u> in MTC section, <u>DI-64, "Removal and Installation of Drive Computer"</u> in DI section and <u>AV-12, "Removal and Installation of Audio Unit"</u> in AV section.



L. Air Conditioner Finisher

Refer to ATC-63, "Removal and Installation" in ATC section and MTC-43, "Removal and Installation" in MTC section.

ΙΡ

Α

В


J

K

L


M. Instrument Panel Stay Cover

- 1. Remove at LH/RH mounting clips.
- 2. Pull instrument stay cover toward rear of vehicle, disengage metal clips, orient straight above cup holder, and remove.




N. Glove Box Lid

1. Remove glove box pin and then remove glove box lid.



O. Glove Box Cover Assembly

- 1. Pull out tray (only vehicles equipped with tray).
- 2. Remove screws shown in figure, and then remove glove box cover assembly.
- After removal, separate parts. Refer to <u>IP-11, "GLOVE BOX COVER ASSEMBLY"</u> in "Disassembly and Assembly".




P. Side Ventilator Grille

Refer to <u>ATC-80, "DUCTS AND GRILLES"</u> in ATC section and <u>MTC-57, "DUCTS AND GRILLES"</u> in MTC section.

Q. Instrument Side Mask

- 1. Rotate instrument side mask to center of vehicle forward insertion area, disengage metal clips and plastic hooks, and remove.
- 2. Pull out inserted area and remove from vehicle.



R. Passenger Seat Air Bag Module

Refer to SRS-40, "FRONT PASSENGER AIR BAG MODULE" in SRS section.

S. Steering Wheel

Refer to <u>SRS-36</u>, "<u>DRIVER AIR BAG MODULE</u>" and <u>SRS-38</u>, "<u>SPIRAL CABLE</u>" in SRS section.


T. Instrument Panel & Pad Α 1. Tilt down steering column. 2. Remove screws, and remove instrument panel and pad from passenger door opening. 3. After removal, separate parts. Refer to IP-11, "INSTRUMENT PANEL PAD" in "Disassembly and Assem-В bly". **U. Instrument Pad** 1. Remove instrument pad screws (6). C 2. Remove metal clips (4) engaged in instrument panel, and remove instrument pad. REMOVAL AND INSTALLATION OF INSTRUMENT PAD D Removal 1. Remove front pillar garnish. Refer to IP-5, "A. Front Pillar Garnish". Remove upper instrument panel. Refer to IP-6, "B. Upper Instrument Panel". F Remove steering lock escutcheon. Refer to IP-6, "C. Steering Lock Escutcheon". Remove switch panel finisher. Refer to IP-6, "E. Switch Panel Finisher". F Remove steering column cover. Refer to IP-6, "F. Steering Column Cover". 6. Remove combination switch. Refer to IP-6, "G. Combination Switch". 7 Remove cluster lid "A". Refer to IP-7, "H. Cluster lid "A"". G 8. Remove combination meter. Refer to IP-7, "I. Combination Meter". 9. Remove instrument panel finisher. Refer to IP-7, "J. Instrument Finisher". 10. Remove cluster lid "C". Refer to IP-7, "K. Cluster Lid C". Н 11. Remove mask. Refer to IP-7, "L. Air Conditioner Finisher". 12. Remove glove box lid. Refer to IP-8, "N. Glove Box Lid". 13. Remove glove box cover assembly. Refer to IP-8, "O. Glove Box Cover Assembly". IΡ 14. Remove side ventilator grille (LH/RH). Refer to IP-8, "P. Side Ventilator Grille" . 15. Remove passenger air bag module. Refer to IP-8, "R. Passenger Seat Air Bag Module". Installation Install in the reverse order of removal. REMOVAL AND INSTALLATION OF CONSOLE BOX. Removal 1. For manual transmission vehicles, remove shift knob from shift lever. 2. Pull up parking brake 3. Remove inside key antenna (center console) (vehicles with key system only) connector from console box. M 4. Remove console mask. 5. Move the seat and remove the screws.

6. Lift up the console box and remove the front side clips.

Installation

Install in the reverse order of removal.


CONSOLE BOX



1. Console box

- 2. Console mask
- 3. Cup holder

- 1. Remove console mask. (hooks: 2 locations)
- 2. Open and secure the cup holder at the position where the lock opens, and then in this state pull it straight up to remove it.



Disassembly and Assembly INSTRUMENT PANEL PAD


EIS004OK

Α

В

D


Е



1. Instrument pad

Instrument panel

GLOVE BOX COVER ASSEMBLY



1. Glove box cover

2. Tray bracket assembly

ΙP

M

Н