

<b>Name:</b> Ruud Van G. Apostol	<b>Date:</b> 11/14/25
<b>Course / Section:</b> CPE212 / CPE31S4	<b>Instructor:</b> Engr. Robin Valenzuela

Procedure:

1. Create a repository and label it as "Final\_Exam\_Surname"


### Create a new repository

Repositories contain a project's files and version history. Have a project elsewhere? [Import a repository](#).  
Required fields are marked with an asterisk (\*).

1


General

Owner \*

 qrvgapostol

Repository name \*

Final\_Exam\_Apostol

 Final\_Exam\_Apostol is available.

Great repository names are short and memorable. How about musical-fiesta?

Description

Exam

Code

Issues

Pull requests

Actions

Projects

Wiki

 **Final\_Exam\_Apostol** Public

main

1 Branch

0 Tags

Go to file

 qrvgapostol Initial commit

README.md

Initial commit

README

# Final\_Exam\_Apostol

Exam

## 2. Clone your new repository in your VM

```
Apostol@ApostolCN:~$ git clone git@github.com:qrvgapostol/Final_Exam_Apostol.git
Cloning into 'Final_Exam_Apostol'...
remote: Enumerating objects: 8, done.
remote: Counting objects: 100% (8/8), done.
remote: Compressing objects: 100% (6/6), done.
remote: Total 8 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (8/8), done.
Apostol@ApostolCN:~$ ls
ansible                Dockerfile              playbook.yml
Apostol_PrelimExam     Documents               Public
config.yaml            Downloads               roles
CPE212                 Final_Exam_Apostol     snap
CPE212_Apostol         inventory_file.yaml    sysad2_Apostol
CPE212_Apostol_RuudVan inventory.ini            Templates
CPE_MIDEXAM_APOSTOL   Music                  Videos
Desktop                Pictures
Apostol@ApostolCN:~$ cd Final_Exam_Apostol
Apostol@ApostolCN:~/Final_Exam_Apostol$
```

## 3. Create an Ansible playbook that does the following with an input of a config.yaml file and structure inventory file.

### 3.1 Install and configure one enterprise service that can be installed in Debian and Centos servers

#### Control Node:

```
Apostol@ApostolCN:~/Final_Exam_Apostol$ systemctl status apache2
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; enabled; preset: >
   Active: active (running) since Fri 2025-11-14 06:16:21 UTC; 22min ago
     Docs: https://httpd.apache.org/docs/2.4/
   Process: 7003 ExecStart=/usr/sbin/apachectl start (code=exited, status=0/SU>
 Main PID: 7035 (apache2)
    Tasks: 6 (limit: 6760)
   Memory: 17.7M (peak: 18.4M)
      CPU: 210ms
   CGroup: /system.slice/apache2.service
           └─7035 /usr/sbin/apache2 -k start
             └─7142 /usr/sbin/apache2 -k start
               └─7143 /usr/sbin/apache2 -k start
                 └─7144 /usr/sbin/apache2 -k start
                   └─7145 /usr/sbin/apache2 -k start
                     └─7146 /usr/sbin/apache2 -k start
```

## Server2:

```
Apostol@Server2:~$ systemctl status apache2
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; enabled; preset: v
   Active: active (running) since Fri 2025-11-14 05:46:00 UTC; 53min ago
     Docs: https://httpd.apache.org/docs/2.4/
   Main PID: 2774 (apache2)
     Tasks: 6 (limit: 7600)
    Memory: 21.5M (peak: 22.1M)
       CPU: 380ms
    CGroup: /system.slice/apache2.service
           └─2774 /usr/sbin/apache2 -k start
           └─2778 /usr/sbin/apache2 -k start
           └─2779 /usr/sbin/apache2 -k start
           └─2780 /usr/sbin/apache2 -k start
           └─2781 /usr/sbin/apache2 -k start
           └─2782 /usr/sbin/apache2 -k start
```

## Server1:

```
Apostol@Server1:~$ systemctl status apache2
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; enabled; preset: v
   Active: active (running) since Fri 2025-11-14 05:44:35 UTC; 57min ago
     Docs: https://httpd.apache.org/docs/2.4/
   Main PID: 1788 (apache2)
     Tasks: 6 (limit: 7600)
    Memory: 21.6M (peak: 22.0M)
       CPU: 299ms
    CGroup: /system.slice/apache2.service
           └─1788 /usr/sbin/apache2 -k start
           └─1844 /usr/sbin/apache2 -k start
```

## CentOS:

```
[Apostol@vbox ~]$ sudo systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: di
   Active: active (running) since Fri 2025-11-14 13:53:18 PST; 49min ago
     Docs: man:httpd.service\(8\)
   Main PID: 966 (httpd)
    Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0; Bytes>
     Tasks: 177 (limit: 19847)
    Memory: 18.7M (peak: 19.2M)
       CPU: 5.901s
    CGroup: /system.slice/httpd.service
```

3.2 Install and configure one monitoring tool that can be installed in Debian and Centos servers (if it is a stack there should be option of different host)

CentOS:

```
[Apostol@vbox ~]$ sudo systemctl status node_exporter
* node_exporter.service - Prometheus Node Exporter
   Loaded: loaded (/etc/systemd/system/node_exporter.service; enabled; preset>
```

Server 2:

```
Apostol@Server2:~$ systemctl status node_exporter
● node_exporter.service - Prometheus Node Exporter
   Loaded: loaded (/etc/systemd/system/node_exporter.service; enabled; preset>
   Active: active (running) since Fri 2025-11-14 06:24:32 UTC; 7min ago
   Main PID: 9355 (node_exporter)
     Tasks: 5 (limit: 7600)
    Memory: 2.1M (peak: 2.4M)
       CPU: 24ms
    CGroup: /system.slice/node_exporter.service
           └─9355 /usr/local/bin/node_exporter
```

4.4 Change Motd as "Ansible Managed by <username>"

Centos:

```
Apostol@ApostolCN:~$ ssh Apostol@192.168.56.113
Ansible Managed by Apostol_Ruud Van
Activate the web console with: systemctl enable --now cockpit.socket

Last login: Fri Nov 14 14:16:22 2025 from 192.168.56.104
[Apostol@vbox ~]$
```


Server2:

```
Ansible Managed by ruud_apostol
Last login: Fri Nov 14 06:24:33 2025 from 192.168.56.104
Apostol@Server2:~$
```

4. Push and commit your files in GitHub

5. Make sure to show evidence of input (codes) process (codes successfully running) and output (evidence of installation)

**Playbooks.yml:**




The screenshot shows a terminal window with the title bar 'Apostol@ApostolCN: ~/Final\_Exam\_Apostol'. The window contains the GNU nano 7.2 editor editing 'playbooks.yml'. The visible code is as follows:

```
---
- name: Setup enterprise service and monitoring
  hosts: all
  become: true
  vars_files:
    - ./config.yml

  tasks:

    - name: Ensure package manager cache is up-to-date
      ansible.builtin.package:
        update_cache: yes

    # 3.1 Enterprise Service: Apache
    - name: Install Apache web server
      ansible.builtin.package:
        name: "{{ 'apache2' if ansible_os_family == 'Debian' else 'httpd' }}"
        state: present
```



The continuation of the 'playbooks.yml' file code is as follows:

```
    # 3.1 Enterprise Service: Apache
    - name: Install Apache web server
      ansible.builtin.package:
        name: "{{ 'apache2' if ansible_os_family == 'Debian' else 'httpd' }}"
        state: present

    - name: Start and enable Apache service
      ansible.builtin.service:
        name: "{{ 'apache2' if ansible_os_family == 'Debian' else 'httpd' }}"
        state: started
        enabled: yes

    # 3.2 Monitoring Tool: Node Exporter
    - name: Download Node Exporter binary
      ansible.builtin.get_url:
        url: "https://github.com/prometheus/node_exporter/releases/download/v1.1.0/node_exporter-1.1.0-linux-amd64.tar.gz"
        dest: /tmp/node_exporter.tar.gz
        mode: '0644'
      when: monitoring_tool is defined and monitoring_tool == "node_exporter"
```

```

- name: Extract Node Exporter
  ansible.builtin.unarchive:
    src: /tmp/node_exporter.tar.gz
    dest: /usr/local/bin/
    remote_src: yes
    extra_opts: [--strip-components=1]
  when: monitoring_tool is defined and monitoring_tool == "node_exporter"

- name: Create systemd service for Node Exporter
  ansible.builtin.copy:
    dest: /etc/systemd/system/node_exporter.service
    content: |
      [Unit]
      Description=Prometheus Node Exporter
      After=network.target

      [Service]
      ExecStart=/usr/local/bin/node_exporter
      User=nobody

```


```

- name: Start and enable Node Exporter
  ansible.builtin.systemd:
    name: node_exporter
    state: started
    enabled: yes
  when: monitoring_tool is defined and monitoring_tool == "node_exporter"

# 4.4 MOTD Message
- name: Update MOTD
  ansible.builtin.copy:
    dest: /etc/motd
    content: "Ansible Managed by [{ motd_user | default('Apostol_Ruud Van') }]"
    owner: root
    group: root
    mode: '0644'

```

### Config.yml:



```

le Machine View Input Devices Help
Nov 14 06:57
Apostol@ApostolCN: ~/Final_Exam_Apostol
GNU nano 7.2 config.yml
enterprise_service: apache
monitoring_tool: node_exporter
motd_user: ruud_apostol

```

5. For your final exam to be counted, please paste your repository link as an answer in this exam.

**Link:** [https://github.com/qrvgapostol/Final\\_Exam\\_Apostol](https://github.com/qrvgapostol/Final_Exam_Apostol)

Note: Extra points if you will implement the said services via containerization.