A Rule-Constrained Large Language Model Pipeline for Rule-Consistent Explanation of Vietnamese Complete Blood Count Results

Vo Hoang Khang[1,2,*] and Truong Quang Dai[1,2,3]

[1] Vietnam-Korea Institute of Technology, HUTECH University, Ho Chi Minh City, Vietnam
[2] Faculty of Information Technology, HUTECH University, Ho Chi Minh City, Vietnam
[3] FPT Telecom, Ho Chi Minh City, Vietnam
{vh.khang@hutech.edu.vn, truongquangdaihutech@gmail.com}
* Corresponding author: Vo Hoang Khang (vh.khang@hutech.edu.vn)

Abstract. Vietnamese patients increasingly ask general-purpose language models to explain laboratory reports, yet an unconstrained model can misstate results or falsely reassure. This study evaluates a rule-constrained pipeline in which deterministic rules assign every clinical label before invoking a language model; the model only paraphrases those labels, and a post-generation validator checks the output. On 150 synthetic complete blood count panels with known labels, an unconstrained Qwen2.5-3B model misstated at least one analyte direction in 91.3% of panels (95% CI 85.7–94.9) and falsely reassured in 32.0% (25.1–39.8). Prompt constraints reduced these rates to 12.7% and 8.0%; adding validation left no output violating the implemented checks, with 64.0% of panels served by model text and 36.0% by fixed templates. Two comparisons bound what this shows: a template-only configuration reaches the same pass rate with no model at all, and a 7B model cuts the template share to 4.0% while raising unconstrained false reassurance to 46.7%. The measure therefore reports rule consistency under the implemented checks, not clinical safety, and size does not substitute for the rule layer. Readability and patient comprehension were not measured. The contribution is an auditable architecture and a separately reported false-reassurance metric, not evidence of clinical benefit.

Keywords: health informatics, health literacy, large language models, laboratory results, output validation, patient safety.

1 Introduction

A patient leaving a Vietnamese laboratory receives a panel of values annotated with terms such as PDW, MCHC, and Monocyte, in units such as G/L, fL, and pg. The reference interval shows whether a value is out of range, but not what the analyte measures or whether the deviation matters. Health literacy remains limited in

Vietnam, including among digitally connected adults [1–4], and patients who receive results without explanation often search online [5]. Increasingly, that search means pasting the report into a general-purpose language model.

Such models can fail in two ways. They can misstate facts: asked in Vietnamese what white blood cells are, the 3B model used here answered that they are lymphocytes and, unprompted, mentioned cancer. More consequentially, they can describe an abnormal panel as normal. This false reassurance is fluent and plausible, and it removes the reason to seek care, so we treat it as a distinct error class.

Three questions guide the study: (RQ1) How often does unconstrained generation misstate results or falsely reassure on panels with known labels? (RQ2) How much do rule-assigned labels and prompt constraints reduce these errors? (RQ3) Can a post-generation validator eliminate outputs that violate the implemented checks, and what does that cost in fallback rate and latency? The study is an internal evaluation on synthetic data, not a clinical trial, and it does not measure whether patients understand the output.

2 Related Work and Contributions

Studies of language models for laboratory results mainly evaluate answer quality. He et al. [6] compared model and peer answers to patient questions, while Munoz-Zuluaga et al. [7] and Cadamuro et al. [8] reported incorrect or superficial answers and advised against diagnostic use. Similar assessments cover radiology reports [9] and scientific articles for patients [10]. Table 1 positions the present design against these studies; it is a selective comparison, not a systematic review.

Table 1. Comparison of related studies on language models explaining medical results.

Study	**Data and design**	**Reported evidence**	**Comparison with this study**
He et al. (2024) [6]	53 patient questions from a health forum; LLMs vs. peer answers.	Relevance, accuracy, helpfulness, harm; GPT-4 best.	Here: rule-assigned labels and validated output.
Munoz-Zuluaga et al. (2023) [7]	30 physician-written interpretation questions; GPT-4.	46.7% correct, 23.3% partially correct, 30% incorrect.	Here: patient-facing; false reassurance measured.
Cadamuro et al. (2023) [8]	EFLM working-group assessment of ChatGPT on test results.	Superficial or incorrect answers; not for diagnosis.	Here: clinical judgement removed from the model.
Bozer and Pekçevik (2025) [9]	Radiology reports explained by several LLMs; expert rating.	Readability, understandability, communication.	Here: consistency with assigned labels.
This study	150 synthetic CBC panels; 3 configurations; Qwen2.5-3B on CPU.	Six error classes, fallback rate, latency.	Auditable pipeline; no clinical validation.

Output control is a second line of work. Grammar-constrained decoding restricts generation to strings valid under a grammar [11], guided generation makes schema-constrained output efficient [12], and knowledge-constrained decoding prunes hallucinated tokens [13]. Structural validity does not ensure semantic correctness, so our validator checks content against labels computed independently of the model.

Unit heterogeneity is also known in laboratory data: 6–19% of tests could not be mapped accurately to LOINC in oncology data [14], harmonisation reduced 2,019 unit expressions to about 40 reference units [15], and automated LOINC mapping [16] and unit harmonisation [17] have been proposed. These works target data reuse; here, an unconverted unit caused a safety failure inside the rule layer.

The contribution is not a new language model but a safety architecture for rule-consistent patient-facing explanation, and it addresses three gaps. First, studies of language models on medical results evaluate answer quality without isolating false reassurance, although that error is the one that removes the reason to seek care. Second, controlled decoding enforces the structure of an output but not its agreement with a clinical label assigned outside the model. Third, unit harmonisation is treated as an interoperability problem, whereas here an unconverted unit is a safety failure inside the rule layer itself. The paper does not propose a new language model and does not claim clinical benefit.

Rules that decide and a model that only renders those decisions is an established pattern rather than a new one. Guardrail toolkits place programmable checks around a language model [18], and the data-to-text literature has long separated content selection from surface realisation [19]. Work on data-to-document generation reports that neural generators misstate facts present in their input [20], and accuracy evaluation in that field relies on human protocols rather than automatic scores [21]. Our pipeline inherits that division of labour and adds nothing to it architecturally. What we contribute is narrower: false reassurance measured as a separate class, the cost of the pass rate reported alongside it, and a quantified failure of the deterministic layer under Vietnamese unit conventions.

3 Rule-Constrained Pipeline

The design principle is that no clinical judgement is delegated to the language model. Fig. 1 shows the four layers: Layers 1, 2, and 4 are deterministic, and only Layer 3 uses the model.




Fig. 1. Four-layer pipeline; clinical labels are fixed before generation and verified after it.

3.1 Normalisation and Rule-Based Classification

Layer 1 maps analyte aliases, such as WBC, SLBC, or the full Vietnamese name, to canonical codes; the % and # markers are kept as tokens so that NEUT% and NEUT# do not collapse into one key. Values are then converted to canonical units. Units matter: haemoglobin reported as 14 g/dL is normal, but compared directly with a 130–175 g/L interval it is classified as severe anaemia. Layer 1 therefore refuses an analyte whose unit is unrecognised or missing when units of different magnitude are possible, and reports it separately.

Layer 2 compares each value x_j with its reference interval $[l_j, h_j]$ and assigns normal, monitor, or seek care. A value outside the interval is labelled monitor if its distance d_j to the nearest bound satisfies

$$d_j \leq s_j (h_j - l_j), \tag{1}$$

and seek care otherwise, where sj is an analyte-specific severity factor between 0.15 and 0.50 for the 22 analytes. The factors were set heuristically, not from a critical-value list. The panel label is the most severe analyte label, so classification is exact with respect to the configured intervals and severity factors and cannot be altered by the model; this is not a claim that those thresholds are clinically validated. The names monitor and seek care denote deviation categories, not triage advice: mapping one to patient-facing wording would require validation against a laboratory's critical-value policy and clinician review. Intervals come from one Vietnamese laboratory for adults; both are listed per analyte, with provenance, in Appendix A.

3.2 Constrained Generation and Validation

Layer 3 runs Qwen2.5-3B locally through Ollama, so laboratory data never leaves the institution. For each analyte, the prompt supplies the value, the interval, the pre-assigned direction and label, and a plain-language description. Three constraints apply: the model receives labels instead of deriving them; it must not name diseases, causes, medications, or treatments; and it must return a fixed JSON schema.

Layer 4 compares each generated item with the Layer 2 labels and detects six error classes: false reassurance in the closing statement, direction mismatch in the structured status field, contradictory wording in the prose, forbidden terms, fabricated analytes, and omitted analytes. Before matching, text is lower-cased, Vietnamese diacritics are removed, and phrases naming the reference interval are masked so that "normal" is not read as a status claim. A failing output is regenerated up to a limit and then replaced by a fixed template stating value, interval, and label, so no unvalidated model text is returned. The checks are lexical and bound by their patterns: an output can satisfy all six and still mislead through indirect phrasing. Appendix B gives the algorithm, the pattern table for each class, and worked cases.

4 Experimental Design

4.1 Synthetic Data and Configurations

The benchmark contains 150 synthetic complete blood count panels with 10–18 analytes each (mean 14.1, 2,118 readings), divided equally into normal, monitor, and seek-care panels. Synthetic data provides known labels and a balanced design, and avoids handling patient records. Aliases and units are sampled at random to exercise Layer 1; values are rounded as laboratories print them, and panels whose rounded values leave the intended class are regenerated. The generator is seeded, so the benchmark regenerates exactly; it is supplied with the analyte table, reference intervals, unit conversions, aliases and severity factors in the supplementary archive, and Appendix A reports the full distributions.

Seven configurations are compared on the same panels. Baseline gives raw values and intervals to the model with no labels, constraints, or validation, approximating a patient pasting a report into a chatbot. Template only uses Layers 1 and 2 and prints the fixed template directly, with no language model at all; it is the deterministic floor against which any model-based configuration has to justify itself. Constrained uses Layers 1–3 without validation. Full uses all four layers, and Full without retry is Full with regeneration disabled, so a first failure falls straight back to the template.

The constrained configuration bundles three mechanisms: rule-assigned labels, the content prohibitions, and the fixed JSON schema. To separate them, three further configurations were run on the same panels and model. Labels only supplies the labels and the schema; Constraints only keeps the prohibitions and the schema but gives raw values; Validator only uses the baseline prompt and adds Layer 4. Template only and Full without retry answer what the model is worth against the rules alone, and what regeneration is worth against a single attempt. Two further runs address size

and stability: baseline and Full were repeated with Qwen2.5-7B, and the constrained configuration was run five times to separate decoding variability from the differences between configurations.

4.2 Metrics

The validator-pass rate is the proportion of panels whose final output passes the implemented Layer 4 checks, including fallback templates; model-generated pass counts only panels passed by model text. The name is deliberate: the validator is both the filter and the measure, so a high rate shows only that nothing returned violates the implemented checks. Error metrics count panels with at least one instance of each of the six classes; formatting errors are reported separately. Runtime was measured on an Intel Core i5-9400F with 24 GB of memory and an NVIDIA GTX 1050 Ti with 4 GB: Qwen2.5-3B at Q4_K_M occupies about 3 GB and is offloaded to the card in full, whereas 7B does not fit and runs roughly half on the card and half on the processor. Generation used Ollama at temperature 0.2, a 2,048-token limit, JSON output mode, and no fixed seed. Proportions carry 95% Wilson confidence intervals, and configurations are compared with the McNemar test, since every configuration sees the same panels.

5 Experimental Results

Table 2 reports the comparison. Every error metric decreases monotonically from baseline to constrained to full.

Table 2. Comparison of the three main configurations on 150 synthetic panels (%).

Metric	Baseline	Constrained	Full
Validator pass	0.0	48.0	100.0
Model-generated pass	0.0	48.0	64.0
False reassurance	32.0	8.0	0.0
Direction mismatch	91.3	12.7	0.0
Contradictory wording	56.0	5.3	0.0
Forbidden terms	79.3	15.3	0.0
Fabricated analytes	32.0	10.0	0.0
Omitted analytes	71.3	28.7	0.0
Mean time per panel (s)	38.9	35.8	68.3

Unconstrained generation failed on content. Baseline passed the validator on no panel, misstated at least one direction in 91.3% of panels (95% CI 85.7–94.9) and asserted that all results were normal on 32.0% (25.1–39.8), roughly one patient in three. Pre-assigned labels and prompt constraints produced the largest drop, reducing direction mismatch to 12.7% (8.3–18.9), forbidden terms to 15.3% (10.4–22.0), contradictory wording to 5.3%, and false reassurance to 8.0% (4.6–13.5), a significant change in

pass rate (McNemar, $p < 0.001$). Nevertheless, 52.0% of constrained outputs still failed validation.

Full passed the validator on all 150 panels (95% CI 97.5–100.0). The figure needs qualification twice over. First, 64.0% of panels (56.1–71.2) were served by model text and 36.0% by fixed templates after regeneration failed, so the rate is a property of the pipeline and not evidence that a 3B model writes reliably; regeneration raised the model-written share from 46.0% (38.2–54.0) without retry to 64.0% with it, at roughly double the latency. Second, a configuration with no model at all reaches the same rate, which is taken up below.

In baseline, 97.3% of outputs used display names instead of canonical codes and 2.0% were unparseable; both fell to zero under the schema constraint. Full required 1.97 generation attempts on average and 68.3 s per panel (SD 33.7; p50 66.4, p95 121.5, p99 134.1), about twice the baseline latency of 38.9 s (p95 63.6). Re-scoring the outputs that Layer 4 rejected shows what regeneration was called on to fix: of the 54 panels that ended in a template, 66.7% had omitted an analyte, 38.9% contained a forbidden term, 29.6% misstated a direction and 18.5% falsely reassured.

One detail deserves scrutiny: 97.3% of baseline outputs identified analytes by display name instead of the canonical code, so part of the 0.0% pass rate could be formatting rather than content. Re-scoring every baseline output after mapping each name back through the alias table, which removes code-format errors entirely, raises the pass rate from 0.0% to 0.7%, one panel in 150. Direction mismatch rises from 91.3% to 92.7%, because items previously counted as fabricated now resolve to a real analyte and are judged on their stated direction; false reassurance (32.0%) and contradictory wording (56.0%) are unchanged. The baseline fails on content, not on formatting.

Section 3.1 treats unit heterogeneity as a safety problem rather than a data-reuse problem, and the claim can be quantified on the same panels. Of 2,118 analyte readings, 143 (6.8%) were reported in a unit of different magnitude from the canonical one. Had the pipeline compared those readings against the reference interval without conversion, 135 of them (94.4%) would have received the wrong label, affecting 97 of 150 panels (64.7%). All 135 errors were false alarms at the most severe level; a normal haemoglobin of 14.56 g/dL, for example, is classified as seek care against a 130–175 g/L interval. None ran in the safer direction. The failure is confined to the deterministic layer and is invisible to Layer 4, because every later stage faithfully reproduces the label.

Table 3 separates the mechanisms. Labels carry the correctness improvement: alone they cut direction mismatch from 91.3% to 14.0% (9.3–20.5) and yield a 38.7% pass rate (31.2–46.7) where the baseline yields none. Prompt constraints alone do not: direction mismatch stays at 87.3% and false reassurance rises to 43.3% (35.7–51.3), above the baseline, while their one measurable effect is on vocabulary, with forbidden terms falling from 79.3% to 35.3%. Instructing the model to be careful makes it speak more cautiously, not more correctly. Adding the prohibitions on top of the labels raises the pass rate to 48.0%, a difference that does not reach significance on 150 panels (McNemar, $p = 0.082$). The validator alone reaches 100.0% with 0.0% of panels served by model text: without labels to check against, Layer 4 can enforce the checks only by discarding the explanation.

Table 3. Contribution of each mechanism, 150 synthetic panels, values as % of panels except the last column. Template only uses no language model.

Configuration	Validator pass	Model text	Direction	False reass.	Forbidden	Time (s)
Baseline	0.0	0.0	91.3	32.0	79.3	38.9
Template only	100.0	0.0	0.0	0.0	0.0	0.003
Labels only	38.7	38.7	14.0	10.7	46.0	38.4
Constraints only	0.0	0.0	87.3	43.3	35.3	27.0
Validator only	100.0	0.0	0.0	0.0	0.0	95.5
Constrained	48.0	48.0	12.7	8.0	15.3	35.8
Full, no retry	100.0	46.0	0.0	0.0	0.0	35.2
Full	100.0	64.0	0.0	0.0	0.0	68.3

One comparison bounds what the language model contributes. The template-only configuration, which prints the Layer 2 labels directly and never calls a model, passes the validator on all 150 panels in 0.38 s for the whole benchmark, against 68.3 s per panel for the full pipeline. The McNemar test on the paired panels cannot distinguish the two ($p = 1.000$), and the same holds for validator-only. This is not a defect of the implementation but of the measure: a pass rate defined by consistency with the rules is maximised by output that the rules wrote. What the full pipeline adds is the 64.0% of panels that keep generated prose rather than a fixed sentence, and whether that prose is easier for a patient to read is the question this evaluation does not answer.

The error classes are easier to judge from instances than from rates. In panel SYN-0087, labelled monitor, the baseline closing statement read “Tất cả các chỉ số đều nằm trong khoảng bình thường” (all indices are within the normal range) and then named two abnormal ones, which is why the closing statement is checked apart from the per-analyte fields. In panel SYN-0149 the same configuration wrote that a haematocrit of 56.3% lay within a normal range of 40–50%, omitted red blood cells, and wrote “dấu hiệu của” (a sign of) about basophils, which the forbidden-term list blocks as diagnostic phrasing. Appendix C lists one worked example per class with the validator decision and the replacement output.

Model size changes what the pipeline costs, not how safe it is. Qwen2.5-7B was run on the same panels and scored by the same code. Under unconstrained generation it still passes on no panel, and on the error that matters most it is worse: false reassurance rises from 32.0% to 46.7% (95% CI 38.9–54.6) and fabricated analytes from 32.0% to 41.3%, while direction mismatch falls from 91.3% to 76.0% and omissions from 71.3% to 57.3%. The larger model writes more fluently and asserts normality more often. Inside the full pipeline the comparison reverses: both models pass on all 150 panels, but 7B is served by model text on 96.0% of panels (91.5–98.2) against 64.0%, needing 1.16 attempts against 1.97. A model more than twice the size buys a smaller fallback share, not a safer one, at 161.5 s per panel against 68.3 s.

Because decoding is not deterministic, the constrained configuration was run five times on the same panels. The pass rate averages 50.3% with a standard deviation of 2.4 points (range 48.0–53.3), so the single run in Table 2 sits at the low end of ordinary variation, and no per-class rate moves by more than about three points. The

panel level is far less stable: across the five runs only 31 of 150 panels pass every time and 37 fail every time, while 82 (54.7%) pass in some runs and fail in others. Aggregate rates are reproducible to within a few points, but an individual explanation is not reproducible at all, which argues for checking every output rather than trusting a configuration that scored well once.

6 Discussion and Application Prospects

6.1 Implications for Health Informatics

The results support a division of labour rather than better prompting: comparison against a reference interval is left to rules, and paraphrasing to the model. The two components can then improve independently; replacing heuristic thresholds with a laboratory's critical-value list changes only the labels, and a larger model would raise the model-written share without changing what Layer 4 enforces.

False reassurance deserves separate reporting. It may score well on readability because it is simple and calming, yet it was neither rare nor removed by instruction and reached zero only with mechanical verification. A prompt-level prohibition should not be taken as evidence of its absence.

Unit heterogeneity is a safety problem, not only a data-reuse problem. The g/dL-versus-g/L failure occurred in the deterministic layer with complete internal consistency, and no downstream check could detect it; standards such as LOINC and HL7 FHIR are therefore preconditions for rule-based clinical logic in Vietnamese laboratory reporting. A runtime of 68.3 s per panel, with a 95th percentile of 121.5 s, is acceptable for a once-per-report task on a consumer graphics card released in 2016, which is the relevant hardware bar for a provincial hospital rather than datacentre equipment; for the 36.0% fallback panels, output is no better than the report, although it never conflicts with the assigned labels.

6.2 Study Limitations

No medical professional reviewed the outputs, so they are shown to be consistent with the assigned labels, not clinically appropriate or comprehensible. The validator is both the filter and the measure, so its pass rate is not independent evidence of safety: a deterministic template reaches the same rate, and an output can satisfy every check and still mislead through indirect phrasing. Its errors run both ways: the contradictory-wording check reads a sentence quoting the reference interval without a comparator as a status claim, affecting an estimated quarter of the sentences it rejects. We left that unchanged rather than retune the validator after seeing the results; it inflates the fallback rate and understates the model. The severity factors are heuristic, and panels are synthetic, lacking the noise, missing fields and format variation of real reports.

Only structured complete blood count panels are supported; one-sided intervals and qualitative results are not handled. Only the constrained configuration was repeated, so the intervals for the other configurations carry the sampling uncertainty of 150

panels but not decoding variability. Sex- and age-specific intervals are not handled either, which matters most for haemoglobin, haematocrit and red cell count: a woman's result may be labelled abnormal against a male-derived interval. Independent expert review, a patient comprehension study, validated critical-value thresholds, broader test panels, and evaluation on real reports from multiple laboratories remain future work.

7 Conclusion

This study presents a pipeline in which rules fix every clinical label before a language model paraphrases it and a validator checks the result. On 150 synthetic panels, false reassurance fell from 32.0% under unconstrained generation to 8.0% with prompt constraints and to zero under the implemented checks, with 64.0% of panels served by model text and 36.0% by templates. A deterministic template reaches the same pass rate with no model, and a model more than twice the size raises unconstrained false reassurance rather than lowering it, so the result should be read as rule consistency under the implemented checks and not as clinical safety. The contribution is an auditable architecture and a separately reported false-reassurance metric; independent expert review and a patient comprehension study are required before any patient-facing use.

References

[1] Tran, M.T., Lai, H.T., Hoang, H.T., et al.: Health literacy among older adults: a descriptive cross-sectional analysis in Vietnam. Journal of Health Literacy 10(2), 91–100 (2025). https://doi.org/10.22038/jhl.2025.82477.1632

[2] Hoa, H.V., Giang, H.T., Vu, P.T., Tuyen, D.V., Khue, P.M.: Factors associated with health literacy among the elderly people in Vietnam. BioMed Research International 2020, 3490635 (2020). https://doi.org/10.1155/2020/3490635

[3] Dinh, T.T.H., Bonner, A.: Psychometric properties of the health literacy questionnaire tested in Vietnamese adults with chronic diseases. BMC Public Health 25, 44 (2025). https://doi.org/10.1186/s12889-024-21156-7

[4] Nguyen, B.N., Ngo, T.T., et al.: Health and eHealth literacy in Vietnam: evidence from a national survey. Patient Education and Counseling 148, 109583 (2026). https://doi.org/10.1016/j.pec.2026.109583

[5] Giardina, T.D., Baldwin, J., Nystrom, D.T., Sittig, D.F., Singh, H.: Patient perceptions of receiving test results via online portals: a mixed-methods study. Journal of the American Medical Informatics Association 25(4), 440–446 (2018)

[6] He, Z., Bhasuran, B., Jin, Q., et al.: Quality of answers of generative large language models versus peer users for interpreting laboratory test results for lay patients: evaluation study. Journal of Medical Internet Research 26, e56655 (2024). https://doi.org/10.2196/56655

[7] Munoz-Zuluaga, C., Zhao, Z., Wang, F., Greenblatt, M.B., Yang, H.S.: Assessing the accuracy and clinical utility of ChatGPT in laboratory medicine. Clinical Chemistry 69(8), 939–940 (2023)

[8] Cadamuro, J., Cabitza, F., Debeljak, Z., et al.: Potentials and pitfalls of ChatGPT and natural-language artificial intelligence models for the understanding of laboratory medicine test results. Clinical Chemistry and Laboratory Medicine 61(7), 1158–1166 (2023)
[9] Bozer, A., Pekçevik, Y.: Comparative evaluation of large language models in explaining radiology reports: expert assessment of readability, understandability, and communication features. Insights into Imaging 16, 232 (2025). https://doi.org/10.1186/s13244-025-02121-3
[10] Kianian, R., Sun, D., Rojas-Carabali, W., Agrawal, R., Tsui, E.: Large language models may help patients understand peer-reviewed scientific articles about ophthalmology: development and usability study. Journal of Medical Internet Research 26, e59843 (2024). https://doi.org/10.2196/59843
[11] Geng, S., Josifoski, M., Peyrard, M., West, R.: Grammar-constrained decoding for structured NLP tasks without finetuning. In: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (2023)
[12] Willard, B.T., Louf, R.: Efficient guided generation for large language models. arXiv:2307.09702 (2023)
[13] Choi, S., Fang, T., Wang, Z., Song, Y.: KCTS: knowledge-constrained tree search decoding with token-level hallucination detection. In: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (2023). https://doi.org/10.18653/v1/2023.emnlp-main.867
[14] Naliyatthaliyazchayil, P., Stenerson, T.: Harmonizing Logical Observation Identifiers Names and Codes (LOINC) codes and units in real-world oncology data: method development and evaluation. JMIR Medical Informatics 14, e81254 (2026). https://doi.org/10.2196/81254
[15] Zayed, A.M., Sarikakis, I., Delvaux, N.: Automated standardization and harmonization of laboratory units in large-scale clinical data using open-source R functions. International Journal of Medical Informatics 205, 106131 (2025). https://doi.org/10.1016/j.ijmedinf.2025.106131
[16] Parr, S.K., Shotwell, M.S., Jeffery, A.D., Lasko, T.A., Matheny, M.E.: Automated mapping of laboratory tests to LOINC codes using noisy labels in a national electronic health record system database. Journal of the American Medical Informatics Association 25(10), 1292–1300 (2018). https://doi.org/10.1093/jamia/ocy110
[17] de la Torre, J.: Scalable unit harmonization in medical informatics via Bayesian-optimized retrieval and transformer-based re-ranking. International Journal of Medical Informatics 206, 106180 (2026). https://doi.org/10.1016/j.ijmedinf.2025.106180
[18] Rebedea, T., Dinu, R., Sreedhar, M.N., Parisien, C., Cohen, J.: NeMo Guardrails: a toolkit for controllable and safe LLM applications with programmable rails. In: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pp. 431–445 (2023)
[19] Gatt, A., Krahmer, E.: Survey of the state of the art in natural language generation: core tasks, applications and evaluation. Journal of Artificial Intelligence Research 61, 65–170 (2018)
[20] Wiseman, S., Shieber, S.M., Rush, A.M.: Challenges in data-to-document generation. In: Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, pp. 2253–2263 (2017)
[21] Thomson, C., Reiter, E.: A gold standard methodology for evaluating accuracy in data-to-text systems. In: Proceedings of the 13th International Conference on Natural Language Generation, pp. 158–168 (2020)