

Project Name: Project 1: Voting System**Team# 09****Test Stage:** Unit ☒ System ☐**Test Date:** 21 March 2018**Test Case ID#:** CandidateTest_constructor_01**Name(s) of Testers:** Shalom Nguyen

Test Description: To test the default values in the candidate object constructor and the getters/setters to private data of said object.

The unit tests are in the unittest.cc in the testing folder. Once user runs make, a directory is created in the testing folder. Traverse the directory (/build/bin) and execute the executable (unittest).

Automated: yes ☒ no ☐**Results:** Pass ☒ Fail ☐**Preconditions for Test:**

1. default values are set in the constructor
 - a. if the default values in the constructor are altered, the unit test must be accommodated.
 - b. expected values are fixed constants.
 - c. to pass the test, these changes must be accounted for.

| Step # | Test Step Description | Test Data | Expected Result | Actual Result | Notes |
|--------|------------------------------|---|--|--|---|
| 1 | Instantiate the class object | default values of the default constructor in candidate.cc | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | the member data, ballot_list_ is a pointer to a Ballot object and therefore, cannot be actually tested. |
| 2 | calling object's setters | candidate_name_ = "Test"; num_ballots_ = 99; isWinner = true; | candidate_name_ == "Test"; num_ballots_ == 99; isWinner == true; | candidate_name_ == "Test"; num_ballots_ == 99; isWinner == true; | |

Post condition(s) for Test:

In its current state, the object, in this case, candidate, now has been assigned the above values (2). However, after testing, the object is destroyed via destructor and therefore, the system state remains the same.

Project Name: Project 1: Voting System**Team# 09****Test Stage:** Unit ☒ System ☐**Test Date:** 21 March 2018**Test Case ID#:** CandidateTest_toString_02**Name(s) of Testers:** Shalom Nguyen**Test Description:** To test the toString function.

The unit tests are in the unittest.cc in the testing folder. Once user runs make, a directory is created in the testing folder. Traverse the directory (/build/bin) and execute the executable (unittest).

Automated: yes ☒ no ☐**Results:** Pass ☒ Fail ☐**Preconditions for Test:**

1. var candidate_name_ exists

| Step # | Test Step Description | Test Data | Expected Result | Actual Result | Notes |
|--------|------------------------------------|---|--|--|---|
| 1 | Instantiate the class object | default values of the default constructor in candidate.cc | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | the member data, ballot_list_ is a pointer to a Ballot object and therefore, cannot be actually tested. |
| 2 | Calling object's setCandidate_name | candidate_name_ = "QWERTY"; | candidate_name_ = "QWERTY"; | candidate_name_ = "QWERTY"; | |
| 3 | Test toString | candidate_name_ | candidate_name_ = "QWERTY"; | candidate_name_ = "QWERTY"; | toString is a getter(: candidate_name_) |
| 4 | Return to default value | candidate_name_ = ""; | candidate_name_ == ""; | candidate_name_ == ""; | |
| 5 | Test values are as expected | candidate object | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | |

Post condition(s) for Test:

After testing, the object is destroyed via destructor and therefore, the system state remains the same.

Project Name: Project 1: Voting System

Team# 09

Test Stage: Unit ☒ System ☐

Test Date: 21 March 2018

Test Case ID#: CandidateTest_toStringWithVotes_03

Name(s) of Testers: Shalom Nguyen

Test Description: To test the toStringWithVotes

The unit tests are in the unittest.cc in the testing folder. Once user runs make, a directory is created in the testing folder. Traverse the directory (/build/bin) and execute the executable (unittest).

Automated: yes ☒ no ☐

Results: Pass ☒ Fail ☐

Preconditions for Test:

1. Initialization: candidate_name_, num_ballots_, and ballot_list_

| Step # | Test Step Description | Test Data | Expected Result | Actual Result | Notes |
|--------|------------------------------|--|--|--|---|
| 1 | Instantiate the class object | default values of the default constructor in candidate.cc | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | the member data, ballot_list_ is a pointer to a Ballot object and therefore, cannot be actually tested. |
| 2 | calling object's setters | candidate_name_ = "default"; num_ballots_ = 1; | candidate_name_ = "default"; num_ballots_ = 1; | candidate_name_ = "default"; num_ballots_ = 1; | |
| 3 | test toStringWithVotes | Ballot* someBallot = new Ballot; someBallot->setBallot_id(1); ballot_list_ = someBallot; | "default: 1" | "default: 1" | |
| 4 | Return to default values | candidate_name_ = ""; num_ballots_ = 0; | candidate_name_ == ""; num_ballots_ == 0; | candidate_name_ == ""; num_ballots_ == 0; | |
| 5 | Test values are as expected | candidate object | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | candidate_name_ == ""; num_ballots_ == 0; isWinner == false; | |

Post condition(s) for Test:

After testing, the object is destroyed via destructor and therefore, the system state remains the same. There may exist a Ballot* to someBallot even after testing.
