ALPHA & OMEGA SEMICONDUCTOR

# AOD254

## 150V N-Channel MOSFET

### General Description

The AOD254 uses trench MOSFET technology that is uniquely optimized to provide the most efficient high frequency switching performance.Power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Crss.In addition,switching behavior is well controlled with a soft recovery body diode.This device is ideal for boost converters and synchronous rectifiers for consumer, telecom, industrial power supplies and LED backlighting.

### Product Summary

| | |
|---|---|
| $V_{DS}$ | 150V |
| $I_D$ (at $V_{GS}$=10V) | 28A |
| $R_{DS(ON)}$ (at $V_{GS}$=10V) | < 46mΩ |
| $R_{DS(ON)}$ (at $V_{GS}$ =4.5V) | < 53mΩ |

100% UIS Tested
100% $R_g$ Tested

Green Product

**TO252 DPAK**







**Absolute Maximum Ratings $T_A$=25°C unless otherwise noted**

| Parameter | | Symbol | Maximum | Units |
|---|---|---|---|---|
| Drain-Source Voltage | | $V_{DS}$ | 150 | V |
| Gate-Source Voltage | | $V_{GS}$ | ±20 | V |
| Continuous Drain Current | $T_C$=25°C | $I_D$ | 28 | A |
| | $T_C$=100°C | | 20 | |
| Pulsed Drain Current [C] | | $I_{DM}$ | 45 | |
| Continuous Drain Current | $T_A$=25°C | $I_{DSM}$ | 4.5 | A |
| | $T_A$=70°C | | 3.6 | |
| Avalanche Current [C] | | $I_{AS}$ | 12 | A |
| Avalanche energy L=0.1mH [C] | | $E_{AS}$ | 7 | mJ |
| Power Dissipation [B] | $T_C$=25°C | $P_D$ | 100 | W |
| | $T_C$=100°C | | 50 | |
| Power Dissipation [A] | $T_A$=25°C | $P_{DSM}$ | 2.5 | W |
| | $T_A$=70°C | | 1.6 | |
| Junction and Storage Temperature Range | | $T_J$, $T_{STG}$ | -55 to 175 | °C |

**Thermal Characteristics**

| Parameter | | Symbol | Typ | Max | Units |
|---|---|---|---|---|---|
| Maximum Junction-to-Ambient [A] | t ≤ 10s | $R_{\theta JA}$ | 15 | 20 | °C/W |
| Maximum Junction-to-Ambient [A D] | Steady-State | | 41 | 50 | °C/W |
| Maximum Junction-to-Case | Steady-State | $R_{\theta JC}$ | 1 | 1.5 | °C/W |

**Electrical Characteristics ($T_J$=25°C unless otherwise noted)**

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **STATIC PARAMETERS** | | | | | | |
| $BV_{DSS}$ | Drain-Source Breakdown Voltage | $I_D$=250µA, $V_{GS}$=0V | 150 | | | V |
| $I_{DSS}$ | Zero Gate Voltage Drain Current | $V_{DS}$=150V, $V_{GS}$=0V | | | 1 | µA |
| | | $T_J$=55°C | | | 5 | |
| $I_{GSS}$ | Gate-Body leakage current | $V_{DS}$=0V, $V_{GS}$=±20V | | | ±100 | nA |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}$=$V_{GS}$, $I_D$=250µA | 1.7 | 2.2 | 2.7 | V |
| $I_{D(ON)}$ | On state drain current | $V_{GS}$=10V, $V_{DS}$=5V | 45 | | | A |
| $R_{DS(ON)}$ | Static Drain-Source On-Resistance | $V_{GS}$=10V, $I_D$=20A | | 37 | 46 | mΩ |
| | | $T_J$=125°C | | 74 | 90 | |
| | | $V_{GS}$=4.5V, $I_D$=20A | | 40 | 53 | mΩ |
| $g_{FS}$ | Forward Transconductance | $V_{DS}$=5V, $I_D$=20A | | 55 | | S |
| $V_{SD}$ | Diode Forward Voltage | $I_S$=1A,$V_{GS}$=0V | | 0.7 | 1 | V |
| $I_S$ | Maximum Body-Diode Continuous Current [G] | | | | 46 | A |
| **DYNAMIC PARAMETERS** | | | | | | |
| $C_{iss}$ | Input Capacitance | $V_{GS}$=0V, $V_{DS}$=75V, f=1MHz | | 2150 | | pF |
| $C_{oss}$ | Output Capacitance | | | 110 | | pF |
| $C_{rss}$ | Reverse Transfer Capacitance | | | 4 | | pF |
| $R_g$ | Gate resistance | $V_{GS}$=0V, $V_{DS}$=0V, f=1MHz | | 2.3 | | Ω |
| **SWITCHING PARAMETERS** | | | | | | |
| $Q_g$(10V) | Total Gate Charge | $V_{GS}$=10V, $V_{DS}$=75V, $I_D$=20A | | 27 | 40 | nC |
| $Q_g$(4.5V) | Total Gate Charge | | | 12 | 17 | nC |
| $Q_{gs}$ | Gate Source Charge | | | 7 | | nC |
| $Q_{gd}$ | Gate Drain Charge | | | 3 | | nC |
| $t_{D(on)}$ | Turn-On DelayTime | $V_{GS}$=10V, $V_{DS}$=75V, $R_L$=3.75Ω, $R_{GEN}$=3Ω | | 9 | | ns |
| $t_r$ | Turn-On Rise Time | | | 10 | | ns |
| $t_{D(off)}$ | Turn-Off DelayTime | | | 29 | | ns |
| $t_f$ | Turn-Off Fall Time | | | 4 | | ns |
| $t_{rr}$ | Body Diode Reverse Recovery Time | $I_F$=20A, dI/dt=500A/µs | | 51 | | ns |
| $Q_{rr}$ | Body Diode Reverse Recovery Charge | $I_F$=20A, dI/dt=500A/µs | | 434 | | nC |

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A$ =25° C. The Power dissipation $P_{DSM}$ is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design, and the maximum temperature of 175° C may be used if the PCB allows it.
B. The power dissipation $P_D$ is based on $T_{J(MAX)}$=175° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=175° C. Ratings are based on low frequency and duty cycles to keep initial $T_J$ =25° C.
D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.
E. The static characteristics in Figures 1 to 6 are obtained using <300µs pulses, duty cycle 0.5% max.
F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=175° C. The SOA curve provides a single pulse rating.
G. The maximum current rating is package limited.
H. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A$=25° C.

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




**Figure 12: Single Pulse Avalanche capability (Note C)**




**Figure 13: Power De-rating (Note F)**




**Figure 14: Current De-rating (Note F)**




**Figure 15: Single Pulse Power Rating Junction-to-Ambient (Note H)**




**Figure 16: Normalized Maximum Transient Thermal Impedance (Note H)**

## Gate Charge Test Circuit & Waveform




## Resistive Switching Test Circuit & Waveforms




## Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




## Diode Recovery Test Circuit & Waveforms