Shengjie Quan

Professor: Adam C. Champion

CSE 3461

March 18, 2016

Response to Homework 3

- 1. There are four columns in the VC forwarding table. Names are as follow:
 - Incoming Interface
 - Incoming VC #
 - Outgoing Interface
 - Outgoing VC #

Their meaning are intuitive by their names.

There are two columns in the datagram network forwarding table. Names are as follow:

- Destination Address Range
- Link Interface

Their meaning are intuitive by their names.

2. a. Below is the longest prefix forwarding table:

Destination Address Range	Link Interface
11100000 00***** ****** ****	0
11100000 01000000 ****** ***	1
11100000 ******* ****** *****	2
11100001 0****** ****** *****	2
otherwise	3

b. Below is the forwarding result:

Address	Link Interface
11001000 10010001 01010001 01010101	3
11100001 01000000 11000011 00111100	2
11100001 10000000 00010001 01110111	3

- 3. In the situation that both Arnold and Bernard are behind a NAT, it is impossible to establish a TCP connection between them. A TCP connection requires a three way hand shake to start (by sending SYN packages). However, since both side are behind NAT, the router will have no idea which internal client to send the SYN package to without application-specific configuration. So the SYN will be dropped and the connection will not be established.
- 4. Below is the result of running Dijkstra's shortest-path algorithm starting from u:

Step	N	D(t), p(t)	D(v), p(v)	D(w), p(w)	D(x), p(x)	D(y), p(y)	D(z), p(z)
0	u	2, u	3, u	3, u	∞	∞	∞
1	u t		3, u	3, u	∞	9, t	∞
2	u t v			3, u	6, v	9, t	∞
3	u t v w				6, v	9, t	∞
4	utvwx					9, t	14, x
5	utvwxy						14, x
6	utvwxyz						

- 5. The distance table is attached at the end.
- 6. Anycasting is a "network addressing and routing methodology" which allows "nodes to access one of a collection of servers providing a well-known service, without manual configuration in each node of the list of servers". The packages sent by a sender can be routed to "the topologically nearest node in a group of potential receivers". The packages are sent to several nodes but identified by the same destination address. One application is that anycasting simplified network configuration process. As mentioned previously anycasting allows packages to be sent to several nodes but identified by the same destination address. For example, a worldwide service (e.g. Youtube) need to deployed. In traditional way, DNS servers need to be configures at different places (e.g. Asia, Europe, America) in order to direct users to their nearest server. With the help of anycasting, we can just configure one IP address everywhere.
- 7. a. Below is the routing table of stdlinux. Destination is the destination host or network. Gateway is the address of the gateway (* means not yet set). Genmask is the netmask of the destination network. In Flags, U means router is up, G means gateway is used, etc. MSS is the abbreviation of maximum segment size. The irtt is the some kind of

time to live (timed out setting). Iface is the Internet interface to which packages will be sent for this route.

```
% /bin/netstat -r
2 Kernel IP routing 5....
3 Destination Gateway
4 164.107.113.0 *
   Kernel IP routing table
                                    Genmask
                                                     Flags
                                                             MSS Window irtt Iface
                                                     U
                                                             0 0
                                    255.255.255.0
                                                                             0 eth0
   link-local
                                    255.255.0.0
                                                     U
                                                                0 0
                                                                             0 eth0
                  hsrp113.cse.ohi 0.0.0.0
                                                     UG
                                                                0 0
   default
                                                                             0 eth0
```

b. The titles of each columns are the same. hsrp113.cse.ohio-state.edu is now resolved into 164.107.113.1. For *, it is resolved to 0.0.0.0. link-local is resolved to 169.254.0.0.

1	Destination	Gateway	Genmask	Flags	MSS Window	irtt Iface	
2	164.107.113.0	0.0.0.0	255.255.255.0	U	0 0	0 eth0	
3	169.254.0.0	0.0.0.0	255.255.0.0	U	0 0	0 eth0	
4	0.0.0.0	164.107.113.1	0.0.0.0	UG	0 0	0 eth0	

			Step 1					Sı	tep 2						Step 3		
Node:	u		İ			Node:	u					Node:	u				
		(Cost Via					Co	st Via					C	ost Via		
	D^u	ν	y		DV		D^u	v	y		DV		D^u	v	y		DV
Dest	v	1	$ \infty $		v, 1	Dest	v	1	∞		v, 1	Dest	v	1	5		v, 1
	x	4	∞		x, ∞		x	4	5		x, 4		x	4	5		x, 4
	y	∞	2		y, 2		y	∞	2		y, 2		y	4	2		y, 2
	Z	∞	∞		Ζ, ∞		Z	7	∞		z, 7		Z	6	7		z, 6
Node:	v					Node:	V					Node:	v				
riode.	<u> </u>		Cost Via			1,000.	<u>'</u>	Co	st Via			11000.	<u> </u>	C	ost Via		
	D^{v}	и	x	Z	DV		D^{ν}	и	x	z	DV		D^{ν}	u	x	z	DV
Dest	u	1	∞	∞	u, 1	Dest	u	1	∞	∞	u, 1	Dest	и	1	7	12	u, 1
	x	∞	3	∞	x, 3		x	5	3	8	x, 3		x	5	3	8	x, 3
	y	∞	∞	∞	y, ∞		y	3	6	∞	y, 3		y	3	6	11	y, 3
	Z	∞	∞	6	z, 6		Z	8	5	6	z, 5		Z	7	5	6	z, 5
Node:	X					Node:	X					Node:	X				
10000.11		Cost Via					Cost Via						Cost Via				
	D^{x}	v	y	Z	DV		D^{x}	ν	y	z	DV		D^{x}	v	y	z	DV
Dest	и	∞	∞	∞	u, ∞	Dest	и	4	5	∞	u, 4	Dest	u	4	5	8	u, 4
	v	3	∞	∞	v, 3		v	3	∞	8	v, 3		v	3	6	7	v, 3
	у	∞	3	$ \infty $	y, 3		y	6	3	$ \infty $	y, 3		y	6	3	7	y, 3
	Z	∞	∞	2	z, 2		Z	8	∞	2	z, 2		Z	8	8	2	z, 2
Node:	V					Node:	V					Node:	V				
Trode. y		Cost Via		1 (ode:	Cost Via			11000.		Cost Via							
	Dy	и	x		DV		D^{y}	u	x		DV		Dy	и	x		DV
Dest	u	2	$ \infty $		u, 2	Dest	и	2	7		u, 2	Dest	и	2	7		u, 2
	v	∞	∞		v, ∞		v	3	6		v, 3		v	3	6		v, 3
	x	∞	3		y, 3		x	6	3		y, 3		x	6	3		y, 3
	Z	∞	∞		Ζ, ∞		Z	9	5		z, 5		Z	8	5		z, 5
Node:	z					Node:	 Z					Node:	 Z				
		Cost Via				Cost Via					Cost Via						
	D^z	v	x		DV		D^z	ν	x		DV		D^z	v	x		DV
Dest	и	∞	∞		u, ∞	Dest	u	7	6		u, 6	Dest	u	7	6		u, 6
	v	6	∞		v, 6		v	6	5		v, 5		v	6	5		v, 5
	x	∞	2		y, 2		x	9	2		y, 2		x	9	2		y, 2
	y	∞	∞		z, ∞		y	9	5		z, 5		y	9	5		z, 5