QuantRule - User Journey and Value

2026-11-12

1. The operator

One systematic researcher. They own the candles, choose the hypothesis, submit batch runs, and decide whether to accept, revise, or stop. They are not a tenant, not an account, and not a team. A reviewer is the secondary reader: someone who must reproduce a result from an image digest and a canonical digest.

2. The first run

#	The operator does	Sees	Value
1	Clones the repository and runs `make up`	`ready -> http://localhost:8080`	one command, no configuration file
2	Opens the URL	`connected . v1.0.0`	a client that is only a browser
3	Creates a profile, or keeps `default`	the switcher shows the active profile	research lines stay separate
4	Uploads a candle CSV once	`data_version`, candles, coverage	data identified by content
5	Picks a config, sees `valid`, submits	`202`, the run appears `queued`	submission returns immediately
6	Closes the laptop	-	the run does not depend on the session
7	Returns and opens the URL	`succeeded`, stages, provenance, digest, artifacts	evidence with an audit trail
8	Copies the digest, or runs `make verify`	one hash	reproducible, comparable, defensible

3. The research loop

Before committing to a run, the operator can explore:

#	Does	Sees	Value
1	Creates a simulation run from a recorded bundle and a premise	a seeded window selection	a bounded, reproducible sample

#	Does	Sees	Value
2	Opens a window	candles, EMAs, events, levels	the context, with the future visible
3	Marks entries and exits as good or bad	marks drawn on the chart	judgment captured in a schema
4	Runs the oracle	the deterministic marks for the same window	a mechanical second opinion
5	Reviews the difference	a candidate rule with at most two conditions	a testable hypothesis
6	Runs the check on a later, unmarked window	an event study, 30-event minimum	a screen, not an edge
7	Decides test, refine, or stop	a decision record	a hypothesis for Strategy Research, or a stop

The loop is hindsight by design. It never feeds a run, and a strategy can never read it.

4. Remote compute

The operator starts the same stack on a server, points the browser at it, and submits from any machine. Closing the laptop changes nothing, because the run is a server job.

5. Profiles

Profiles organise research: one per instrument, timeframe set, or campaign. They share the content-addressed bytes and keep separate records. They are not a security boundary, and the product never calls them one.

6. The desktop shell

A GitHub Release asset installs a Tauri window. It asks for the gateway URL once, then behaves exactly like the browser: same screens, same profiles, same data. It contains no engine and reads no local file.

7. What the product is worth

Value	Because
Reproducible	The same inputs and image digest produce the same data artifacts
Auditable	Every result names its data version, config hash, model version, and image digest
Detachable	A run outlives the client that submitted it
Portable	Any machine with the URL uses it; the compute can move
Organised	Profiles keep separate research lines separate
Sovereign	No account, no vendor; candle data stays on the operator's network

Value	Because
Honest	A negative result is valid and the workflow can stop

8. What the operator never does

- Type a filesystem path.
- Create an account.
- Install Docker to use the desktop shell.
- Compare a bundle by hand.
- Wait with a terminal open.
- Lose a research line in a single undifferentiated list.