Checkpoint A — Context and First Behaviour

QuantRule

2026-11-11

Contents

1 Checkpoint A — Context and First Behaviour **1**
1.1 Claim . . . 1
1.2 User and context . . . 1
1.3 Scope fence . . . 1
1.4 Evidence . . . 1
1.5 Limit . . . 2
1.6 Decision . . . 2

1 Checkpoint A — Context and First Behaviour

1.1 Claim

For a solo systematic researcher with local OHLCV data, QuantRule will turn one rule-based hypothesis into a reproducible, portfolio-constrained evidence bundle, measured by a byte-identical rerun and a complete provenance manifest, with the limitation that the evidence is historical and does not establish future profit.

1.2 User and context

- User: a solo researcher on Linux who owns the candles.
- Current friction: backtests are easy to run but hard to reproduce, compare, and defend.
- First increment: import data, configure a model/strategy/portfolio, run one backtest, and inspect the evidence.

1.3 Scope fence

Included: local app, local data, local research memory, Linux distribution.

Excluded: accounts, team cloud, cloud compute, live trading, prop-firm rules, Windows and macOS.

1.4 Evidence

- The current shell run is deterministic; `cargo test` passes 1,443 tests.
- `v0.8.0` freezes the pre-Tauri surface.
- Phase 3 will provide the installer and the end-to-end demo.

1.5 Limit

The evidence is single-user and historical. It does not prove adoption, team collaboration, or future profitability.

1.6 Decision

Proceed to the local Tauri increment; do not build the team cloud until the solo workflow is validated.