Checkpoint E — Delivery, Observation, and Recovery

QuantRule

2026-11-11

Contents

1 Checkpoint E — Delivery, Observation, and Recovery **1**
1.1 Claim . . . 1
1.2 Delivery . . . 1
1.3 Observation . . . 1
1.4 Recovery . . . 1
1.5 Evidence . . . 2
1.6 Limit . . . 2
1.7 Decision . . . 2

1 Checkpoint E — Delivery, Observation, and Recovery

1.1 Claim

A solo researcher can install the Linux app, run the first workflow, observe failures, and recover the local workspace without a cloud service.

1.2 Delivery

- Linux AppImage and deb installers.
- Static download page with checksums and release notes.
- Headless CLI for automation and reproducibility.
- No account, no backend, no cloud data.

1.3 Observation

- Deterministic command output and run artifacts.
- Optional local logs and crash reports; no strategy or candle contents.
- Export/import and workspace backup.
- A failed run is an error with a clear message, not an outage.

1.4 Recovery

Failure	Recovery
Corrupt workspace	Restore from export/backup
Failed update	Reinstall the previous verified installer
Data mismatch	Re-import the dataset and verify its checksum

Failure	Recovery
Lost machine	Restore the research memory export and re-download data
Network source failure	Retry or import a local CSV

1.5 Evidence

- Installer smoke test on a clean Linux environment.
- Backup/restore test.
- Offline test.
- Checksums match the download page.

1.6 Limit

There is no cloud backup and no team recovery. The team cloud is future work.

1.7 Decision

Ship Linux installers and the static download page; add auto-update only if it does not delay the first release.