Checkpoint E — Delivery, Observation, and Recovery

QuantRule

2026-11-12

Contents

1 Checkpoint E — Delivery, Observation, and Recovery **1**
1.1 Claim . . . 1
1.2 Delivery . . . 1
1.3 Observation . . . 1
1.4 Recovery . . . 1
1.5 Evidence . . . 2
1.6 Limit . . . 2
1.7 Decision . . . 2

1 Checkpoint E — Delivery, Observation, and Recovery

1.1 Claim

A solo researcher can install the Linux app, run the first workflow, observe failures, and recover the local workspace without a cloud service.

1.2 Delivery

- Linux AppImage and deb installers.
- Static download page with checksums and release notes.
- Headless CLI for automation and reproducibility.
- No account, no backend, no cloud data.

1.3 Observation

- Deterministic command output and run artifacts.
- Optional local logs and crash reports; no strategy or candle contents.
- Export/import and workspace backup.
- A failed run is an error with a clear message, not an outage.

1.4 Recovery

Failure	Recovery
Corrupt workspace	Restore from export/backup
Failed update	Reinstall the previous verified installer
Data mismatch	Re-import the dataset and verify its checksum

Failure	Recovery
Lost machine	Restore the research memory export and re-download data
Network source failure	Retry or import a local CSV

1.5 Evidence

- Ubuntu 24.04 container: the `.deb` installs and launches under Xvfb.
- The AppImage launches with `bwrap --unshare-net`.
- Research-memory export/import and backup/restore tests pass.
- The release note records the image digest, and the image check runs at release time checksums.
- The Phase 3 report is `docs/reports/2026-11-11/implementation-verification.md`.

1.6 Limit

There is no cloud backup, auto-update, or team recovery. The native UI is not WebDriver-driven. The team cloud is future work.

1.7 Decision

Ship Linux installers and the static download page; add auto-update only if it does not delay the first release.