

Improving Tokenisation by Alternative Treatment of Spaces

Edward Gow-Smith, Harish Tayyar Madabushi,
Carolina Scarton and Aline Villavicencio

Department of Computer Science, University of Sheffield
United Kingdom

{egow-smith1, h.tayyarmadabushi, c.scarton, a.villavicencio}
@sheffield.ac.uk

Abstract

Tokenisation is the first step in almost all NLP tasks, and state-of-the-art transformer-based language models all use subword tokenisation algorithms to process input text. Existing algorithms have problems, often producing tokenisations of limited linguistic validity, and representing equivalent strings differently depending on their position within a word. We hypothesise that these problems hinder the ability of transformer-based models to handle complex words, and suggest that these problems are a result of allowing tokens to include spaces. We thus experiment with an alternative tokenisation approach where spaces are always treated as individual tokens. Specifically, we apply this modification to the BPE and Unigram algorithms. We find that our modified algorithms lead to improved performance on downstream NLP tasks that involve handling complex words, whilst having no detrimental effect on performance in general natural language understanding tasks. Intrinsically, we find our modified algorithms give more morphologically correct tokenisations, in particular when handling prefixes. Given the results of our experiments, we advocate for always treating spaces as individual tokens as an improved tokenisation method.

1 Introduction

Tokenisation is a key initial step in processing natural language, as it identifies the linguistic units to be processed, converting them to numerical IDs which can then be vectorised and manipulated by mathematical operations.

Earlier NLP approaches used simple string-searching techniques with regular expressions to tokenise text, however these pattern-matching tokenisation methods have drawbacks: they require large vocabulary sizes to cover the training data, they cannot handle out-of-vocabulary words, and they do not work for languages without spaces as word boundaries. To address these issues, subword

tokenisation was introduced. The first explicit mention (and popularisation) of this approach was by [Sennrich et al. \(2015\)](#), though it was indirectly introduced earlier by [Schuster and Nakajima \(2012\)](#). This method works by learning from training data to build a vocabulary (of a fixed size), and then tokenising text at inference time using this vocabulary (and possibly other learned parameters). More frequent words are represented as single tokens, with rare words being broken down into multiple subword tokens, possibly down to the character level.

State-of-the-art transformer-based language models all use subword tokenisation algorithms based on either byte-pair encoding (BPE) ([Sennrich et al., 2015](#)) or Unigram ([Kudo, 2018](#)). The original transformer model ([Vaswani et al., 2017](#)) uses BPE, whilst BERT ([Devlin et al., 2018](#)), which consists of a transformer encoder pretrained with a masked language modelling objective, uses WordPiece tokenisation ([Schuster and Nakajima, 2012](#)), which is a variant of BPE with a language model loss function. WordPiece is also used by ERNIE ([Sun et al., 2019](#)), DistilBERT ([Sanh et al., 2019](#)), ELECTRA ([Clark et al., 2020](#)), StructBERT ([Wang et al., 2019](#)) and NEZHA ([Wei et al., 2019](#)). GPT-2 ([Radford et al., 2019](#)) introduced byte-level BPE, operating on byte sequences rather than Unicode code points, which allows all sequences to be encoded using a base vocabulary of 256, avoiding the issue of unknown characters. The same approach is used in RoBERTa ([Liu et al., 2019](#)), DeBERTa ([He et al., 2020](#)), and BART ([Lewis et al., 2020](#)).

The algorithms of BPE and Unigram are implemented in the SentencePiece library ([Kudo and Richardson, 2018](#)). There is a lack of clarity regarding SentencePiece in the literature, with it being erroneously considered as its own algorithm rather than an implementation of other algorithms. For example, in the paper introducing T5 ([Raffel et al., 2019](#)) they state that they "use SentencePiece to

encode text as WordPiece tokens", which is not in fact implemented in SentencePiece. Looking at their code, we find they use the default SentencePiece implementation, which is Unigram. XLNET (Yang et al., 2019) say they tokenise with SentencePiece, but do not say which algorithm they use - again, looking at their code, we find they use the default of Unigram. Equivalently, ALBERT (Lan et al., 2019) say they tokenise with SentencePiece as for XLNET, meaning they again use Unigram.

Despite their ubiquity, existing tokenisation algorithms have problems, which we hypothesise hinders the ability of language models to handle complex words (Section 2). We suggest that these problems are pervasive across all existing subword tokenisation algorithms due to a fundamental equivalence in allowing tokens to include spaces, and thus experiment with an alternative treatment of spaces where they are always taken as individual tokens, and implement this approach by making simple modifications to the existing BPE and Unigram algorithms (Section 3). We evaluate our modified algorithms intrinsically (Section 4), quantitatively finding that they improve morphological correctness, in particular when handling prefixes. Qualitatively, we take examples from previous papers and show how our modified algorithms are able to alleviate the discussed issues. We also evaluate our modified algorithms extrinsically by pre-training and finetuning transformer-based models (Section 5), showing they give improved performance on NLP tasks that require handling complex words with no detrimental effect on performance in the general domain.

2 Problems with Existing Tokenisation Algorithms

Existing tokenisation algorithms often produce unintuitive tokenisations for complex words, incorrectly splitting prefixes and producing unmeaningful subword tokens, which are problems that have been discussed in previous works. Church (2020) looks at the BERT (WordPiece) tokenisations for complex words, highlighting the many unnatural tokenisations that arise, with tokens often splitting up morphemes and digraphs. Nayak et al. (2020) also discuss the issues with BERT’s tokeniser, specifically highlighting problems with the splitting of prefixes, and they show that poor tokenisation leads to weak semantic representations. Hofmann et al. (2021) find that BERT performs poorly on classifying

complex words containing prefixes, performing much better on suffixes. They suggest a reason is that BERT’s tokeniser is seldom accurate for splitting prefixes, but is much more often correct for splitting suffixes. Schick and Schütze (2020) argue that a reason BERT struggles to understand rare words is due to suboptimal tokenisation of these words. Here we give a few of our own examples of BERT tokenisations that illustrate the problems¹:

```
joint → _joint
jointed → _joint, ed
disjointed → _di, s, jo, int, ed
unisex → _un, ise, x
true → _true
untrue → _un, tr, ue
estimate → _estimate
overestimate → _over, est, imate
```

We see here that the prefixed words are tokenised poorly: the prefix is either incorrectly split, as in “disjointed” and “unisex”, or the prefix is correctly split but the rest of the word is tokenised differently to the standalone case, as in “untrue” and “overestimate”. We note that suffixes are handled better than prefixes, which is due to spaces being prepended rather than appended to words (see Section 3).

For these latter examples, there is a second problem: even if base were tokenised as a single token, the addition of the space symbol means there would be no explicit link between the prefixed word and the base as a word in itself. As an example, we cherry-pick a rare example of a morphologically correct tokenisation by BERT of a word containing a prefix, showing both strings and token IDs:

```
beatable → _beat, able (3786, 3085)
unbeatable → _un, beat, able (4895, 19442, 3085)
```

We can see that, even though these tokenisations are reasonable, the subword “beat” is assigned different IDs in the two cases due to the prepending of the special space symbol.

We hypothesise that both of these problems hinder the ability of existing language models (such as BERT) to deal with complex words. Regarding the first problem, we argue that the morphological correctness of a tokeniser is a metric which will correlate with the ability of language models to deal with complex words: correctly splitting affixes

¹BERT’s tokeniser actually prepends the space symbol to subword units not occurring at the start of words, and the space symbol they use is “##” rather than “_”, but these are inconsequential differences and we standardise the output here for clarity.

means morphologically related words (those sharing a common base) are given related tokenisations. The splitting of prefixes is particularly important as prefixes always have a semantic function, unlike suffixes which can have syntactic and semantic functions (Giraud and Grainger, 2003). Also, tokenisations made up of meaningful subword tokens (morphemes or groups of morphemes) will allow language models to build stronger representations with less data, since the representations of complex words can be computed from the representations of the subwords. Regarding the second problem, the fact that base forms are represented differently depending on their position within a word means a reduction in relevant training instances and hence a further weakening of representations for complex words.

3 Our Modified Algorithms

We suggest that the problems discussed in Section 2 arise as a result of how spaces are handled by existing algorithms: all subword tokenisation algorithms currently used by transformer-based models allow tokens to include space symbols as the first character². This means equivalent strings are treated differently depending on whether they appear at the start of a word or not. This difference occurs when training these tokenisers, which leads to suboptimal tokenisations of prefixed words. It also occurs when using these tokenisers in NLP models, leading to equivalent strings being assigned different tokens depending on whether they occur at the start of a word or not.

Thus, to attempt to alleviate these issues, and hence improve the handling of complex words by language models, we propose an alternative treatment of spaces where they are always assigned individual tokens. This simple modification can be made to any existing subword tokenisation algorithm, though for brevity we restrict our attention to BPE and Unigram; in particular, we do not make modifications to the WordPiece algorithm but it is a variant of BPE and treats spaces equivalently, so the same modification could be applied. We do include the default WordPiece algorithm in our intrinsic evaluation (Section 4) for comparison. Our modified algorithms and the defaults are shown

in Figure 1 and Figure 2 for BPE and Unigram, respectively³.

In the following sections, we compare our modified tokenisation algorithms to the defaults by evaluating them intrinsically (Section 4) and extrinsically (Section 5).

4 Intrinsic Evaluation: Morphological Correctness

Given our hypothesis that the morphological correctness of a tokeniser, especially when handling prefixes, correlates with the performance of language models on dealing with complex words (Section 2), we perform a controlled intrinsic evaluation of our tokenisers using this metric. We train our modified algorithms and the defaults on 1 million sentences from English Wikipedia for BPE and Unigram, with a fixed vocabulary size of 16,000, and then run evaluation on four morphological datasets: LADEC, MorphoLex, MorphyNet and DagoBERT.

The LADEC dataset (Gagné et al., 2019) consists of 7,804 noun compounds with a unique morphological parse (we exclude those with multiple parses). MorphoLex (Sánchez-Gutiérrez et al., 2018) provides derivational morphology for 68,624 entries from the English Lexicon Project (Balota et al., 2007). Here we only consider those with a concatenative parse (i.e. no overlapping tokens), resulting in 12,028 entries. MorphyNet (Batsuren et al., 2021) provides derivational and inflectional morphology for words across 15 languages, expanding on the UniMorph dataset (McCarthy et al., 2020). Taking only those derivational morphology entries in English with a concatenative parse gives 193,945 entries. The DagoBERT dataset (Hofmann et al., 2020) comprises 279,443 words containing low-frequency derivatives, taken from Reddit posts. Again we take those with a concatenative parse, giving 268,513 entries.

We evaluate a tokeniser on these datasets using the evaluation method introduced by Creutz et al. (2004), which produces metrics by comparing the boundaries of a generated tokenisation with a gold standard reference: false negatives are boundaries appearing in the reference but not in the generated tokenisation, whilst false positives are boundaries appearing in the generated tokenisation but not in

²Splitting on spaces occurs as a first step, so space symbols cannot occur in the middle of tokens. The default implementation splits before spaces, meaning space symbols occur only at the start of words.

³We release code for training our modified algorithms, as well as running both our intrinsic and extrinsic experiments at <https://github.com/edwardgowsmith/improved-tokenisation-methods>

(a) Default BPE	(b) Modified BPE (BPE')
Training	Training
input :training data T , vocabulary size s output :vocabulary V 1 Replace whitespace in T with the space symbol 2 Prepend space symbol to first word of every sentence in T ⁴ 3 Vocabulary V initialised as all characters 4 while $ V < s$ do 5 Find most frequently occurring bigram in T that only includes spaces as first character 6 Apply merge operation on the bigram to make a new token 7 Add merge operation to V 8 end	input :training data T , vocabulary size s output :vocabulary V 1 Replace whitespace in T with the space symbol 2 Vocabulary V initialised as all characters 3 while $ V < s$ do 4 Find most frequently occurring bigram in T that does not include spaces 5 Apply merge operation on the bigram to make a new token 6 Add merge operation to V 7 end
Tokenisation	Tokenisation
input :text T , vocabulary V output :tokens τ 1 Replace whitespace in T with the space symbol 2 Prepend space symbol to first word of every sentence in T 3 Apply the merge operations from V in order to T .	input :text T , vocabulary V output :tokens τ 1 Replace whitespace in T with the space symbol 2 Apply the merge operations from V in order to T .

Figure 1: Default and modified BPE algorithms. Red text is removed from the default algorithm, whilst green text is added.

(a) Default Unigram	(b) Modified Unigram (Unigram')
Training	Training
input :training data T , vocabulary size s output :vocabulary V , language model parameters Θ 1 Replace whitespace in T with the space symbol 2 Prepend space symbol to first word of every sentence in T 3 Vocabulary V initialised as all substrings occurring in T only including spaces as first character ⁵ 4 while $ V > s$ do 5 Optimise a Unigram language model with parameters Θ to fit the data using the EM algorithm 6 For each substring in V , compute the loss from removing this from the vocabulary 7 Remove the substring with the smallest loss from V 8 end	input :training data T , vocabulary size s output :vocabulary V , language model parameters Θ 1 Replace whitespace in T with the space symbol 2 Vocabulary V initialised as all substrings occurring in T that do not include spaces, plus the space symbol 3 while $ V > s$ do 4 Optimise a Unigram language model with parameters Θ to fit the data using the EM algorithm 5 For each substring in V , compute the loss from removing this from the vocabulary 6 Remove the substring with the smallest loss from V 7 end
Tokenisation	Tokenisation
input :text T , vocabulary V , language model parameters Θ output :tokens τ 1 Replace whitespace in T with the space symbol 2 Prepend space symbol to first word of every sentence in T 3 Use the Viterbi algorithm with the learned language modelling parameters and the vocabulary to tokenise T	input :text T , vocabulary V , language model parameters Θ output :tokens τ 1 Replace whitespace in T with the space symbol 2 Use the Viterbi algorithm with the learned language modelling parameters and the vocabulary to tokenise T with spaces being given an arbitrarily high score so they are always selected as individual tokens

Figure 2: Default and modified Unigram algorithms. Red text is removed from the default algorithm, whilst green text is added.

the reference. Because it makes sense to store common words as single tokens in the vocabulary, even if they can be decomposed into morphemes, we report precision along with F1 as a potentially more meaningful metric, since this allows undersegmentation whilst penalising oversegmentation. We also compute the mean sequence length (number of tokens) for each tokeniser across each dataset. Results are shown in Table 1. Here, and throughout,

⁴In the standard implementation, space symbols are added at the start of sentences so that words are equivalent whether they appear at the start of a sentence or not.

⁵This is only tractable for languages that include spaces. For languages without them, other initialisation methods must be used.

the prime symbol (') denotes the given algorithm modified to always treat spaces as individual tokens.

The general trend is that Unigram outperforms BPE (consistent with findings by Bostrom and Durrett 2020), with the modified algorithms performing better than their default counterparts. On the MorphoLex dataset, however, the default Unigram algorithm performs the best. This is also the only dataset where default Unigram gives a shorter mean sequence length than Unigram'. To investigate this further, we perform evaluation on the subsets of the data containing only prefixed and only suffixed entries, shown in Table 2. We can see that Unigram'

performs best on prefixed entries, but worse than default Unigram on suffixed entries. Since the dataset consists of many more entries containing suffixes than those containing prefixes (7,422 vs 2,692), this could explain the performance difference. Because the correct tokenisation of prefixed words is particularly important (Section 2), we believe that this performance trade-off is beneficial. In Section 5, we confirm this through evaluation on downstream tasks.

Interestingly, BPE' gives the shortest sequence length on three of the four datasets, but not the most morphologically correct tokenisations. Since BPE was developed as a compression algorithm, the short sequence lengths are perhaps expected, but here we only see a weak correlation between sequence length and morphological correctness⁶.

For a qualitative analysis, we take examples from papers that highlight problems with existing tokenisers (Section 2) and generate the output from the default and modified algorithms for BPE and Unigram, shown in Table 3. These examples illustrate how our modified algorithms are able to generate improved tokenisations for complex words. For example, whereas the default Unigram algorithm tokenises “unicycle” into “_un” “i” “cycle”, which is misleading as the string “un” does not have its typical semantic role, our modified Unigram algorithm tokenises it more meaningfully into “uni” “cycle”. Also, the modified algorithms explicitly create links between words containing prefixes and their bases. For the words “accessible” and “unaccessible”, the modified algorithms tokenise the subword “accessible” identically in both cases. The default Unigram and BPE algorithms do correctly split the prefix “un”, but the rest of the word is tokenised differently, which is problematic, and even if the tokenisation was equivalent, the inclusion of the space symbol means there would be no link between these forms (Section 2). We note that our modified algorithms are not immune to oversegmentation, with Unigram' tokenising “responsiveness” into seven tokens, although this is arguably inevitable with a limited vocabulary size.

We investigate the vocabularies of the default and modified algorithms, shown in Table 4. We remove the “[CLS]”, “[SEP]”, and “[UNK]” tokens from the vocabularies. For the default algorithms, we also remove tokens that are duplicates apart

from prepended space symbols, and we find that there is significant vocabulary degeneracy (8.7% and 9.1% for BPE and Unigram, respectively). We also find that a large percentage of the vocabulary is transferred over from the default to the modified algorithm (90.0% and 90.1% for BPE and Unigram, respectively). We see that all of the algorithms have a similar number of prefixes in their vocabularies, which suggests the tokenisation algorithm plays an important role, as performance differences on handling prefixes are large (Table 2) despite similar vocabularies. This is supported by work by Hofmann et al. (2021), who find that employing a fixed vocabulary in a morphologically correct way leads to performance improvements. We also see, however, that Unigram' has fewer suffixes in its vocabulary than default Unigram, which reflects the performance difference seen in Table 2.

We note that an interesting result of our modifications is an improvement at word segmentation. As an example, the outputs of the default and modified Unigram algorithms when passed the concatenated sentence “thisisaisentencethatneedstobesegmented” are:

Unigram _this, isa, s, ent, ence, that, ne, ed, s, to, be, s, eg, ment, ed

Unigram' this, is, a, sentence, that, needs, to, be, segment, e, d

5 Extrinsic Evaluation: Pretrain-Finetune

Given the improved intrinsic performance of our algorithms, we wish to evaluate how this impacts the extrinsic performance of NLP models, in general and in particular on tasks involving complex words. As in Section 4, we train the default and modified BPE and Unigram algorithms on 1 million sentences from English Wikipedia, with a fixed vocabulary size of 16,000, but we also implement a variant of our modified algorithm that removes spaces as a post-processing step. The reasoning behind this is that it reduces the sequence length significantly with minimal information loss, and more closely mirrors existing models which have no explicit space information. Example tokenisations for the Unigram algorithms given the input “This is an input sentence.” are:

Unigram _This, _is, _an, _input, _sentence, .

Unigram' This, _, is, _, an, _, input, _, sentence, .

Unigram' no spaces This, is, an, input, sentence, .

⁶Pearson's correlation of between -0.262 and -0.857 depending on the dataset.

	LADEC			MorphoLex			MorphyNet			DagoBERT		
	Seq Length	Precision	F1	Seq Length	Precision	F1	Seq Length	Precision	F1	Seq Length	Precision	F1
WordPiece	2.97	44.5	59.1	2.64	45.1	51.0	3.15	21.8	31.6	3.20	32.5	44.1
BPE	2.98	41.2	54.8	2.67	43.4	49.5	3.17	19.9	29.0	3.22	28.4	38.6
BPE'	2.60	53.8	66.2	2.47	50.8	54.7	2.93	24.6	34.8	2.86	37.4	48.0
Unigram	2.80	51.9	66.8	2.56	58.1	64.3	3.09	32.3	46.6	3.16	45.3	61.1
Unigram'	2.67	56.7	70.9	2.65	53.9	61.2	3.03	33.6	48.1	2.81	54.5	69.2

Table 1: Performance of the tokenisation algorithms across four morphological datasets, showing the average sequence length, precision and F1 score generated following the standard introduced by Creutz et al. (2004). Best results are shown in bold.

	Only Prefixes			Only Suffixes		
	Seq Length	Precision	F1	Seq Length	Precision	F1
WordPiece	2.56	26.7	32.2	2.56	48.4	53.4
BPE	2.54	33.5	40.2	2.62	44.0	49.4
BPE'	2.26	50.4	55.4	2.50	45.9	49.8
Unigram	2.51	53.4	63.6	2.53	55.2	60.5
Unigram'	2.48	57.2	67.4	2.75	46.4	53.9

Table 2: Performance of the tokenisation algorithms on subsets of the MorphoLex dataset with entries containing only prefixes and only suffixes. Best results are shown in bold.

For each of the tokenisers, we pretrain RoBERTa (base) on the full text of English Wikipedia, and then finetune on downstream tasks, keeping all hyperparameters fixed, changing only the tokenisation algorithm used. For evaluation of the models in a general domain, we use the GLUE benchmark (Wang et al., 2018), excluding WNLI. For evaluation in specifically handling complex words, we use the two Superbizarre topicality tasks (Hofmann et al., 2021), which require the binary classification of derivationally complex English words⁷.

Over the whole of the English Wikipedia data, the sequence lengths for each of the tokenisation approaches are:

BPE 3.72e+09
 BPE' 5.88e+09
 BPE' no spaces 3.61e+09
 Unigram 3.68e+09
 Unigram' 5.94e+09
 Unigram' no spaces 3.67e+09

As in the evaluation in Table 1, the modified models without spaces give shorter sequences than their default counterparts, with BPE' without spaces giving the shortest mean sequence length. The difference in sequence lengths of the models means a difference in number of updates per epoch during pretraining. Hence, fixing the number of updates (and thus training time) will advantage models with shorter sequence lengths, especially

⁷We do not consider the Superbizarre sentiment task due to a higher proportion of uninformative words.

disadvantaging the models that include spaces. Because of this, we perform two evaluations: one fixing the number of pretraining updates, and one fixing the number of pretraining epochs⁸.

Due to computational constraints, we only ran pretraining once for each model. For finetuning, we ran each experiment with 10 different seeds, reporting the mean development result and standard deviation. Results are shown in Table 5 and Table 6 for fixed updates and fixed epochs, respectively. Full training procedure is given in Appendix A.

On the Superbizarre datasets, we can see that Unigram outperforms BPE, with Unigram' no spaces performing significantly better than all other models using a Welch's t-test ($p < 0.05$), see Appendix C. Note that DelBERT (Hofmann et al., 2021), a model which is passed the input segmented according to gold standard references, achieves 73.1 on the Arxiv dev set and 72.3 on the Arxiv test set, both worse than our (unsupervised) model, although DelBERT outperforms our best models on the Reddit task, achieving 69.6 and 70.1 on the dev and test sets, respectively.

On the mean GLUE benchmark, the modified models without spaces perform as well or better than their default counterparts, with Unigram' performing the best when both updates and epochs are fixed. However, this result is not statistically significant (see Appendix C), and over the individual GLUE tasks the best performing models vary, with high variances across seeds on some tasks due to the small dataset sizes (see Appendix B). Since the GLUE tasks do not rely on handling complex words, a significant performance difference is probably not expected, but we see no drop in performance with the modified algorithms.

The modified models that include spaces per-

⁸In finetuning, the number of updates and epochs is equivalent for all models as one example is processed at a time. In pretraining, we follow the standard implementation of RoBERTa by taking contiguous sentences from the training data up to the max sequence length.

Input	BPE	BPE'	Unigram	Unigram'
directional	_direction, al	direction, al	_direction, al	direction, al
unidirectional	_un, id, ire, ction, al	un, id, ire, ction, al	_un, i, direct, ional	uni, direction, al
electroneutral	_elect, r, one, ut, ral	electr, one, utr, al	_electron, eu, tral	electro, neutral
neurotransmitter	_neuro, trans, mit, ter	neuro, transmitter	_neuro, trans, mitt, er	neuro, transmitter
responsiveness	_respons, iveness	respons, iveness	_re, s, pon, s, ive, ness	r, e, sp, on, s, ive, ness
hyporesponsiveness	_hyp, ores, p, ons, iveness	hypo, respons, iveness	_hypo, res, pon, s, ive, ness	hypo, r, e, sp, on, s, ive, ness
hyperresponsiveness	_hyper, resp, ons, iveness	hyper, respons, iveness	_hyper, res, pon, s, ive, ness	hyper, r, e, sp, on, s, ive, ness
saturated	_sat, urated	sat, urated	_sat, ur, ated	saturated
unsaturated	_uns, atur, ated	un, sat, urated	_un, sa, tur, ated	un, saturated
equal	_equal	equal	_equal	equal
unequal	_un, equ, al	une, qual	_un, e, qual	un, equal
multiplayer	_multip, layer	multi, player	_multi, play, er	multi, player
nonmultiplayer	_non, m, ult, ip, layer	non, multi, player	_non, mul, ti, play, er	non, multi, player
overpriced	_over, p, ric, ed	over, pr, iced	_over, p, ric, ed	over, price, d
accessible	_accessible	accessible	_accessible	accessible
unaccessible	_un, ac, cess, ible	un, accessible	_un, ac, ces, s, ible	un, accessible
unicycle	_un, icy, cle	un, icy, cle	_un, i, cycle	uni, cycle

Table 3: Example tokenisations of the default and modified BPE and Unigram algorithms, with inputs taken from the following papers: Church (2020), Nayak et al. (2020), Hofmann et al. (2020) and Schich and Schütze (2020).

	Vocab Size	Unique Elements	#Prefixes	#Suffixes
WordPiece	15123	-	107	184
BPE	14613	1459	114	182
BPE'	15997	2843	123	192
Unigram	14544	1443	123	201
Unigram'	15997	2896	116	147

Table 4: Vocabularies of the models, showing size, number of unique elements, and numbers of prefixes and suffixes.

form poorly on the GLUE benchmark, even when the number of epochs is fixed rather than updates, meaning they are trained for $\sim 65\%$ more updates than the modified models without spaces. This suggests that this method of including spaces as additional tokens is suboptimal for general language tasks, though interestingly Unigram' with spaces is the second best performing model across all Superbizarre datasets. The tokenisers themselves perform splitting on spaces as a first step, so additionally including spaces may be simply passing noise to the model for the masked language modelling task, especially due to the high frequency of spaces. This means the pretraining loss decreases rapidly due to space prediction, but plateaus earlier (see Appendix A). Due to the much greater sequence lengths, the models that include spaces also discard examples that are too long during finetuning, which could lead to worse results.

6 Related Work

There is previous work which has compared subword tokenisation algorithms. Gallé (2019) investigates various compression algorithms for tokenisation, including BPE, and finds an inverse link

between mean tokens per sentence and translation quality, hypothesising that the compression capability of BPE leads to its effectiveness in NLP tasks. In our experiments we find that Unigram' outperforms BPE' on the complex words tasks, and there to be no significant difference between them on the general language understanding (GLUE) tasks. This is despite Unigram' having a longer sequence length, suggesting this factor is not wholly indicative of model performance. However, if we look at the results for fixed pretraining updates, we do see a slight negative correlation between sequence length and performance on the Superbizarre datasets, and a very strong negative correlation on the GLUE benchmark⁹, though this is skewed by the models including spaces performing very poorly. Intrinsically, we see a correlation (albeit weak) between sequence length and morphological correctness (see Section 4).

Bostrom and Durrett (2020) compare Unigram and BPE, finding that Unigram generates more morphologically correct tokenisations and gives improved downstream task performance. Whilst we saw similar improvements in intrinsic performance, we were unable to replicate the performance difference on MNLI that they found, finding no significant difference in performance (see Appendix B). We did not perform evaluation on the other two English datasets they used. Wei et al. (2021) perform comparison between byte-level BPE and byte-level Unigram, finding BPE to perform better than Unigram across seven languages on the XNLI dataset, which

⁹Pearson correlations between -0.157 and -0.224 for the Superbizarre datasets, and -0.985 for GLUE.

	Epochs	GLUE	Superbizarre Reddit		Superbizarre Arxiv	
			Dev	Test	Dev	Test
BPE	27	81.6	66.8	66.6	71.1	70.2
BPE'	16	79.2	66.6	66.2	70.3	69.3
BPE' no spaces	28	81.7	67.2	66.9	70.9	70.0
Unigram	27	81.5	68.0	67.8	72.2	71.4
Unigram'	16	78.4	68.2	68.2	72.5	71.6
Unigram' no spaces	27	81.9	68.8	68.8	73.0	72.3

Table 5: Finetuning results after pretraining for 100,000 updates. Shown are mean results across 10 seeds. Results that are significantly better than all others using a Welch’s t-test ($p < 0.05$) are shown in bold. More detailed results are given in [Appendix B](#).

	Updates	GLUE	Superbizarre Reddit		Superbizarre Arxiv	
			Dev	Test	Dev	Test
BPE	109,761	81.5	67.1	66.8	71.0	70.1
BPE'	177,845	79.5	66.8	66.5	70.5	69.8
BPE' no spaces	106,485	81.5	67.1	67.1	70.8	70.1
Unigram	108,606	81.6	67.9	67.9	72.2	71.6
Unigram'	179,909	79.1	68.3	68.3	72.5	71.8
Unigram' no spaces	108,441	81.8	68.8	69.0	73.2	72.5

Table 6: Finetuning results after pretraining for 30 epochs. Shown are mean results across 10 seeds. Results that are significantly better than all others using a Welch’s t-test ($p < 0.05$) are shown in bold. More detailed results are given in [Appendix B](#).

is contrary to our findings and those of [Bostrom and Durrett \(2020\)](#).

There have also been attempts to generate improved tokenisation methods. [Hofmann et al. \(2021\)](#) introduce DelBERT, which takes input words tokenised according to gold standard morphological references, with an unchanged vocabulary. They find this improves performance on handling complex words. We note that this is a supervised method, whereas ours is unsupervised and allows simple extension to other languages. [Wei et al. \(2021\)](#) experiment with different methods of handling spaces within their byte-level BPE algorithm which appear similar to those implemented here, although they find these alternatives perform worse than the default on XNLI. They do not release code for their experiments so we are unable to make a controlled comparison.

7 Conclusion and Future Work

We hypothesise that problems with current tokenisation algorithms arise from allowing tokens to include spaces, and thus experiment with an al-

ternative tokenisation approach where spaces are always treated as individual tokens. We find that this leads to improved performance on NLP tasks involving complex words, whilst having no detrimental effect on performance in general natural language understanding tasks. Whilst our work focuses on BPE and Unigram, our modifications can be applied to any existing subword tokenisation algorithm, including WordPiece, and hence to any transformer-based model. We also only worked with English, but the algorithms used are unsupervised and language-independent.

Our best-performing models use lossy tokenisation (removing the space tokens as a post-processing step), which may not be ideal for all tasks. We did not perform evaluation on sequence-to-sequence tasks, and indeed the subword tokenisation algorithms discussed here were introduced in the field of NMT, where space information is likely more important. Future work could thus look at alternative methods for including space information that maintain the performance gains seen here whilst keeping tokenisation lossless.

References

- David A Balota, Melvin J Yap, Keith A Hutchison, Michael J Cortese, Brett Kessler, Bjorn Loftis, James H Neely, Douglas L Nelson, Greg B Simpson, and Rebecca Treiman. 2007. The english lexicon project. *Behavior research methods*, 39(3):445–459.
- Khuyagbaatar Batsuren, Gábor Bella, and Fausto Giunchiglia. 2021. Morphynet: a large multilingual database of derivational and inflectional morphology. In *Proceedings of the 18th SIGMORPHON Workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 39–48.
- Kaj Bostrom and Greg Durrett. 2020. Byte pair encoding is suboptimal for language model pretraining. *arXiv preprint arXiv:2004.03720*.
- Kenneth Ward Church. 2020. Emerging trends: Subwords, seriously? *Natural Language Engineering*, 26(3):375–382.
- Kevin Clark, Minh-Thang Luong, Quoc V Le, and Christopher D Manning. 2020. Electra: Pre-training text encoders as discriminators rather than generators. *arXiv preprint arXiv:2003.10555*.
- Mathias Johan Philip Creutz, Bo Krister Johan Linden, et al. 2004. Morpheme segmentation gold standards for finnish and english. *Publications in Computer and Information Science Report A77*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.
- Christina L Gagné, Thomas L Spalding, and Daniel Schmidtke. 2019. Ladec: the large database of english compounds. *Behavior research methods*, 51(5):2152–2179.
- Matthias Gallé. 2019. Investigating the effectiveness of bpe: the power of shorter sequences. In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (EMNLP-IJCNLP)*, pages 1375–1381.
- Hélène Giraudo and Jonathan Grainger. 2003. On the role of derivational affixes in recognizing complex words. In R.H. Baayen & R. Schreuder, editor, *Morphological Structure in Language Processing*. De Gruyter Mouton.
- Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. 2020. Deberta: Decoding-enhanced bert with disentangled attention. *arXiv preprint arXiv:2006.03654*.
- Valentin Hofmann, Janet Pierrehumbert, and Hinrich Schütze. 2021. Superbizarre is not superb: Derivational morphology improves bert’s interpretation of complex words. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 3594–3608.
- Valentin Hofmann, Janet B Pierrehumbert, and Hinrich Schütze. 2020. Dagobert: Generating derivational morphology with a pretrained language model. *arXiv preprint arXiv:2005.00672*.
- Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.
- Taku Kudo. 2018. Subword regularization: Improving neural network translation models with multiple subword candidates. *arXiv preprint arXiv:1804.10959*.
- Taku Kudo and John Richardson. 2018. Sentencepiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. *arXiv preprint arXiv:1808.06226*.
- Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. 2019. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*.
- Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2020. [BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7871–7880, Online. Association for Computational Linguistics.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.
- Arya D McCarthy, Christo Kirov, Matteo Grella, Amrit Nidhi, Patrick Xia, Kyle Gorman, Ekaterina Vylomova, Sabrina J Mielke, Garrett Nicolai, Miikka Silfverberg, et al. 2020. Unimorph 3.0: Universal morphology.
- Anmol Nayak, Hariprasad Timmapathini, Karthikeyan Ponnalagu, and Vijendran Gopalan Venkoparao. 2020. Domain adaptation challenges of bert in tokenization and sub-word representations of out-of-vocabulary words. In *Proceedings of the First Workshop on Insights from Negative Results in NLP*, pages 1–5.
- Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. 2019. fairseq: A fast, extensible toolkit for sequence modeling. *arXiv preprint arXiv:1904.01038*.

- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2019. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*.
- Claudia H Sánchez-Gutiérrez, Hugo Mailhot, S Hélène Deacon, and Maximiliano A Wilson. 2018. Morpholex: A derivational morphological database for 70,000 english words. *Behavior research methods*, 50(4):1568–1580.
- Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*.
- Timo Schick and Hinrich Schütze. 2020. Rare words: A major problem for contextualized embeddings and how to fix it by attentive mimicking. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 8766–8774.
- Mike Schuster and Kaisuke Nakajima. 2012. Japanese and korean voice search. In *2012 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5149–5152. IEEE.
- Rico Sennrich, Barry Haddow, and Alexandra Birch. 2015. Neural machine translation of rare words with subword units. *arXiv preprint arXiv:1508.07909*.
- Yu Sun, Shuohuan Wang, Yukun Li, Shikun Feng, Xuyi Chen, Han Zhang, Xin Tian, Danxiang Zhu, Hao Tian, and Hua Wu. 2019. Ernie: Enhanced representation through knowledge integration. *arXiv preprint arXiv:1904.09223*.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. 2018. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*.
- Wei Wang, Bin Bi, Ming Yan, Chen Wu, Zuyi Bao, Jiangnan Xia, Liwei Peng, and Luo Si. 2019. Structbert: incorporating language structures into pre-training for deep language understanding. *arXiv preprint arXiv:1908.04577*.
- Junqiu Wei, Qun Liu, Yinpeng Guo, and Xin Jiang. 2021. Training multilingual pre-trained language model with byte-level subwords. *arXiv preprint arXiv:2101.09469*.
- Junqiu Wei, Xiaozhe Ren, Xiaoguang Li, Wenyong Huang, Yi Liao, Yasheng Wang, Jiashu Lin, Xin Jiang, Xiao Chen, and Qun Liu. 2019. Nezha: Neural contextualized representation for chinese language understanding. *arXiv preprint arXiv:1909.00204*.
- Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. 2019. Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32.

A Training Details

Hyperparameters for tokenisation, pretraining, finetuning are shown in Table 7, Table 8 and Table 9, respectively. We did not use stochastic tokenisation (BPE-dropout or subword regularisation).

Implementation	SentencePiece (Kudo and Richardson, 2018)
Vocabulary Size	16000
BPE-dropout	0
Unigram Subword Regularisation	0

Table 7: Hyperparameters for tokenisation.

Implementation	fairseq (Ott et al., 2019)
Architecture	RoBERTa (base) (Liu et al., 2019)
Precision	16 bit
Optimizer	ADAM (Kingma and Ba, 2014), $\epsilon = 1e-6$, $\beta = (0.9, 0.98)$
Sequence length	512
Learning rate scheduler	Linear warm-up for 10000 updates to $5e-4$, then reduce to $1e-4$ upon increased training loss at epoch
Training for	100000 updates / 30 epochs
Batch size	2048
Dropout	0.1
Attention Dropout	0.1
Weight Decay	0.01

Table 8: Hyperparameters for pretraining.

Implementation	fairseq (Ott et al., 2019)
Architecture	RoBERTa (base) (Liu et al., 2019)
Precision	16 bit
Optimizer	ADAM (Kingma and Ba, 2014), $\epsilon = 1e-6$, $\beta = (0.9, 0.98)$
Sequence length	512
Learning rate scheduler	Linear warm-up to $2e-3$ for 6% of updates, then linear decay to 0
Training for	20 epochs
Batch size	32
Dropout	0.1
Attention Dropout	0.1
Weight Decay	0.01

Table 9: Hyperparameters for finetuning.

A.1 Pretraining

Pretraining was run on 8 NVIDIA Tesla V100s. We ran pretraining on the text of English Wikipedia. A Wikipedia dump was processed with the Python package WikiExtractor¹⁰, and then split into sentences using BlingFire¹¹. In order to perform a fair comparison across models, we removed all sentences with sequence lengths longer than 510 when tokenised with the modified models including spaces. However, this was a very small amount

of the data ($\sim 0.002\%$) and would thus have a negligible effect on performance.

Loss curves are shown in Figure 3.

A.2 Finetuning

Finetuning was run on a single NVIDIA Tesla V100. All finetuning experiments were ran with a batch size of 32, and a peak learning rate of $2e-3$ with linear warm-up for 6% of updates, then linear decay to 0. All other parameters were kept the same as for pretraining. Experiments were ran for 20 epochs, and the best performing epoch was taken, with 10 random seeds per model. For the Superbizarre datasets, we took the best performing epoch for each seed on the dev set and evaluated it on the test set.

B Detailed Results

Detailed results are shown in Table 10 and Table 11 for fixed pretraining updates and fixed pretraining epochs, respectively. The standard deviations on the mean GLUE score are calculated assuming zero covariance between tasks.

C Significance Tests

Here we give full Welch’s t-test results comparing the best performing model to all the others for each dataset, shown in Table 12 and Table 13 for fixed pretraining updates and fixed pretraining epochs, respectively.

¹⁰<https://github.com/attardi/wikiextractor/>

¹¹<https://github.com/microsoft/BlingFire>




Figure 3: Pretraining loss curves for the six models.

Epochs		GLUE										Superbizarre Reddit		Superbizarre Arxiv	
		MRPC	CoLA	STS-B	RTE	SST-2	QQP	QNLI	MNLI-m	MNLI-mm	Mean	Dev	Test	Dev	Test
BPE	27	84.5 (0.8)	55.4 (2.5)	87.1 (0.3)	68.6 (2.7)	91.6 (0.4)	89.7 (0.1)	91.3 (0.2)	83.1 (0.2)	83.5 (0.3)	81.6 (1.3)	66.8 (0.8)	66.6 (0.9)	71.1 (0.2)	70.2 (0.2)
BPE'	16	83.0 (1.0)	48.9 (2.9)	86.0 (0.2)	59.5 (1.9)	91.6 (0.4)	89.2 (0.1)	90.7 (0.3)	81.6 (0.2)	82.3 (0.1)	79.2 (1.2)	66.6 (0.2)	66.2 (0.2)	70.3 (0.1)	69.3 (0.2)
BPE' no spaces	28	84.4 (0.6)	54.4 (1.4)	87.0 (0.2)	70.3 (0.8)	92.2 (0.5)	89.7 (0.1)	91.1 (0.2)	83.1 (0.2)	83.2 (0.2)	81.7 (0.6)	67.2 (0.2)	66.9 (0.2)	70.9 (0.1)	70.0 (0.2)
Unigram	27	85.0 (1.2)	52.3 (1.4)	87.3 (0.2)	69.8 (1.9)	91.7 (0.5)	89.5 (0.1)	91.9 (0.4)	83.1 (0.2)	83.1 (0.2)	81.5 (0.9)	68.0 (0.2)	67.8 (0.3)	72.2 (0.3)	71.4 (0.2)
Unigram'	16	83.3 (0.6)	39.5 (15.4)	84.8 (0.4)	64.0 (1.8)	91.3 (0.4)	89.1 (0.1)	89.8 (0.3)	81.4 (0.2)	82.1 (0.2)	78.4 (5.2)	68.2 (0.4)	68.2 (0.3)	72.5 (0.2)	71.6 (0.3)
Unigram' no spaces	27	85.2 (1.4)	54.6 (1.4)	87.8 (0.3)	71.1 (1.5)	91.6 (0.4)	89.5 (0.1)	91.3 (0.3)	83.0 (0.2)	83.1 (0.2)	81.9 (0.9)	68.8 (0.1)	68.8 (0.3)	73.0 (0.2)	72.3 (0.3)

Table 10: Full finetuning results after pretraining for 100000 updates. Shown are mean dev set results across 10 seeds, with standard deviations in parentheses.

Updates		GLUE										Superbizarre Reddit		Superbizarre Arxiv	
		MRPC	CoLA	STS-B	RTE	SST-2	QQP	QNLI	MNLI-m	MNLI-mm	Mean	Dev	Test	Dev	Test
BPE	109761	84.4 (0.8)	53.5 (1.7)	87.2 (0.2)	68.7 (0.9)	91.8 (0.3)	89.7 (0.1)	91.4 (0.2)	83.1 (0.2)	83.5 (0.3)	81.5 (0.7)	67.1 (0.2)	66.8 (0.3)	71.0 (0.2)	70.1 (0.3)
BPE'	177845	83.2 (1.1)	48.9 (1.4)	86.6 (0.2)	60.0 (2.6)	92.0 (0.2)	89.2 (0.0)	90.7 (0.3)	82.2 (0.2)	82.9 (0.2)	79.5 (1.1)	66.8 (0.3)	66.5 (0.1)	70.5 (0.1)	69.8 (0.2)
BPE' no spaces	106485	85.0 (0.6)	53.4 (0.9)	86.9 (0.3)	69.1 (0.6)	92.0 (0.4)	89.5 (0.1)	91.2 (0.3)	83.2 (0.2)	83.2 (0.2)	81.5 (0.5)	67.1 (0.2)	67.1 (0.3)	70.8 (0.2)	70.1 (0.2)
Unigram	108606	84.8 (0.9)	53.1 (2.3)	87.4 (0.2)	70.1 (1.8)	91.6 (0.3)	89.6 (0.1)	91.3 (0.5)	83.0 (0.1)	83.2 (0.2)	81.6 (1.0)	67.9 (0.2)	67.9 (0.3)	72.2 (0.1)	71.6 (0.1)
Unigram'	179909	82.0 (0.9)	45.9 (2.0)	84.7 (0.2)	64.9 (1.5)	91.5 (0.3)	89.0 (0.1)	90.1 (0.2)	81.5 (0.1)	82.0 (0.1)	79.1 (0.9)	68.3 (0.5)	68.3 (0.4)	72.5 (0.2)	71.8 (0.3)
Unigram' no spaces	108441	84.8 (0.8)	54.5 (1.9)	87.8 (0.2)	70.0 (1.8)	91.5 (0.3)	89.6 (0.1)	91.5 (0.2)	83.2 (0.1)	83.2 (0.2)	81.8 (0.9)	68.8 (0.2)	69.0 (0.2)	73.2 (0.2)	72.5 (0.2)

Table 11: Full finetuning results after pretraining for 30 epochs. Shown are mean dev set results across 10 seeds, with standard deviations in parentheses.

	GLUE	Superbizarre Reddit		Superbizarre Arxiv	
		Dev	Test	Dev	Test
BPE	0.61	2.15e-05	1.34e-05	5.70e-15	5.26e-13
BPE'	2.7e-05	1.50e-16	5.26e-14	3.82e-17	8.61e-15
BPE' no spaces	0.58	7.22e-14	9.04e-12	1.75e-15	5.54e-14
Unigram	0.36	2.27e-08	1.69e-06	5.15e-07	1.11e-07
Unigram'	6.0e-02	6.22e-04	7.83e-05	1.74e-05	6.05e-06

Table 12: P values for Welch’s t-test comparing Unigram’ no spaces to other models for fixed pretraining updates.

	GLUE	Superbizarre Reddit		Superbizarre Arxiv	
		Dev	Test	Dev	Test
BPE	0.41	1.47e-13	2.25e-13	2.77e-15	1.48e-13
BPE'	8.72e-05	1.19e-12	7.84e-16	3.46e-16	4.53e-14
BPE' no spaces	0.41	1.28e-12	2.01e-15	1.21e-15	2.35E-12
Unigram	0.66	2.92e-08	1.19e-09	3.96e-09	8.78e-08
Unigram'	2.8e-06	1.45e-02	1.69e-06	1.55e-06	3.90e-04

Table 13: P values for Welch’s t-test comparing Unigram’ no spaces to other models for fixed pretraining epochs.