

## 1. 로그인

login as: **centos**

Authenticating with public key "imported-openssh-key"

Passphrase for key "imported-openssh-key": **암호입력**

Last login: Tue Feb 19 04:48:25 2019 from 210.178.106.248

## 2. 관리자 계정으로 전환

```
[centos@ip-172-31-27-176 ~]$
```

```
[centos@ip-172-31-27-176 ~]$ sudo su
```

```
[root@ip-172-31-27-176 centos]#
```

## 3. 호스트이름 변경

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# hostnamectl status
```

Static hostname: **ip-172-31-27-176.ap-northeast-2.compute.internal**

Icon name: computer-vm

Chassis: vm

Machine ID: 05cb8c7b39fe0f70e3ce97e5beab809d

Boot ID: 138cf88e5b4542e78c67febcc7efe8b9

Virtualization: xen

Operating System: CentOS Linux 7 (Core)

CPE OS Name: cpe:/o:centos:centos:7

Kernel: Linux 3.10.0-957.1.3.el7.x86\_64

Architecture: x86-64

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# hostnamectl set-hostname LinuxDBServer
```

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# hostnamectl status
```

Static hostname: **linuxdbserver**

Pretty hostname: **LinuxDBServer**

Icon name: computer-vm

Chassis: vm

Machine ID: 05cb8c7b39fe0f70e3ce97e5beab809d

Boot ID: 138cf88e5b4542e78c67febcc7efe8b9

Virtualization: xen

Operating System: CentOS Linux 7 (Core)

CPE OS Name: cpe:/o:centos:centos:7

Kernel: Linux 3.10.0-957.1.3.el7.x86\_64

Architecture: x86-64

#### 4. ip 주소 확인

```
[root@ip-172-31-27-176 centos]# ip addr show
```

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000
    link/ether 00:0c:29:06:47:81 brd ff:ff:ff:ff:ff:ff
    inet 172.31.27.176/24 brd 192.168.192.255 scope global noprefixroute dynamic ens33
        valid_lft 1255sec preferred_lft 1255sec
    inet6 fe80::7d3e:6a43:da42:37c3/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
```

#### 5. 로컬 네임서버 설정

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# vi /etc/hosts
```

```
#127.0.0.1 localhost localhost.localdomain localhost4 localhost4.localdomain4
```

```
##::1 localhost localhost.localdomain localhost6 localhost6.localdomain6
```

```
127.0.0.1      localhost
```

```
172.31.27.176 LinuxDBServer
```

#### 6. 서버 시간대/시스템 언어 설정

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# cp /usr/share/zoneinfo/Asia/Seoul /etc/localtime
```

```
cp: overwrite '/etc/localtime'? y
```

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# date
```

```
Tue Feb 19 14:15:03 KST 2019
```

```
[root@ip-172-31-27-176 centos]#
```

```
[root@ip-172-31-27-176 centos]# locale
```

```
LANG=en_US.UTF-8
```

```
LC_CTYPE="en_US.UTF-8"
```

```
LC_NUMERIC="en_US.UTF-8"
```

```
LC_TIME="en_US.UTF-8"
LC_COLLATE="en_US.UTF-8"
LC_MONETARY="en_US.UTF-8"
LC_MESSAGES="en_US.UTF-8"
LC_PAPER="en_US.UTF-8"
LC_NAME="en_US.UTF-8"
LC_ADDRESS="en_US.UTF-8"
LC_TELEPHONE="en_US.UTF-8"
LC_MEASUREMENT="en_US.UTF-8"
LC_IDENTIFICATION="en_US.UTF-8"
LC_ALL=
```

```
[root@ip-172-31-27-176 centos]#
[root@ip-172-31-27-176 centos]# vi /etc/locale.conf
#LANG=en_US.UTF-8
LANG="ko_KR.UTF-8"
```

## 7. 시스템 재시작

```
[root@ip-172-31-27-176 centos]#
[root@ip-172-31-27-176 centos]# reboot
```

## 8. 다시 시스템 로그인

```
login as: centos
Authenticating with public key "imported-openssh-key"
Passphrase for key "imported-openssh-key": 암호입력
Last login: Tue Feb 19 14:09:38 2019 from 210.178.106.248
```

```
[centos@linuxdbserver ~]$
[centos@linuxdbserver ~]$ date
2019. 02. 19. (화) 14:19:29 KST
```

```
[centos@linuxdbserver ~]$
```