



Agents

HSE Faculty of Computer Science

Murat Khazhgeriev



Так что же ты такой, агент?

Определение

Определение агента



Определение агента

Агент – нечто, что взаимодействует с некоторой **средой**, пользуясь действиями из доступного **инструментария**



Так что же ты такой, агент?

Определение

Определение агента

Агент – нечто, что взаимодействует с некоторой **средой**, пользуясь действиями из доступного **инструментария**



Агент – система, которая **независимо** выполняет вашу работу



Определение агента


Агент – нечто, что взаимодействует с некоторой **средой**, пользуясь действиями из доступного **инструментария**

Агент – система, которая **независимо** выполняет вашу работу




Агент – система, независимо от человека выполняющая работу, **итеративно** взаимодействуя с некоторой средой при помощи доступного инструментария

Агент, пользуясь инструментами, размышляя о выполнении задачи, может выполнять ее автономно




Пайплайн мульти-агентных систем допускает распараллеливание процесса

Workflow Agent



LLM Agent



Main building blocks:

Workflow Agent: Fixed order of agent invocations

LLM Agent: Model decides whether to use another agent or not


Control flow types:

Handoff - Full control and context transfer to another agent

Agent-as-tool - Call the agent and return his response back immediately. Usually no context is passed


Пример МАС

High-level Architecture of Advanced Research




Пример МАС с оркестратором

Multi-agent System Process Diagram



Пример МАС без единого узла отказа



Пример: как строится диалог с агентской системой

1. Python API interface:

```
from openai import OpenAI
import json

client = OpenAI()

# 1. Define a list of callable tools for the model
tools = [
    {
        "type": "function",
        "name": "get_horoscope",
        "description": "Get today's horoscope for an astrological sign.",
        "parameters": {
            "type": "object",
            "properties": {
                "sign": {
                    "type": "string",
                    "description": "An astrological sign like Taurus or Aquarius",
                },
            },
            "required": ["sign"],
        },
    },
]

def get_horoscope(sign):
    return f"{sign}: Next Tuesday you will befriend a baby otter."
```

```
# Create a running input list we will add to over time
input_list = [
    {"role": "user", "content": "What is my horoscope? I am an Aquarius."}
]

# 2. Prompt the model with tools defined
response = client.responses.create(
    model="gpt-5",
    tools=tools,
    input=input_list,
)

# Save function call outputs for subsequent requests
input_list += response.output

for item in response.output:
    if item.type == "function_call":
        if item.name == "get_horoscope":
            # 3. Execute the function logic for get_horoscope
            horoscope = get_horoscope(json.loads(item.arguments))

            # 4. Provide function call results to the model
            input_list.append({
                "type": "function_call_output",
                "call_id": item.call_id,
                "output": json.dumps({
                    "horoscope": horoscope
                })
            })
```

```
print("Final input:")
print(input_list)

response = client.responses.create(
    model="gpt-5",
    instructions="Respond only with a horoscope generated by a tool.",
    tools=tools,
    input=input_list,
)

# 5. The model should be able to give a response!
print("Final output:")
print(response.model_dump_json(indent=2))
print("\n" + response.output_text)
```

Пример: как строится диалог с агентской системой

2. OpenAI API interface:

```
{
  "model": "gwen3-32b",
  "instructions": "Respond only with a horoscope
generated by a tool.",
  "tools": [
    {
      "type": "function",
      "name": "get_horoscope",
      "description": "Get today's horoscope for an
astrological sign.",
      "parameters": {
        "type": "object",
        "properties": {
          "sign": {
            "type": "string",
            "description": "An astrological sign
like Taurus or Aquarius"
          }
        },
        "required": ["sign"]
      }
    }
  ]
}
```

```
"input": [
  {
    "role": "user",
    "content": "What is my horoscope? I am an
Aquarius."
  },
  {
    "role": "assistant",
    "content": [
      {
        "type": "function_call",
        "name": "get_horoscope",
        "arguments": "{\"sign\": \"Aquarius\"}",
        "call_id": "call_12345"
      }
    ]
  },
  {
    "type": "function_call_output",
    "call_id": "call_12345",
    "output": "{\"horoscope\": \"Aquarius: Next
Tuesday you will befriend a baby otter.\"}"
  }
]
```

Пример: как строится диалог с агентской системой

3. LLM Chat template:

```
<|im_start|>system
# Tools

You may call one or more functions to assist with
the user query.

You are provided with function signatures within
<tools></tools> XML tags:
<tools>
{
  "type": "function",
  "name": "get_horoscope",
  "description": "Get today's horoscope for an
astrological sign.",
  "parameters": {
    "type": "object",
    "properties": {
      "sign": {
        "type": "string",
        "description": "An astrological sign like
Taurus or Aquarius"
      }
    },
    "required": ["sign"]
  }
}
</tools>
```

```
For each function call, return a json object with
function name and arguments within
<tool_call></tool_call> XML tags:
<tool_call>
{"name": <function-name>, "arguments":
<args-json-object>}
</tool_call>
<|im_end|>
<|im_start|>user
What is my horoscope? I am an Aquarius.
<|im_end|>
<|im_start|>assistant
<tool_call>
{"name": "get_horoscope", "arguments": {"sign":
"Aquarius"}}
</tool_call>
<|im_end|>
<|im_start|>user
<tool_response>
{"call_id": "call_12345", "output": {"horoscope":
"Aquarius: Next Tuesday you will befriend a baby
otter."}}
</tool_response>
<|im_end|>
<|im_start|>system
Respond only with a horoscope generated by a tool.
<|im_end|>
<|im_start|>assistant
Aquarius: Next Tuesday you will befriend a baby
otter.
```

Можно выделить три широких типа инструментов, доступных агенту

Дополнение информации агента

- Выход в интернет
- Парсинг нетекстовых типов данных (звука, изображений)
- Доступ к почте (чтение)
- Хожение по API
- Retrieval Augmented Generation (RAG)*
- etc.

Расширение возможностей агента

- Переводчики (в широком смысле) e.g. языков, единиц измерения
- Доступ к геолокации, времени
- Интерпретаторы и компиляторы языков программирования
- Калькулятор
- etc.

Возможность агента действовать

- Управление роботами (в т.ч. автомобилями)
- Исполнение написанного агентом кода и запросов
- Доступ к почте (с возможностью писать)
- etc.




Пример популярных инструментов

Commonly Used Tools:

- **Web Search:** For accessing real-time, up-to-date information.
 - ➔ ○ Google API
 - Serp
 - Yandex
 - ➔ ○ Tavily: Designed specifically for LLMs
- **Code Interpreter:** For executing code (Python, etc.) to perform calculations, data analysis, or file manipulation.
 - Python sandbox
 - Bash
 - JS
 - e.t.c
- **Database Query:** To retrieve structured information from SQL or NoSQL databases.
 - Postgres
 - Clickhouse
 - e.t.c
- **External APIs:** To interact with any service (GitHub, Spotify, corporate systems).
- **Retrieval:** To search over a private knowledge base (e.g., using a vector database).
 - Confluence/Wiki
 - Vector DB over documents

Retrieval-Augmented Generation (RAG) тоже может быть одним из инструментов



Retrieval-Augmented Generation (RAG) тоже может быть одним из инструментов




Figure 16: An Overview of Single Agentic RAG

Retrieval-Augmented Generation (RAG) тоже может быть одним из инструментов




Figure 17: An Overview of Multi-Agent Agentic RAG Systems

Retrieval-Augmented Generation (RAG) тоже может быть одним из инструментов




Figure 20: An Overview of Adaptive Agentic RAG


Reason -> Act

ReAct: Synergizing Reasoning and Acting in Language Models:

Mostly prompting and response processing technique.

Main idea:

Let LLM reason first, perform some actions and then observe the outcome



React: пример (1/4)

```
{
  "messages": [
    {
      "role": "system",
      "content": 'Answer the following questions as best you can. You have access to the following tools:\n\nSearch: A search engine. Useful for when you need to answer questions about current events. Input should be a search query.\n\nCalculator: Useful for when you need to answer questions about math.\n\nThe way you use the tools is by specifying a json blob.\n\nSpecifically, this json should have a action key (with the name of the tool to use) and a action_input key (with the input to the tool going here).\n\nThe only values that should be in the "action" field are: Search, Calculator\n\nThe $JSON_BLOB should only contain a SINGLE action, do NOT return a list of multiple actions. Here is an example of a valid $JSON_BLOB:\n\n```\n  "action": $TOOL_NAME,\n  "action_input": $INPUT\n```\n\nALWAYS use the following format:\n\nQuestion: the input question you must answer\nThought: you should always think about what to do\nAction: `"$JSON_BLOB"`\nObservation: the result of the action\n... (this Thought/Action/Observation can repeat N times)\nThought: I now know the final answer\nFinal Answer: the final answer to the original input question\n\nBegin! Reminder to always use the exact characters Final Answer when responding.',
    },
    {
      "role": "user",
      "content": "Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?\n\n",
    },
  ],
  "model": "gpt-3.5-turbo",
  "request_timeout": 60,
  "max_tokens": None,
  "stream": False,
  "n": 1,
  "temperature": 0.0,
  "stop": ["Observation:"],
}
```

React: пример (2/4)

Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?

This was your previous work (but I haven't seen any of it! I only see what you return as final answer):

Thought: I need to use a search engine to find Olivia Wilde's boyfriend and a calculator to raise his age to the 0.23 power.

Action:

```
{  
  "action": "Search",  
  "action_input": "Olivia Wilde boyfriend"  
}
```

Observation: Sudeikis and Wilde's relationship ended in November 2020. Wilde was publicly served with court documents regarding child custody while she was presenting Don't Worry Darling at CinemaCon 2022. In January 2021, Wilde began dating singer Harry Styles after meeting during the filming of Don't Worry Darling.

Thought:



React: пример (3/4)

Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?

This was your previous work (but I haven't seen any of it! I only see what you return as final answer):

Thought: I need to use a search engine to find Olivia Wilde's boyfriend and a calculator to raise his age to the 0.23 power.

Action:

```
{  
  "action": "Search",  
  "action_input": "Olivia Wilde boyfriend"  
}
```

Observation: Sudeikis and Wilde's relationship ended in November 2020. Wilde was publicly served with court documents regarding child custody while she was presenting Don't Worry Darling at CinemaCon 2022. In January 2021, Wilde began dating singer Harry Styles after meeting during the filming of Don't Worry Darling.

Thought: I need to use a search engine to find Harry Styles' current age.

Action:

```
{  
  "action": "Search",  
  "action_input": "Harry Styles age"  
}
```

Observation: 29 years

Thought:

React: пример (4/4)

Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?

This was your previous work (but I haven't seen any of it! I only see what you return as final answer):

Thought: I need to use a search engine to find Olivia Wilde's boyfriend and a calculator to raise his age to the 0.23 power.

Action:

```
{
  "action": "Search",
  "action_input": "Olivia Wilde boyfriend"
}
```

Observation: Sudeikis and Wilde's relationship ended in November 2020. Wilde was publicly served with court documents regarding child custody while she was presenting Don't Worry Darling at CinemaCon 2022. In January 2021, Wilde began dating singer Harry Styles after meeting during the filming of Don't Worry Darling.

Thought: I need to use a search engine to find Harry Styles' current age.

Action:

```
{
  "action": "Search",
  "action_input": "Harry Styles age"
}
```

Observation: 29 years

Thought: Now I need to calculate 29 raised to the 0.23 power.

Action:

```
{
  "action": "Calculator",
  "action_input": "29^0.23"
}
```

Observation: Answer: 2.169459462491557

Thought:

LLM Response:


I now know the final answer.

Final Answer: 2.169459462491557

Архитектура агента на основе генеративной модели




Model Context Protocol (MCP)







Model Context Protocol (MCP)




Агент – больше, чем просто LLM



Агента можно оценивать как LLM, а можно как сервис в совокупности.
И это важно.



Пример анализа LLM как самостоятельной модели



Пример анализа LLM как самостоятельной модели

Conceptual Physics	When you drop a ball from rest it accelerates downward at 9.8 m/s^2 . If you instead throw it downward assuming no air resistance its acceleration immediately after leaving your hand is	
	(A) 9.8 m/s^2	✓
	(B) more than 9.8 m/s^2	✗
	(C) less than 9.8 m/s^2	✗
	(D) Cannot say unless the speed of throw is given.	✗
College Mathematics	In the complex z -plane, the set of points satisfying the equation $z^2 = z ^2$ is a	
	(A) pair of points	✗
	(B) circle	✗
	(C) half-line	✗
	(D) line	✓

Figure 4: Examples from the Conceptual Physics and College Mathematics STEM tasks.



Пример анализа LLM как самостоятельной модели

Выбрать задачи☒ Все задачи

☒ RWSD i

☒ PARus i

☒ RCB i

☒ MultiQ i

☒ ruWorldTree i

☒ ruOpenBookQA i

☒ CheGeKa i

☒ ruTiE i

☒ USE i

☒ MathLogicQA i

☒ ruMultiAr i

☒ LCS i

☒ ruModAr i

☒ MaMuRAMu i

☒ ruCodeEval i

Выбрать домены☒ Все домены

☒ Астрономия

☒ Безопасность

☒ Бизнес и управление

☒ Биология

☒ География


☒ Инженерия

☒ Искусство


Развернуть список доменов

	Модель, команда	Результат	RWSD	PARus	RCB	MultiQ	ruWorldTree	ruOpenBookQA	CheGeKa
1	Human Benchmark MERA	0.852	0.835	0.982	0.565 / 0.587	0.928 / 0.91	0.935 / 0.935	0.875 / 0.865	0.719 / 0.645
2	Claude 3.7 Sonnet Ilmarena.ru	0.682	0.788	0.954	0.591 / 0.578	0.623 / 0.468	0.994 / 0.994	0.955 / 0.955	0.63 / 0.526
3	Gemini 2.0 Flash Ilmarena.ru	0.678	0.462	0.934	0.516 / 0.469	0.624 / 0.471	0.994 / 0.994	0.935 / 0.935	0.586 / 0.5
4	DeepSeek-V3 Ilmarena.ru	0.677	0.612	0.93	0.525 / 0.464	0.581 / 0.421	0.99 / 0.99	0.933 / 0.932	0.523 / 0.44
5	Gemini 1.5 Pro Ilmarena.ru	0.675	0.627	0.958	0.598 / 0.57	0.568 / 0.418	0.99 / 0.99	0.95 / 0.95	0.63 / 0.534
6	DeepSeek-V3-0324 685.0B Ilmarena.ru	0.674	0.658	0.93	0.564 / 0.492	0.592 / 0.456	0.985 / 0.985	0.925 / 0.925	0.531 / 0.442
7	GigaChat 2 Max GIGACHAT	0.67	0.642	0.93	0.575 / 0.403	0.534 / 0.4	0.996 / 0.996	0.948 / 0.761	0.414 / 0.344
8	Qwen2.5-Max Ilmarena.ru	0.664	0.742	0.932	0.587 / 0.544	0.574 / 0.403	0.989 / 0.989	0.953 / 0.953	0.447 / 0.363

RAG – пример сервиса, построенного вокруг модели



Критический навык – умение оценить, можно ли доверять сервису



Ручная проверка: дорого, но иногда нет выбора

LLM input	LLM output	Label	Comment
		✓	
		✓	
		✗	Irrelevant
		✗	Too wordy



Имея примеры правильных ответов, можно сравнить результаты с ними




Мы как разработчик/заказчик выставляем требование на желаемые характеристики сервиса


Response	Concise?	Polite?	Helpful?
	✓	✓	✓
	✓	✓	✗
	✓	✓	✗
	✓	✓	✓



В наиболее критических узлах системы мы ставим т.н. ограждения (guardrails)



В наиболее критических узлах системы мы ставим т.н. ограждения (guardrails)




Популярные агентские фреймворки



crewai

Agno



LangGraph



smolagents



СПАСИБО ЗА ВНИМАНИЕ