



Technical Documentation API Cargus

<https://urgentcargus.developer.azure-api.net/>

Technology Used: **REST Web Api Microsoft**

Contents

Contents	2
1 Registering for API StandardUrgentOnlineAPI	4
2 PHP call example.....	11
3 Authentication.....	13
3.1 Logging in and obtaining token.....	13
3.2 Token Verification.....	13
4 Geography	14
4.1 The list of countries in the system	14
4.2 The list of counties in a country	14
4.3 The list of localities in a county	15
4.4 The list of streets in a locality.....	15
5 Pick up points.....	15
5.1 The list of pick up points per customer.....	16
5.2 Adding (assigning) a pick up point for user	17
5.3 Listing the active pick up points per user.....	17
5.4 Adding a pick up point for a user	19
5.5 Modifying a pick up point	20
6 Show address book.....	22
7 Query Ship & Go centers.....	22
8 Rates.....	24
8.1 The list of contracted prices.....	24
8.2 Price calculation for a shipment	25
9 Transport notes administration	31
9.1 Pick-up from another location.....	31
9.2 Generating transport waybill.....	31
9.3 EASY COLLECT transport waybill	34
9.3.1 – Query Ship & Go centers.....	34

9.3.2	– Generating Easy Collect Waybill	36
9.4	Generating transport waybills with return waybill	39
9.5	Generating transport waybills with AWB range	46
9.6	Deleting a transport note.....	47
9.7	Get routing details by address.....	47
9.8	Listing the transport notes of a given period	50
9.9	Listing transport notes information for an order	52
9.10	Printing transport notes in PDF or HTML format.....	52
9.11	Tracking the shipments with return or redirected AWB's	54
9.12	Listing returning AWB's	57
9.13	Check last event from a set interval.....	59
9.14	Display confirmation picture	
10	Order management (courier request)	59
10.1	Launching or cancelling an order for a pick up point.....	60
10.2	Launching or cancelling all orders	60
10.3	Listing orders information for a pick up point.....	60
10.4	Listing order information for a given period.....	62
10.5	Listing order information using its number	63
11	Tracking cash on delivery	64
11.1	List cash on delivery from a set period of time	65
11.2	Listing refunds after a certain date	66
11.3	Refund listing according to a certain barcode.....	66
12	Invoices	68
12.1	Invoices list	68
12.2	Printing invoices in PDF format	69
13	Work flow for integration	70
14	Implementation conditions for the multipiece service	70
15	ANNEX	70

1 Registering for API StandardUrgentOnlineAPI
<https://urgentcargus.developer.azure-api.net/>

1. You have to create an account first of all by accessing the "Sign up" button.

2.



[Home](#) [APIs](#) [Products](#) [Sign in](#) [Sign up](#)

Welcome to Cargus!

Sign up

Explore APIs



Sign up

Already a member? [Sign in](#).

Email *

e.g. name@example.com

Password *

Confirm password *

First name *

e.g. John

Last name *

e.g. Doe

Enter the characters you see.

[New](#) | [Audio](#)



Enter the captcha here

Sign up

3. Fill in the required data, then confirm the registration for the service by following the confirmation link received by e-mail.
4. Being logged in, go back to the initial page and click on PRODUCTS



[Home](#) [APIs](#) [Products](#) [Reports](#) [Profile](#) [Sign out](#)

Welcome to Cargus!

Explore APIs



APIs

 Search APIs

Group by tag ☐



Name	Description	Type
UrgentOnlineAPI		REST
Web Express API		REST



5. Subscribe to our API: **StandardUrgentOnlineAPI**



[Home](#) [APIs](#) [Products](#) [Reports](#) [Profile](#) [Sign out](#)

UrgentOnlineAPI

Standard product for UrgentOnlineAPI usage

UrgentOnlineAPI 

Your subscriptions

You don't have subscriptions yet.

CARGUS Subscription key|

Subscribe



6. A service administrator will approve your subscription request. After the approval you will receive a confirmation e-mail, then you can start using the API service.

7. Click on **PROFILE** and retain the **Primary Key** for calling the API methods.



User profile

Account details

Email

gigel1688@gmail.com

First name

gigel

Last name

FRANARU

Registration date

10/10/2024

Change name

Change password

Close account

Subscriptions

Subscription details			Product	State	Action
Name	CARGUS Subscription key	Rename	UrgentOnlineAPI	Active	Cancel
Started on	10/10/2024				
Primary key	ae6fa72665c640e88fe63e2a47641: Hide Regenerate				
Secondary key	xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx: Show Regenerate				

Name	CARGUS Subscription key	Rename
Started on	10/10/2024	
Primary key	xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	Show Regenerate

The value in this format `XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX` will be sent in the header of each request, in the form of two parameters: **'Ocp-Apim-Subscription-Key: XX'**, **'Ocp-Apim-Trace:true'**

8. Also, for API authentication, you need to send in the header another parameter, of this form: **'Authorization: Bearer TOKEN '**, where TOKEN is the character string obtained from calling the **LoginUser** method.

9. For a complete definition of the API and on-page calling you can use the interface, accessing APIs -> UrgentOnlineAPI:

10.



Home

APIs

APIs

 Search APIs

Group by tag ☐



Name

Description

[UrgentOnlineAPI](#)



UrgentOnlineAPI

UrgentOnlineAPI

Search operations

Group by tag

API definition

Changelog

Try it

ty

AwbDocuments

AwbGeneral

AwbPickup

AwbRetur

Awbs

AwbScan

Print awb labels

Print awb labels

AwbDocuments

Request

GET https://urgentcargus.azure-api.net/api/AwbDocuments?barCodes={barCodes}&type={type}&format[{&printMainOnce}][&printOneAwbPerPage][&senderName][&printReturn]

REQUEST PARAMETERS

Name	In	Required	Type	Description
barCodes	template	true	string	



Complaint

Counties

Countries

InvoiceDocuments

Invoices

Localities

LoginUser

Marketing

NiqAuth

>

REQUEST HEADERS

Name	Required	Type	Description
Authorization	true	string	access token

Response: 200 OK
Ok

application/json text/json application/xml text/xml

APIAWBDOCUMENTSGET200APPLICATIONJSONRESPONSE

{}

DEFAULT

DEFAULT -JSON

Copy

2 PHPcall example:

```
<?php
class UrgentCurier
{
    private $Curl;
    public $url='https://urgentcargus.azure-api.net/api';

    function __construct()
    {
        $this->Curl = curl_init();
        curl_setopt($this->Curl, CURLOPT_RETURNTRANSFER, true);
        curl_setopt($this->Curl,CURLOPT_CONNECTTIMEOUT, 2);
        curl_setopt($this->Curl, CURLOPT_TIMEOUT, 3);
    }

    function CallMethod($function, $parameters="", $verb,$token=null)
    {
        curl_setopt($this->Curl, CURLOPT_POSTFIELDS, $parameters);
        curl_setopt($this->Curl, CURLOPT_CUSTOMREQUEST, $verb);
        curl_setopt($this->Curl, CURLOPT_URL, $this->url . '/' . $function);

        //LoginUser este singura metoda pentru care nu se trimite Token
        if ($function=="LoginUser") {
            curl_setopt($this->Curl, CURLOPT_HTTPHEADER, array('Ocp-Apim-Subscription-
            Key:xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx','Ocp-Apim-Trace:true','Content-Type:
            application/json', 'Content-Length: ' . strlen($parameters)));
        }
        else{
            curl_setopt($this->Curl, CURLOPT_HTTPHEADER, array('Ocp-Apim-Subscription-
            Key: xxxxxxxxxxxxxxxxxxxxxxxxxxxxx','Ocp-Apim-Trace:true','Authorization: Bearer
            '.$token, 'Content-Type: application/json', 'Content-Length: ' .
            strlen($parameters)));
        }

        $result=curl_exec($this->Curl);
        $header=curl_getinfo($this->Curl);

        $output['message']=$result;
        $output['status']=$header['http_code'];
        return $output;
    }
}
$urgent = new UrgentCurier();
?>
```

3 Authentication

3.1 Logging in and obtaining token

The method **LoginUser** called by POST is used to authenticate and obtain the token. The obtained token is valid for 24 hours.

You send :

UserName – the webexpress user
Password – the user password

It returns :

Token – will be used in all the called methods as a means of authentication

Example:

```
$fields=array('UserName' => 'test.integration9', 'Password' => 'a');
$json=json_encode($fields);
$login=$urgent->CallMethod('LoginUser', $json, 'POST');
if ($login['status'] != "200") {

    echo "<b class='bad'>LoginUser: FALSE</b>";
}
else{
    $token = json_decode($login['message']);
    echo "<b class='good'>LoginUser: </b>".$token;
}
```

3.2 Token Verification

The method used is **TokenVerification**. It is a GET type method and it is used if you want to verify the authentication.

You send:

Token – returned by the LoginUser method

It returns :

true / false

Example:

```
$result=$urgent->CallMethod('TokenVerification', $json="", 'GET', $token);
if ($result['status']!="200") {
    echo "<b class='bad'>Token check: FALSE</b>";
}
else{
    $data=$result['message'];
```

```
echo "<b class='good'>Token check: </b>".$data; }
```

4 Geography

4.1 The list of countries in the system

The method used is **Countries**, called through GET and it returns the list of the countries in the Cargus system.

You send:

It returns:

A list with the accepted countries. The list provides the following information:

CountryId – the country id

CountryName – the country name

Abbreviation – the country code

Example:

```
$resultCountries = $urgent->CallMethod('Countries', $json="", 'GET', $token);

if ($resultCountries['status'] != "200") {
    echo "<b class='bad'>GET Countries: </b>".$resultCountries['message'];
}
else{
    $jsonCountriesList = $resultCountries['message'];
    echo "<b class='good'>GET Countries: </b>".$jsonCountriesList;
}
```

4.2 The list of counties in a country

The **Counties** method is used to return the list of the counties in a country. It is a GET type method, and in the URL the country id is sent.

You send :

countryId - the country id, returned by the Countries method

It returns:

A list of the accepted. The list provides the following information:

CountyId – county id

Name – county name

Abbreviation – county code

Example:

```
$resultCounties = $urgent->CallMethod('Counties?countryId=1', $json="", 'GET', $token);
if ($resultCounties['status'] != "200") {
    echo "<b class='bad'>GET Counties: </b>".$resultCounties['message'];
}
```

```

else {
    $jsonCountiesList = $resultCounties['message'];
    echo "<b class='good'>GET Counties List: </b>".$jsonCountiesList;
}

```

4.3 The list of localities in a county

The **Localities** method, called through GET, is used to return the list of localities in a given county.

You send :

countryId - the country id returned by the Countries method
 countyId – the county returned by the Counties method

It returns:

A list of accepted localities and the corresponding information. The list provides the following information:

LocalityId – locality id
 Name – locality name
 ParentId – the territorial agency to which the locality belongs
 ParentName – the name of the territorial agency
 ExtraKm – chargeable extra kilometers
 InNetwork – in the network
 CountyId – county id
 CountryId – country id
 CodPostal – postal code
 MaxHour – pick up hour

Example:

```

$resultLocalities = $urgent->CallMethod('Localities?countryId=1&countyId=5', $json="", 'GET',
$token);
if($resultLocalities ['status']!="200") {
    echo "<b class='bad'>GET Localities: </b>".$resultLocalities['message'];
}
else{
    $jsonLocalitiesList = $resultLocalities['message'];
    echo "<b class='good'>GET Localities List: </b>".$jsonLocalitiesList;
}

```

4.4 The list of streets in a locality

The **Streets** method, called through GET, is used to return the list of the streets in the Cargus nomenclature, in a given locality.

You send :

localityId - the locality id, returned by the Localities method.

It returns:

A list of the streets in the nomenclature and the afferent information. The list provides the following information:

StreetId – street id
Name – streetname

Example:

```
$resultStreets = $urgent->CallMethod('Streets?localityId=157', $json="", 'GET', $token);  
if ($resultStreets ['status']!="200") {  
    echo "<b class='bad'>GET Streets: </b>". $resultStreets['message'];  
}  
else{  
    $jsonStreetsList = $resultStreets['message'];  
    echo "<b class='good'>GET Streets List: </b>". $jsonStreetsList;  
}
```

5 Pick up points

A customer has more pick up points. A user has access to one or multiple pick up points.

By default, a customer has one pick up point per headquarters, which is used in the application as LocationId=0.

5.1 The list of pick up points per customer

The **PickupLocations/GetForClient** method is a GET type method. It is used to return the list of pick up points for a customer.

You send :

token – identify the customer

It returns:

A list of pick up points and the afferent information. The list provides the following information:

LocationId – pick up point id
Name – pick up point name
CountyId – county id
CountyName – county name
LocalityId – locality id
LocalityName – locality name
StreetId – street id
StreetName – street name
BuildingNumber – street number
AddressText - address
ContactPerson – contact
PhoneNumber – contact phone number
Email – e-mail address
"CodPostal": - postal code for the pickup location

Example:

```

$resultPickupLocations = $urgent->CallMethod('PickupLocations/GetForClient', $json="", 'GET',
$token);
if ($resultPickupLocations ['status']!="200") {
    echo "<b class='bad'>GET PickupLocations: </b>".$resultPickupLocations['message'];
}
else{
    $jsonPickupLocations = $resultPickupLocations['message'];
    echo "<b class='good'>GET PickupLocations List: </b>".$jsonPickupLocations;
}

```

5.2 Adding (assigning) a pick up point for user

The **PickupLocations/AssignToUser** method, called through POST, is used to add (assign) a pick up point per user.

You send:

token – identifies the customer

LocationId – the id of the pick up point which will be assigned to the logged in user

It returns:

1 – if the activation is successful / error – if the activation was not successful

Example:

```

$resultAssignToUser = $urgent-
>CallMethod('PickupLocations/AssignToUser?LocationId=201008098', $json="", 'POST',$token);

if ($resultAssignToUser ['status']!="200") {
    echo "<b class='bad'>GET AssignToUser: </b>".$resultAssignToUser['message'];
}
else{
    $jsonAssignToUser = $resultAssignToUser['message'];
    echo "<b class='good'>POST AssignToUser Status: </b>".$jsonAssignToUser;
}

```

5.3 Listing the active pick up points per user

The **PickupLocations** method, called through GET, is used to list the pick up points that are active for a given user.

You send :

token – identify the customer

It returns:

LocationId – the pick up point id

Name – the pick up point name

CountyId – the county id

CountyName – the county name

LocalityId – the locality id
LocalityName – the locality name
StreetId – the street id
StreetName – the street name
BuildingNumber – the street number
AddressText – the address
ContactPerson – the contact
PhoneNumber – the contact's phone number
Email – the e-mail address
CodPostal – postal code for pickup point

Example:

```
$resultPickupLocations = $urgent->CallMethod('PickupLocations', $json="", 'GET', $token);  
if ($resultPickupLocations ['status']!="200") {  
    echo "<b class='bad'>GET PickupLocations: </b>". $resultPickupLocations['message'];  
}  
else{  
    $jsonPickupLocations = $resultPickupLocations['message'];  
    echo "<b class='good'>GET PickupLocations Status: </b>". $jsonPickupLocations;  
}
```

5.4 Adding a pick up point for a user

The **PickupLocations** method is used to add a new pick up point for a user. The pick up point is active by default. The method is a POST type method.

You send :

- AutomaticEOD – booking closing hour
- LocationId – pick up point id
- Name – pick up point name
- CountyId – county id
- CountyName – county name
- LocalityId – locality id
- LocalityName – locality name
- StreetId - street id or 0
- StreetName – street name
- BuildingNumber – street number
- AddressText - address
- ContactPerson – contact name
- PhoneNumber – contact phone number
- Email – e-mail address
- CodPostal– postal code for pickup point

It returns:

the id of the pick up point

Example:

```
$jsonPickupLocations = '{
    "AutomaticEOD": "17:30",
    "LocationId": "",
    "Name": "Punct ridicare 2 Pitesti",
    "CountyId": 5,
    "CountyName": "Arges",
    "LocalityId": 157,
    "LocalityName": "Pitesti",
    "StreetId": 0,
    "StreetName": "Gheorghe S. Ioan, general, Strada",
    "BuildingNumber": "5",
    "AddressText": "Str. Ionescu Gheorghe",
    "ContactPerson": "Gheorghe",
    "PhoneNumber": "072769821",
    "CodPostal": "string",
    "Email": "a@a.com"
}';

$resultPickupLocationsPost = $urgent->CallMethod('PickupLocations',
```

```

$jsonPickupLocations, 'POST', $token);
if ($resultPickupLocationsPost ['status']!="200") {
    echo "<b class='bad'>Post PickupLocations:
</b>". $resultPickupLocationsPost['message'];
}
else {
    $jsonPickupLocationsPost = $resultPickupLocationsPost['message'];
    echo "<b class='good'>Post PickupLocations id-location:
</b>". $jsonPickupLocationsPost;
}

```

5.5 Modifying a pick up point

The **PickupLocations** method is used to modify a pick up point. This method is a PUT type method.

You send :

AutomaticEOD – booking closing hour; if none, type NULL
 LocationId – pick up point id
 Name – pick up point name
 CountyId – county id
 CountyName – county name
 LocalityId – locality id
 LocalityName – locality name
 StreetId - street id or 0
 StreetName – street name
 BuildingNumber – street number
 AddressText - pick up point address

ContactPerson – contact name
PhoneNumber – contact phone number
Email – e-mail address
CodPostal – postal code for pickup point

It returns:

True

Example:

```
$jsonPickupLocations =  
{  
  "AutomaticEOD": null,  
  "LocationId": "31498",  
  "Name": "ecomMODIFICAT",  
  "CountyId": 5,  
  "CountyName": "Arges",  
  "LocalityId": 157,  
  "LocalityName": "pitesti",  
  "StreetId": 0,  
  "StreetName": "Gheorghe S. Ioan, general, Strada",  
  "BuildingNumber": "5",  
  "AddressText": "bl 5 ap 5",  
  "ContactPerson": "Gheorghe",  
  "PhoneNumber": "072769821",  
  "CodPostal": "string",  
  "Email": "a@a.com"  
};
```

```
$result = $urgent->CallMethod('PickupLocations', $jsonPickupLocations, 'PUT', $token);
```

```
if ($result['status'] != "200") {  
    echo("<b class='bad'>PUT PickupLocations: </b>". $result['message']);  
}  
else {  
    $data = $result['message']; echo "<b class='good'>PUT PickupLocations:  
</b>". $data;  
}
```

6 Show address book

The **Recipient** method, called through GET, is used to list established address book

You send :

token – identify the customer

It returns:

A list of your address book , which contains the following

LocationId – pick up point id
Name – recipient name
CountyId – county id
CountyName- county name
LocalityId – locality id
LocalityName – locality name
StreetId – street id
StreetName – street name
BuildingNumber – bulding number
AddressText – address
ContactPerson – contact person
PhoneNumber – phone number
Email – e-mail
CodPostal– postal code for delivery point

Example:

```
$resultRecipients = $urgent->CallMethod('Recipients', $json="", 'GET', $token);  
if ($resultRecipients ['status']!="200") {  
    echo "<b class='bad'>GET 'Recipients': </b>". $resultRecipients ['message'];  
}  
else{  
    $jsonRecipients = $ resultRecipients ['message'];  
    echo "<b class='good'>GET resultRecipients List: </b>". $ jsonRecipients;  
}
```

7 Query Ship & Go centers

The **PUDO_Get** is called. It is used to return the list of Ship & Go points.

You send:

Token-Used to identify the client

It returns:

A list of delivery points and related information. The list includes the following information:

Example:

```
{
  "Id": 114142,
  "Name": "CARGUS SHIP & GO MAGURELE",
  "LocationId": 1,
  "CityId": 1793631,
  "City": "Magurele",
  "StreetId": 39689,
  "ZoneId": 8728,
  "PostalCode": "077125",
  "AdditionalAddressInfo": "",
  "Longitude": 26.041645,
  "Latitude": 44.367229,
  "PointType": 5,
  "OpenHoursMoStart": "08:00",
  "OpenHoursMoEnd": "18:00",
  "OpenHoursTuStart": "08:00",
  "OpenHoursTuEnd": "18:00",
  "OpenHoursWeStart": "08:00",
  "OpenHoursWeEnd": "18:00",
  "OpenHoursThStart": "08:00",
  "OpenHoursThEnd": "18:00",
  "OpenHoursFrStart": "08:00",
  "OpenHoursFrEnd": "18:00",
  "OpenHoursSaStart": "",
  "OpenHoursSaEnd": "",
  "OpenHoursSuStart": "",
  "OpenHoursSuEnd": "",
  "StreetNo": "99-115",
  "PhoneNumber": "021 9330",
  "ServiceCOD": false,
  "PaymentType": 1,
  "CountyId": 27,
  "County": "Ilfov",
  "Email": "",
  "MainPicture": "",
  "Entrance": null,
  "Floor": null,
  "Apartment": null,
  "Sector": null,
  "StreetName": "Atomistilor"
},
```

Where:

"Id" – id of the delivery point

"Name" – name of the delivery point

"LocationId" – something internal
 "CityId" – city id for delivery point
 "City" – city name for delivery point
 "StreetId" – street id for delivery point
 "ZoneId" – something internal
 "PostalCode" – zipcode for delivery point
 "AdditionalAddressInfo" – additional address info for the delivery point
 "Longitude" – coordinates on map for the delivery point
 "Latitude" – coordinates on map for the delivery point
 "PointType" – used for delivery points associated with Cargus Warehouse
 "OpenHoursMoStart" – open time on monday
 "OpenHoursMoEnd" – close time on monday
 "OpenHoursTuStart" – open time on tuesday
 "OpenHoursTuEnd" – close time on tuesday
 "OpenHoursWeStart" – open time on wednesday
 "OpenHoursWeEnd" – close time on wednesday
 "OpenHoursThStart" – open time on thursday
 "OpenHoursThEnd" – close time on thursday
 "OpenHoursFrStart" – open time on friday
 "OpenHoursFrEnd" – close time on friday
 "OpenHoursSaStart" – open time on saturday
 "OpenHoursSaEnd" – close time on saturday
 "OpenHoursSuStart" – open time on sunday
 "OpenHoursSuEnd" – close time on sunday
 "StreetNo" – street number of the delivery point
 "PhoneNumber" – phone number of the delivery point
 "ServiceCOD" – the delivery point dose or dose not allow COD
 "PaymentType" – payment type of the delivery point (1 – no payment available 2 – pay only by card, 3 – pay by cash or card, 4 – pay only cash)
 "CountyId" – county id of the delivery point
 "County" – county name of the delivery point
 "Email" – email of the delivery point
 "MainPicture" – picture of the delivery point
 "Entrance" – entrance informations of the delivery point
 "Floor" – floor of the delivery point
 "Apartment" – apartment of the delivery point
 "Sector" – district of the delivery point
 "StreetName" – street name for delivery point

8 Rates

8.1 The list of contracted prices

The **PriceTable** method, called through GET, is used to list the prices established in the contract.

You send :

token – identify the customer

it returns:

PriceTableId – price id
Name – price name

Example:

```
$resultPriceTables=$urgent->CallMethod('PriceTables',$json="", 'GET', $token);

if ($resultPriceTables ['status']!="200") {
    echo "<b class='bad"
'>GET PriceTables : </b>".$resultPriceTables ['message'];
}
else {
    $data=$resultPriceTables ['message'];
    echo "<b class='good'>GET PriceTables : </b>".$data;
}
```

8.2 Price calculation for a shipment

The **ShippingCalculations** method, called through POST, is used to calculate the price of a shipment.

You send :

FromLocalityId – id of the sender's locality
ToLocalityId – id of the consignee's locality
FromCountyName - name of the sender's county / OPTIONAL
FromLocalityName – name of the sender's locality /OPTIONAL
ToCountyName – name of the consignee's county / OPTIONAL
ToLocalityName – name of the consignee's locality /OPTIONAL
Parcels – number of parcels
Envelopes – number of envelopes
TotalWeight – the total weight of the shipment
ServiceId – 34 for totalweight 0 ≤ 31 kg ; 35 for 31 kg < totalweight ≤ 50 ; 36 for totalweight > 50 kg
DeclaredValue – declared value
CashRepayment - cash repayment returned in the envelope
BankRepayment – bank repayment – in the bank account
OtherRepayment – anything returned// receipt, parcel in exchange
PaymentInstrumentId – payment instrument id// 1 – cheque, 2 –bo, 3
PaymentInstrumentValue – payment instrument value
OpenPackage – open package // use TRUE or FALSE
ShipmentPayer – shipment payer. Send 1 for sender and 2 for consignee
PriceTableId – price id, returned by the PriceTables method

It returns:

BaseCost – base prices, without contract
ExtraKmCost – extra kilometers price
WeightCost – contracted price
InsuranceCost – insured price (insurance)
SpecialCost – special taxes
RepaymentCost – repayment cost : cash(envelope) or return (OtherRepayment)
Subtotal – total without VAT
Tax - VAT
GrandTotal – total price

Example:

```
$json='{  
    "FromLocalityId" :150,  
    "ToLocalityId" :150,  
    "Parcels": 1,  
    "Envelopes": 0,  
    "TotalWeight": 1,  
    "DeclaredValue": 0,  
    "CashRepayment": 0,  
    "BankRepayment": 0,  
    "OtherRepayment": "",  
    "OpenPackage": true,  
    "PriceTableId": 23049,  
    "ShipmentPayer": 1,  
};  
  
$result=$urgent->CallMethod('ShippingCalculation', $json, 'POST', $token);  
if ($result['status']!="200") {  
    echo("<b class='bad'>POST ShippingCalculation: </b>".$result['message']);  
}  
else{  
    $data=$result['message'];  
    echo "<b class='good'>POST ShippingCalculation: </b>".$data;  
}
```

9 Transport waybills administration

9.1 Pick-up from another location

POST called **AwbPickup** method, is used for generating a new AWB and for sending a new order to the courier.

You send:

PickupStartDate – start date and hour for pick up

PickupEndDate – end date and hour for pick up

SenderClientId – For all cases it is null. It is a feature created for those who want to create AWBs on behalf of another client.

TertiaryClientId – The third party id is used if you want to send on behalf of another client. It will be charged with the associated tariff for that customer .

Sender - Sender

Name – sender name

CountyId – county id

CountyName – county name

LocalityId – locality id

LocalityName – locality name

StreetId – street id

StreetName – street name, exactly as found in the Cargus nomenclature

BuildingNumber – street number

AddressText – address

ContactPerson – contact person for the current order

PhoneNumber – contact phone number

Email – e-mail address

CodPostal – postal code for pickup point

Recipient – Consignee

LocationId – pick up point id (recipient warehouse)

Name – recipient name

CountyId – county id

LocalityId – locality id

StreetId – street id

StreetName – street name // Optional

BuildingNumber – street number

AddressText – address

ContactPerson – contact person
PhoneNumber – contact phone number
Email – recipient e-mail address

Parcels – number of parcels
Envelopes – number of envelopes. Maximum of 9
TotalWeight – approximate total weight
DeclaredValue – declared value for insurance
CashRepayment – cash repayment (the sum returned to the sender in an envelope)
BankRepayment – bank repayment (the sum returned to the sender in the collector account)
OtherRepayment – other repayment
OpenPackage – open package
ServiceId - 34 for totalweight $0 \leq 31$ kg ; 35 for $31 \text{ kg} < \text{totalweight} \leq 50$; 36 for totalweight > 50 kg
HasTertReimbursement – if true the reimbursement comes back to TertiaryClientId and its obligatory
PriceTableId – price id
ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient
SaturdayDelivery – Saturday delivery
MorningDelivery – morning delivery
Observations - observations
PackageContent – package content
CustomString – reference customer series
SenderReference1 – sender reference 1
RecipientReference1 – recipient reference 1
RecipientReference2 – recipient reference 2
InvoiceReference – invoice reference

It returns:

Bar code number generated

Example:

```
$json='{  
  "PickupStartDate": "2017-10-25T14:11",  
  "PickupEndDate": "2017-10-25T18:55",  
  
  "Sender": {  
  
    "Name": "popescuvasile",  
    "CountyName": "iasi",  
    "LocalityName": "iasi",  
    "AddressText": "Strada principala nr 1 bl 2",  
    "ContactPerson": "popescu vasile",  
    "PhoneNumber": "0723222222",  
    "CodPostal": "string"
```

```

    "Email": "yahoo@yahoo.com"
  },
  "Recipient": {
    "LocationId": 201165677, //
  },
  "Parcels": 2,
  "Envelopes": 0,
  "TotalWeight": 25,
  "ServiceId": 34,
  "DeclaredValue": 0,
  "CashRepayment": 0,
  "BankRepayment": 0,
  "OtherRepayment": "string",
  "BarCodeRepayment": "string",
  "PaymentInstrumentId": 0,
  "PaymentInstrumentValue": 0,
  "HasTertReimbursement": false,
  "OpenPackage": true,
  "PriceTableId": 0,
  "ShipmentPayer": 1,
  "ShippingRepayment": 0,
  "SaturdayDelivery": true,
  "MorningDelivery": true,
  "Observations": "string",
  "PackageContent": "string",
  "CustomString": "",
  "BarCode": "",
  "ParcelCodes": [
    {
      "Code": "0",
      "Type": 1,
      "Weight": 25,
      "Length": 20,
      "Width": 20,
      "Height": 20,
      "ParcelContent": "briefcase"
    }
  ],
  "ValidationDate": "2019-10-24T12:33:12.035Z",
  "ShippingCost": {
    "BaseCost": 0,
    "ExtraKmCost": 0,
    "WeightCost": 0,
    "InsuranceCost": 0,
    "SpecialCost": 0,
    "RepaymentCost": 0,
    "Subtotal": 0,

```

```

    "Tax": 0,
    "GrandTotal": 0
  },
  "Status": "string",
  "SenderReference1": "string",
  "RecipientReference1": "string",
  "RecipientReference2": "string",
  "InvoiceReference": "string",
  "Length": 0,
  "Width": 0,
  "Height": 0
}

```

```

  }';

```

```

$result=$urgent->CallMethod('AwbPickup', $json, 'POST', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>POSTAwb: </b>".$result['message']);
}
else{
    $data=$result['message'];
    echo "<b class='good'>POST Awb: </b>".$data;
}

```

9.2 Generating transport waybill

The **Awbs** method, called through POST, is used to add a new AWB.

You send:

Sender

SenderClientId – In all cases it is null. It's a facility created for those who want to create AWBs in the name of another customer.

TertiaryClientId – tertiary id, if the shipment is made in another customer's account

LocationId – pick up point id (sender warehouse)

Recipient - Consignee

Name – recipient name

CountyId – county id

CountyName: - county name

LocalityId – locality id

LocalityName - locality name

StreetId – street id

StreetName – street name // Optional

BuildingNumber – street number

AddressText – address

ContactPerson – contact person

PhoneNumber – contact phone number

Email – recipient e-mail address

CodPostal – postal code of the consignee

Parcels – number of parcels

Envelopes – number of envelopes. Maximum of 9

TotalWeight – approximate total weight

DeclaredValue – declared value for insurance

CashRepayment – cash repayment (the sum returned to the sender in an envelope)

BankRepayment – bank repayment (the sum returned to the sender in the collector account)

OtherRepayment – other repayment

OpenPackage – open package

ServicId: - 34 for totalweight $0 \leq 31$ kg ; 35 for $31 \text{ kg} < \text{totalweight} \leq 50$; 36 for $\text{totalweight} > 50$ kg

PriceTableId – price id

ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient

SaturdayDelivery – Saturday delivery

Observations - observation

PackageContent – package content

CustomString – reference customer series

SenderReference1 – reference sender 1

RecipientReference1 – reference recipient 1

RecipientReference2 – reference recipient 2

InvoiceReference – reference invoice
CodPostal– postal code for delivery point

It returns:

Generated barcode

Example:

```
{
  "SenderClientId": null,
  "TertiaryClientId": null,
  "TertiaryLocationId": 0,
  "Sender": {
    "LocationId": 201266091,
  },
  "Recipient": {
    "LocationId": 0,
    "Name": "Gheorghita Vasile",
    "CountyId": 0,
    "CountyName": "Iasi",
    "LocalityId": 0,
    "LocalityName": "Iasi",
    "StreetId": 0,
    "StreetName": "Str 11 iunie",
    "BuildingNumber": "14",
    "AddressText": "Str 11 iunie nr 14",
    "ContactPerson": "Gheorghita Vasile",
    "PhoneNumber": "0740123123",
    "Email": "Vasile@gmail.com",
    "CodPostal": "123456",
    "CountryId": 0
  },
  "Parcels": 2,
  "Envelopes": 0,
  "TotalWeight": 25,
  "ServiceId": 34,
  "DeclaredValue": 0,
  "CashRepayment": 0,
  "BankRepayment": 0,
  "OtherRepayment": "string",
  "BarCodeRepayment": "string",
  "PaymentInstrumentId": 0,
  "PaymentInstrumentValue": 0,
  "HasTertReimbursement": false,
  "OpenPackage": true,
  "PriceTableId": 0,
  "ShipmentPayer": 1,
  "ShippingRepayment": 0,
  "SaturdayDelivery": true,
```



```
"MorningDelivery": true,
"Observations": "string",
"PackageContent": "string",
"CustomString": "",
"ParcelCodes": [
{
  "Code": "0",
  "Type": 1,
  "Weight":25,
  "Length":25,
  "Width":25,
  "Height":25,
  "ParcelContent":"briefcase"
}
]
}
```

```
};
```

```
$result=$urgent->CallMethod('Awbs', $json, 'POST', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>POST Awb: </b>".$result['message']);
}
```

```

    }
    else{
        $data=$result['message'];
        echo "<b class='good'>POST Awb: </b>".$data;
    }

```

9.3 EASY COLLECT transport waybill

This service involves sending the shipment to the Shipper & Go Cargus Ship, where it will be picked up by the shipper. Two steps are required, as follows:

9.3.1 – Query Ship & Go centers

The **PODO**_Get is called. It is used to return the list of Ship & Go points.

You send:

Token-Used to identify the client

It returns:

A list of delivery points and related information. The list includes the following information:

Example:

```

{
  "Id": 114142,
  "Name": "CARGUS SHIP & GO MAGURELE",
  "LocationId": 1,
  "CityId": 1793631,
  "City": "Magurele",
  "StreetId": 39689,
  "ZoneId": 8728,
  "PostalCode": "077125",
  "AdditionalAddressInfo": "",
  "Longitude": 26.041645,
  "Latitude": 44.367229,
  "PointType": 5,
  "OpenHoursMoStart": "08:00",
  "OpenHoursMoEnd": "18:00",
  "OpenHoursTuStart": "08:00",
  "OpenHoursTuEnd": "18:00",
  "OpenHoursWeStart": "08:00",
  "OpenHoursWeEnd": "18:00",
  "OpenHoursThStart": "08:00",
  "OpenHoursThEnd": "18:00",

```

```

"OpenHoursFrStart": "08:00",
"OpenHoursFrEnd": "18:00",
"OpenHoursSaStart": "",
"OpenHoursSaEnd": "",
"OpenHoursSuStart": "",
"OpenHoursSuEnd": "",
"StreetNo": "99-115",
"PhoneNumber": "021 9330",
"ServiceCOD": false,
"PaymentType": 1,
"CountyId": 27,
"County": "Ilfov",
"Email": "",
"MainPicture": "",
"Entrance": null,
"Floor": null,
"Apartment": null,
"Sector": null,
"StreetName": "Atomistilor"
},

```

Where:

```

"Id" – id of the delivery point
"Name" – name of the delivery point
"LocationId": 1,
"CityId" – city id for delivery point
"City" – city name for delivery point
"StreetId" – street id for delivery point
"ZoneId": 8728,
"PostalCode" – zipcode for delivery point
"AdditionalAddressInfo" – additional address info for the delivery point
"Longitude" – coordinates on map for the delivery point
"Latitude" – coordinates on map for the delivery point
"PointType" – used for deliverypoints associated with Cargus Warehouse
"OpenHoursMoStart" – open time on monday
"OpenHoursMoEnd" – close time on monday
"OpenHoursTuStart" – open time on tuesday
"OpenHoursTuEnd" – close time on tuesday
"OpenHoursWeStart" – open time on wednesday
"OpenHoursWeEnd" – close time on wednesday
"OpenHoursThStart" – open time on thursday
"OpenHoursThEnd" – close time on thursday
"OpenHoursFrStart" – open time on friday
"OpenHoursFrEnd" – close time on friday
"OpenHoursSaStart" – open time on saturday
"OpenHoursSaEnd" – close time on saturday
"OpenHoursSuStart" – open time on sunday

```

"OpenHoursSuEnd" – close time on sunday
 "StreetNo" – street number of the delivery point
 "PhoneNumber" – phone number of the delivery point
 "ServiceCOD": false,
 "PaymentType" – payment type of the delivery point (1 – no payment available 2 – pay only by card, 3 – pay by cash or card, 4 – pay only cash)
 "CountyId" – county id of the delivery point
 "County" – county name of the delivery point
 "Email" – email of the delivery point
 "MainPicture" – picture of the delivery point
 "Entrance" – entrance informations of the delivery point
 "Floor" – floor of the delivery point
 "Apartment" – apartment of the delivery point
 "Sector" – district of the delivery point
 "StreetName" – street name for delivery point

9.3.2 – Generating Easy Collect Waybill

The **Awbs** method called by POST is used to add a new awb.

You send:

SenderClientId – For all cases it is null. It is a feature created for those who want to create AWBs on behalf of another client.

TertiaryClientId – The thirdparty id is used if you want to send on behalf of another client. It will be charged with the associated tariff for that customer .

DeliveryPudoPoint – Ship & Go delivery point id (pick up point id obtained using **PUDO_get**)

Sender - Sender

LocationId – pick up point id (sender warehouse)

Recipient – Consignee

ContactPerson – contact person // mandatory

PhoneNumber – contact phone number // mandatory

Email – recipient e-mail address // mandatory

Parcels – number of parcels

Envelopes – number of envelopes. Maximum of 9

TotalWeight – approximate total weight

DeclaredValue – declared value for insurance

CashRepayment – cash repayment (the sum returned to the sender in an envelope)

BankRepayment – bank repayment (the sum returned to the sender in the collector account)

OtherRepayment – other repayment

OpenPackage – open package

HasTertReimbursement – tert reimbursement

PriceTableId – price id
 ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient
 ServiceId – 38 // service assigned to PUDO Delivery is 38
 SaturdayDelivery – Saturday delivery // only for the locality that is opened on Saturday
 Observations - observation
 PackageContent – package content
 CustomString – reference customer series
 SenderReference1 – reference sender 1
 RecipientReference1 – reference recipient 1
 RecipientReference2 – reference recipient 2
 InvoiceReference – reference invoice

It returns:

Generated barcode

Example:

```

$json='{
  "DeliveryPudoPoint": 114125
  "Sender":{"LocationId":28244},
  "Recipient":{"
    "Name": "Gheorghita Vasile",
    "ContactPerson": "Gheorghita Vasile",
    "PhoneNumber": "0740123123",
    "Email": "Vasile@gmail.com"
  },
  "Parcels": 1,
  "Envelopes": 0,
  "TotalWeight": 166,
  "ServiceId": 38,
  "DeclaredValue": 0,
  "CashRepayment": 0,
  "BankRepayment": 0,
  "OtherRepayment": "string",
  "BarCodeRepayment": "string",
  "PaymentInstrumentId": 0,
  "PaymentInstrumentValue": 0,
  "HasTertReimbursement": false,
  "OpenPackage": true,
  "PriceTableId": 0,
  "ShipmentPayer": 1,
  "ShippingRepayment": 0,
  "SaturdayDelivery": true,
  "MorningDelivery": true,
  "Observations": "string",
  "PackageContent": "string",
  "CustomString": "",
  "ParcelCodes": [
    {

```

```

"Code": "0",
"Type": 1,
"Weight":25,
"Length":20,
"Width":20,
"Height":10,
"ParcelContent":"briefcase"
}
]
}

```

```

$result=$urgent->CallMethod('Awbs', $json, 'POST', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>POSTAwb: </b>".$result['message']);
}
else{
    $data=$result['message'];
    echo "<b class='good'>POST Awb: </b>".$dat
}

```

It returns: Main AWB

9.4 Generating transport waybills with Return Waybill

The **Awbs** method, called through POST, is used to add a new AWB.

You send:

ConsumerReturnTypes - 0 for no return option / 1 for Return Code / 2 for Pre-Printed return waybill

ReturnCodeExpirationDays – number of days before the return waybill expires

Sender

SenderClientId – In all cases it is null. It's a facility created for those who want to create AWBs in the name of another customer.

TertiaryClientId – tertiary id, if the shipment is made in another customer's account

LocationId – pick up point id (sender warehouse)

Recipient - Consignee

Name – recipient name

CountyId – county id

CountyName: - county name

LocalityId – locality id

LocalityName - locality name

StreetId – street id

StreetName – street name // Optional

BuildingNumber – street number

AddressText – address

ContactPerson – contact person

PhoneNumber – contact phone number

Email – recipient e-mail address

CodPostal – postal code of the consignee

Parcels – number of parcels

Envelopes – number of envelopes. Maximum of 9

TotalWeight – approximate total weight

DeclaredValue – declared value for insurance

CashRepayment – cash repayment (the sum returned to the sender in an envelope)

BankRepayment – bank repayment (the sum returned to the sender in the collector account)

OtherRepayment – other repayment

OpenPackage – open package

Serviceld: - 34 for totalweight 0 ≤ 31 kg ; 35 for 31 kg < totalweight ≤ 50 ; 50 for totalweight > 50 kg

PriceTableId – price id

ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient

SaturdayDelivery – Saturday delivery

Observations - observation
PackageContent – package content
CustomString – reference customer series
SenderReference1 – reference sender 1
RecipientReference1 – reference recipient 1
RecipientReference2 – reference recipient 2
InvoiceReference – reference invoice
CodPostal– postal code for delivery point

It returns:

Generated barcode

Example:

```
{
  "SenderClientId": null,
  "TertiaryClientId": null,
  "TertiaryLocationId": 0,
  "ConsumerReturnTypes": 2,
  "ReturnCodeExpirationDays": 10,
  "Sender": {
    "LocationId": 201266091,
  },
  "Recipient": {
    "LocationId": 0,
    "Name": "Gheorghita Vasile",
    "CountyId": 0,
    "CountyName": "Iasi",
    "LocalityId": 0,
    "LocalityName": "Iasi",
    "StreetId": 0,
    "StreetName": "Str 11 iunie",
    "BuildingNumber": "14",
    "AddressText": "Str 11 iunie nr 14",
    "ContactPerson": "Gheorghita Vasile",
    "PhoneNumber": "0740123123",
    "Email": "Vasile@gmail.com",
    "CodPostal": "123456",
    "CountryId": 0
  },
  "Parcels": 2,
  "Envelopes": 0,
  "TotalWeight": 25,
  "ServiceId": 34,
  "DeclaredValue": 0,
  "CashRepayment": 0,
  "BankRepayment": 0,
  "OtherRepayment": "string",
  "BarcodeRepayment": "string",
}
```



```

    "PaymentInstrumentId": 0,
    "PaymentInstrumentValue": 0,
    "HasTertReimbursement": false,
    "OpenPackage": true,
    "PriceTableId": 0,
    "ShipmentPayer": 1,
    "ShippingRepayment": 0,
    "SaturdayDelivery": true,
    "MorningDelivery": true,
    "Observations": "string",
    "PackageContent": "string",
    "CustomString": "",
    "ParcelCodes": [
        {
            "Code": "0",
            "Type": 1,
            "Weight": 25,
            "Length": 25,
            "Width": 25,
            "Height": 25,
            "ParcelContent": "briefcase"
        }
    ]
}

};

$result=$urgent->CallMethod('Awbs', $json, 'POST', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>POST Awb: </b>".$result['message']);
}

```

```
}  
else{  
    $data=$result['message'];  
    echo "<b class='good'>POST Awb: </b>".$data;  
}
```

9.4 Generating transport waybills with AWB range

The **Awbs** method, called through POST, is used to add a new AWB with a number assigned

You send:

Sender

SenderClientId – In all cases it is null. It's a facility created for those who want to create AWBs in the name of another customer.

TertiaryClientId – tertiary id, if the shipment is made in another customer's account

LocationId – pick up point id (sender warehouse)

Recipient - Consignee

Name – recipient name

CountyId – county id

CountyName: - county name

LocalityId – locality id

LocalityName - locality name

StreetId – street id

StreetName – street name // Optional

BuildingNumber – street number

AddressText – address

ContactPerson – contact person

PhoneNumber – contact phone number
Email – recipient e-mail address
CodPostal– postal code of the consignee

Parcels – number of parcels
Envelopes – number of envelopes. Maximum of 9
TotalWeight – approximate total weight
DeclaredValue – declared value for insurance
CashRepayment – cash repayment (the sum returned to the sender in an envelope)
BankRepayment – bank repayment (the sum returned to the sender in the collector account)
OtherRepayment – other repayment
OpenPackage – open package
ServiceId: - 34 for totalweight $0 \leq 31$ kg ; 35 for $31 \text{ kg} < \text{totalweight} \leq 50$; 36 for totalweight > 50 kg
PriceTableId – price id
ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient
SaturdayDelivery – Saturday delivery
Observations - observation
PackageContent – package content
CustomString – reference customer series
SenderReference1 – reference sender 1
RecipientReference1 – reference recipient 1
RecipientReference2 – reference recipient 2
InvoiceReference – reference invoice
CodPostal– postal code for delivery point

It returns:

Generated barcode

Example:

```
$json='{
  "Sender":{"LocationId":28244},
  "Recipient":{
    "Name":"Ion Popescu",
    "CountyId":33,
    "LocalityId":161,
    "StreetId":0,
    "StreetName":"Str. Ionescu",
    "BuildingNumber":"25",
    "AddressText":"Bl. 129, Sc. 3, Ap. 4",
    "ContactPerson":" Ion Popescu ",
    "PhoneNumber":"072111222",
    "CodPostal": "string"
    "Email":"a@a.com"
  },
  "Parcels": 1,
  "Envelopes": 0,
```

```

"TotalWeight": 1,
"ServiceId": 34,
"DeclaredValue": 0,
"CashRepayment": 0,
"BankRepayment": 0,
"OtherRepayment": "string",
"BarCodeRepayment": "string",
"PaymentInstrumentId": 0,
"PaymentInstrumentValue": 0,
"HasTertReimbursement": false,
"OpenPackage": true,
"PriceTableId": 0,
"ShipmentPayer": 1,
"ShippingRepayment": 0,
"SaturdayDelivery": true,
"MorningDelivery": true,
"Observations": "string",
"PackageContent": "string",
"CustomString": "PLMI10875236",
"BarCode": "PLMI10875236",
"ParcelCodes": [
  {
    "Code": "XXXI10875236",
    "Type": 1,
    "Weight": 1,
    "Length": 10,
    "Width": 10,
    "Height": 10,

  }
],
"ValidationDate": "2019-10-24T12:33:12.035Z",
"ShippingCost": {
  "BaseCost": 0,
  "ExtraKmCost": 0,
  "WeightCost": 0,
  "InsuranceCost": 0,
  "SpecialCost": 0,
  "RepaymentCost": 0,
  "Subtotal": 0,
  "Tax": 0,
  "GrandTotal": 0
},
"Status": "string",
"SenderReference1": "string",
"RecipientReference1": "string",
"RecipientReference2": "string",
"InvoiceReference": "string",
"Length": 0,
"Width": 0,

```

```
"Height": 0
}
```

```
$result=$urgent->CallMethod('Awbs', $json, 'POST', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>POST Awb: </b>".$result['message']);
}
else{
    $data=$result['message'];
    echo "<b class='good'>POST Awb: </b>".$data;
}
```

It returns: Main AWB

9.5 Deleting a transport note

The **Awbs** method deletes a transport note that has no checkpoint. It is a DELETE type method.

You send: barCode – the transport note number

It returns: true – if successful
 false – if the transport note doesn't exist or has a checkpoint

Example:

```
$resultDelete=$urgent->CallMethod('Awbs?barCode= 804713464', $json="", 'DELETE', $token);
if ($resultDelete ['status']!="200") {
    echo("<b class='bad'>Awb deleted : </b>".$resultDelete ['message']);
}
else{
    $data=$resultDelete ['message'];
}
```

9.6 Get routing details by address

The GetRoutingAddress method, called through POST, is used to get routing details by address.

You send:

```
{
  "TotalWeight": 1,
  "Sender": {
    "CountyName": "IASI",
    "LocalityId": 0,
    "LocalityName": "IASI",
    "ZipCode": "700259"
  },
  "Recipient": {
    "CountyName": "CONSTANTA",
    "LocalityName": "CONSTANTA",
    "AddressText": "PALAS 22",
    "ZipCode": "900320"
  }
}
```

It returns:

```
{
  "TransitPriority": "A",
  "TransitRoute": "Brasov",
  "TransitCodes": "500",
  "DeliveryRoute": "C2-Constanta\r900 - 01-45-04"
}
```

9.7 Listing the transport notes of a given period

The **AWBS/ GETBYDATE** method, called through GET, is used to return the list of AWBs of a certain period.

You send :

FromDate - start date in mm-dd-yyyy format
ToDate - end date in mm-dd-yyyy format
pageNumber – page number
itemsPerPage – number of AWBs per page

It returns:

A list of AWBs, containing the following information:

```
[
  {
    "SenderClientId": null,
    "TertiaryClientId": null,
```

```

"Sender": {
  "LocationId": 1005962049,
  "Name": "ECOM TEST",
  "CountyId": 0,
  "CountyName": "Ilfov",
  "LocalityId": 29445916,
  "LocalityName": "Tunari",
  "StreetId": 0,
  "StreetName": "",
  "BuildingNumber": "",
  "AddressText": "nr: 32; Sos centura nr 32",
  "ContactPerson": "Ionut Petraru",
  "PhoneNumber": "",
  "CodPostal": "string"
  "Email": ""
},
"Recipient": {
  "LocationId": 1,
  "Name": "test",
  "CountyId": 1,
  "CountyName": "Bucuresti",
  "LocalityId": 150,
  "LocalityName": "BUCURESTI",
  "StreetId": 0,
  "StreetName": "",
  "BuildingNumber": "",
  "AddressText": ", dsfggfhgfhg",
  "ContactPerson": "",
  "PhoneNumber": "",
  "CodPostal": "string"
  "Email": ""
},
"Parcels": 2,
"Envelopes": 0,

"TotalWeight": 344,
"ServiceId": 1,
"DeclaredValue": 0,
"CashRepayment": 0,
"BankRepayment": 0,
"OtherRepayment": "string",
"BarCodeRepayment": "string",
"PaymentInstrumentId": 0,
"PaymentInstrumentValue": 0,
"HasTertReimbursement": false,
"OpenPackage": true,
"PriceTableId": 0,
"ShipmentPayer": 1,
"ShippingRepayment": 0,

```



```

"SaturdayDelivery": true,
"MorningDelivery": true,
"Observations": "string",
"PackageContent": "string",
"CustomString": "URGC10875236",
"BarCode": "URGC10875236",
"ParcelCodes": [
{
  "Code": "URGC10875236",
  "Type": 1,
  "Weight":166.67,
  "Length":100,
  "Width":100,
  "Height":100,

}
],
"ValidationDate": "2019-10-24T12:33:12.035Z",
"ShippingCost": {
  "BaseCost": 0,
  "ExtraKmCost": 0,
  "WeightCost": 0,
  "InsuranceCost": 0,
  "SpecialCost": 0,
  "RepaymentCost": 0,
  "Subtotal": 0,
  "Tax": 0,
  "GrandTotal": 0
},
"Status": "string",
"SenderReference1": "string",
"RecipientReference1": "string",
"RecipientReference2": "string",
"InvoiceReference": "string",
"Length": 0,
"Width": 0,
"Height": 0
}

```

Example:

```

$resultGetByDate=$urgent->CallMethod('Awbs/GetByDate?FromDate=02-08-2016&ToDate=02-08-2016&pageNumber=1&itemsPerPage=100', $json="", 'GET', $token);

if ($resultGetByDate['status']!="200") {
    echo"<b class='bad'>GET GetByDate : </b>".$resultGetByDate['message'];
}
else {
    $dataGetByDate=$resultGetByDate['message'];
}

```

```

        echo "<b class='good'>GET GetByDate : </b>".$dataGetByDate;
    }

```

9.8 Listing transport notes information for an order

The **Awbs** method, called through GET, returns information about the sent notes.

You send:

barCode – the AWB
 or
 orderId – order number
 Important! Do not send both.

It returns:

```

[
{
  "SenderClientId": null,
  "TertiaryClientId": null,
  "Sender": {
    "LocationId": 1005962049,
    "Name": "ECOM TEST",
    "CountyId": 0,
    "CountyName": "Ilfov",
    "LocalityId": 29445916,
    "LocalityName": "Tunari",
    "StreetId": 0,
    "StreetName": "",
    "BuildingNumber": "",
    "AddressText": "nr: 32; Sos centura nr 32",
    "ContactPerson": "Ionut Petraru",
    "PhoneNumber": "",
    "CodPostal": "string"
    "Email": ""
  },
  "Recipient": {
    "LocationId": 1,
    "Name": "test",
    "CountyId": 1,
    "CountyName": "Bucuresti",
    "LocalityId": 150,
    "LocalityName": "BUCURESTI",
    "StreetId": 0,
    "StreetName": "",
    "BuildingNumber": "",
    "AddressText": " , dsgfggfhgfhg",
    "ContactPerson": "",
    "PhoneNumber": "",
    "CodPostal": "string"
  }
}
]

```

```

    "Email": "",
  },
  "Parcels": 0,
  "Envelopes": 1,
  "TotalWeight": 1,
  "ServiceId": null,
  "DeclaredValue": 0,
  "CashRepayment": 120,
  "BankRepayment": 0,
  "OtherRepayment": "",
  "PaymentInstrumentId": 0,
  "PaymentInstrumentValue": 0,
  "HasTertReimbursement": false,
  "OpenPackage": false,
  "PriceTableId": 17430,
  "ShipmentPayer": 3,
  "SaturdayDelivery": false,
  "MorningDelivery": false,
  "Observations": "",
  "PackageContent": "",
  "CustomString": "",
  "BarCode": "804523201",
  "ParcelCodes": null,
  "ValidationDate": "2016-02-08T06:38:06.267",
  "ShippingCost": null,
  "Status": "Tiparit",
  "SenderReference1": "",
  "RecipientReference1": "",
  "RecipientReference2": "",
  "InvoiceReference": ""

```

Example:

For an AWB:

```

$resultAwbDetails=$urgent->CallMethod('Awbs?barCode=804737910', $json="", 'GET',
$token);
if ($resultAwbDetails['status']!="200") {
    echo "<b class='bad'>GET awb details: </b>". $resultAwbDetails['message'];
}
else{
    $data=$resultAwbDetails['message'];
    echo "<b class='good'>GET awb details By AWB: </b>". $data;
}

```

For an order:

```

$resultAwbDetails=$urgent->CallMethod('Awbs?orderId=201243788', $json="", 'GET',
$token);
if ($resultAwbDetails['status']!="200") {
    echo "<b class='bad'>GET awb details: </b>". $resultAwbDetails['message'];
}

```

```

    }
    else{
        $data=$resultAwbDetails['message'];
        echo "<b class='good'>GET awb details By order ID : </b>". $data;
    }

```

9.9 Printing transport notes in PDF or HTML format

The **AwbDocuments** method, called through GET, is used to print the transport notes in PDF or HTML. You may specify either A4 or Label

You send :

barCode - a list (json) of AWBs to print
 type – PDF or HTML
 format - 0 - A4; 1 - Label 10x14
 printMainOnce - 0 or nothing - Main AWB will print twice; 1 - Main AWB will print once, 2 - Main AWB will print once format label 10x14

It returns:

The code in base64

Example:

```

header("Content-type:application/pdf");

$awb=array(804419419,804418863);
$jsonAwb=json_encode($awb);

$result=$urgent-
>CallMethod('AwbDocuments?barCodes='.$jsonAwb.'&type=PDF&format=1&printMainOnce=1'
,$json="", 'GET', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>Awb Documents: </b>". $result['message']);
}
else{
    $data=$result['message'];
    echo base64_decode($data);
}

```

9.10 Tracking the shipments with return or redirected AWB's

The **AwbTrace/WithRedirect**, method, called through GET is used for tracking shipments of return or redirected AWB's

You send :

barCode - a list of searched AWB's

It returns:

Information with the events . the list has the following information:

Code – AWB number
Type – package =1 sau envelope =0
MeasuredWeight - weight
VolumetricWeight – volumetric weight

ConfirmationName – person who confirmed the shipment
Observation – observations regarding the awb
ResponseCode – the return or redirected AWB

Event

Date – event date
Description – event description
LocalityName – locality name

Example:

```
$awbList=array(804115458, 804346669);  
$jsonAwb=json_encode($awbList);  
$resultTrace = $urgent->CallMethod('AwbTrace/WithRedirect?barCode='.$jsonAwb, $json="",  
'GET', $token);  
if ($resultTrace['status'] != "200") {  
    echo "<b class='bad'>GET ERROR Trace: </b>". $resultTrace['message'];  
}  
else{  
    $result = $resultTrace['message'];  
    echo "<b class='good'>GET Trace: </b>". $result;  
}
```

9.11 Listing returning AWB's

The **AwbRetur** method, called through GET is used for pulling up all of the AWB's the return to the customer in the specified date.

You send :

date - the date in the following format yyyy-mm-dd

It returns:

Awb – information regarding the AWB
Sender - Sender
LocationId – pick up point id

Name – sender name
CountyId – county id
CountyName – county name
LocalityId – locality id
LocalityName – locality name
StreetId – street id
StreetName – street name, exactly as found in the Cargus nomenclature
BuildingNumber – street number
AddressText – address
ContactPerson – contact person for the current order
PhoneNumber – contact phone number
Email – e-mail address

Recipient – Consignee
Name – recipient name
CountyId – county id
LocalityId – locality id
StreetId – street id
StreetName – street name // Optional
BuildingNumber – street number
AddressText – address
ContactPerson – contact person
PhoneNumber – contact phone number
Email – recipient e-mail address

Parcels – number of parcels
Envelopes – number of envelopes. Maximum of 9
TotalWeight – approximate total weight
DeclaredValue – declared value for insurance
CashRepayment – cash repayment (the sum returned to the sender in an envelope)
BankRepayment – bank repayment (the sum returned to the sender in the collector account)
OtherRepayment – other repayment
OpenPackage – open package
HasTertReimbursement – if true the reimbursement comes back to TertiaryClientId and it's obligatory
PriceTableId – price id
ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient
SaturdayDelivery – Saturday delivery
MorningDelivery – morning delivery
Observations - observations
PackageContent – package content
CustomString – reference customer series
SenderReference1 – sender reference 1
RecipientReference1 – recipient reference 1
RecipientReference2 – recipient reference 2
InvoiceReference – invoice reference

ParcelCodes – list that contains the main AWB and the secondary ones that are attached

Code – code of the envelope or parcel.

Type - envelope=1 or parcel=0

ValidationDate – date that it entered in the system

ShippingCost – details of the shipping cost

Status – shipping status

AwbRetur – details about the returning AWB

Sender - sender name

LocationId – pick up point id

Name – sender name

CountyId – county id

CountyName – county name

LocalityId – locality id

LocalityName – locality name

StreetId – street id

StreetName – street name, exactly as found in the Cargus nomenclature

BuildingNumber – street number

AddressText – address

ContactPerson – contact person for the current order

PhoneNumber – contact phone number

Email – e-mail address

Recipient – Consignee

LocationId – pick up pointid

Name – recipient name

CountyId – county id

LocalityId – locality id

StreetId – street id

StreetName – street name // Optional

BuildingNumber – street number

AddressText – address

ContactPerson – contact person

PhoneNumber – contact phone number

Email – recipient e-mail address

Parcels – number of parcels

Envelopes – number of envelopes. Maximum of 9

TotalWeight – approximate total weight

DeclaredValue – declared value for insurance

CashRepayment – cash repayment (the sum returned to the sender in an envelope)

BankRepayment – bank repayment (the sum returned to the sender in the collector account)

OtherRepayment – other repayment

OpenPackage – open package

HasTertReimbursement – if true the reimbursement comes back to TertiaryClientId and it's obligatory

PriceTableId – price id

ShipmentPayer – shipment payer. Send 1 for sender and 2 for recipient

SaturdayDelivery – Saturday delivery

MorningDelivery – morning delivery

Observations - observations

PackageContent – package content

CustomString – reference customer series

SenderReference1 – sender reference 1

RecipientReference1 – recipient reference 1

RecipientReference2 – recipient reference 2

InvoiceReference – invoice reference

ParcelCodes – list that contains the main AWB and the secondary ones that are attached

Code – code of the envelope or parcel.

Type - envelope=1 or parcel=0

ValidationDate – date that it entered in the system

ShippingCost – details cost of the shipping

Courier – courier

TimestampDeparture – date when the courier scans it

ClientObservation – observations for the return AWB

Example:

```
$result=$urgent->CallMethod('AwbRetur?data='.$Date, $json='', 'GET', $token);
if ($result['status']!="200")
{
    echo("<b class='bad'>POST Awb: </b>". $result['message']);
}
else
{
    $data=$result['message'];
    echo "<b class='good'>POST Awb: </b>". $data;
}
```

9.12 Check last event from a set interval

The **AwbTrace/GetDeltaEvents** method, called through GET is used for checking the status from a set interval .

You send :

FromDate - from date (format :mm-dd-yyyy)

ToDate - to date (format :mm-dd-yyyy)

It returns:

Date – date of creation of AWB

Barcode – AWB number

Sender – sender

Receiver – receiver

FromLocality – sender locality

ToLocality – receiver locality

CustomString – reference customer series

RepaymentDate – repayment date

RepaymentId – repayment id

RepaymentValue – repayment amount

DeductionDate – date of payment order

DeductionId – number of payment order

StatusExpression – detailed status

ConfirmationDate – confirmation date

ConfirmationPersonaName – confirmation name

Packages

Code – AWB number

Type – package =1 sau envelope =0

MeasuredWeight - weight

VolumetricWeight – volumetric weight

Events – Events

Date – date

EventId – id-ul evenimentului

Description – description of event

LocalityName – locality name where the event was added

Example:

```
$result=$urgent-
>CallMethod('AwbTrace/GetDeltaEvents?FromDate='.$FromDate.'&ToDate='.$ToDate,
$json='', 'GET', $token);
if ($result['status']!="200")
{
    echo("<b class='bad'>POST Awb: </b>". $result['message']);
}
else
{
    $data=$result['message'];
}
```

```

        echo "<b class='good'>POST Awb: </b>".$data;
    }

```

9.13 Display confirmation picture

The **AwbScan**, method, called through GET is used to pull up pictures for confirmation

You send :

barCode - AWB code

It returns:

Code in base64

Example:

```

$result=$urgent->CallMethod('AwbScan?barCodes='804419419, $json="", 'GET', $token);
if ($result['status']!="200") {
    echo("<b class='bad'>Awb Scan: </b>".$result['message']);
}
else{
    $data=$result['message'];
    header("Content-type:image");
    echo base64_decode($data);
}

```

10 Order management (courier request)

10.1 Launching or cancelling an order for a pick up point

The **Orders** method, called through PUT, validates or cancels an order from a pick up point.

You send:

LocationId – pick up point id – 0 for headquarters
 action – action id . if you send it, 0 cancels and 1 validates
 PickupStartDate – start date and hour for pick up
 PickupEndDate – end date and hour for pick up

It returns:

Order number

Example:

```
$resultPutOrder = $urgent-
>CallMethod('Orders?locationId=201008098&action=0&PickupStartDate=2016-02-16T12:16:15.827Z&PickupEndDate=2016-02-16T12:19:15.827Z',$json="", 'PUT', $token);
if ($resultPutOrder['status']!="200") {
    echo("<b class='bad'>PUT Order: </b>". $resultPutOrder['message']);
}
else{
    $dataPutOrder=$resultPutOrder['message'];
    echo "<b class='good'>PUT Order: </b>". $dataPutOrder;
}
```

10.2 Launching or cancelling all orders

The **Orders/PutAll** method validates or cancels all the orders, on all pick up points.

You send:

action – if you send, 0 cancels and 1 validates
PickupStartDate – start date and hour for pick up
PickupEndDate – end date and hour for pick up

It returns:

Order number

Example:

```
$resultPutOrder = $urgent->CallMethod('Orders/PutAll?action=1&PickupStartDate=2016-02-16T12:16:15.827Z&PickupEndDate=2016-02-16T12:19:15.827Z',$json="", 'PUT', $token);
if ($resultPutOrder['status']!="200") {
    echo("<b class='bad'>PUT Order: </b>". $resultPutOrder['message']);
}
else{
    $dataPutOrder=$resultPutOrder['message'];
    echo "<b class='good'>PUT Order: </b>". $dataPutOrder;
}
```

10.3 Listing orders information for a pick up point

The **Orders** method, called through GET, offers information about the orders from a specific pick up point.

You send:

LocationId – pick up point id – 0 for headquarters

status – order status – 0 current order / 1 validated order
pageNumber – number of pages displayed
itemsPerPage – number of orders per page

It returns:

An order list. An order contains the following information:

OrderId – order number
LocationId – pick up point id
PickUpSiteName – pick up point address
PickupStartDate – start date and hour for order pick up
PickupEndDate – end date and hour for order pick up
if the order status is 0 then the order generation date is displayed.
NoParcel – total number of parcels
NoEnvelop – total number of envelopes
TotalWeight – order total weight
NoAwb – order total number of AWBs
Observations – order observation
PackageContent – package content
CreationDate – date and hour of order generation
ValidationDate – date and hour of order shipping
ProcessedDate – date of processed order
OrdStatus – order status
AdresaExp – sender address
Email – this should be the e-mail of the pick up point
OrderType – order type (on which channel it has been generated)

Example:

```
$resultOrders = $urgent-  
>CallMethod('Orders?locationId=0&status=1&pageNumber=1&itemsPerPage=100', $json="",  
'GET', $token);  
  
if ($resultOrders['status'] != "200") {  
    echo("<b class='bad'>GET Order: </b>". $resultOrders['message']);  
}  
else{  
    $dataOrders=$resultOrders['message'];  
    echo "<b class='good'>GET Orders: </b>". $dataOrders;  
}
```

10.4 Listing order information for a given period

The **Orders/GetByDate** method is called through GET and offers information about the orders in a certain period.

You send:

FromDate – start date in yyyy-mm-dd format

ToDate - end date in yyyy-mm-dd format
pageNumber – number of page displayed
itemsPerPage – number of AWBs per page

It returns:

An order list. An order contains the following information:

OrderId – order number
LocationId – pick up point id
PickUpSiteName – pick up point address
PickupStartDate – start date and hour for order pick up
PickupEndDate - end date and hour of order pick up
 If the order has the status 0 then the order generation date is displayed
NoParcel – total number of parcels
NoEnvelop – total number of envelopes
TotalWeight – total weight of the shipment
NoAwb – total number of AWBs
Observations – order observation
PackageContent - parcel content
CreationDate – date and hour of order creation
ValidationDate – date and hour of order shipping
ProcessedDate - order processed date
OrdStatus – order status
AdresaExp – sender address
Email – this should be the pick up point e-mail address
OrderType – order type (on which channel it has been generated)

Example:

```
$resultOrdersGetByDate =$urgent->CallMethod('Orders/GetByDate?FromDate=2016-02-15&ToDate=2016-02-19&pageNumber=1&itemsPerPage=100', $json="", 'GET', $token);
```

```
if ($resultOrdersGetByDate ['status']!="200") {  
    echo "<b class='bad'>GET Result Orders ByDate :  
</b>". $resultOrdersGetByDate['message'];  
}  
else {  
    $dataOrdersGetByDate = $resultOrdersGetByDate['message'];  
    echo "<b class='good'>GET Result Orders ByDate: </b>". $dataOrdersGetByDate;  
}
```

10.5 Listing order information using its number

The **Orders/GetByOrderId** method is called through GET and offers information about the orders searched using its number

You send:

orderId – order number

It returns:

Information regarding that order :

OrderId – order number

LocationId – pick up point id

PickUpSiteName – pick up point address

PickupStartDate – start date and hour for order pick up

PickupEndDate - end date and hour of order pick up

If the order has the status 0 then the order generation date is displayed

NoParcel – total number of parcels

NoEnvelop – total number of envelopes

TotalWeight – total weight of the shipment

NoAwb – total number of AWBs

Observations – order observation

PackageContent - parcel content

CreationDate – date and hour of order creation

ValidationDate – date and hour of order shipping

ProcessedDate - order processed date

OrdStatus – order status

AdresaExp – sender address

Email – this should be the pick up point e-mail address

OrderType – order type (on which channel it has been generated)

Example:

```
$resultOrders = $urgent->CallMethod('Orders/GetByOrderId?orderId=201245248', $json="",  
'GET', $token);
```

```
if ($resultOrders['status'] != "200") {  
    echo("<b class='bad'>GET Order: </b>". $resultOrders['message']);  
}  
else{  
    $dataOrders=$resultOrders['message'];  
    echo "<b class='good'>GET Orders: </b>". $dataOrders;  
}
```

11 Tracking cash on delivery

The **CashAccount** method is used to display the information about repayment in collector account.

11.1 List cash on delivery from a set period of time

The **CashAccount/GetByDate** method is called through GET and pulls up information from a set period of time .

You send:

FromDate - start date in yyyy-mm-dd format
ToDate - end date in yyyy-mm-dd format
Token – identify the customer

It returns:

Date – emission date
BarCode - AWB code
Sender – sender
Receiver – receiver
FromLocality – sender locality
ToLocality – receiver locality
CustomString – reference customer series
RepaymentDate – repayment date
RepaymentId – repayment id
RepaymentValue – repayment amount
DeductionDate – date of payment order
DeductionId – number of payment order

Example:

```
$resultCashAccount=$Surgent->CallMethod('CashAccount/GetByDate?FromDate=2016-03-24&ToDate=2016-03-25', $json="", 'GET', $token);
```

```
if($resultCashAccount ['status']!="200") {  
    echo "<b class='bad'>GET CashAccount : </b>". $resultCashAccount['message'];  
}  
else{  
    $dataCashAccount =$resultCashAccount['message'];  
    echo "<b class='good'>GET Get Cash Account : </b>". $dataCashAccount;  
}
```

11.2 Listing refunds after a certain date

Metoda **CashAccount/GetByDeductionDate** method is called through GET and pulls up information payment orders from a specific date .

You send:

DeductionDate – date of payment order
Token identify the customer

It returns:

Date – emission date
BarCode - AWB code
Sender – sender
Receiver – receiver
FromLocality – sender locality
ToLocality – receiver locality
CustomString – reference customer series
RepaymentDate – repayment date
RepaymentId – repayment id
RepaymentValue – repayment amount
DeductionDate – date of payment order
DeductionId – number of payment order

Example:

```
$result=$urgent->CallMethod('CashAccount/GetByDeductionDate?DeductionDate=2016-03-29',$json="", 'GET', $token);

print_r($result);

if ($result['status']!="200") {
    echo "<b class='bad'>GET CashAccount?GetByDeductionDate: </b>". $result['message'];
}
else{
    $data=$result['message'];
    echo "<b class='good'>GET CashAccount?GetByDeductionDate: </b>". $data;
}
```

11.3 Refund listing according to a certain barcode

The **CashAccount** method is used to display the information about repayment in collector account.

You send:

Token – identify the customer
BarCode - AWB code

It returns:

Date – emission date
BarCode - AWB code
Sender – sender
Receiver – receiver

FromLocality – sender locality
ToLocality – receiver locality
CustomString – reference customer series
RepaymentDate – repayment date
RepaymentId – repayment id
RepaymentValue – repayment amount
DeductionDate – date of payment order
DeductionId – number of payment order

Example:

```
$resultCashAccount =$urgent->CallMethod('CashAccount?barCode=804373743', $json="", 'GET',  
$token);
```

```
if ($resultCashAccount ['status']!="200") {  
    echo "<b class='bad'>GET CashAccount : </b>". $resultCashAccount ['message'];  
}  
else{  
    $dataCashAccount =$resultCashAccount ['message'];  
    echo "<b class='good'>GET Get Cash Account : </b>". $dataCashAccount;  
}
```

12 Invoices

12.1 Invoices list

The **Invoices** method returns information about the invoices in a certain period.

You send :

FromDate - start date in yyyy-mm-dd format
ToDate - end date in yyyy-mm-dd format
pageNumber – number of page displayed
itemsPerPage – number of AWBs per page

It returns:

InvoiceId - 2109644734,
Date – emission date
DueDate – invoice date
Series – invoice series
Number – invoice number

Value – value without VAT
Total – total
Closed – closed invoice
Balance - balance
CurrencyId – currency

Example:

```
$resultInvoices=$urgent->CallMethod('Invoices?FromDate=2016-01-01&ToDate=2016-02-19&pageNumber=1&itemsPerPage=100', $json="", 'GET', $token);  
if($resultInvoices ['status']!="200") {  
    echo "<b class='bad'>GET Invoices : </b>". $resultInvoices['message'];  
} else{  
    $dataInvoices = $resultInvoices['message'];  
    echo "<b class='good'>GET Invoices : </b>". $dataInvoices;  
}
```

12.2 Printing invoices in PDF format

The **InvoiceDocuments** method is a GET type method and returns a string that must be decoded in base64.

You send :

InvoiceId - the invoice id returned by the Invoices method

It returns:

The code in base64

Example:

```
header("Content-type:application/pdf");  
$resultInvoiceDocuments = $urgent->CallMethod('InvoiceDocuments?InvoiceId=1010219190',  
$json="", 'GET', $token);  
if($resultInvoiceDocuments['status'] != "200") {  
    //echo "<b class='bad'>GET InvoiceDocuments :  
</b>". $resultInvoiceDocuments['message'];  
}  
else {  
    $dataInvoiceDocuments = $resultInvoiceDocuments['message'];  
    //echo "<b class='good'>GET InvoiceDocuments : </b>". $dataInvoiceDocuments;  
  
    echo base64_decode($dataInvoiceDocuments);  
}
```

13 Work flow for integration

The PickupLocations is called to add: PL1 lift point. Id returned idPL1.

1. You can use the Localities method to pick up the local id
 2. You can use the Streets method to get the Street id
 - Note that a working point has AutomaticEOD (end of day)
- Call Awbs to add awb. The sender uses idPL1. At this point you have an open command on idPL1.

The order closes when:

- - Call Orders with PUT for the idPL1 lift point with action = 1 to launch the command.
- or
- Touch AutomaticEOD to the hoist point

14 Implementation conditions for the multipiece service

The multipiese service doesn't allow:

- a taxable weight greater than 31 kg per piece;
- more than 15 pieces per shipment;
- a weight greater than 465 Kg for a shipment.

15 ANNEX

SERVICEID

id	old service name	new service name
1	Standard	Standard
34	Economic standard	Standard
35	Standard Plus	Standard 31+
36	Pallet Standard	Standard 50+
38	Easy collect standard	Click & Collect
39	Economic standard M	Standard
40	Economic Std. M Plus	Standard 31+
41	Export Standard	Standard

It is mandatory to declare the dimensions per parcel when generating AWBs, for all customers who have the services listed below included in their contract.

ServiceId: 34

Conditions:

- Delivery Type: Door to door
- Maximum weight: 31kg
- One piece per shipment is allowed
- Delivery and pick up by courier of envelopes and standard parcels
- Envelopes is maxim 1 kilo
- Conversion formula for volumetric weight: $L \times l \times H / 6.000$
- Chargeable weight: highest between volumetric and gravimetric weight
- Available for National and Local deliveries

ServiceId: 35

Conditions:

- Delivery Type: Door to door
- Maximum weight: 32 - 50 kg
- One piece per shipment is allowed
- Delivery and pick up by courier of standard parcels
- Conversion formula for volumetric weight: $L \times l \times H / 6.000$
- Chargeable weight: highest between volumetric and gravimetric weight
- Available for National and Local deliveries

I. Shipment consisting of a single parcel

1. ServiceId 39:

Conditions:

The parcel weight (Weight) and the total shipment weight (TotalWeight) must be less than or equal to 31 kg.

2. ServiceId 40:

Conditions:

- The parcel weight (Weight) must be greater than 31 kg, but less than or equal to 50 kg.
- The total shipment weight (TotalWeight) must be between 1 kg and 50 kg (inclusive).

3. ServiceId 36:

Conditions:

- The parcel weight (Weight) must be greater than or equal to 51 kg.
- The total shipment weight (TotalWeight) must be between 1 kg and 800 kg (inclusive).

II. Shipment consisting of multiple parcels (maximum 15 parcels)

1. ServiceId 36:

- Not valid for shipments consisting of multiple parcels.
- This service is only allowed for shipments with a single parcel.

2. ServiceId 39:

Conditions:

- The weight of each parcel (Weight) must be less than or equal to 31 kg.
- The total shipment weight (TotalWeight) must be between 1 kg and 465 kg (inclusive).

3. ServiceId 40:

Conditions:

- The weight of each parcel (Weight) must be less than or equal to 50 kg.
- The total shipment weight (TotalWeight) must be between 1 kg and 750 kg (inclusive).

Status: 0 – open order
1 – closed order

OrderType: 1 – online –generated on Webexpress
2 – by telephone
3 – external – generated by API
4 – pick up – generated by " Pick Up From Another Location" in Webexpress
5 – email- generated by e-mail
6 – predetermined –generated in the internal system every day