

# University of Tartu ICPC Team Notebook

## (2018-2019) March 22, 2019

1	crc.sh
2	2D geometry
3	3D geometry
4	Maxflow Complexity
5	Min Rotation of string
6	gcc ordered set, hashtable
7	PRNGs and Hash functions
8	Triangle centers
9	Seg-Seg intersection, halfplane intersection area
10	Convex polygon algorithms
11	Delaunay triangulation $\mathcal{O}(n \log n)$
12	Aho Corasick $\mathcal{O}( \alpha  \sum \text{len})$
13	Suffix automaton and tree $\mathcal{O}((n+q) \log( \alpha ))$
14	Dinic
15	Min Cost Max Flow with Cycle Cancelling $\mathcal{O}(\text{cap} \cdot nm)$
16	DMST $\mathcal{O}(E \log V)$
17	Bridges $\mathcal{O}(n)$
18	2-Sat $\mathcal{O}(n)$ and SCC $\mathcal{O}(n)$
19	Generic persistent compressed lazy segment tree
20	Templated HLD $\mathcal{O}(M(n) \log n)$ per query
21	Splay Tree + Link-Cut $\mathcal{O}(N \log N)$
22	Templated multi dimensional BIT $\mathcal{O}(\log(n)^{\text{dim}})$ per query

23	Treap $\mathcal{O}(\log n)$ per query	22
24	Radixsort 50M 64 bit integers as single array in 1 sec	23
25	FFT 5M length/sec	23
26	Fast mod mult, Rabbin Miller prime check, Pollard rho factorization $\mathcal{O}(\sqrt{p})$	25
27	Symmetric Submodular Functions; Queyrannes's algorithm	26
28	Berlekamp-Massey $\mathcal{O}(\mathcal{L}N)$	26

```

1 alias g++='g++ -g -Wall -Wshadow -Wconversion \
2   -fsanitize=undefined,address -DCDEBUG'           #.bashrc
3 alias a='setxkbmap us -option'                     #.bashrc
4 alias m='setxkbmap us -option caps:escape'         #.bashrc
5 alias ma='setxkbmap us -variant dvp -option caps:escape' #.bashrc
6 #settings
7 gsettings set
8   ↳ org.compiz.core:/org/compiz/profiles/Default/plugins/core/ hsize 4
9 gsettings set org.gnome.desktop.wm.preferences focus-mode 'sloppy'
10 set si cin #.vimrc
11 set ts=4 sw=4 noet #.vimrc
12 set cb=unnamedplus #.vimrc
13 (global-set-key (kbd "C-x <next>") 'other-window) #.emacs
14 (global-set-key (kbd "C-x <prior>") 'previous-multiframe-window)
15 (global-set-key (kbd "C-M-z") []ansi-term)
16 (global-linum-mode 1)
17 (column-number-mode 1)
18 (show-paren-mode 1)
19 (setq-default indent-tabs-mode nil) #.emacs
20 valgrind --vgdb-error=0 ./a <inp & #valgrind
21 gdb a #valgrind
22 target remote | vgdb #valgrind

```

```

1 crc.sh
2 #!/bin/envbash
3 for j in `seq 1 1 200`; do
4   sed '/^\s*$/d' $1 | head -$j | tr -d '[:space:]' | cksum | cut -f1
5   ↳ -d ' ' | tail -c 5 #whistespaces don't matter.
6 done #there shouldn't be any COMMENTS.
7 #copy lines being checked to separate file.
8 # $ ./crc.sh tmp.cpp | grep XXXX

```

## 2 2D geometry

Define  $\text{orient}(A, B, C) = \overline{AB} \times \overline{AC}$ . CCW iff  $> 0$ .  
Define  $\text{perp}((a, b)) = (-b, a)$ . The vectors are orthogonal.

For line  $ax + by = c$  def  $\bar{v} = (-b, a)$ .

Line through  $P$  and  $Q$  has  $\bar{v} = \overline{PQ}$  and  $c = \bar{v} \times P$ .

$\text{side}_l(P) = \bar{v}_l \times P - c_l$  sign determines which side  $P$  is on from  $l$ .

$\text{dist}_l(P) = \text{side}_l(P) / \|\bar{v}_l\|$  squared is integer.

Sorting points along a line: comparator is  $\bar{v} \cdot A < \bar{v} \cdot B$ .

Translating line by  $\bar{t}$ : new line has  $c' = c + \bar{v} \times \bar{t}$ .

Line intersection: is  $(c_l \bar{v}_m - c_m \bar{v}_l) / (\bar{v}_l \times \bar{v}_m)$ .

Project  $P$  onto  $l$ : is  $P - \text{perp}(v) \text{side}_l(P) / \|v\|^2$ .

Angle bisectors:  $\bar{v} = \bar{v}_l / \|\bar{v}_l\| + \bar{v}_m / \|\bar{v}_m\|$

$c = c_l / \|\bar{v}_l\| + c_m / \|\bar{v}_m\|$ .

$P$  is on segment  $AB$  iff  $\text{orient}(A, B, P) = 0$  and  $\overline{PA} \cdot \overline{PB} \leq 0$ .

Proper intersection of  $AB$  and  $CD$  exists iff  $\text{orient}(C, D, A)$  and  $\text{orient}(C, D, B)$  have opp. signs and  $\text{orient}(A, B, C)$  and  $\text{orient}(A, B, D)$  have opp. signs. Coordinates:

$$\frac{A \text{ orient}(C, D, B) - B \text{ orient}(C, D, A)}{\text{orient}(C, D, B) - \text{orient}(C, D, A)}.$$

Circumcircle center:

```
pt circumCenter(pt a, pt b, pt c) {
    b = b-a, c = c-a; // consider coordinates
    // relative to A
    assert(cross(b,c) != 0); // no circumcircle if
    // A,B,C aligned
    return a + perp(b*sq(c) - c*sq(b))/cross(b,c)
    /2;
```

Circle-line intersect:

```
int circleLine(pt o, double r, line l, pair<pt,
    pt> &out) {
    double h2 = r*r - l.sqDist(o);
    if (h2 >= 0) { // the line touches the circle
        pt p = l.proj(o); // point P
        pt h = l.v*sqrt(h2)/abs(l.v); // vector
        // paral to l, of len h
        out = {p-h, p+h};
    }
    return 1 + sgn(h2);
```

Circle-circle intersect:

```
int circleCircle(pt o1, double r1, pt o2, double
    r2, pair<pt,pt> &out) {
    pt d=o2-o1; double d2=sq(d);
```

```
if (d2 == 0) {assert(r1 != r2); return 0;} //
    // concentric circles
    double pd = (d2 + r1*r1 - r2*r2)/2; // = |O_1P
    // | * d
    double h2 = r1*r1 - pd*pd/d2; // = h^2
    if (h2 >= 0) {
        pt p = o1 + d*pd/d2, h = perp(d)*sqrt(h2/d2)
        ;
        out = {p-h, p+h};}
    return 1 + sgn(h2);
```

Tangent lines:

```
int tangents(pt o1, double r1, pt o2, double r2,
    bool inner, vector<pair<pt,pt>> &out) {
    if (inner) r2 = -r2;
    pt d = o2-o1;
    double dr = r1-r2, d2 = sq(d), h2 = d2-dr*dr;
    if (d2 == 0 || h2 < 0) {assert(h2 != 0);
        return 0;}
    for (double sign : {-1,1}) {
        pt v = (d*dr + perp(d)*sqrt(h2)*sign)/d2;
        out.push_back({o1 + v*r1, o2 + v*r2});}
    return 1 + (h2 > 0);
```

## 3 3D geometry

$\text{orient}(P, Q, R, S) = (\overline{PQ} \times \overline{PR}) \cdot \overline{PS}$ .

$S$  above  $PQR$  iff  $> 0$ .

For plane  $ax + by + cz = d$  def  $\bar{n} = (a, b, c)$ .

Line with normal  $\bar{n}$  through point  $P$  has  $d = \bar{n} \cdot P$ .

$\text{side}_\Pi(P) = \bar{n} \cdot P - d$  sign determines side from  $\Pi$ .

$\text{dist}_\Pi(P) = \text{side}_\Pi(P) / \|\bar{n}\|$ .

Translating plane by  $\bar{t}$  makes  $d' = d + \bar{n} \cdot \bar{t}$ .

Plane-plane intersection of has direction  $\bar{n}_1 \times \bar{n}_2$  and goes

through  $((d_1 \bar{n}_2 - d_2 \bar{n}_1) \times \bar{d}) / \|\bar{d}\|^2$ .

Line-line distance:

```
double dist(line3d l1, line3d l2) {
    p3 n = l1.d*l2.d;
    if (n == zero) // parallel
        return l1.dist(l2.o);
    return abs((l2.o-l1.o)|n)/abs(n);
```

Spherical to Cartesian:

$(r \cos \varphi \cos \lambda, r \cos \varphi \sin \lambda, r \sin \varphi)$ .

Sphere-line intersection:

```
int sphereLine(p3 o, double r, line3d l, pair<p3
    ,p3> &out) {
    double h2 = r*r - l.sqDist(o);
    if (h2 < 0) return 0; // the line doesn't
    // touch the sphere
    p3 p = l.proj(o); // point P
    p3 h = l.d*sqrt(h2)/abs(l.d); // vector
    // parallel to l, of length h
    out = {p-h, p+h};
```

```
return 1 + (h2 > 0);
```

Great-circle distance between points  $A$  and  $B$  is  $r \angle AOB$ .

Spherical segment intersection:

```
bool properInter(p3 a, p3 b, p3 c, p3 d, p3 &out
    ) {
    p3 ab = a*b, cd = c*d; // normals of planes
    // OAB and OCD
    int oa = sgn(cd|a),
        ob = sgn(cd|b),
        oc = sgn(ab|c),
        od = sgn(ab|d);
    out = ab*cd*od; // four multiplications =>
    // careful with overflow !
    return (oa != ob && oc != od && oa != oc);
}
bool onSphSegment(p3 a, p3 b, p3 p) {
    p3 n = a*b;
    if (n == zero)
        return a*p == zero && (a|p) > 0;
    return (n|p) == 0 && (n|a*p) >= 0 && (n|b*p)
        <= 0;
}
struct directionSet : vector<p3> {
    using vector::vector; // import constructors
    void insert(p3 p) {
        for (p3 q : *this) if (p*q == zero) return;
        push_back(p);
    }
};
directionSet intersSph(p3 a, p3 b, p3 c, p3 d) {
    assert(validSegment(a, b) && validSegment(c, d
        ));
    p3 out;
    if (properInter(a, b, c, d, out)) return {out
        };
    directionSet s;
    if (onSphSegment(c, d, a)) s.insert(a);
    if (onSphSegment(c, d, b)) s.insert(b);
    if (onSphSegment(a, b, c)) s.insert(c);
    if (onSphSegment(a, b, d)) s.insert(d);
    return s;
}
```

Angle between spherical segments  $AB$  and  $AC$  is angle between  $A \times B$  and  $A \times C$ .

Oriented angle: subtract from  $2\pi$  if mixed product is negative.

Area of a spherical polygon:

$$r^2 [\text{sum of interior angles} - (n - 2)\pi].$$

## 4 Maxflow Complexity

$\mathcal{O}(V^2E)$  – Dinic

$\Theta(VE \log U)$  – Capacity scaling

$\Theta(\text{flow}E)$  – Small flow

$\Theta(\min\{V^{\frac{2}{3}}, E^{\frac{1}{2}}\}E)$  – Unitary capacities

$\Theta(\sqrt{V}E)$  – Each vertex other than S,T has only a single incoming unitary edge or outgoing one (bipartite matching)

$\Theta(\text{flow}E \log V)$  – Min-cost-max flow

## 5 Min Rotation of string

```
int a=0, N=s.size();
s += s;
ran(b,0,N){
    ran(i,0,N) {
        if (a+i == b || s[a+i] < s[b+i]) {
            b += max(0, i-1);
            break;
        }
        if (s[a+i] > s[b+i]) {
            a = b;
            break;
        }
    }
}
return a;
```

## 6 gcc ordered set, hashtable

```

1 #define DEBUG(...) cerr << __VA_ARGS__ << endl;
2 #ifndef CDEBUG
3 #undef DEBUG
4 #define DEBUG(...) ((void)0);
5 #define NDEBUG
6 #endif
7 #define ran(i, a, b) for (auto i = (a); i < (b); i++)
8 #include <bits/stdc++.h>
9 typedef long long ll; #1736
10 typedef long double ld;
11 using namespace std; #1386
12 #pragma GCC optimize("Ofast") // better vectorization
13 #pragma GCC target("avx,avx2") // double vectorized performance
14 #include <bits/extc++.h>
15 using namespace __gnu_pbds;
16 template <typename T, typename U>
17 using hashmap = gp_hash_table<T, U>; // dumb, 3x faster than stl
18 template <typename T> #1392
19 using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
20   tree_order_statistics_node_update>; #3907
21 int main() {
22   ordered_set<int> cur;
23   cur.insert(1);
24   cur.insert(3);
25   cout << cur.order_of_key(2)
26     << endl; // the number of elements in the set less than 2
27   cout << *cur.find_by_order(0)
28     << endl; // the 0-th smallest number in the set(0-based)
29   cout << *cur.find_by_order(1)
30     << endl; // the 1-th smallest number in the set(0-based)
31   ordered_set<int> oth;
32   oth.insert(5); // to join: cur < oth
33   cur.join(oth); // cur = 1, 3, 5, oth =
34   cur.split(1, oth); // cur = 1, oth = 3, 5
35   hashmap<int, int> h({}, {}, {}, {}, {1 << 16});
36 }

```

## 7 PRNGs and Hash functions

```

1 mt19937 gen;
2 uint64_t rand64() { return gen() ^ ((uint64_t)gen() << 32); } #4798
3 uint64_t rand64() {
4   static uint64_t x = 1; //x != 0
5   x ^= x >> 12;
6   x ^= x << 25;
7   x ^= x >> 27; #6087
8   return x * 0x2545f4914f6cdd1d; // can remove mult
9 } #9038
10 uint64_t mix(uint64_t x){ //can replace constant with variable
11   uint64_t mem[2] = { x, 0xdeadbeeffeebdaedull };
12   asm volatile (
13     "pxor %%xmm0, %%xmm0;"

```

```

14     "movdqa (%0), %%xmm1;" #2024
15     "aesenc %%xmm0, %%xmm1;"
16     "movdqa %%xmm1, (%0);"
17     :
18     : "r" (&mem[0])
19     : "memory" #6956
20   );
21   return mem[0]; // use both slots for 128 bit hash
22 }
23 uint64_t mix(uint64_t x) { //x != 0
24   x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
25   x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
26   x = x ^ (x >> 31);
27   return x; #7126
28 } #1575
29 uint64_t unmix(uint64_t x) {
30   x = (x ^ (x >> 31) ^ (x >> 62)) * 0x319642b2d24d8ec3;
31   x = (x ^ (x >> 27) ^ (x >> 54)) * 0x96de1b173f119089;
32   x = x ^ (x >> 30) ^ (x >> 60);
33   return x; #4780
34 } #2094
35 uint64_t combine(uint64_t x, uint64_t y) {
36   if (y < x) swap(x, y); // remove for ord
37   return mix(mix(x) + y);
38 } #1466

```

## 8 Triangle centers

```

1 const double min_delta = 1e-13;
2 const double coord_max = 1e6;
3 typedef complex<double> point;
4 point A, B, C; // vertices of the triangle
5 bool collinear() { #0823
6   double min_diff = min(abs(A - B), min(abs(A - C), abs(B - C)));
7   if (min_diff < coord_max * min_delta) return true;
8   point sp = (B - A) / (C - A);
9   double ang = M_PI / 2 - abs(abs(arg(sp)) - M_PI / 2);
10  return ang < min_delta; // positive angle with the real line
11 } #8446 #8446
12 point circum_center() {
13   if (collinear()) return point(NAN, NAN);
14   // squared lengths of sides
15   double a2 = norm(B - C);
16   double b2 = norm(A - C);
17   double c2 = norm(A - B); #6715
18   // barycentric coordinates of the circumcenter
19   double c_A = a2 * (b2 + c2 - a2); // sin(2 * alpha) works also
20   double c_B = b2 * (a2 + c2 - b2);
21   double c_C = c2 * (a2 + b2 - c2);
22   double sum = c_A + c_B + c_C;
23   c_A /= sum; #9407
24   c_B /= sum;
25   c_C /= sum;

```

```

26 return c_A * A + c_B * B + c_C * C; // cartesian
27 }
28 point centroid() { // center of mass
29 return (A + B + C) / 3.0;
30 }
31 point ortho_center() { // euler line
32 point O = circum_center();
33 return O + 3.0 * (centroid() - O);
34 };
35 point nine_point_circle_center() { // euler line
36 point O = circum_center();
37 return O + 1.5 * (centroid() - O);
38 };
39 point in_center() {
40 if (collinear()) return point(NAN, NAN);
41 double a = abs(B - C); // side lengths
42 double b = abs(A - C);
43 double c = abs(A - B);
44 // trilinear coordinates are (1,1,1)
45 double sum = a + b + c;
46 a /= sum;
47 b /= sum;
48 c /= sum; // barycentric
49 return a * A + b * B + c * C; // cartesian
50 }

```

#6856  
#3895  
#8193  
%3031  
#5954  
#4892

## 9 Seg-Seg intersection, halfplane intersection area

```

1 struct Seg {
2 Vec a, b;
3 Vec d() { return b - a; }
4 };
5 Vec intersection(Seg l, Seg r) {
6 Vec dl = l.d(), dr = r.d();
7 if (cross(dl, dr) == 0) return {nanl(""), nanl("")};
8 double h = cross(dr, l.a - r.a) / len(dr);
9 double dh = cross(dr, dl) / len(dr);
10 return l.a + dl * (h / -dh);
11 }
12 // Returns the area bounded by halfplanes
13 double calc_area(const vector<Seg>& lines) {
14 double lb = -HUGE_VAL, ub = HUGE_VAL;
15 vector<Seg> slines[2];
16 for (auto line : lines) {
17 if (line.b.y == line.a.y) {
18 if (line.a.x < line.b.x) {
19 lb = max(lb, line.a.y);
20 } else {
21 ub = min(ub, line.a.y);
22 }
23 } else if (line.a.y < line.b.y) {
24 slines[1].push_back(line);
25 } else {

```

#6327  
#8893  
#1804  
#6288

```

26 slines[0].push_back({line.b, line.a});
27 }
28 }
29 ran(i, 0, 2) {
30 sort(slines[i].begin(), slines[i].end(), [&](Seg l, Seg r) {
31 if (cross(l.d(), r.d()) == 0)
32 return normal(l.d()) * l.a > normal(r.d()) * r.a;
33 return (1 - 2 * i) * cross(l.d(), r.d()) < 0;
34 });
35 }
36 // Now find the application area of the lines and clean up redundant
37 // ones
38 vector<double> ap_s[2];
39 ran(side, 0, 2) {
40 vector<double>& apply = ap_s[side];
41 vector<Seg> clines;
42 for (auto line : slines[side]) {
43 while (clines.size() > 0) {
44 Seg other = clines.back();
45 if (cross(line.d(), other.d()) != 0) {
46 double start = intersection(line, other).y;
47 if (start > apply.back()) break;
48 }
49 clines.pop_back();
50 apply.pop_back();
51 }
52 if (clines.size() == 0) {
53 apply.push_back(-HUGE_VAL);
54 } else {
55 apply.push_back(intersection(line, clines.back()).y);
56 }
57 clines.push_back(line);
58 }
59 slines[side] = clines;
60 }
61 ap_s[0].push_back(HUGE_VALL);
62 ap_s[1].push_back(HUGE_VALL);
63 double result = 0;
64 {
65 double lb = -HUGE_VALL, ub;
66 for (int i = 0, j = 0;
67 i < (int)slines[0].size() && j < (int)slines[1].size();
68 lb = ub) {
69 ub = min(ap_s[0][i + 1], ap_s[1][j + 1]);
70 double alb = lb, aub = ub;
71 Seg l[2] = {slines[0][i], slines[1][j]};
72 if (cross(l[1].d(), l[0].d()) > 0) {
73 alb = max(alb, intersection(l[0], l[1]).y);
74 } else if (cross(l[1].d(), l[0].d()) < 0) {
75 aub = min(aub, intersection(l[0], l[1]).y);
76 }

```

#3607  
#4919  
#9949  
#3099  
#7856  
#0868  
#8545  
#3234  
#4531  
#2627

```

77     alb = max(alb, lb);
78     aub = min(aub, ub);
79     aub = max(aub, alb);
80     ran(k, 0, 2) {
81         double x1 =
82             l[0].a.x + (alb - l[0].a.y) / l[0].d().y * l[0].d().x;
83         double x2 =
84             l[0].a.x + (aub - l[0].a.y) / l[0].d().y * l[0].d().x;
85         result += (-1 + 2 * k) * (aub - alb) * (x1 + x2) / 2;
86     }
87     if (ap_s[0][i + 1] < ap_s[1][j + 1]) {
88         i++;
89     } else {
90         j++;
91     }
92 }
93 }
94 return result;
95 }

```

#8493

#9267

#3074

%0513

## 10 Convex polygon algorithms

```

1 typedef pair<int, int> Vec;
2 typedef pair<Vec, Vec> Seg;
3 typedef vector<Seg>::iterator SegIt;
4 #define F first
5 #define S second
6 #define MP(x, y) make_pair(x, y)
7 Vec sub(const Vec &v1, const Vec &v2) {
8     return MP(v1.F - v2.F, v1.S - v2.S);
9 }
10 ll dot(const Vec &v1, const Vec &v2) {
11     return (ll)v1.F * v2.F + (ll)v1.S * v2.S;
12 }
13 ll cross(const Vec &v1, const Vec &v2) {
14     return (ll)v1.F * v2.S - (ll)v2.F * v1.S;
15 }
16 ll dist_sq(const Vec &p1, const Vec &p2) {
17     return (ll)(p2.F - p1.F) * (p2.F - p1.F) +
18         (ll)(p2.S - p1.S) * (p2.S - p1.S);
19 }
20 struct Point;
21 multiset<Point>::iterator end_node;
22 struct Point {
23     Vec p;
24     typename multiset<Point>::iterator get_it() const {
25         tuple<void*> tmp = {(void*)this - 32}; // gcc rb_tree dependent
26         return *(multiset<Point>::iterator *)(&tmp);
27     }
28     bool operator<(const Point &rhs) const {
29         return (p.F < rhs.p.F); // sort by x
30     }
31     bool operator<(const Vec &q) const {

```

#7360

#9034

#3379

%0923

#7198

#2890

```

32     auto nxt = next(get_it());
33     if (nxt == end_node) return 0; // nxt == end()
34     return q.S * dot(p, {q.F, 1}) <
35         q.S * dot(nxt->p, {q.F, 1}); // convex hull trick
36 }
37 };
38 template <int part> // 1 = upper, -1 = lower
39 struct HullDynamic : public multiset<Point, less<>> {
40     bool bad(iterator y) {
41         if (y == begin()) return 0;
42         auto x = prev(y);
43         auto z = next(y);
44         if (z == end()) return y->p.F == x->p.F && y->p.S <= x->p.S;
45         return part * cross(sub(y->p, x->p), sub(y->p, z->p)) <= 0;
46     }
47     void insert_point(int m, int b) { // O(log(N))
48         auto y = insert({m, b});
49         if (bad(y)) {
50             erase(y);
51             return;
52         }
53         while (next(y) != end() && bad(next(y))) erase(next(y));
54         while (y != begin() && bad(prev(y))) erase(prev(y));
55     }
56     ll eval(int x) { // O(log(N)) upper maximize dot(x, 1, v)
57         end_node = end(); // lower minimize dot(x, 1, v)
58         auto it = lower_bound((Vec){x, part});
59         return (ll)it->p.F * x + it->p.S;
60     }
61 };
62 struct Hull {
63     vector<Seg> hull;
64     SegIt up_beg;
65     template <typename It>
66     void extend(It beg, It end) { // O(n)
67         vector<Vec> r;
68         for (auto it = beg; it != end; ++it) {
69             if (r.empty() || *it != r.back()) {
70                 while (r.size() >= 2) {
71                     int n = r.size();
72                     Vec v1 = {r[n - 1].F - r[n - 2].F, r[n - 1].S - r[n - 2].S};
73                     Vec v2 = {it->F - r[n - 2].F, it->S - r[n - 2].S};
74                     if (cross(v1, v2) > 0) break;
75                     r.pop_back();
76                 }
77                 r.push_back(*it);
78             }
79         }
80         ran(i, 0, (int)r.size() - 1) hull.emplace_back(r[i], r[i + 1]);
81     }
82     Hull(vector<Vec> &vert) { // at least 2 distinct points

```

#9972

#5204

#5415

#1418

#4908

%9769

#4033

#3588

#6639

```

83  sort(ver.begin(), ver.end()); // O(n log(n))
84  extend(ver.begin(), ver.end()); #6560
85  int diff = hull.size();
86  extend(ver.rbegin(), ver.rend());
87  up_beg = hull.begin() + diff;
88  } #0722
89  bool contains(Vec p) { // O(log(n))
90  if (p < hull.front().F || p > up_beg->F) return false;
91  {
92  auto it_low = lower_bound(
93  hull.begin(), up_beg, MP(MP(p.F, (int)-2e9), MP(0, 0)));
94  if (it_low != hull.begin()) --it_low; #3373
95  Vec a = {it_low->S.F - it_low->F.F, it_low->S.S - it_low->F.S};
96  Vec b = {p.F - it_low->F.F, p.S - it_low->F.S};
97  if (cross(a, b) < 0) // < 0 is inclusive, <=0 is exclusive
98  return false;
99  } #2197
100 {
101 auto it_up = lower_bound(hull.rbegin(),
102 hull.rbegin() + (hull.end() - up_beg),
103 MP(MP(p.F, (int)2e9), MP(0, 0)));
104 if (it_up - hull.rbegin() == hull.end() - up_beg) --it_up;
105 Vec a = {it_up->F.F - it_up->S.F, it_up->F.S - it_up->S.S};
106 Vec b = {p.F - it_up->S.F, p.S - it_up->S.S};
107 if (cross(a, b) > 0) // > 0 is inclusive, >=0 is exclusive #7227
108 return false;
109 }
110 return true; #1826
111 }
112 // The function can have only one local min and max
113 // and may be constant only at min and max.
114 template <typename T>
115 SegIt max(function<T(Seg &)> f) { // O(log(n))
116 auto l = hull.begin();
117 auto r = hull.end();
118 SegIt b = hull.end(); #8566
119 T b_v;
120 while (r - l > 2) {
121 auto m = l + (r - l) / 2;
122 T l_v = f(*l);
123 T l_n_v = f(*(l + 1)); #3586
124 T m_v = f(*m);
125 T m_n_v = f(*(m + 1));
126 if (b == hull.end() || l_v > b_v) {
127 b = l; // If max is at l we may remove it from the range. #7332
128 b_v = l_v;
129 }
130 if (l_n_v > l_v) {
131 if (m_v < l_v) {
132 r = m;
133 } else { #7279

```

```

134 if (m_n_v > m_v) {
135 l = m + 1;
136 } else {
137 r = m + 1;
138 }
139 }
140 } else {
141 if (m_v < l_v) {
142 l = m + 1;
143 } else { #7311
144 if (m_n_v > m_v) {
145 l = m + 1;
146 } else {
147 r = m + 1;
148 }
149 }
150 }
151 }
152 T l_v = f(*l);
153 if (b == hull.end() || l_v > b_v) { #9864
154 b = l;
155 b_v = l_v;
156 }
157 if (r - l > 1) {
158 T l_n_v = f(*(l + 1));
159 if (b == hull.end() || l_n_v > b_v) { #5972
160 b = l + 1;
161 b_v = l_n_v;
162 }
163 }
164 return b; #9086
165 } #9504
166 SegIt closest(Vec p) { // p can't be internal(can be on border),
167 // hull must have atleast 3 points
168 Seg &ref_p = hull.front(); // O(log(n))
169 return max(function<double(Seg &)>(
170 [&p, &ref_p](
171 Seg &seg) { // accuracy of used type should be coord-2 #0134
172 if (p == seg.F) return 10 - M_PI;
173 Vec v1 = {seg.S.F - seg.F.F, seg.S.S - seg.F.S};
174 Vec v2 = {p.F - seg.F.F, p.S - seg.F.S};
175 ll c_p = cross(v1, v2);
176 if (c_p > 0) { // order the backside by angle
177 Vec v1 = {ref_p.F.F - p.F, ref_p.F.S - p.S};
178 Vec v2 = {seg.F.F - p.F, seg.F.S - p.S};
179 ll d_p = dot(v1, v2); #5063
180 ll c_p = cross(v2, v1);
181 return atan2(c_p, d_p) / 2;
182 }
183 ll d_p = dot(v1, v2);
184 double res = atan2(d_p, c_p); #0469

```

```

185     if (d_p <= 0 && res > 0) res = -M_PI;
186     if (res > 0) {
187         res += 20;
188     } else {
189         res = 10 - res;
190     }
191     return res;
192 }));
193 }
194 template <int DIRECTION> // 1 or -1
195 Vec tan_point(Vec p) { // can't be internal or on border
196     // -1 iff CCW rotation of ray from p to res takes it away from
197     // polygon?
198     Seg &ref_p = hull.front(); // O(log(n))
199     auto best_seg = max(function<double(Seg &)>(
200         [&p, &ref_p](
201             Seg &seg) { // accuracy of used type should be coord^2
202                 Vec v1 = {ref_p.F.F - p.F, ref_p.F.S - p.S};
203                 Vec v2 = {seg.F.F - p.F, seg.F.S - p.S};
204                 ll d_p = dot(v1, v2);
205                 ll c_p = DIRECTION * cross(v2, v1);
206                 return atan2(c_p, d_p); // order by signed angle
207             }));
208     return best_seg->F;
209 }
210 SegIt max_in_dir(Vec v) { // first is the ans. O(log(n))
211     return max(
212         function<ll(Seg &)>([&v](Seg &seg) { return dot(v, seg.F); }));
213 }
214 pair<SegIt, SegIt> intersections(Seg l) { // O(log(n))
215     int x = l.S.F - l.F.F;
216     int y = l.S.S - l.F.S;
217     Vec dir = {-y, x};
218     auto it_max = max_in_dir(dir);
219     auto it_min = max_in_dir(MP(y, -x));
220     ll opt_val = dot(dir, l.F);
221     if (dot(dir, it_max->F) < opt_val ||
222         dot(dir, it_min->F) > opt_val)
223         return MP(hull.end(), hull.end());
224     SegIt it_r1, it_r2;
225     function<bool(const Seg &, const Seg &)> inc_c(
226         [&dir](const Seg &lft, const Seg &rgt) {
227             return dot(dir, lft.F) < dot(dir, rgt.F);
228         });
229     function<bool(const Seg &, const Seg &)> dec_c(
230         [&dir](const Seg &lft, const Seg &rgt) {
231             return dot(dir, lft.F) > dot(dir, rgt.F);
232         });
233     if (it_min <= it_max) {
234         it_r1 = upper_bound(it_min, it_max + 1, l, inc_c) - 1;
235         if (dot(dir, hull.front().F) >= opt_val) {

```

#7417

%8283

#5209

#9762

%5037

%9596

#4740

#0276

#1828

#8337

```

236     it_r2 = upper_bound(hull.begin(), it_min + 1, l, dec_c) - 1;
237 } else {
238     it_r2 = upper_bound(it_max, hull.end(), l, dec_c) - 1;
239 }
240 } else {
241     it_r1 = upper_bound(it_max, it_min + 1, l, dec_c) - 1;
242     if (dot(dir, hull.front().F) <= opt_val) {
243         it_r2 = upper_bound(hull.begin(), it_max + 1, l, inc_c) - 1;
244     } else {
245         it_r2 = upper_bound(it_min, hull.end(), l, inc_c) - 1;
246     }
247 }
248 return MP(it_r1, it_r2);
249 }
250 Seg diameter() { // O(n)
251     Seg res;
252     ll dia_sq = 0;
253     auto it1 = hull.begin();
254     auto it2 = up_beg;
255     Vec v1 = {hull.back().S.F - hull.back().F.F,
256             hull.back().S.S - hull.back().F.S};
257     while (it2 != hull.begin()) {
258         Vec v2 = {(it2 - 1)->S.F - (it2 - 1)->F.F,
259                 (it2 - 1)->S.S - (it2 - 1)->F.S};
260         if (cross(v1, v2) > 0) break;
261         --it2;
262     }
263     while (it2 != hull.end()) { // check all antipodal pairs
264         if (dist_sq(it1->F, it2->F) > dia_sq) {
265             res = {it1->F, it2->F};
266             dia_sq = dist_sq(res.F, res.S);
267         }
268         Vec v1 = {it1->S.F - it1->F.F, it1->S.S - it1->F.S};
269         Vec v2 = {it2->S.F - it2->F.F, it2->S.S - it2->F.S};
270         if (cross(v1, v2) == 0) {
271             if (dist_sq(it1->S, it2->F) > dia_sq) {
272                 res = {it1->S, it2->F};
273                 dia_sq = dist_sq(res.F, res.S);
274             }
275             if (dist_sq(it1->F, it2->S) > dia_sq) {
276                 res = {it1->F, it2->S};
277                 dia_sq = dist_sq(res.F, res.S);
278             } // report cross pairs at parallel lines.
279             ++it1;
280             ++it2;
281         } else if (cross(v1, v2) < 0) {
282             ++it1;
283         } else {
284             ++it2;
285         }
286     }

```

#1848

#3840

#5268

%5268

#2632

#5150

#1246

#9381

#7011

#5626

#4406



```

287     return res;
288 }
289 };                                     %9383

11 Delaunay triangulation  $\mathcal{O}(n \log n)$ 
1 const int max_co = (1 << 28) - 5;
2 struct Vec {
3     int x, y;
4     bool operator==(const Vec &oth) { return x == oth.x && y == oth.y; }
5     bool operator!=(const Vec &oth) { return !operator==(oth); }
6     Vec operator-(const Vec &oth) { return {x - oth.x, y - oth.y}; }
7 };                                     #2919
8 ll cross(Vec a, Vec b) { return (ll)a.x * b.y - (ll)a.y * b.x; }
9 ll dot(Vec a, Vec b) { return (ll)a.x * b.x + (ll)a.y * b.y; }
10 struct Edge {
11     Vec tar;
12     Edge *nxt;
13     Edge *inv = NULL;
14     Edge *rep = NULL;
15     bool vis = false;
16 };
17 struct Seg {
18     Vec a, b;
19     bool operator==(const Seg &oth) { return a == oth.a && b == oth.b; }
20     bool operator!=(const Seg &oth) { return !operator==(oth); }
21 };
22 ll orient(Vec a, Vec b, Vec c) {
23     return (ll)a.x * (b.y - c.y) + (ll)b.x * (c.y - a.y) +
24         (ll)c.x * (a.y - b.y);
25 }                                     %6334
26 bool in_c_circle(Vec *arr, Vec d) {
27     if (cross(arr[1] - arr[0], arr[2] - arr[0]) == 0)
28         return true; // degenerate
29     ll m[3][3];
30     ran(i, 0, 3) {
31         m[i][0] = arr[i].x - d.x;
32         m[i][1] = arr[i].y - d.y;
33         m[i][2] = m[i][0] * m[i][0];
34         m[i][2] += m[i][1] * m[i][1];
35     }                                     #4264
36     __int128 res = 0;
37     res += (__int128)(m[0][0] * m[1][1] - m[0][1] * m[1][0]) * m[2][2];
38     res += (__int128)(m[1][0] * m[2][1] - m[1][1] * m[2][0]) * m[0][2];
39     res -= (__int128)(m[0][0] * m[2][1] - m[0][1] * m[2][0]) * m[1][2];
40     return res > 0;
41 }                                     #7305
42 Edge *add_triangle(Edge *a, Edge *b, Edge *c) {
43     Edge *old[] = {a, b, c};
44     Edge *tmp = new Edge[3];
45     ran(i, 0, 3) {
46         old[i]->rep = tmp + i;
47         tmp[i] = {old[i]->tar, tmp + (i + 1) % 3, old[i]->inv};
48     }

```

```

48     if (tmp[i].inv) tmp[i].inv->inv = tmp + i;
49 }
50 return tmp;
51 }                                     #8178
52 Edge *add_point(Vec p, Edge *cur) { // returns outgoing edge
53     Edge *triangle[] = {cur, cur->nxt, cur->nxt->nxt};
54     ran(i, 0, 3) {
55         if (orient(triangle[i]->tar, triangle[(i + 1) % 3]->tar, p) < 0)
56             return NULL;
57     }
58     ran(i, 0, 3) {
59         if (triangle[i]->rep) {
60             Edge *res = add_point(p, triangle[i]->rep);
61             if (res)
62                 return res; // unless we are on last layer we must exit here
63         }
64     }
65     Edge p_as_e{p};
66     Edge tmp{cur->tar};
67     tmp.inv = add_triangle(&p_as_e, &tmp, cur = cur->nxt);
68     Edge *res = tmp.inv->nxt;
69     tmp.tar = cur->tar;
70     tmp.inv = add_triangle(&p_as_e, &tmp, cur = cur->nxt);
71     tmp.tar = cur->tar;
72     res->inv = add_triangle(&p_as_e, &tmp, cur = cur->nxt);
73     res->inv->inv = res;
74     return res;
75 }
76 Edge *delaunay(vector<Vec> &points) {
77     random_shuffle(points.begin(), points.end());
78     Vec arr[] = {{4 * max_co, 4 * max_co}, {-4 * max_co, max_co},
79         {max_co, -4 * max_co}};
80     Edge *res = new Edge[3];
81     ran(i, 0, 3) res[i] = {arr[i], res + (i + 1) % 3};
82     for (Vec &cur : points) {
83         Edge *loc = add_point(cur, res);
84         Edge *out = loc;
85         arr[0] = cur;
86         while (true) {
87             arr[1] = out->tar;
88             arr[2] = out->nxt->tar;
89             Edge *e = out->nxt->inv;
90             if (e && in_c_circle(arr, e->nxt->tar)) {
91                 Edge tmp{cur};
92                 tmp.inv = add_triangle(&tmp, out, e->nxt);
93                 tmp.tar = e->nxt->tar;
94                 tmp.inv->inv = add_triangle(&tmp, e->nxt->nxt, out->nxt->nxt);
95                 out = tmp.inv->nxt;
96                 continue;
97             }
98             out = out->nxt->nxt->inv;
99 }

```

#8178

#0233

#5636

#1432

#8359

#3029

#4575

#3471

#9851

#0151

```

99     if (out->tar == loc->tar) break;
100 }
101 }
102 return res;
103 }
104 void extract_triangles(Edge *cur, vector<vector<Seg> > &res) {
105     if (!cur->vis) {
106         bool inc = true;
107         Edge *it = cur;
108         do {
109             it->vis = true;
110             if (it->rep) {
111                 extract_triangles(it->rep, res);
112                 inc = false;
113             }
114             it = it->nxt;
115         } while (it != cur);
116         if (inc) {
117             Edge *triangle[3] = {cur, cur->nxt, cur->nxt->nxt};
118             res.resize(res.size() + 1);
119             vector<Seg> &tar = res.back();
120             ran(i, 0, 3) {
121                 if ((abs(triangle[i]->tar.x) < max_co &&
122                     abs(triangle[(i + 1) % 3]->tar.x) < max_co))
123                     tar.push_back(
124                         {triangle[i]->tar, triangle[(i + 1) % 3]->tar});
125             }
126             if (tar.empty()) res.pop_back();
127         }
128     }
129 }

```

%6769

#3769

#2104

#6207

#3011

#8602

%5626

## 12 Aho Corasick $O(|\alpha| \sum \text{len})$

```

1 const int alpha_size = 26;
2 struct Node {
3     Node *nxt[alpha_size]; // May use other structures to move in trie
4     Node *suffix;
5     Node() { memset(nxt, 0, alpha_size * sizeof(Node *)); }
6     int cnt = 0;
7 };
8 Node *aho_corasick(vector<vector<char> > &dict) {
9     Node *root = new Node;
10    root->suffix = 0;
11    vector<pair<vector<char> *, Node *> > state;
12    for (vector<char> &s : dict) state.emplace_back(&s, root);
13    for (int i = 0; !state.empty(); ++i) {
14        vector<pair<vector<char> *, Node *> > nstate;
15        for (auto &cur : state) {
16            Node *nxt = cur.second->nxt[(*cur.first)[i]];
17            if (nxt) {
18                cur.second = nxt;
19            } else {

```

#1006

#9056

#1331

```

20     nxt = new Node;
21     cur.second->nxt[(*cur.first)[i]] = nxt;
22     Node *suf = cur.second->suffix;
23     cur.second = nxt;
24     nxt->suffix = root; // set correct suffix link
25     while (suf) {
26         if (suf->nxt[(*cur.first)[i]]) {
27             nxt->suffix = suf->nxt[(*cur.first)[i]];
28             break;
29         }
30         suf = suf->suffix;
31     }
32 }
33 if (cur.first->size() > i + 1) nstate.push_back(cur);
34 }
35 state = nstate;
36 }
37 return root;
38 }
39 // auxiliary functions for searching and counting
40 Node *walk(Node *cur,
41 char c) { // longest prefix in dict that is suffix of walked string.
42     while (true) {
43         if (cur->nxt[c]) return cur->nxt[c];
44         if (!cur->suffix) return cur;
45         cur = cur->suffix;
46     }
47 }
48 void cnt_matches(Node *root, vector<char> &match_in) {
49     Node *cur = root;
50     for (char c : match_in) {
51         cur = walk(cur, c);
52         ++cur->cnt;
53     }
54 }
55 void add_cnt(Node *root) { // After counting matches propagate ONCE to
56     // suffixes for final counts
57     vector<Node *> to_visit = {root};
58     ran(i, 0, to_visit.size()) {
59         Node *cur = to_visit[i];
60         ran(j, 0, alpha_size) {
61             if (cur->nxt[j]) to_visit.push_back(cur->nxt[j]);
62         }
63     }
64     for (int i = to_visit.size() - 1; i > 0; --i)
65         to_visit[i]->suffix->cnt += to_visit[i]->cnt;
66 }
67 int main() {
68     int n, len;
69     scanf("%d %d", &n, &len);
70     vector<char> a(len + 1);

```

#5283

#3580

#3263

%2882

#5414

%1529

#0015

%8156

#0662

#7950

%0488

```

71 scanf("%s", a.data());
72 a.pop_back();
73 for (char &c : a) c -= 'a';
74 vector<vector<char> > dict(n);
75 ran(i, 0, n) {
76     scanf("%d", &len);
77     dict[i].resize(len + 1);
78     scanf("%s", dict[i].data());
79     dict[i].pop_back();
80     for (char &c : dict[i]) c -= 'a';
81 }
82 Node *root = aho_corasick(dict);
83 cnt_matches(root, a);
84 add_cnt(root);
85 ran(i, 0, n) {
86     Node *cur = root;
87     for (char c : dict[i]) cur = walk(cur, c);
88     printf("%d\n", cur->cnt);
89 }
90 }

```

### 13 Suffix automaton and tree $\mathcal{O}((n + q) \log(|\alpha|))$

```

1 struct Node {
2     map<char, Node *> nxt_char;
3     // Map is faster than hashtable and unsorted arrays
4     int len; // Length of longest suffix in equivalence class.
5     Node *suf;
6     bool has_nxt(char c) const { return nxt_char.count(c); }
7     Node *nxt(char c) {
8         if (!has_nxt(c)) return NULL;
9         return nxt_char[c];
10    }
11    void set_nxt(char c, Node *node) { nxt_char[c] = node; }
12    Node *split(int new_len, char c) {
13        Node *new_n = new Node;
14        new_n->nxt_char = nxt_char;
15        new_n->len = new_len;
16        new_n->suf = suf;
17        suf = new_n;
18        return new_n;
19    }
20    // Extra functions for matching and counting
21    Node *lower(int depth) {
22        // move to longest suf of current with a maximum length of depth.
23        if (suf->len >= depth) return suf->lower(depth);
24        return this;
25    }
26    Node *walk(char c, int depth, int &match_len) {
27        // move to longest suffix of walked path that is a substring
28        match_len = min(match_len, len);
29        // includes depth limit (needed for finding matches)
30        if (has_nxt(c)) { // as suffixes are in classes match_len must be

```

#9664

#8305

#4595

%3114

#2130

```

31 // tracked externally
32 ++match_len;
33 return nxt(c)->lower(depth);
34 }
35 if (suf) return suf->walk(c, depth, match_len);
36 return this;
37 }
38 int paths_to_end = 0;
39 void set_as_end() { // All suffixes of current node are marked as
40     // ending nodes.
41     paths_to_end += 1;
42     if (suf) suf->set_as_end();
43 }
44 bool vis = false;
45 void calc_paths() {
46     // Call ONCE from ROOT. For each node calculates number of ways
47     // to reach an end node. paths_to_end is occurrence count for any
48     // strings in current suffix equivalence class.
49     if (!vis) {
50         vis = true;
51         for (auto cur : nxt_char) {
52             cur.second->calc_paths();
53             paths_to_end += cur.second->paths_to_end;
54         }
55     }
56 }
57 // Transform into suffix tree of reverse string
58 map<char, Node *> tree_links;
59 int end_dist = 1 << 30;
60 int calc_end_dist() {
61     if (end_dist == 1 << 30) {
62         if (nxt_char.empty()) end_dist = 0;
63         for (auto cur : nxt_char)
64             end_dist = min(end_dist, 1 + cur.second->calc_end_dist());
65     }
66     return end_dist;
67 }
68 bool vis_t = false;
69 void build_suffix_tree(string &s) { // Call ONCE from ROOT.
70     if (!vis_t) {
71         vis_t = true;
72         if (suf)
73             suf->tree_links[s[s.size() - end_dist - suf->len - 1]] = this;
74         for (auto cur : nxt_char) cur.second->build_suffix_tree(s);
75     }
76 }
77 };
78 struct SufAuto {
79     Node *last;
80     Node *root;
81     void extend(char new_c) {

```

#9589

%2262

#3041

#2404

#7906

#7524

#2021

#6270

%1268

```

82 Node *nlast = new Node;                                #0936
83 nlast->len = last->len + 1;
84 Node *swn = last;
85 while (swn && !swn->has_nxt(new_c)) {
86     swn->set_nxt(new_c, nlast);
87     swn = swn->suf;                                     #1831
88 }
89 if (!swn) {
90     nlast->suf = root;
91 } else {
92     Node *max_sbstr = swn->nxt(new_c);                   #0855
93     if (swn->len + 1 == max_sbstr->len) {
94         nlast->suf = max_sbstr;
95     } else { // remove for minimal DFA that matches suffixes and
96             // crap
97         Node *eq_sbstr = max_sbstr->split(swn->len + 1, new_c);
98         nlast->suf = eq_sbstr;                           #1749
99         Node *x = swn; // x = with_edge_to_eq_sbstr
100        while (x != 0 && x->nxt(new_c) == max_sbstr) {
101            x->set_nxt(new_c, eq_sbstr);
102            x = x->suf;
103        }                                                #4310
104    }
105 }
106 last = nlast;                                          %6146
107 }
108 SufAuto(string &s) {
109     root = new Node;
110     root->len = 0;
111     root->suf = NULL;
112     last = root;                                       #9604
113     for (char c : s) extend(c);
114     root->calc_end_dist(); // To build suffix tree use reversed string
115     root->build_suffix_tree(s);
116 }
117 };                                                    #6251                                %6251

```

#### 14 Dinic

```

1 struct MaxFlow {
2     const static ll INF = 1e18;
3     int source, sink;
4     vector<int> start, now, lvl, adj, rcap, cap_loc, bfs;
5     vector<int> cap, orig_cap; /*ly*/
6     ll sink_pot = 0;
7     vector<bool> visited;
8     vector<ll> cost;
9     priority_queue<pair<ll, int>, vector<pair<ll, int> >,
10         greater<pair<ll, int> > >
11         dist_que; /*ry*/
12     void add_flow(int idx, ll flow, bool cont = true) {
13         cap[idx] -= flow;
14         if (cont) add_flow(rcap[idx], -flow, false);

```

```

15 }
16 MaxFlow(
17     const vector<tuple<int, int, ll, ll /*ly*/, ll /*ry*/> > &edges) {
18     for (auto &cur : edges) { // from, to, cap, rcap/*ly*/, cost/*ry*/
19         start.resize(
20             max(max(get<0>(cur), get<1>(cur)) + 2, (int)start.size()));
21         ++start[get<0>(cur) + 1];
22         ++start[get<1>(cur) + 1];
23     }
24     ran(i, 1, (int)start.size()) start[i] += start[i - 1];
25     now = start;
26     adj.resize(start.back());
27     cap.resize(start.back());
28     rcap.resize(start.back()); /*ly*/
29     cost.resize(start.back()); /*ry*/
30     for (auto &cur : edges) {
31         int u, v;
32         ll c, rc /*ly*/, c_cost /*ry*/;
33         tie(u, v, c, rc /*ly*/, c_cost /*ry*/) = cur;
34         assert(u != v);
35         adj[now[u]] = v;
36         adj[now[v]] = u;
37         rcap[now[u]] = now[v];
38         rcap[now[v]] = now[u];
39         cap_loc.push_back(now[u]); /*ly*/
40         cost[now[u]] = c_cost;
41         cost[now[v]] = -c_cost; /*ry*/
42         cap[now[u]++] = c;
43         cap[now[v]++] = rc;
44         orig_cap.push_back(c);
45     }
46 }
47 bool dinic_bfs(int min_cap) {
48     lvl.clear();
49     lvl.resize(start.size());
50     bfs.clear();
51     bfs.resize(1, source);
52     now = start;
53     lvl[source] = 1;
54     ran(i, 0, (int)bfs.size()) {
55         int u = bfs[i];
56         while (now[u] < start[u + 1]) {
57             int v = adj[now[u]];
58             if (/*ly*/ cost[now[u]] == 0 &&
59                 /*ry*/ cap[now[u]] >= min_cap && lvl[v] == 0) {
60                 lvl[v] = lvl[u] + 1;
61                 if (v == sink) return true;
62                 bfs.push_back(v);
63             }
64             ++now[u];
65         }

```

```

66     }
67     return false;
68 }
69 ll dinic_dfs(int u, ll flow, int min_cap) {
70     if (u == sink) return flow;
71     if (lvl[u] == lvl[sink]) return 0;
72     ll res = 0;
73     while (now[u] < start[u + 1]) {
74         int v = adj[now[u]];
75         if (lvl[v] == lvl[u] + 1 /*ly*/ && cost[now[u]] == 0 /*ry*/ &&
76             cap[now[u]] >= min_cap) {
77             ll cur = dinic_dfs(v, min(flow, (ll)cap[now[u]]), min_cap);
78             if (cur) {
79                 add_flow(now[u], cur);
80                 flow -= cur;
81                 res += cur;
82                 if (!flow) break;
83             }
84         }
85         ++now[u];
86     }
87     return res;
88 } /*ly*/
89 bool recalc_dist(bool check_imp = false) {
90     now = start;
91     visited.clear();
92     visited.resize(start.size());
93     dist_que.emplace(0, source); /*lp*/
94     bool imp = false; /*rp*/
95     while (!dist_que.empty()) {
96         int u;
97         ll dist;
98         tie(dist, u) = dist_que.top();
99         dist_que.pop();
100         if (!visited[u]) {
101             visited[u] = true; /*lp*/
102             if (check_imp && dist != 0) imp = true; /*rp*/
103             if (u == sink) sink_pot += dist;
104             while (now[u] < start[u + 1]) {
105                 int v = adj[now[u]];
106                 if (!visited[v] && cap[now[u]])
107                     dist_que.emplace(dist + cost[now[u]], v);
108                 cost[now[u]] += dist;
109                 cost[rcap[now[u]++]] -= dist;
110             }
111         }
112     } /*lp*/
113     if (check_imp) return imp; /*rp*/
114     return visited[sink];
115 } /*ry*/ /*lp*/
116 bool recalc_dist_bellman_ford() { /* return whether there is
117     /* a negative cycle

```

```

118     int i = 0;
119     for (; i < (int)start.size() - 1 && recalc_dist(true); ++i) {
120     }
121     return i == (int)start.size() - 1;
122 } /*rp*/
123 /*ly*/ pair<ll, /*ry*/ ll /*ly*/> /*ry*/ calc_flow(
124     int _source, int _sink) {
125     source = _source;
126     sink = _sink;
127     assert(max(source, sink) < start.size() - 1); /*ly*/
128     ll tot_flow = 0;
129     ll tot_cost = 0; /*lp*/
130     if (recalc_dist_bellman_ford()) {
131         assert(false);
132     } else { /*rp*/
133         while (recalc_dist()) { /*ry*/
134             ll flow = 0;
135             for (int min_cap = 1 << 30; min_cap; min_cap >= 1) {
136                 while (dinic_bfs(min_cap)) {
137                     now = start;
138                     ll cur;
139                     while (cur = dinic_dfs(source, INF, min_cap)) flow += cur;
140                 }
141             } /*ly*/
142             tot_flow += flow;
143             tot_cost += sink_pot * flow; /*ry*/
144         }
145     }
146     return /*ly*/ {tot_ /*ry*/ flow /*ly*/, tot_cost} /*ry*/;
147 }
148 ll flow_on_edge(int idx) {
149     assert(idx < cap.size());
150     return orig_cap[idx] - cap[cap_loc[idx]];
151 }
152 };
153 const int nmax = 1055;
154 int main() {
155     int t;
156     scanf("%d", &t);
157     for (int i = 0; i < t; ++i) {
158         vector<tuple<int, int, ll, ll, ll> > edges;
159         int n;
160         scanf("%d", &n);
161         for (int j = 1; j <= n; ++j) {
162             edges.emplace_back(j, 2 * n + 1, 1, 0, 0);
163         }
164         for (int j = 1; j <= n; ++j) {
165             int card;
166             scanf("%d", &card);
167             edges.emplace_back(0, card, 1, 0, 0);
168         }

```

```

169 int ex_c;
170 scanf("%d", &ex_c);
171 for (int j = 0; j < ex_c; ++j) {
172     int a, b;
173     scanf("%d %d", &a, &b);
174     if (b < a) swap(a, b);
175     edges.emplace_back(a, b, nmax, 0, 1);
176     edges.emplace_back(b, n + b, nmax, 0, 0);
177     edges.emplace_back(n + b, a, nmax, 0, 1);
178 }
179 int v = 2 * n + 2;
180 MaxFlow mf(edges);
181 printf("%d\n", (int)mf.calc_flow(0, v - 1).second);
182 // cout << mf.flow_on_edge(edge_index) << endl;
183 }
184 }

```

### 15 Min Cost Max Flow with Cycle Cancellation $\mathcal{O}(\text{cap} \cdot nm)$

```

1 struct Network {
2     struct Node;
3     struct Edge {
4         Node *u, *v;
5         int f, c, cost;
6         Node* from(Node* pos) {
7             if (pos == u) return v;
8             return u;
9         }
10        int getCap(Node* pos) {
11            if (pos == u) return c - f;
12            return f;
13        }
14        int addFlow(Node* pos, int toAdd) {
15            if (pos == u) {
16                f += toAdd;
17                return toAdd * cost;
18            } else {
19                f -= toAdd;
20                return -toAdd * cost;
21            }
22        }
23    };
24    struct Node {
25        vector<Edge*> conn;
26        int index;
27    };
28    deque<Node> nodes;
29    deque<Edge> edges;
30    Node* addNode() {
31        nodes.push_back(Node());
32        nodes.back().index = nodes.size() - 1;
33        return &nodes.back();
34    }

```

```

35 Edge* addEdge(Node* u, Node* v, int f, int c, int cost) {
36     edges.push_back({u, v, f, c, cost});
37     u->conn.push_back(&edges.back());
38     v->conn.push_back(&edges.back());
39     return &edges.back();
40 }
41 // Assumes all needed flow has already been added
42 int minCostMaxFlow() {
43     int n = nodes.size();
44     int result = 0;
45     struct State {
46         int p;
47         Edge* used;
48     };
49     while (1) {
50         vector<vector<State>> state(1, vector<State>(n, {0, 0}));
51         for (int lev = 0; lev < n; lev++) {
52             state.push_back(state[lev]);
53             for (int i = 0; i < n; i++) {
54                 if (lev == 0 || state[lev][i].p < state[lev - 1][i].p) {
55                     for (Edge* edge : nodes[i].conn) {
56                         if (edge->getCap(&nodes[i]) > 0) {
57                             int np =
58                                 state[lev][i].p +
59                                 (edge->u == &nodes[i] ? edge->cost : -edge->cost);
60                             int ni = edge->from(&nodes[i])->index;
61                             if (np < state[lev + 1][ni].p) {
62                                 state[lev + 1][ni].p = np;
63                                 state[lev + 1][ni].used = edge;
64                             }
65                         }
66                     }
67                 }
68             }
69         }
70         // Now look at the last level
71         bool valid = false;
72         for (int i = 0; i < n; i++)
73             if (state[n - 1][i].p > state[n][i].p) {
74                 valid = true;
75                 vector<Edge*> path;
76                 int cap = 1000000000;
77                 Node* cur = &nodes[i];
78                 int clef = n;
79                 vector<bool> explr(n, false);
80                 while (!explr[cur->index]) {
81                     explr[cur->index] = true;
82                     State cstate = state[clef][cur->index];
83                     cur = cstate.used->from(cur);
84                     path.push_back(cstate.used);
85                 }

```

#5123

#0927

#7358

#0078

#7871

#3940

#3693

#5398

#6663

#3984

```

86     reverse(path.begin(), path.end());
87     {
88         int i = 0;
89         Node* cur2 = cur;
90         do {
91             cur2 = path[i]->from(cur2);
92             i++;
93         } while (cur2 != cur);
94         path.resize(i);
95     }
96     for (auto edge : path) {
97         cap = min(cap, edge->getCap(cur));
98         cur = edge->from(cur);
99     }
100    for (auto edge : path) {
101        result += edge->addFlow(cur, cap);
102        cur = edge->from(cur);
103    }
104    }
105    if (!valid) break;
106 }
107 return result;
108 }
109 };

```

#9784

#9838

#8867

#4467

#4029  
%2900

## 16 DMST $\mathcal{O}(E \log V)$

```

1 struct EdgeDesc {
2     int from, to, w;
3 };
4 struct DMST {
5     struct Node;
6     struct Edge {
7         Node *from;
8         Node *tar;
9         int w;
10        bool inc;
11    };
12    struct Circle {
13        bool vis = false;
14        vector<Edge*> cont;
15        void clean(int idx);
16    };
17    const static greater<pair<ll, Edge*>> comp;
18    static vector<Circle> to_proc;
19    static bool no_dmst;
20    static Node *root; // Can use inline static since C++17
21    struct Node {
22        Node *par = NULL;
23        vector<pair<int, int>> out_cands; // Circ, edge idx
24        vector<pair<ll, Edge*>> con;
25        bool in_use = false;
26        ll w = 0; // extra to add to edges in con

```

#6091

#2186

#4353

#9916

```

27 Node *anc() {
28     if (!par) return this;
29     while (par->par) par = par->par;
30     return par;
31 }
32 void clean() {
33     if (!no_dmst) {
34         in_use = false;
35         for (auto &cur : out_cands)
36             to_proc[cur.first].clean(cur.second);
37     }
38 }
39 Node *con_to_root() {
40     if (anc() == root) return root;
41     in_use = true;
42     Node *super = this; // Will become root or the first Node
43                        // encountered in a loop.
44     while (super == this) {
45         while (
46             !con.empty() && con.front().second->tar->anc() == anc()) {
47             pop_heap(con.begin(), con.end(), comp);
48             con.pop_back();
49         }
50         if (con.empty()) {
51             no_dmst = true;
52             return root;
53         }
54         pop_heap(con.begin(), con.end(), comp);
55         auto nxt = con.back();
56         con.pop_back();
57         w = -nxt.first;
58         if (nxt.second->tar
59             ->in_use) { // anc() wouldn't change anything
60             super = nxt.second->tar->anc();
61             to_proc.resize(to_proc.size() + 1);
62         } else {
63             super = nxt.second->tar->con_to_root();
64         }
65         if (super != root) {
66             to_proc.back().cont.push_back(nxt.second);
67             out_cands.emplace_back(
68                 to_proc.size() - 1, to_proc.back().cont.size() - 1);
69         } else { // Clean circles
70             nxt.second->inc = true;
71             nxt.second->from->clean();
72         }
73     }
74     if (super != root) { // we are some loops non first Node.
75         if (con.size() > super->con.size()) {
76             swap(con,
77                 super->con); // Largest con in loop should not be copied.

```

#0564

#0300

#0747

#3927

#2561

#8600

#6612

#7005

#1096

#2844

```

78     swap(w, super->w);
79 }
80 for (auto cur : con) {                                     #3498
81     super->con.emplace_back(
82         cur.first - super->w + w, cur.second);
83     push_heap(super->con.begin(), super->con.end(), comp);
84 }
85 }                                                         #6348
86 par = super; // root or anc() of first Node encountered in a
87             // loop
88 return super;
89 }
90 };
91 Node *croot;                                              #0309
92 vector<Node> graph;
93 vector<Edge> edges;
94 DMST(int n, vector<EdgeDesc> &desc,
95     int r) { // Self loops and multiple edges are okay.
96     graph.resize(n);                                     #8100
97     croot = &graph[r];
98     for (auto &cur : desc) // Edges are reversed internally
99         edges.push_back(Edge{&graph[cur.to], &graph[cur.from], cur.w});
100     for (int i = 0; i < desc.size(); ++i)
101         graph[desc[i].to].con.emplace_back(desc[i].w, &edges[i]);
102     for (int i = 0; i < n; ++i)                          #8811
103         make_heap(graph[i].con.begin(), graph[i].con.end(), comp);
104 }
105 bool find() {
106     root = croot;
107     no_dmst = false;                                     #5307
108     for (auto &cur : graph) {
109         cur.con_to_root();
110         to_proc.clear();
111         if (no_dmst) return false;
112     }                                                      #6725
113     return true;                                          #1568
114 }
115 ll weight() {
116     ll res = 0;
117     for (auto &cur : edges) {
118         if (cur.inc) res += cur.w;
119     }
120     return res;                                          #6369
121 }                                                         #1477
122 };
123 void DMST::Circle::clean(int idx) {
124     if (!vis) {
125         vis = true;
126         for (int i = 0; i < cont.size(); ++i) {          #6503
127             if (i != idx) {
128                 cont[i]->inc = true;

```

```

129         cont[i]->from->clean();
130     }
131 }                                                         #8144
132 }
133 }
134 const greater<pair<ll, DMST::Edge *> > DMST::comp;
135 vector<DMST::Circle> DMST::to_proc;
136 bool DMST::no_dmst;                                     #2354
137 DMST::Node *DMST::root;                                #2870

17 Bridges  $O(n)$ 
1 struct vert;
2 struct edge {
3     bool exists = true;
4     vert *dest;
5     edge *rev;
6     edge(vert *_dest) : dest(_dest) { rev = NULL; }
7     vert &operator*() { return *dest; }
8     vert *operator->() { return dest; }
9     bool is_bridge();
10 };
11 struct vert {
12     deque<edge> con;
13     int val = 0;
14     int seen;
15     int dfs(int upd, edge *ban) { // handles multiple edges
16         if (!val) {
17             val = upd;
18             seen = val;
19             for (edge &nxt : con) {
20                 if (nxt.exists && (&nxt) != ban)
21                     seen = min(seen, nxt->dfs(upd + 1, nxt.rev));
22             }
23             return seen;
24         }
25     }
26 void remove_adj_bridges() {
27     for (edge &nxt : con) {
28         if (nxt.is_bridge()) nxt.exists = false;
29     }
30 }                                                         #7106
31 int cnt_adj_bridges() {
32     int res = 0;
33     for (edge &nxt : con) res += nxt.is_bridge();
34     return res;
35 }                                                         #9056
36 };
37 bool edge::is_bridge() {
38     return exists &&
39         (dest->seen > rev->dest->val || dest->val < rev->dest->seen);
40 }                                                         #5223
41 vert graph[nmax];

```



```

42 int main() { // Mechanics Practice BRIDGES
43     int n, m;
44     cin >> n >> m;
45     for (int i = 0; i < m; ++i) {
46         int u, v;
47         scanf("%d %d", &u, &v);
48         graph[u].con.emplace_back(graph + v);
49         graph[v].con.emplace_back(graph + u);
50         graph[u].con.back().rev = &graph[v].con.back();
51         graph[v].con.back().rev = &graph[u].con.back();
52     }
53     graph[1].dfs(1, NULL);
54     int res = 0;
55     for (int i = 1; i <= n; ++i) res += graph[i].cnt_adj_bridges();
56     cout << res / 2 << endl;
57 }

```

### 18 2-Sat $\mathcal{O}(n)$ and SCC $\mathcal{O}(n)$

```

1 struct Graph {
2     int n;
3     vector<vector<int>> > con;
4     Graph(int nsize) {
5         n = nsize;
6         con.resize(n);
7     }
8     void add_edge(int u, int v) { con[u].push_back(v); }
9     void top_dfs(int pos, vector<int> &result, vector<bool> &explr,
10         vector<vector<int>> &revcon) {
11         if (explr[pos]) return;
12         explr[pos] = true;
13         for (auto next : revcon[pos])
14             top_dfs(next, result, explr, revcon);
15         result.push_back(pos);
16     }
17     vector<int> topsort() {
18         vector<vector<int>> > revcon(n);
19         ran(u, 0, n) {
20             for (auto v : con[u]) revcon[v].push_back(u);
21         }
22         vector<int> result;
23         vector<bool> explr(n, false);
24         ran(i, 0, n) top_dfs(i, result, explr, revcon);
25         reverse(result.begin(), result.end());
26         return result;
27     }
28     void dfs(int pos, vector<int> &result, vector<bool> &explr) {
29         if (explr[pos]) return;
30         explr[pos] = true;
31         for (auto next : con[pos]) dfs(next, result, explr);
32         result.push_back(pos);
33     }
34     vector<vector<int>> > scc() {

```

#0321

#2422

#2081

%7763

#3875

#7568

%5339

#6880

%3565

```

35     vector<int> order = topsort();
36     reverse(order.begin(), order.end());
37     vector<bool> explr(n, false);
38     vector<vector<int>> > res;
39     for (auto it = order.rbegin(); it != order.rend(); ++it) {
40         vector<int> comp;
41         top_dfs(*it, comp, explr, con);
42         sort(comp.begin(), comp.end());
43         res.push_back(comp);
44     }
45     sort(res.begin(), res.end());
46     return res;
47 }
48 };
49 int main() {
50     int n, m;
51     cin >> n >> m;
52     Graph g(2 * m);
53     ran(i, 0, n) {
54         int a, sa, b, sb;
55         cin >> a >> sa >> b >> sb;
56         a--, b--;
57         g.add_edge(2 * a + 1 - sa, 2 * b + sb);
58         g.add_edge(2 * b + 1 - sb, 2 * a + sa);
59     }
60     vector<int> state(2 * m, 0);
61     {
62         vector<int> order = g.topsort();
63         vector<bool> explr(2 * m, false);
64         for (auto u : order) {
65             vector<int> traversed;
66             g.dfs(u, traversed, explr);
67             if (traversed.size() > 0 && !state[traversed[0] ^ 1]) {
68                 for (auto c : traversed) state[c] = 1;
69             }
70         }
71     }
72     ran(i, 0, m) {
73         if (state[2 * i] == state[2 * i + 1]) {
74             cout << "IMPOSSIBLE\n";
75             return 0;
76         }
77     }
78     ran(i, 0, m) cout << state[2 * i + 1] << '\n';
79     return 0;
80 }

```

#9931

#2243

#0543

%0543

### 19 Generic persistent compressed lazy segment tree

```

1 struct Seg {
2     ll sum = 0;
3     void recalc(const Seg &lhs_seg, int lhs_len, const Seg &rhs_seg,
4         int rhs_len) {

```

```

5     sum = lhs_seg.sum + rhs_seg.sum;                                #7684
6 }
7 } __attribute__((packed));
8 struct Lazy {
9     ll add;
10    ll assign_val; // LLONG_MIN if no assign;
11    void init() {                                                    #7883
12        add = 0;
13        assign_val = LLONG_MIN;
14    }
15    Lazy() { init(); }
16    void split(Lazy &lhs_lazy, Lazy &rhs_lazy, int len) {            #7654
17        lhs_lazy = *this;
18        rhs_lazy = *this;
19        init();
20    }
21    void merge(Lazy &oth, int len) {
22        if (oth.assign_val != LLONG_MIN) {                            #0050
23            add = 0;
24            assign_val = oth.assign_val;
25        }
26        add += oth.add;
27    }
28    void apply_to_seg(Seg &cur, int len) const {                      #2924
29        if (assign_val != LLONG_MIN) {
30            cur.sum = len * assign_val;
31        }
32        cur.sum += len * add;                                         #6280
33    }
34 } __attribute__((packed));
35 %0625 struct Node { // Following code should not need to be modified
36     int ver;
37     bool is_lazy = false;
38     Seg seg;
39     Lazy lazy;
40     Node *lc = NULL, *rc = NULL;
41     void init() {
42         if (!lc) {
43             lc = new Node{ver};
44             rc = new Node{ver};
45         }
46     }
47     Node *upd(int L, int R, int l, int r, Lazy &val, int tar_ver) {
48         if (ver != tar_ver) {                                        #8874
49             Node *rep = new Node(*this);
50             rep->ver = tar_ver;
51             return rep->upd(L, R, l, r, val, tar_ver);
52         }
53         if (L >= l && R <= r) {
54             val.apply_to_seg(seg, R - L);                            #2138
55             lazy.merge(val, R - L);
56             is_lazy = true;

```

```

57     } else {
58         init();
59         int M = (L + R) / 2;                                         #8209
60         if (is_lazy) {
61             Lazy l_val, r_val;
62             lazy.split(l_val, r_val, R - L);
63             lc = lc->upd(L, M, L, M, l_val, ver);
64             rc = rc->upd(M, R, M, R, r_val, ver);                     #8104
65             is_lazy = false;
66         }
67         Lazy l_val, r_val;
68         val.split(l_val, r_val, R - L);
69         if (l < M) lc = lc->upd(L, M, l, r, l_val, ver);
70         if (M < r) rc = rc->upd(M, R, l, r, r_val, ver);
71         seg.recalc(lc->seg, M - L, rc->seg, R - M);                  #8581
72     }
73     return this;
74 }
75 void get(int L, int R, int l, int r, Seg *&lft_res, Seg *&tmp,     #9373
76     bool last_ver) {
77     if (L >= l && R <= r) {
78         tmp->recalc(*lft_res, L - l, seg, R - L);
79         swap(lft_res, tmp);
80     } else {
81         init();
82         int M = (L + R) / 2;
83         if (is_lazy) {
84             Lazy l_val, r_val;
85             lazy.split(l_val, r_val, R - L);
86             lc = lc->upd(L, M, L, M, l_val, ver + last_ver);
87             lc->ver = ver;
88             rc = rc->upd(M, R, M, R, r_val, ver + last_ver);
89             rc->ver = ver;
90             is_lazy = false;
91         }
92         if (l < M) lc->get(L, M, l, r, lft_res, tmp, last_ver);
93         if (M < r) rc->get(M, R, l, r, lft_res, tmp, last_ver);
94     }
95 }
96 } __attribute__((packed));
97 struct SegTree { // indexes start from 0, ranges are [beg, end)
98     vector<Node *> roots; // versions start from 0
99     int len;                                                         #4873
100    SegTree(int _len) : len(_len) { roots.push_back(new Node{0}); }
101    int upd(int l, int r, Lazy &val, bool new_ver = false) {
102        Node *cur_root =
103            roots.back()->upd(0, len, l, r, val, roots.size() - !new_ver);
104        if (cur_root != roots.back()) roots.push_back(cur_root);
105        return roots.size() - 1;                                       #1461
106    }
107    Seg get(int l, int r, int ver = -1) {

```

```

108     if (ver == -1) ver = roots.size() - 1;
109     Seg seg1, seg2;
110     Seg *pres = &seg1, *ptmp = &seg2; #9427
111     roots[ver]->get(0, len, 1, r, pres, ptmp, roots.size() - 1);
112     return *pres;
113 }
114 };
115
116 %7542 int main() {
117     int n, m; // solves Mechanics Practice LAZY
118     cin >> n >> m;
119     SegTree seg_tree(1 << 17);
120     for (int i = 0; i < n; ++i) {
121         Lazy tmp;
122         scanf("%lld", &tmp.assign_val);
123         seg_tree.upd(i, i + 1, tmp);
124     }
125     for (int i = 0; i < m; ++i) {
126         int o;
127         int l, r;
128         scanf("%d %d %d", &o, &l, &r);
129         --l;
130         if (o == 1) {
131             Lazy tmp;
132             scanf("%lld", &tmp.add);
133             seg_tree.upd(l, r, tmp);
134         } else if (o == 2) {
135             Lazy tmp;
136             scanf("%lld", &tmp.assign_val);
137             seg_tree.upd(l, r, tmp);
138         } else {
139             Seg res = seg_tree.get(l, r);
140             printf("%lld\n", res.sum);
141         }
142     }

```

## 20 Templated HLD $\mathcal{O}(M(n)\log n)$ per query

```

1 class dummy {
2 public:
3     dummy() {}
4     dummy(int, int) {}
5     void set(int, int) {} #9531
6     int query(int left, int right) {
7         cout << this << ' ' << left << ' ' << right << endl;
8     }
9 }; #7932
10 /* T should be the type of the data stored in each vertex;
11 * DS should be the underlying data structure that is used to perform
12 * the group operation. It should have the following methods:
13 * * DS () - empty constructor
14 * * DS (int size, T initial) - constructs the structure with the
15 * given size, initially filled with initial.

```

```

16 * * void set (int index, T value) - set the value at index `index` to
17 * `value`
18 * * T query (int left, int right) - return the "sum" of elements
19 * between left and right, inclusive.
20 */
21 template <typename T, class DS>
22 class HLD {
23     int vertexc;
24     vector<int> *adj;
25     vector<int> subtree_size; #6178
26     DS structure;
27     DS aux;
28     void build_sizes(int vertex, int parent) {
29         subtree_size[vertex] = 1;
30         for (int child : adj[vertex]) { #2037
31             if (child != parent) {
32                 build_sizes(child, vertex);
33                 subtree_size[vertex] += subtree_size[child];
34             }
35         }
36     }
37     int cur;
38     vector<int> ord;
39     vector<int> chain_root;
40     vector<int> par; #9593
41     void build_hld(int vertex, int parent, int chain_source) {
42         cur++;
43         ord[vertex] = cur;
44         chain_root[vertex] = chain_source;
45         par[vertex] = parent; #0432
46         if (adj[vertex].size() > 1 ||
47             (vertex == 1 && adj[vertex].size() == 1)) {
48             int big_child, big_size = -1;
49             for (int child : adj[vertex]) {
50                 if ((child != parent) && (subtree_size[child] > big_size)) {
51                     big_child = child; #9151
52                     big_size = subtree_size[child];
53                 }
54             }
55             build_hld(big_child, vertex, chain_source);
56             for (int child : adj[vertex]) { #3027
57                 if ((child != parent) && (child != big_child))
58                     build_hld(child, vertex, child);
59             }
60         }
61     } #8562
62 public:
63     HLD(int _vertexc) {
64         vertexc = _vertexc;
65         adj = new vector<int>[vertexc + 5];
66     } #3486

```

```

67 void add_edge(int u, int v) {
68     adj[u].push_back(v);
69     adj[v].push_back(u);
70 }
71 void build(T initial) {
72     subtree_size = vector<int>(vertexc + 5);
73     ord = vector<int>(vertexc + 5);
74     chain_root = vector<int>(vertexc + 5);
75     par = vector<int>(vertexc + 5);
76     cur = 0;
77     build_sizes(1, -1);
78     build_hld(1, -1, 1);
79     structure = DS(vertexc + 5, initial);
80     aux = DS(50, initial);
81 }
82 void set(int vertex, int value) {
83     structure.set(ord[vertex], value);
84 }
85 T query_path(
86     int u, int v) { /* returns the "sum" of the path u->v */
87     int cur_id = 0;
88     while (chain_root[u] != chain_root[v]) {
89         if (ord[u] > ord[v]) {
90             cur_id++;
91             aux.set(cur_id, structure.query(ord[chain_root[u]], ord[u]));
92             u = par[chain_root[u]];
93         } else {
94             cur_id++;
95             aux.set(cur_id, structure.query(ord[chain_root[v]], ord[v]));
96             v = par[chain_root[v]];
97         }
98     }
99     cur_id++;
100     aux.set(cur_id,
101         structure.query(min(ord[u], ord[v]), max(ord[u], ord[v])));
102     return aux.query(1, cur_id);
103 }
104 void print() {
105     for (int i = 1; i <= vertexc; i++)
106         cout << i << ' ' << ord[i] << ' ' << chain_root[i] << ' '
107         << par[i] << endl;
108 }
109 };
110 int main() {
111     int vertexc;
112     cin >> vertexc;
113     HLD<int, dummy> hld(vertexc);
114     for (int i = 0; i < vertexc - 1; i++) {
115         int u, v;
116         cin >> u >> v;
117         hld.add_edge(u, v);
118     }

```

#4566

#2693

#7758

#4754

#4538

#1595

#7150

%1905

```

119 hld.build(0);
120 hld.print();
121 int queryc;
122 cin >> queryc;
123 for (int i = 0; i < queryc; i++) {
124     int u, v;
125     cin >> u >> v;
126     hld.query_path(u, v);
127     cout << endl;
128 }
129 }

```

## 21 Splay Tree + Link-Cut $O(N \log N)$

```

1 struct Tree *treev;
2 struct Tree {
3     struct T {
4         int i;
5         constexpr T() : i(-1) {}
6         T(int _i) : i(_i) {}
7         operator int() const { return i; }
8         explicit operator bool() const { return i != -1; }
9         Tree *operator->() { return treev + i; }
10    };
11    T c[2], p;
12    /* insert monoid here */
13    /*lg*/ T link; /*rg*/
14    Tree() {
15        /* init monoid here */
16        /*lg*/ link = -1; /*rg*/
17    }
18 };
19 using T = Tree::T;
20 constexpr T NIL;
21 void update(T t) { /* recalculate the monoid here */
22 }
23 void propagate(T t) {
24     assert(t);
25     /*lg*/
26     for (T c : t->c)
27         if (c) c->link = t->link;
28     /*rg*/
29     /* lazily propagate updates here */
30 }
31 /*lp*/
32 void lazy_reverse(T t) { /* lazily reverse t here */
33 }
34 /*rp*/
35 T splay(T n) {
36     for (;;) {
37         propagate(n);
38         T p = n->p;

```

#7635

#2337

#0939

#3006

#8514

#3792

```

39  if (p == NIL) break;
40  propagate(p);
41  ll px = p->c[1] == n;
42  assert(p->c[px] == n);
43  T g = p->p;
44  if (g == NIL) { /* zig */
45      p->c[px] = n->c[px ^ 1];
46      p->c[px]->p = p;
47      n->c[px ^ 1] = p;
48      n->c[px ^ 1]->p = n;
49      n->p = NIL;
50      update(p);
51      update(n);
52      break;
53  }
54  propagate(g);
55  ll gx = g->c[1] == p;
56  assert(g->c[gx] == p);
57  T gg = g->p;
58  ll ggx = gg && gg->c[1] == g;
59  if (gg) assert(gg->c[ggx] == g);
60  if (gx == px) { /* zig zig */
61      g->c[gx] = p->c[gx ^ 1];
62      g->c[gx]->p = g;
63      p->c[gx ^ 1] = g;
64      p->c[gx ^ 1]->p = p;
65      p->c[gx] = n->c[gx ^ 1];
66      p->c[gx]->p = p;
67      n->c[gx ^ 1] = p;
68      n->c[gx ^ 1]->p = n;
69  } else { /* zig zag */
70      g->c[gx] = n->c[gx ^ 1];
71      g->c[gx]->p = g;
72      n->c[gx ^ 1] = g;
73      n->c[gx ^ 1]->p = n;
74      p->c[gx ^ 1] = n->c[gx];
75      p->c[gx ^ 1]->p = p;
76      n->c[gx] = p;
77      n->c[gx]->p = n;
78  }
79  if (gg) gg->c[ggx] = n;
80  n->p = gg;
81  update(g);
82  update(p);
83  update(n);
84  if (gg) update(gg);
85  }
86  return n;
87  }
88  T extreme(T t, int x) {
89      while (t->c[x]) t = t->c[x];
90      return t;

```

#0245

#4750

#8981

#5659

#5608

#1439

#9140

#2928

#9645

#4920

```

91  }
92  T set_child(T t, int x, T a) {
93      T o = t->c[x];
94      t->c[x] = a;
95      update(t);
96      o->p = NIL;
97      a->p = t;
98      return o;
99  }
100 /****** Link-Cut Tree: *****/
101 T expose(T t) {
102     set_child(splay(t), 1, NIL);
103     T leader = splay(extreme(t, 0));
104     if (leader->link == NIL) return t;
105     set_child(splay(leader), 0, expose(leader->link));
106     return splay(t);
107 }
108 void link(T t, T p) {
109     assert(t->link == NIL);
110     t->link = p;
111 }
112 T cut(T t) {
113     T p = t->link;
114     if (p) expose(p);
115     t->link = NIL;
116     return p;
117 }
118 /*lp*/
119 void make_root(T t) {
120     expose(t);
121     lazy_reverse(extreme(splay(t), 0));
122 }
123 /*rp*/

```

#2821

#4262

#4240

%8430

## 22 Templated multi dimensional BIT $O(\log(n)^{\dim})$ per query

```

1  // Fully overloaded any dimensional BIT, use any type for coordinates,
2  // elements, return value. Includes coordinate compression.
3  template <typename E_T, typename C_T, C_T n_inf, typename R_T>
4  struct BIT {
5      vector<C_T> pos;
6      vector<E_T> elems;
7      bool act = false;
8      BIT() { pos.push_back(n_inf); }
9      void init() {
10         if (act) {
11             for (E_T &c_elem : elems) c_elem.init();
12         } else {
13             act = true;
14             sort(pos.begin(), pos.end());
15             pos.resize(unique(pos.begin(), pos.end()) - pos.begin());
16             elems.resize(pos.size());

```

#3273

#2594

```

17     }                                     #7774
18 }
19 template <typename... loc_form>
20 void update(C_T cx, loc_form... args) {
21     if (act) {
22         int x = lower_bound(pos.begin(), pos.end(), cx) - pos.begin();
23         for (; x < (int)pos.size(); x += x & -x) #7303
24             elems[x].update(args...);
25     } else {
26         pos.push_back(cx);
27     }
28 }                                     #8505
29 template <typename... loc_form>
30 R_T query(C_T cx, loc_form... args) { // sum in (-inf, cx)
31     R_T res = 0;
32     int x = lower_bound(pos.begin(), pos.end(), cx) - pos.begin() - 1;
33     for (; x > 0; x -= x & -x) res += elems[x].query(args...);
34     return res; #2526
35 }
36 };
37 template <typename I_T>
38 struct wrapped {
39     I_T a = 0; #6509
40     void update(I_T b) { a += b; }
41     I_T query() { return a; }
42     // Should never be called, needed for compilation
43     void init() { DEBUG('i') }
44     void update() { DEBUG('u') }
45 }; #2858
46                                     %2858 int main() {
47     // return type should be same as type inside wrapped
48     BIT<BIT<wrapped<ll>, int, INT_MIN, ll>, int, INT_MIN, ll> fenwick;
49     int dim = 2;
50     vector<tuple<int, int, ll> > to_insert;
51     to_insert.emplace_back(1, 1, 1);
52     // set up all pos that are to be used for update
53     for (int i = 0; i < dim; ++i) {
54         for (auto &cur : to_insert)
55             fenwick.update(get<0>(cur), get<1>(cur));
56         // May include value which won't be used
57         fenwick.init();
58     }
59     // actual use
60     for (auto &cur : to_insert)
61         fenwick.update(get<0>(cur), get<1>(cur), get<2>(cur));
62     cout << fenwick.query(2, 2) << '\n';
63 }

```

### 23 Treap $\mathcal{O}(\log n)$ per query

```

1 mt19937 randgen;
2 struct Treap {
3     struct Node {

```

```

4     int key;
5     int value; #5615
6     unsigned int priority;
7     long long total;
8     Node* lch;
9     Node* rch;
10    Node(int new_key, int new_value) { #5698
11        key = new_key;
12        value = new_value;
13        priority = randgen();
14        total = new_value;
15        lch = 0;
16        rch = 0;
17    }
18    void update() {
19        total = value;
20        if (lch) total += lch->total; #4295
21        if (rch) total += rch->total;
22    }
23 };
24 deque<Node> nodes;
25 Node* root = 0; #9633
26 pair<Node*, Node*> split(int key, Node* cur) {
27     if (cur == 0) return {0, 0};
28     pair<Node*, Node*> result;
29     if (key <= cur->key) {
30         auto ret = split(key, cur->lch); #5233
31         cur->lch = ret.second;
32         result = {ret.first, cur};
33     } else {
34         auto ret = split(key, cur->rch);
35         cur->rch = ret.first; #6988
36         result = {cur, ret.second};
37     }
38     cur->update();
39     return result;
40 } #7230
41 Node* merge(Node* left, Node* right) {
42     if (left == 0) return right;
43     if (right == 0) return left;
44     Node* top;
45     if (left->priority < right->priority) { #6282
46         left->rch = merge(left->rch, right);
47         top = left;
48     } else {
49         right->lch = merge(left, right->lch);
50         top = right; #3510
51     }
52     top->update();
53     return top;
54 }

```

```

55 void insert(int key, int value) {
56     nodes.push_back(Node(key, value));
57     Node* cur = &nodes.back();
58     pair<Node*, Node*> ret = split(key, root);
59     cur = merge(ret.first, cur);
60     cur = merge(cur, ret.second);
61     root = cur;
62 }
63 void erase(int key) {
64     Node *left, *mid, *right;
65     tie(left, mid) = split(key, root);
66     tie(mid, right) = split(key + 1, mid);
67     root = merge(left, right);
68 }
69 long long sum_upto(int key, Node* cur) {
70     if (cur == 0) return 0;
71     if (key <= cur->key) {
72         return sum_upto(key, cur->lch);
73     } else {
74         long long result = cur->value + sum_upto(key, cur->rch);
75         if (cur->lch) result += cur->lch->total;
76         return result;
77     }
78 }
79 long long get(int l, int r) {
80     return sum_upto(r + 1, root) - sum_upto(l, root);
81 }
82 };
83 // Solution for:
84 // http://codeforces.com/group/U01GDa2Gwb/contest/219104/problem/TREAP
85 int main() {
86     ios_base::sync_with_stdio(false);
87     cin.tie(0);
88     int m;
89     Treap treap;
90     cin >> m;
91     for (int i = 0; i < m; i++) {
92         int type;
93         cin >> type;
94         if (type == 1) {
95             int x, y;
96             cin >> x >> y;
97             treap.insert(x, y);
98         } else if (type == 2) {
99             int x;
100             cin >> x;
101             treap.erase(x);
102         } else {
103             int l, r;
104             cin >> l >> r;
105             cout << treap.get(l, r) << endl;
106         }

```

#8918

#9760

#1416

#7634

#8122

#0094

%4959

```

107 }
108 return 0;
109 }

```

## 24 Radixsort 50M 64 bit integers as single array in 1 sec

```

1 template <typename T>
2 void rsort(T *a, T *b, int size, int d = sizeof(T) - 1) {
3     int b_s[256]{};
4     ran(i, 0, size) { ++b_s[(a[i] >> (d * 8)) & 255]; }
5     // ++b_s[*((uchar *) (a + i) + d)];
6     T *mem[257];
7     mem[0] = b;
8     T **l_b = mem + 1;
9     l_b[0] = b;
10    ran(i, 0, 255) { l_b[i + 1] = l_b[i] + b_s[i]; }
11    for (T *it = a; it != a + size; ++it) {
12        T id = ((*it) >> (d * 8)) & 255;
13        *(l_b[id]++) = *it;
14    }
15    l_b = mem;
16    if (d) {
17        T *l_a[256];
18        l_a[0] = a;
19        ran(i, 0, 255) l_a[i + 1] = l_a[i] + b_s[i];
20        ran(i, 0, 256) {
21            if (l_b[i + 1] - l_b[i] < 100) {
22                sort(l_b[i], l_b[i + 1]);
23                if (d & 1) copy(l_b[i], l_b[i + 1], l_a[i]);
24            } else {
25                rsort(l_b[i], l_a[i], b_s[i], d - 1);
26            }
27        }
28    }
29 }
30 const int nmax = 5e7;
31 ll arr[nmax], tmp[nmax];
32 int main() {
33     for (int i = 0; i < nmax; ++i) arr[i] = ((ll)rand() << 32) | rand();
34     rsort(arr, tmp, nmax);
35     assert(is_sorted(arr, arr + nmax));
36 }

```

#5369

#6813

#5681

#1162

#7759

%0571

## 25 FFT 5M length/sec

integer  $c = a * b$  is accurate if  $c_i < 2^{49}$

```

1 struct Complex {
2     double a = 0, b = 0;
3     Complex &operator/=(const int &oth) {
4         a /= oth;
5         b /= oth;
6         return *this;
7     }

```

#1139

```

8 };
9 Complex operator+(const Complex &lft, const Complex &rgt) {
10     return Complex{lft.a + rgt.a, lft.b + rgt.b};
11 }
12 Complex operator-(const Complex &lft, const Complex &rgt) {
13     return Complex{lft.a - rgt.a, lft.b - rgt.b};
14 }
15 Complex operator*(const Complex &lft, const Complex &rgt) {
16     return Complex{
17         lft.a * rgt.a - lft.b * rgt.b, lft.a * rgt.b + lft.b * rgt.a};
18 }
19 Complex conj(const Complex &cur) { return Complex{cur.a, -cur.b}; }
20 void fft_rec(Complex *arr, Complex *root_pow, int len) {
21     if (len != 1) {
22         fft_rec(arr, root_pow, len >> 1);
23         fft_rec(arr + len, root_pow, len >> 1);
24     }
25     root_pow += len;
26     for (int i = 0; i < len; ++i) {
27         Complex tmp = arr[i] + root_pow[i] * arr[i + len];
28         arr[i + len] = arr[i] - root_pow[i] * arr[i + len];
29         arr[i] = tmp;
30     }
31 }
32 void fft(vector<Complex> &arr, int ord, bool invert) {
33     assert(arr.size() == 1 << ord);
34     static vector<Complex> root_pow(1);
35     static int inc_pow = 1;
36     static bool is_inv = false;
37     if (inc_pow <= ord) {
38         int idx = root_pow.size();
39         root_pow.resize(1 << ord);
40         for (; inc_pow <= ord; ++inc_pow) {
41             for (int idx_p = 0; idx_p < 1 << (ord - 1);
42                 idx_p += 1 << (ord - inc_pow), ++idx_p) {
43                 root_pow[idx] = Complex{cos(-idx_p * M_PI / (1 << (ord - 1))),
44                     sin(-idx_p * M_PI / (1 << (ord - 1)))};
45                 if (is_inv) root_pow[idx].b = -root_pow[idx].b;
46             }
47         }
48     }
49     if (invert != is_inv) {
50         is_inv = invert;
51         for (Complex &cur : root_pow) cur.b = -cur.b;
52     }
53     for (int i = 1, j = 0; i < (1 << ord); ++i) {
54         int m = 1 << (ord - 1);
55         bool cont = true;
56         while (cont) {
57             cont = j & m;
58             j ^= m;
59             m >>= 1;

```

#8384

#5371

#7637

#0670

#7078

#0102

#3349

#6357

#7526

#0510

```

60     }
61     if (i < j) swap(arr[i], arr[j]);
62 }
63 fft_rec(arr.data(), root_pow.data(), 1 << (ord - 1));
64 if (invert)
65     for (int i = 0; i < (1 << ord); ++i) arr[i] /= (1 << ord);
66 }
67 void mult_poly_mod(
68     vector<int> &a, vector<int> &b, vector<int> &c) { // c += a*b
69     static vector<Complex>
70         arr[4]; // correct upto 0.5-2M elements(mod ~= 1e9)
71     if (c.size() < 400) {
72         for (int i = 0; i < a.size(); ++i)
73             for (int j = 0; j < b.size() && i + j < c.size(); ++j)
74                 c[i + j] = ((ll)a[i] * b[j] + c[i + j]) % mod;
75     } else {
76         int fft_ord = 32 - __builtin_clz(c.size());
77         if (arr[0].size() != 1 << fft_ord)
78             for (int i = 0; i < 4; ++i) arr[i].resize(1 << fft_ord);
79         for (int i = 0; i < 4; ++i)
80             fill(arr[i].begin(), arr[i].end(), Complex{});
81         for (int &cur : a)
82             if (cur < 0) cur += mod;
83         for (int &cur : b)
84             if (cur < 0) cur += mod;
85         const int shift = 15;
86         const int mask = (1 << shift) - 1;
87         for (int i = 0; i < min(a.size(), c.size()); ++i) {
88             arr[0][i].a = a[i] & mask;
89             arr[1][i].a = a[i] >> shift;
90         }
91         for (int i = 0; i < min(b.size(), c.size()); ++i) {
92             arr[0][i].b = b[i] & mask;
93             arr[1][i].b = b[i] >> shift;
94         }
95         for (int i = 0; i < 2; ++i) fft(arr[i], fft_ord, false);
96         for (int i = 0; i < 2; ++i) {
97             for (int j = 0; j < 2; ++j) {
98                 int tar = 2 + (i + j) / 2;
99                 Complex mult = {0, -0.25};
100                 if (i ^ j) mult = {0.25, 0};
101                 for (int k = 0; k < (1 << fft_ord); ++k) {
102                     int rev_k = ((1 << fft_ord) - k) % (1 << fft_ord);
103                     Complex ca = arr[i][k] + conj(arr[i][rev_k]);
104                     Complex cb = arr[j][k] - conj(arr[j][rev_k]);
105                     arr[tar][k] = arr[tar][k] + mult * ca * cb;
106                 }
107             }
108         }
109         for (int i = 2; i < 4; ++i) {
110             fft(arr[i], fft_ord, true);

```

#0506

%4380

#8811

#4629

#9591

#2625

#3501

#9971

#4471



```

111     for (int k = 0; k < (int)c.size(); ++k) { #8403
112         c[k] = (c[k] + (((ll)(arr[i][k].a + 0.5) % mod)
113             << (shift * 2 * (i - 2)))) %
114             mod;
115         c[k] = (c[k] + (((ll)(arr[i][k].b + 0.5) % mod)
116             << (shift * (2 * (i - 2) + 1)))) %
117             mod; #8289
118     }
119 }
120 }
121 } %1231

```

## 26 Fast mod mult, Rabin Miller prime check, Pollard rho factorization $\mathcal{O}(\sqrt{p})$

```

1 struct ModArithm {
2     ull n;
3     ld rec;
4     ModArithm(ull _n) : n(_n) { // n in [2, 1<<63)
5         rec = 1.0L / n; #0237
6     }
7     ull multf(ull a, ull b) { // a, b in [0, min(2*n, 1<<63))
8         ull mult = (ld)a * b * rec + 0.5L;
9         ll res = a * b - mult * n;
10        if (res < 0) res += n; #0780
11        return res; // in [0, n-1)
12    }
13    ull sqp1(ull a) { return multf(a, a) + 1; } #9493
14};
15 ull pow_mod(ull a, ull n, ModArithm &arithm) {
16     ull res = 1;
17     for (ull i = 1; i <= n; i <= 1) {
18         if (n & i) res = arithm.multf(res, a);
19         a = arithm.multf(a, a); #1758
20     }
21     return res; #2144
22 }
23 vector<char> small_primes = {
24     2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37};
25 bool is_prime(ull n) { // n <= 1<<63, 1M rand/s
26     ModArithm arithm(n);
27     if (n == 2 || n == 3) return true; #8104
28     if (!(n & 1) || n == 1) return false;
29     ull s = __builtin_ctz(n - 1);
30     ull d = (n - 1) >> s;
31     for (ull a : small_primes) {
32         if (a >= n) break; #6402
33         a = pow_mod(a, d, arithm);
34         if (a == 1 || a == n - 1) continue;
35         for (ull r = 1; r < s; ++r) {
36             a = arithm.multf(a, a);
37             if (a == 1) return false; #0876
38             if (a == n - 1) break;

```

```

39     }
40     if (a != n - 1) return false;
41 }
42 return true; #4806
43 } %0975
44 ll pollard_rho(ll n) {
45     ModArithm arithm(n);
46     int cum_cnt = 64 - __builtin_clz(n);
47     cum_cnt *= cum_cnt / 5 + 1;
48     while (true) { #2118
49         ll lv = rand() % n;
50         ll v = arithm.sqp1(lv);
51         int idx = 1;
52         int tar = 1;
53         while (true) { #5290
54             ll cur = 1;
55             ll v_cur = v;
56             int j_stop = min(cum_cnt, tar - idx);
57             for (int j = 0; j < j_stop; ++j) {
58                 cur = arithm.multf(cur, abs(v_cur - lv)); #4468
59                 v_cur = arithm.sqp1(v_cur);
60                 ++idx;
61             }
62             if (!cur) {
63                 for (int j = 0; j < cum_cnt; ++j) { #7912
64                     ll g = __gcd(abs(v - lv), n);
65                     if (g == 1) {
66                         v = arithm.sqp1(v);
67                     } else if (g == n) {
68                         break; #0906
69                     } else {
70                         return g;
71                     }
72                 }
73                 break; #7208
74             } else {
75                 ll g = __gcd(cur, n);
76                 if (g != 1) return g;
77             }
78             v = v_cur; #2298
79             idx += j_stop;
80             if (idx == tar) {
81                 lv = v;
82                 tar *= 2;
83                 v = arithm.sqp1(v); #1174
84                 ++idx;
85             }
86         }
87     }
88 } #3542
89 map<ll, int> prime_factor(ll n, #3542

```

```

90 map<ll, int> *res = NULL) { // n <= 1<<61, ~1000/s (<500/s on CF)
91 if (!res) {
92     map<ll, int> res_act;
93     for (int p : small_primes) {
94         while (!(n % p)) {
95             ++res_act[p];
96             n /= p;
97         }
98     }
99     if (n != 1) prime_factor(n, &res_act);
100     return res_act;
101 }
102 if (is_prime(n)) {
103     ++(*res)[n];
104 } else {
105     ll factor = pollard_rho(n);
106     prime_factor(factor, res);
107     prime_factor(n / factor, res);
108 }
109 return map<ll, int>();
110 } // Usage: fact = prime
    factor(n);

```

#3770

#4612

#1963

#5350

%5477

## 27 Symmetric Submodular Functions; Queyrannes's algorithm

**SSF:** such function  $f : V \rightarrow R$  that satisfies  $f(A) = f(V/A)$  and for all  $x \in V, X \subseteq Y \subseteq V$  it holds that  $f(X+x) - f(X) \leq f(Y+x) - f(Y)$ . **Hereditary family:** such set  $I \subseteq 2^V$  so that  $X \subset Y \wedge Y \in I \Rightarrow X \in I$ . **Loop:** such  $v \in V$  so that  $v \notin I$ .  
breaklines

```

1 def minimize():
2     s = merge_all_loops()
3     while size >= 3:
4         t, u = find_pp()
5         {u} is a possible minimizer
6         tu = merge(t, u)
7         if tu not in I:
8             s = merge(tu, s)
9     for x in V:
10        {x} is a possible minimizer
11 def find_pp():
12     W = {s} # s as in minimizer()
13     todo = V/W
14     ord = []
15     while len(todo) > 0:
16         x = min(todo, key=lambda x: f(W+{x}) - f({x}))
17         W += {x}
18         todo -= {x}
19         ord.append(x)
20     return ord[-1], ord[-2]
21 def enum_all_minimal_minimizers(X):
22     # X is a inclusionwise minimal minimizer
23     s = merge(s, X)

```

```

24 yield X
25 for {v} in I:
26     if f({v}) == f(X):
27         yield X
28     s = merge(v, s)
29 while size(V) >= 3:
30     t, u = find_pp()
31     tu = merge(t, u)
32     if tu not in I:
33         s = merge(tu, s)
34     elif f({tu}) = f(X):
35         yield tu
36     s = merge(tu, s)

```

## 28 Berlekamp-Massey $O(LN)$

```

1 template <typename K>
2 static vector<K> berlekamp_massey(vector<K> ss) {
3     vector<K> ts(ss.size());
4     vector<K> cs(ss.size());
5     cs[0] = K::unity;
6     fill(cs.begin() + 1, cs.end(), K::zero);
7     vector<K> bs = cs;
8     int l = 0, m = 1;
9     K b = K::unity;
10    for (int k = 0; k < (int)ss.size(); k++) {
11        K d = ss[k];
12        assert(l <= k);
13        for (int i = 1; i <= l; i++) d += cs[i] * ss[k - i];
14        if (d == K::zero) {
15            m++;
16        } else if (2 * l <= k) {
17            K w = d / b;
18            ts = cs;
19            for (int i = 0; i < (int)cs.size() - m; i++)
20                cs[i + m] -= w * bs[i];
21            l = k + 1 - l;
22            swap(bs, ts);
23            b = d;
24            m = 1;
25        } else {
26            K w = d / b;
27            for (int i = 0; i < (int)cs.size() - m; i++)
28                cs[i + m] -= w * bs[i];
29            m++;
30        }
31    }
32    cs.resize(l + 1);
33    while (cs.back() == K::zero) cs.pop_back();
34    return cs;
35 }

```

#0349

#4390

#8445

#9661

#2815

#8888

#6267

%6267