

Machine Learning

by - Andrew Ng

Tue 19 Jul

week 4




Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

















For the rest of the details of the license, see <https://creativecommons.org/licenses/by-sa/2.0/legalcode>



Decision Trees

Decision Tree Model


Cat classification example

	Ear shape (x_1)	Face shape (x_2)	Whiskers (x_3)	Cat
	Pointy 	Round 	Present 	1
	Floppy 	Not round 	Present	1
	Floppy	Round	Absent 	0
	Pointy	Not round	Present	0
	Pointy	Round	Present	1
	Pointy	Round	Absent	1
	Floppy	Not round	Absent	0
	Pointy	Round	Absent	1
	Floppy	Round	Absent	0
	Floppy	Round	Absent	0


Categorical (discrete values)

X





Y



Decision Tree



Decision Tree






Decision Trees

Learning Process


Decision Tree Learning




Decision Tree Learning




Decision Tree Learning



Decision Tree Learning




Decision Tree Learning




4/4 cats


Decision Tree Learning




Decision Tree Learning




Decision Tree Learning




Decision Tree Learning



Decision Tree Learning



Decision Tree Learning



Decision Tree Learning

Decision 1: How to choose what feature to split on at each node?







Maximize purity (or minimize impurity)

all cats or all dogs

Decision Tree Learning

Decision 1: How to choose what feature to split on at each node?


Maximize purity (or minimize impurity)



Decision Tree Learning

Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth




Decision Tree Learning

Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth


*{ To not make a very big tree
& reduce the risk of overfitting }*



Decision Tree Learning

Decision 2: When do you stop splitting?


- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth
- When improvements in purity score are below a threshold
- When number of examples in a node is below a threshold



Decision Tree Learning


Decision 2: When do you stop splitting?

- When a node is 100% one class
- When splitting a node will result in the tree exceeding a maximum depth
- When improvements in purity score are below a threshold
- When number of examples in a node is below a threshold





Stanford
ONLINE



Decision Tree Learning


Measuring purity

Entropy

Entropy as a measure of impurity

p_1 = fraction of examples that are cats

entropy



$$p_1 = 0 \quad H(p_1) = 0$$

$$p_1 = 2/6 \quad H(p_1) = 0.92 \quad \leftarrow$$

$$p_1 = 3/6 \quad H(p_1) = 1$$


$$p_1 = 5/6 \quad H(p_1) = 0.65 \quad \leftarrow \quad \text{more pure}$$

$$p_1 = 6/6 \quad H(p_1) = 0$$

$$H(p_1) \propto \frac{1}{\text{Purity}}$$

Entropy as a measure of impurity

p_1 = fraction of examples that are cats




$$p_0 = 1 - p_1$$

$$H(p_1) = -p_1 \log_2(p_1) - p_0 \log_2(p_0)$$

$$H(p_1) = -p_1 \log_2(p_1) - (1 - p_1) \log_2(1 - p_1)$$

Note: " $0 \log(0)$ " = 0

if $p_i = 0$




Decision Tree Learning

Choosing a split: Information
Gain *reducing impurity*

Choosing a split

$$p_1 = 5/10 = 0.5$$

$$H(0.5) = 1$$



$$p_1 = 4/5 = 0.8 \quad p_1 = 1/5 = 0.2$$


$$H(0.8) = 0.72 \quad H(0.2) = 0.72$$

$$H(0.5) - \left(\frac{5}{10} H(0.8) + \frac{5}{10} H(0.2) \right)$$

$$= 0.28$$

weighted avg.

$$H(0.5) = 1$$




$$p_1 = 4/7 = 0.57 \quad p_1 = 1/3 = 0.33$$

$$H(0.57) = 0.99 \quad H(0.33) = 0.92$$

$$H(0.5) - \left(\frac{7}{10} H(0.57) + \frac{3}{10} H(0.33) \right)$$

$$= 0.03$$

info gain
not too small then no splitting to avoid overfitting



$$p_1 = 3/4 = 0.75 \quad p_1 = 2/6 = 0.33$$

$$H(0.75) = 0.81 \quad H(0.33) = 0.92$$


$$H(0.5) - \left(\frac{4}{10} H(0.75) + \frac{6}{10} H(0.33) \right)$$

$$= 0.12$$

Information Gain



$$p_1^{\text{root}} = 5/10 = 0.5$$



$$p_1^{\text{left}} = 4/5$$

$$w^{\text{left}} = 5/10$$


$$p_1^{\text{right}} = 1/5$$

$$w^{\text{right}} = 5/10$$

Information gain

$$= H(p_1^{\text{root}}) - \left(w^{\text{left}} H(p_1^{\text{left}}) + w^{\text{right}} H(p_1^{\text{right}}) \right)$$

redⁿ in entropy




Decision Tree Learning

Putting it together


Decision Tree Learning

- Start with all examples at the root node
- Calculate information gain for all possible features, and pick the one with the highest information gain
- Split dataset according to selected feature, and create left and right branches of the tree
- Keep repeating splitting process until stopping criteria is met:
 - When a node is 100% one class
 - When splitting a node will result in the tree exceeding a maximum depth
 - Information gain from additional splits is less than threshold
 - When number of examples in a node is below a threshold

Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting




Recursive splitting



Recursive splitting
















Recursive algorithm




Decision Tree Learning

Using one-hot encoding of
categorical features











Features with three possible values

	Ear shape (x_1)	Face shape (x_2)	Whiskers (x_3)	Cat (y)
	Pointy 	Round	Present	1
	Oval	Not round	Present	1
	Oval 	Round	Absent	0
	Pointy	Not round	Present	0
	Oval	Round	Present	1
	Pointy	Round	Absent	1
	Floppy 	Not round	Absent	0
	Oval	Round	Absent	1
	Floppy	Round	Absent	0
	Floppy	Round	Absent	0

3 possible values













One hot encoding

	Ear shape	Pointy ears	Floppy ears	Oval ears	Face shape	Whiskers	Cat
	Pointy	1	0	0	Round	Present	1
	Oval	0	0	1	Not round	Present	1
	Oval	0	0	1	Round	Absent	0
	Pointy	1	0	0	Not round	Present	0
	Oval	0	0	1	Round	Present	1
	Pointy	1	0	0	Round	Absent	1
	Floppy	0	1	0	Not round	Absent	0
	Oval	0	0	1	Round	Absent	1
	Floppy	0	1	0	Round	Absent	0
	Floppy	0	1	0	Round	Absent	0











One hot encoding


If a categorical feature can take on k values, create k binary features (0 or 1 valued).

One hot encoding

Ear shape		Pointy ears	Floppy ears	Oval ears	Face shape	Whiskers	Cat
	Pointy	1	0	0	Round	Present	1
	Oval	0	0	1	Not round	Present	1
	Oval	0	0	1	Round	Absent	0
	Pointy	1	0	0	Not round	Present	0
	Oval	0	0	1	Round	Present	1
	Pointy	1	0	0	Round	Absent	1
	Floppy	0	1	0	Not round	Absent	0
	Oval	0	0	1	Round	Absent	1
	Floppy	0	1	0	Round	Absent	0
	Floppy	0	1	0	Round	Absent	0

One hot encoding and neural networks

	Pointy ears	Floppy ears	Round ears	Face shape	Whiskers	Cat
	1	0	0	Round 1	Present 1	1
	0	0	1	Not round 0	Present 1	1
	0	0	1	Round 1	Absent 0	0
	1	0	0	Not round 0	Present 1	0
	0	0	1	Round 1	Present 1	1
	1	0	0	Round 1	Absent 0	1
	0	1	0	Not round 0	Absent 0	1
	0	0	1	Round 1	Absent 0	1
	0	1	0	Round 1	Absent 0	1
	0	1	0	Round 1	Absent 0	1













Decision Tree Learning



Continuous valued features

Continuous features



	Ear shape	Face shape	Whiskers	Weight (lbs.)	Cat
	Pointy	Round	Present	7.2	1
	Floppy	Not round	Present	8.8	1
	Floppy	Round	Absent	15	0
	Pointy	Not round	Present	9.2	0
	Pointy	Round	Present	8.4	1
	Pointy	Round	Absent	7.6	1
	Floppy	Not round	Absent	11	0
	Pointy	Round	Absent	10.2	1
	Floppy	Round	Absent	18	0
	Floppy	Round	Absent	20	0


Splitting on a continuous variable



$$H(0.5) - \left(\frac{2}{10} H\left(\frac{2}{2}\right) + \frac{8}{10} H\left(\frac{3}{8}\right) \right) = 0.24$$

$$H(0.5) - \left(\frac{4}{10} H\left(\frac{4}{4}\right) + \frac{6}{10} H\left(\frac{1}{6}\right) \right) = 0.61$$











$$H(0.5) - \left(\frac{7}{10} H\left(\frac{5}{7}\right) + \frac{3}{10} H\left(\frac{0}{3}\right) \right) = 0.40$$



Decision Tree Learning


Regression Trees (optional)

Regression with Decision Trees: Predicting a number

	Ear shape	Face shape	Whiskers	Weight (lbs.)
	Pointy	Round	Present	7.2
	Floppy	Not round	Present	8.8
	Floppy	Round	Absent	15
	Pointy	Not round	Present	9.2
	Pointy	Round	Present	8.4
	Pointy	Round	Absent	7.6
	Floppy	Not round	Absent	11
	Pointy	Round	Absent	10.2
	Floppy	Round	Absent	18
	Floppy	Round	Absent	20


X Y

Regression with Decision Trees



Handwritten blue notes:
 $2 = \frac{2}{10}$
 $1 = \frac{1}{10}$

Choosing a split



Weights: 7.2, 9.2, 8.4, 7.6, 10.2

Weights: 8.8, 15, 11, 18, 20


Variance: 1.47

Variance: 21.87

$$w^{\text{left}} = \frac{5}{10}$$

$$w^{\text{right}} = \frac{5}{10}$$

$$20.51 - \left(\frac{5}{10} * 1.47 + \frac{5}{10} * 21.87 \right) = 8.84$$



Weights: 7.2, 15, 8.4, 7.6, 10.2, 18, 20

Weights: 8.8, 9.2, 11


Variance: 27.80

Variance: 1.37

$$w^{\text{left}} = \frac{7}{10}$$

$$w^{\text{right}} = \frac{3}{10}$$

$$20.51 - \left(\frac{7}{10} * 27.80 + \frac{3}{10} * 1.37 \right) = 0.64$$



Weights: 7.2, 8.8, 9.2, 8.4

Weights: 15, 7.6, 11, 10.2, 18, 20


Variance: 0.75

Variance: 23.32

$$w^{\text{left}} = \frac{4}{10}$$

$$w^{\text{right}} = \frac{6}{10}$$



$$20.51 - \left(\frac{4}{10} * 0.75 + \frac{6}{10} * 23.32 \right) = 6.22$$



Tree ensembles

Using multiple decision trees

Trees are highly sensitive to small changes of the data




Tree ensemble


New test example




Ear shape: Pointy
Face shape: Not Round
Whiskers: Present



Prediction: Cat



Prediction: Not cat



Prediction: Cat

Final prediction: Cat



Tree ensembles


Sampling with replacement

Sampling with replacement


Tokens




Putting it back











Hand-drawn green arrows showing a cycle from the first token back to the pool, and from the second token back to the pool, illustrating the replacement process.


Sampling with replacement:



Sampling with replacement



	Ear shape	Face shape	Whiskers	Cat
	Pointy	Round	Present	1
	Floppy	Not round	Absent	0
	Pointy	Round	Absent	1
	Pointy	Not round	Present	0
	Floppy	Not round	Absent	0
	Pointy	Round	Absent	1
	Pointy	Round	Present	1
	Floppy	Not round	Present	1
	Floppy	Round	Absent	0
	Pointy	Round	Absent	1



Tree ensembles

Random forest algorithm

↳ Go build Tree ensemble


Generating a tree sample

Given training set of size m

For $b = 1$ to B *no. of trees*

Use sampling with replacement to create a new training set of size m

Train a decision tree on the new dataset



Bagged decision tree

Randomizing the feature choice

At each node, when choosing a feature to use to split, if n features are available, pick a random subset of $k < n$ features and allow the algorithm to only choose from that subset of features.


$$k = \sqrt{n}$$

if $n \gg$

Random forest algorithm *avg a lot of small no of features*



Stanford
ONLINE



Tree ensembles

much better

XGBoost

Boosted trees intuition

Given training set of size m

For $b = 1$ to B :


Use sampling with replacement to create a new training set of size m

But instead of picking from all examples with equal ($1/m$) probability, make it more likely to pick examples that the previously trained trees misclassify

Train a decision tree on the new dataset

generated dataset

Ear shape	Face shape	Whiskers	Cat
Pointy	Round	Present	Yes
Floppy	Round	Absent	No
Floppy	Round	Absent	No
Pointy	Round	Present	Yes
Pointy	Not Round	Present	Yes
Floppy	Round	Absent	No
Floppy	Round	Present	Yes
Pointy	Not Round	Absent	No
Pointy	Not Round	Absent	No
Pointy	Not Round	Present	Yes



Ear shape	Face shape	Whiskers	Prediction
Pointy	Round	Present	Cat ✓
Floppy	Not Round	Present	Not cat ✗
Floppy	Round	Absent	Not cat ✓
Pointy	Not Round	Present	Not cat ✗
Pointy	Round	Present	Cat ✓
Pointy	Round	Absent	Not cat ✗
Floppy	Not Round	Absent	Not cat ✓
Pointy	Round	Absent	Not cat ✗
Floppy	Round	Absent	Not cat ✓
Floppy	Round	Absent	Not cat ✓

1, 2, ..., b-1
Higher chance to pick b
original dataset

XGBoost (eXtreme Gradient Boosting)

- Open source implementation of boosted trees
- Fast efficient implementation
- Good choice of default splitting criteria and criteria for when to stop splitting
- Built in regularization to prevent overfitting
- Highly competitive algorithm for machine learning competitions (eg: Kaggle competitions)

Using XGBoost

Classification

```
→ from xgboost import XGBClassifier  
  
→ model = XGBClassifier()  
  
→ model.fit(X_train, y_train)  
→ y_pred = model.predict(X_test)
```

Regression

```
from xgboost import XGBRegressor  
  
model = XGBRegressor()  
  
model.fit(X_train, y_train)  
y_pred = model.predict(X_test)
```





Conclusion

When to use decision trees

Decision Trees vs Neural Networks

Decision Trees and Tree ensembles

- Works well on tabular (structured) data {housing prices}
- Not recommended for unstructured data (images, audio, text)
- Fast



Decision Trees vs Neural Networks

Decision Trees and Tree ensembles

- Works well on tabular (structured) data
- Not recommended for unstructured data (images, audio, text)
- Fast
- Small decision trees may be human interpretable

Neural Networks

- Works well on all types of data, including tabular (structured) and unstructured data
- May be slower than a decision tree
- Works with transfer learning
- When building a system of multiple models working together, it might be easier to string together multiple neural networks