DUO STANDARD/FORTE


Lift+Turn





Standard version shown


- Opening angles: 75°, 90°, 110°
- Unhanded design
- For use with wooden lids or lids with aluminium frames, also suitable for use as flap stay
- For flaps with aluminium frame width 20 or from 45 mm
- With braking and locking mechanisms, can be adjusted using an SW4 hex key
- Self closing function
- Clip-mounting on pre-mounted screw fixing brackets, no tools required
- Height ±2 mm, side +3/-1 mm, tilt ±1.5 mm and pull adjustment facility
- Steel bracket, zinc alloy lid stay in nickel-plated, black or white
- Installation instructions included


Duo Standard flap/lid stay

















For edge distance 37 mm (A)




For edge distance 28 mm (A)




Note: When used as a flap stay, a magnet has to be fitted with an installation height of 189 +32 mm and an outreach of 160 +32 mm



Mounting bracket for fixing to flaps made of wood



Mounting bracket for fixing to aluminium frames



Screw-on bracket for fixing to lateral panel

- Light version - min. installation depth 130 mm
- Order fixing screws separately
- Order qty: 1 pc

Table showing maximum flap weight

	Maximum flap weight (kg)			
	Function braking		Function braking	
Flap height	1 stay	2 stays	1 stay	2 stays
For opening angle 75°				
200	9.0	15.0	11.5	15.0
250	7.0	15.0	9.0	15.0
300	6.0	12.0	7.5	15.0
350	5.0	10.0	6.5	13.0
400	4.5	9.0	6.0	11.5
450	4.0	8.0	5.0	10.0
500	3.5	7.0	4.5	9.0
For opening angle 90°				
200	7.5	15.0	9.5	15.0
250	6.0	12.0	7.5	15.0
300	5.0	10.0	6.0	13.0
350	4.0	8.5	5.5	11.0
400	3.5	7.0	5.0	10.0
450	3.5	6.5	4.0	8.5
500	3.0	6.0	4.0	8.0
For opening angle 110°				
200	6.0	12.0	8.0	15.0
250	5.0	9.5	6.0	12.0
300	4.0	8.0	5.0	10.0
350	3.0	7.0	4.0	9.0
400	3.0	6.0	4.0	7.5
450	2.5	5.0	3.5	7.0
500	2.0	5.0	3.0	6.0

25 YEARS

FIXINGS REQUIRED HOSPA Ø 3.5

FIXINGS REQUIRED VARIANTA ⌀5

For wooden lids/lids with aluminium frame, frame width from 45 mm

For Hospa screws

Distance from edge	Nickel-plated	White	Black
28 mm	373.66.611	373.66.261	373.66.211
37 mm	373.66.612	373.66.262	373.66.212

For Varianta screws

Distance from edge	Nickel-plated	White	Black
37 mm	373.66.614	373.66.264	373.66.214

For lids with aluminium frame, frame width from 20 mm

For sheet metal screws


Distance from edge	28 mm	37 mm
Nickel-plated	373.66.621	373.66.622


DRAWER SYSTEMS, STAYS AND HINGES 2015, © Häfele U.K. Ltd 2015. Dimensional data not binding. We reserve the right to alter specifications without notice.


Duo Forte flap/lid stay




Forte version shown








Installation as flap stay




Separate catch required




No separate catch required. Space required for fitting inside the cabinet when the flap is being closed: 175 mm from front edge of cabinet

For edge distance 37 mm (A)



For edge distance 28 mm (A)



- > Heavy version - min. installation depth 175 mm
- > Order fixing screws separately
- > Order qty: 1 pc

Table showing maximum flap weight

	Maximum flap weight (kg)			
	Function locking		Function braking	
Flap height	1 stay	2 stays	1 stay	2 stays
For opening angle 75°				
200	14.0	15.0	15.0	15.0
250	11.5	15.0	15.0	15.0
300	9.0	15.0	12.0	15.0
350	8.0	15.0	11.0	15.0
400	7.0	14.0	9.0	15.0
450	6.0	12.5	8.0	15.0
500	5.5	11.0	7.0	15.0
550	5.0	10.0	6.5	13.0
600	5.0	9.5	6.0	12.0
650	4.0	8.5	5.5	11.0
700	4.0	8.0	5.0	10.5
For opening angle 90°				
200	12.0	15.0	15.0	15.0
250	9.5	15.0	12.0	15.0
300	8.0	15.0	10.0	15.0
350	7.0	13.5	9.0	15.0
400	6.0	12.0	8.0	15.0
450	5.0	11.0	7.0	14.0
500	5.0	9.5	6.0	12.0
550	4.0	8.5	5.5	11.0
600	4.0	8.0	5.0	10.0
650	3.5	7.0	5.0	9.5
700	3.0	7.0	4.0	9.0
For opening angle 110°				
200	9.5	15.0	12.5	15.0
250	7.5	15.0	10.0	15.0
300	6.5	12.5	8.0	15.0
350	5.5	11.0	7.0	14.0
400	4.5	9.5	6.0	12.5
450	4.0	8.5	5.5	11.0
500	4.0	7.5	5.0	10.0
550	3.5	7.0	4.0	9.0
600	3.0	6.0	4.0	8.0
650	3.0	5.5	4.0	7.5
700	3.0	5.0	3.5	7.0

25 YEARS | FIXINGS REQUIRED HOSPA Ø 3.5 | FIXINGS REQUIRED VARIANTA ⌀5

For wooden lids/lids with aluminium frame, frame width from 45 mm

For Hospa screws

Distance from edge	Nickel-plated	White	Black
28 mm	373.66.631	373.66.371	-
37 mm	373.66.632	373.66.372	373.66.312

For Varianta screws

Distance from edge	Nickel-plated	White	Black
37 mm	373.66.634	373.66.374	373.66.314

For lids with aluminium frame, frame width from 20 mm

For sheet metal screws

Distance from edge	28 mm	37 mm
Nickel-plated	373.66.641	373.66.642

DRAWER SYSTEMS, STAYS AND HINGES 2015, © Häfele U.K. Ltd 2015. Dimensional data not binding. We reserve the right to alter specifications without notice.