

Nocta Agency - Portfolio

Export du code source du site portfolio (sans les vitrines demo bella-vista, nova-habitat, titan-fitness ni les autres projets demo).

Date : 28/06/2026 01:03

Fichiers : 59

.env.example

```
# ngrok ? tunnel public pour revue UX/UI (https://dashboard.ngrok.com/get-started/your-authtoken)
NGROK_AUTHTOKEN=votre_token_ngrok
```

```
# Supabase ? Project Settings ? API
# Pour Maison (auth client) : préfixe NEXT_PUBLIC_ recommandé
NEXT_PUBLIC_SUPABASE_URL=https://VOTRE_PROJECT_REF.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=votre_cle_anon
SUPABASE_URL=https://VOTRE_PROJECT_REF.supabase.co
SUPABASE_ANON_KEY=votre_cle_anon
```

```
# Requis pour Maison (foyer + clé) ? Settings ? API ? service_role
# Ne jamais exposer côté client
SUPABASE_SERVICE_ROLE_KEY=votre_cle_service_role
```

```
# Optionnel ? signature session cookie Maison (sinon dérivé de service_role)
# MAISON_SESSION_SECRET=une_chaine_secrete_longue
```

```
# IA locale ? Qwen via Ollama (100 % local, aucune API cloud)
OLLAMA_BASE_URL=http://localhost:11434
OLLAMA_MODEL=qwen2.5-coder
# OLLAMA_TIMEOUT_MS=120000
```

```
# Mode dev Maison ? bypass connexion supermarché (local uniquement)
# MAISON_DEV_MODE=true
# Foyer dev pré-configuré : clé FAM-DEVMODE (bypass également la connexion courses)
```

```
# e.Leclerc Drive ? connexion compte (OAuth partenaire ou redirection login)
# URL publique de l'app (callbacks OAuth) ? requis en prod / ngrok
# MAISON_APP_URL=https://votre-domaine.ngrok-free.app
# MAISON_LECLERC_OAUTH_CLIENT_ID=
# MAISON_LECLERC_OAUTH_CLIENT_SECRET=
# MAISON_LECLERC_OAUTH_AUTHORIZE_URL=https://www.e.leclerc/auth
# MAISON_LECLERC_OAUTH_TOKEN_URL=
# MAISON_LECLERC_OAUTH_SCOPE=openid profile drive
# MAISON_LECLERC_OAUTH_RETURN_URL_PARAM=returnUrl
```

```
# Notion ? base « Waitlist »
NOTION_TOKEN=ntn_votre_token
NOTION_WAITLIST_DATABASE_ID=35356700-a3d8-40f2-afdf-667543feb15a
NOTION_DIRECT_SYNC=true
```

app/api/priority-list/route.ts

```
import { NextResponse } from "next/server";
import type { PriorityListSubmission } from "@/lib/priority-list";
import { syncWaitlistToNotion } from "@/lib/notion-waitlist";
import { insertWaitlistEntry } from "@/lib/supabase";
import type { WaitlistEntry } from "@/lib/waitlist-types";

function isValidEmail(email: string) {
  return /^[^\\s@]+@[^\\s@]+\\.([^\\s@]+)$/.test(email);
}

function parseBody(body: unknown): PriorityListSubmission | null {
  if (!body || typeof body !== "object") return null;

  const data = body as Record<string, unknown>;
  const name = typeof data.name === "string" ? data.name.trim() : "";
  const email = typeof data.email === "string" ? data.email.trim() : "";
  const company = typeof data.company === "string" ? data.company.trim() : "";
  const website =
    typeof data.website === "string" && data.website.trim()
      ? data.website.trim()
      : undefined;
  const need = typeof data.need === "string" ? data.need.trim() : "";

  if (!name || !email || !company || !need) return null;
  if (!isValidEmail(email)) return null;

  return { name, email, company, website, need };
}

function toWaitlistEntry(submission: PriorityListSubmission): WaitlistEntry {
  return {
    email: submission.email,
    name: submission.name,
    company: submission.company,
    website: submission.website,
    need: submission.need,
    source: "priority_list",
  };
}

export async function POST(request: Request) {
  let rawBody: unknown;

  try {
    rawBody = await request.json();
  } catch (parseErr) {
    console.error("[priority-list] JSON invalide:", parseErr);
    return NextResponse.json(
      { ok: false, message: "Corps de requête invalide." },
      { status: 400 },
    );
  }

  console.info("[priority-list] body reçu:", JSON.stringify(rawBody));

  const submission = parseBody(rawBody);

  if (!submission) {
    console.warn("[priority-list] validation échouée:", JSON.stringify(rawBody));
    return NextResponse.json(
      { ok: false, message: "Veuillez remplir tous les champs obligatoires." },
      { status: 400 },
    );
  }
}
```

```
const entry = toWaitlistEntry(submission);
console.info("[priority-list] entry:", JSON.stringify(entry));

const supabaseResult = await insertWaitlistEntry(entry);
console.info("[priority-list] Supabase:", JSON.stringify(supabaseResult));

if (!supabaseResult.ok) {
  return NextResponse.json(
    { ok: false, message: supabaseResult.message, hint: supabaseResult.hint },
    { status: 500 },
  );
}

try {
  const notionResult = await syncWaitlistToNotion(entry);
  console.info("[priority-list] Notion:", JSON.stringify(notionResult));

  if (!notionResult.ok && !("skipped" in notionResult)) {
    console.warn(
      "[priority-list] Notion échec (inscription Supabase OK):",
      notionResult.message,
    );
  }
} catch (notionErr) {
  console.error("[priority-list] Notion exception (Supabase OK):", notionErr);
}

return NextResponse.json({
  ok: true,
  message:
    "Merci pour votre intérêt. Votre demande a bien été enregistrée dans la liste prioritaire.",
});
}
```

app/api/waitlist/route.ts

```
import { NextResponse } from "next/server";
import { syncWaitlistToNotion } from "@lib/notion-waitlist";
import { insertWaitlistEntry } from "@lib/supabase";

export async function POST(req: Request) {
  let body: unknown;

  try {
    body = await req.json();
  } catch (parseErr) {
    console.error("[waitlist] JSON invalide:", parseErr);
    return NextResponse.json({ error: "Invalid JSON" }, { status: 400 });
  }

  console.info("[waitlist] body reçu:", JSON.stringify(body));

  const email = typeof (body as { email?: unknown })?.email === "string"
    ? (body as { email: string }).email.trim()
    : "";

  if (!email || !email.includes("@")) {
    return NextResponse.json({ error: "Invalid email" }, { status: 400 });
  }

  const entry = { email, source: "waitlist_email" };
  console.info("[waitlist] entry:", JSON.stringify(entry));

  const result = await insertWaitlistEntry(entry);
  console.info("[waitlist] Supabase:", JSON.stringify(result));

  if (!result.ok) {
    return NextResponse.json(
      { error: result.message, code: result.code, hint: result.hint },
      { status: 500 },
    );
  }

  try {
    const notionResult = await syncWaitlistToNotion(entry);
    console.info("[waitlist] Notion:", JSON.stringify(notionResult));
  } catch (notionErr) {
    console.error("[waitlist] Notion exception (Supabase OK):", notionErr);
  }

  return NextResponse.json({ success: true });
}
```

app/globals.css

```
@import "tailwindcss";

:root {
  --background: #ffffff;
  --foreground: #121316;
  --muted: #596074;
  --surface: rgba(255, 255, 255, 0.86);
  --surface-strong: rgba(255, 255, 255, 0.98);
  --border: rgba(44, 48, 60, 0.16);
  --primary: #1a1c22;
  --primary-strong: #2b2f38;
  --primary-soft: #e6e9f4;
  --ring: rgba(100, 118, 170, 0.42);
  --glow: rgba(97, 120, 190, 0.2);
  --glow-soft: rgba(104, 126, 192, 0.12);
  --button-foreground: #f6f8ff;
  /* Accent & hero tokens */
  --accent: #6178be;
  --accent-strong: #4a62a8;
  --accent-soft: rgba(97, 120, 190, 0.14);
  --accent-gradient-start: #5a72b8;
  --accent-gradient-end: #97a8d6;
  --hero-glow: rgba(97, 120, 190, 0.32);
  --hero-glow-soft: rgba(104, 126, 192, 0.18);
  --text-highlight: rgba(97, 120, 190, 0.12);
  --pricing-gold: #c9b06a;
  --pricing-gold-soft: rgba(201, 176, 106, 0.22);
}

@theme inline {
  --color-background: var(--background);
  --color-foreground: var(--foreground);
  --font-sans: var(--font-body);
  --font-mono: var(--font-geist-mono);
}

[data-theme="dark"] {
  --background: #0a0a0d;
  --foreground: #f6f8ff;
  --muted: #9ca6c1;
  --surface: rgba(20, 22, 30, 0.72);
  --surface-strong: rgba(28, 31, 44, 0.9);
  --border: rgba(170, 178, 204, 0.2);
  --primary: #f2f4ff;
  --primary-strong: #d8deef;
  --primary-soft: #2a2f3f;
  --ring: rgba(125, 146, 212, 0.44);
  --glow: rgba(109, 132, 198, 0.22);
  --glow-soft: rgba(110, 132, 196, 0.14);
  --button-foreground: #0d0f14;
  --accent: #849ce6;
  --accent-strong: #a8b8f0;
  --accent-soft: rgba(132, 156, 230, 0.16);
  --accent-gradient-start: #97a8d6;
  --accent-gradient-end: #c4d0f4;
  --hero-glow: rgba(109, 132, 198, 0.38);
  --hero-glow-soft: rgba(110, 132, 196, 0.22);
  --text-highlight: rgba(132, 156, 230, 0.14);
  --pricing-gold: #dbc88a;
  --pricing-gold-soft: rgba(219, 200, 138, 0.18);
}

body {
  background: var(--background);
  color: var(--foreground);
```

```

    font-family: var(--font-body), system-ui, sans-serif;
    letter-spacing: -0.01em;
}

section[id] {
    scroll-margin-top: 6.5rem;
}

.site-header-shell {
    pointer-events: none;
}

.site-header {
    position: relative;
    pointer-events: auto;
    isolation: isolate;
    border: 1px solid color-mix(in srgb, var(--border) 42%, transparent);
    background: color-mix(in srgb, var(--surface) 14%, transparent);
    backdrop-filter: blur(4px) saturate(1.08);
    -webkit-backdrop-filter: blur(4px) saturate(1.08);
    box-shadow:
        0 0 0 1px color-mix(in srgb, var(--ring) 8%, transparent) inset,
        0 1px 0 color-mix(in srgb, white 5%, transparent) inset,
        0 12px 32px -28px color-mix(in srgb, var(--hero-glow) 22%, transparent),
        0 4px 16px -12px rgba(0, 0, 0, 0.14);
    transition:
        background-color 300ms ease,
        border-color 300ms ease,
        box-shadow 300ms ease;
}

.site-header::before {
    content: "";
    position: absolute;
    inset: 0;
    border-radius: inherit;
    background: linear-gradient(
        135deg,
        color-mix(in srgb, white 5%, transparent) 0%,
        transparent 55%,
        color-mix(in srgb, var(--accent) 2%, transparent) 100%
    );
    pointer-events: none;
}

.site-header > * {
    position: relative;
    z-index: 1;
}

[data-theme="light"] .site-header {
    background: color-mix(in srgb, var(--surface-strong) 18%, transparent);
    box-shadow:
        0 0 0 1px color-mix(in srgb, var(--ring) 6%, transparent) inset,
        0 1px 0 rgba(255, 255, 255, 0.28) inset,
        0 12px 28px -26px color-mix(in srgb, var(--hero-glow) 14%, transparent),
        0 6px 18px -16px rgba(36, 48, 88, 0.06);
}

[data-theme="light"] .site-header::before {
    background: linear-gradient(
        135deg,
        rgba(255, 255, 255, 0.22) 0%,
        transparent 55%,
        color-mix(in srgb, var(--accent) 2%, transparent) 100%
    );
}

```

```
.hero-display {
  font-family: var(--font-display), var(--font-body), system-ui, sans-serif;
  font-size: clamp(2.35rem, 5.8vw, 4.25rem);
  line-height: 1.04;
  letter-spacing: -0.04em;
  font-weight: 600;
}

.hero-body {
  font-family: var(--font-body), system-ui, sans-serif;
}

.hero-text-gradient {
  background: linear-gradient(
    120deg,
    var(--accent-gradient-start) 0%,
    var(--accent-gradient-end) 55%,
    var(--foreground) 100%
  );
  -webkit-background-clip: text;
  background-clip: text;
  color: transparent;
}

.hero-text-accent {
  color: var(--accent);
}

.hero-highlight-span {
  background: linear-gradient(
    to right,
    var(--text-highlight),
    transparent 88%
  );
  box-decoration-break: clone;
  -webkit-box-decoration-break: clone;
  padding: 0.08em 0.2em;
  border-radius: 0.25rem;
}

.hero-title-glow {
  background: radial-gradient(
    ellipse at 40% 50%,
    var(--hero-glow-soft),
    transparent 68%
  );
  filter: blur(28px);
  opacity: 0.95;
}

.hero-divider {
  background: linear-gradient(
    90deg,
    transparent,
    var(--accent) 20%,
    var(--accent-gradient-end) 50%,
    transparent 100%
  );
  opacity: 0.55;
}

.hero-badge {
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--accent) 18%, transparent) inset,
    0 12px 28px -18px var(--hero-glow);
  transition:
    border-color 280ms ease,
```



```
    box-shadow 280ms ease,
    transform 280ms ease;
}

.hero-badge:hover {
  border-color: color-mix(in srgb, var(--accent) 35%, var(--border));
  transform: translateY(-1px);
}

.hero-cta-primary {
  transition:
    transform 320ms cubic-bezier(0.22, 1, 0.36, 1),
    box-shadow 320ms ease,
    filter 280ms ease;
}

.hero-cta-primary:hover {
  transform: translateY(-2px) scale(1.015);
  box-shadow:
    0 0 0 1px rgba(255, 255, 255, 0.18) inset,
    0 32px 64px -28px var(--hero-glow) !important;
  filter: brightness(1.04);
}

.hero-cta-secondary {
  transition:
    transform 320ms cubic-bezier(0.22, 1, 0.36, 1),
    border-color 280ms ease,
    box-shadow 280ms ease,
    background-color 280ms ease;
}

.hero-cta-secondary:hover {
  transform: translateY(-2px);
  border-color: color-mix(in srgb, var(--accent) 45%, var(--border));
  box-shadow: 0 16px 36px -24px var(--hero-glow);
}

.hero-proof-pill {
  display: inline-flex;
  align-items: center;
  border-radius: 9999px;
  border: 1px solid var(--border);
  background: var(--surface);
  padding: 0.35rem 0.75rem;
  font-size: 0.72rem;
  color: var(--muted);
  transition:
    border-color 280ms ease,
    color 280ms ease,
    background-color 280ms ease;
}

.hero-proof-pill:hover {
  border-color: color-mix(in srgb, var(--accent) 35%, var(--border));
  color: var(--foreground);
  background: var(--surface-strong);
}

.hero-visual-glow {
  background: radial-gradient(circle, var(--hero-glow-soft), transparent 70%);
}

.hero-visual-card {
  background: linear-gradient(
    165deg,
    color-mix(in srgb, var(--surface-strong) 92%, transparent),
```

```

        color-mix(in srgb, var(--accent) 6%, var(--surface))
    );
    backdrop-filter: blur(16px);
    box-shadow:
        0 0 0 1px color-mix(in srgb, var(--accent) 14%, var(--border)) inset,
        0 40px 80px -44px var(--hero-glow);
    transition:
        transform 420ms cubic-bezier(0.22, 1, 0.36, 1),
        box-shadow 420ms ease;
}

.hero-visual-card:hover {
    transform: translateY(-4px);
    box-shadow:
        0 0 0 1px color-mix(in srgb, var(--accent) 22%, var(--border)) inset,
        0 48px 96px -40px var(--hero-glow);
}

.hero-visual-chrome {
    background: color-mix(in srgb, var(--surface-strong) 80%, transparent);
}

.hero-chart-bar {
    background: linear-gradient(
        to top,
        var(--accent-strong),
        var(--accent-gradient-end)
    );
    opacity: 0.85;
    animation: hero-bar-rise 1.2s cubic-bezier(0.22, 1, 0.36, 1) both;
}

.hero-stat-card {
    transition:
        border-color 280ms ease,
        transform 280ms ease,
        box-shadow 280ms ease;
}

.hero-stat-card:hover {
    border-color: color-mix(in srgb, var(--accent) 30%, var(--border));
    transform: translateY(-2px);
    box-shadow: 0 12px 28px -20px var(--hero-glow);
}

.hero-metric-icon {
    transition: transform 320ms ease, border-color 280ms ease;
}

.hero-visual-card:hover .hero-metric-icon {
    transform: scale(1.06);
    border-color: color-mix(in srgb, var(--accent) 35%, var(--border));
}

@keyframes hero-bar-rise {
    from {
        transform: scaleY(0);
        transform-origin: bottom;
        opacity: 0;
    }
    to {
        transform: scaleY(1);
        transform-origin: bottom;
        opacity: 0.85;
    }
}

```

```
@media (prefers-reduced-motion: reduce) {
  *,
  *::before,
  *::after {
    animation-duration: 0.01ms !important;
    animation-iteration-count: 1 !important;
    transition-duration: 0.01ms !important;
    scroll-behavior: auto !important;
  }
}

.premium-interactive {
  transition:
    transform 380ms cubic-bezier(0.22, 1, 0.36, 1),
    box-shadow 380ms cubic-bezier(0.22, 1, 0.36, 1),
    border-color 300ms ease;
}

.premium-interactive:hover {
  transform: translateY(-4px) scale(1.01);
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--ring) 18%, transparent) inset,
    0 22px 48px -28px color-mix(in srgb, var(--hero-glow) 38%, transparent);
}

.tilt-card-clip {
  isolation: isolate;
  border-radius: 1.5rem;
}

.tilt-card-glow {
  mix-blend-mode: soft-light;
}

.tilt-card-wrap {
  position: relative;
  transform-style: preserve-3d;
  will-change: transform;
  backface-visibility: hidden;
  border-radius: 1.5rem;
}

.tilt-card-wrap:hover {
  box-shadow:
    0 0 0 1px rgba(132, 156, 230, 0.22) inset,
    0 40px 70px -36px rgba(36, 48, 88, 0.55);
}

.concept-project-card {
  transition: box-shadow 420ms ease;
  border-radius: 1.5rem;
  background: var(--surface);
}

.premium-input {
  transition:
    border-color 280ms ease,
    box-shadow 280ms ease,
    background-color 280ms ease;
}

.premium-input:focus {
  box-shadow:
    0 0 0 3px color-mix(in srgb, var(--ring) 35%, transparent),
    0 8px 24px -16px var(--glow);
}
```

```
.premium-link {
  position: relative;
  text-decoration: none;
}

.premium-link::after {
  content: "";
  position: absolute;
  left: 0;
  bottom: -2px;
  width: 100%;
  height: 1px;
  background: currentColor;
  transform: scaleX(0);
  transform-origin: left;
  transition: transform 280ms cubic-bezier(0.22, 1, 0.36, 1);
  opacity: 0.5;
}

.premium-link:hover::after {
  transform: scaleX(1);
}

.hero-gradient {
  background:
    radial-gradient(circle at 14% 16%, rgba(110, 132, 196, 0.14), transparent 42%),
    radial-gradient(circle at 85% 14%, rgba(105, 122, 176, 0.1), transparent 34%),
    radial-gradient(circle at 70% 80%, rgba(118, 133, 184, 0.08), transparent 36%);
  filter: blur(42px);
}

.project-card:hover,
.concept-project-card:hover {
  box-shadow: none;
}

.concept-project-card:hover .project-media img,
.concept-project-card:hover .concept-project-thumb {
  transform: scale(1.03);
}

.concept-project-media {
  background: color-mix(in srgb, var(--accent) 28%, var(--background));
}

.concept-project-media-frame {
  z-index: 0;
}

.concept-project-media-frame img,
.concept-project-thumb {
  transition:
    transform 500ms cubic-bezier(0.22, 1, 0.36, 1),
    filter 420ms ease;
}

.concept-project-color-overlay,
.concept-project-light-wash {
  position: absolute;
  inset: 0;
  pointer-events: none;
  transition: opacity 400ms ease;
}

.concept-project-color-overlay {
  z-index: 2;
}
```

```

.concept-project-light-wash {
  z-index: 1;
  display: none;
}

/* ?? Thème sombre (référence) ?? */
[data-theme="dark"] .concept-project-media {
  background: color-mix(in srgb, var(--accent) 28%, var(--background));
}

[data-theme="dark"] .concept-project-media-frame img,
[data-theme="dark"] .concept-project-thumb {
  filter: grayscale(1) saturate(0) sepia(1) hue-rotate(198deg) saturate(2.6)
  brightness(0.62) contrast(1.22);
}

[data-theme="dark"] .concept-project-card:hover .concept-project-media-frame img,
[data-theme="dark"] .concept-project-card:hover .concept-project-thumb {
  filter: grayscale(1) saturate(0) sepia(1) hue-rotate(198deg) saturate(2.8)
  brightness(0.72) contrast(1.24);
}

[data-theme="dark"] .concept-project-color-overlay {
  background: linear-gradient(
    155deg,
    color-mix(in srgb, var(--accent) 88%, var(--background)) 0%,
    color-mix(in srgb, var(--accent-strong) 72%, var(--background)) 100%
  );
  opacity: 0.62;
}

[data-theme="dark"] .concept-project-card:hover .concept-project-color-overlay {
  opacity: 0.52;
}

/* ?? Thème clair : lumières blanches + bleu-violet charte ?? */
[data-theme="light"] .concept-project-media {
  background: color-mix(in srgb, var(--accent) 12%, var(--background));
}

[data-theme="light"] .concept-project-media-frame img,
[data-theme="light"] .concept-project-thumb {
  filter: grayscale(1) saturate(0) sepia(0.55) hue-rotate(198deg) saturate(2.4)
  brightness(1.16) contrast(0.92);
}

[data-theme="light"] .concept-project-card:hover .concept-project-media-frame img,
[data-theme="light"] .concept-project-card:hover .concept-project-thumb {
  filter: grayscale(1) saturate(0) sepia(0.55) hue-rotate(198deg) saturate(2.6)
  brightness(1.22) contrast(0.96);
}

/* Voile blanc sur les zones claires */
[data-theme="light"] .concept-project-light-wash {
  display: block;
  background: linear-gradient(
    148deg,
    rgba(255, 255, 255, 0.92) 0%,
    rgba(255, 255, 255, 0.55) 38%,
    rgba(255, 255, 255, 0.12) 72%,
    rgba(255, 255, 255, 0) 100%
  );
  mix-blend-mode: soft-light;
  opacity: 0.88;
}

[data-theme="light"] .concept-project-card:hover .concept-project-light-wash {

```

```
    opacity: 0.8;
}

/* Voile bleu-violet charte (--accent) par-dessus */
[data-theme="light"] .concept-project-color-overlay {
  background: linear-gradient(
    160deg,
    color-mix(in srgb, var(--accent-gradient-end) 50%, transparent) 0%,
    color-mix(in srgb, var(--accent) 58%, transparent) 48%,
    color-mix(in srgb, var(--accent-strong) 52%, var(--background)) 100%
  );
  opacity: 0.42;
  mix-blend-mode: multiply;
}

[data-theme="light"] .concept-project-card:hover .concept-project-color-overlay {
  opacity: 0.36;
}

.concept-badge {
  display: inline-flex;
  align-items: center;
  border-radius: 9999px;
  border: 1px solid rgba(132, 156, 230, 0.35);
  background: rgba(10, 10, 13, 0.72);
  padding: 0.35rem 0.75rem;
  font-size: 0.68rem;
  font-weight: 600;
  letter-spacing: 0.12em;
  text-transform: uppercase;
  color: #dbe4ff;
  backdrop-filter: blur(8px);
}

.tech-pill {
  display: inline-flex;
  align-items: center;
  border-radius: 9999px;
  border: 1px solid var(--border);
  background: var(--surface);
  padding: 0.28rem 0.65rem;
  font-size: 0.72rem;
  color: var(--muted);
  transition: border-color 300ms ease, color 300ms ease;
}

.concept-project-card:hover .tech-pill {
  border-color: rgba(132, 156, 230, 0.35);
  color: var(--foreground);
}

.case-study-btn {
  border-color: transparent !important;
  box-shadow: none !important;
}

.case-study-btn::before {
  display: none !important;
}

[data-theme="light"] .case-study-btn {
  background: #121316 !important;
  color: #ffffff !important;
}

[data-theme="light"] .case-study-btn:hover {
  background: #2b2f38 !important;
}
```

```
    color: #ffffff !important;
    border-color: transparent !important;
}

[data-theme="dark"] .case-study-btn {
    background: #ffffff !important;
    color: #121316 !important;
}

[data-theme="dark"] .case-study-btn:hover {
    background: #e8ebf5 !important;
    color: #121316 !important;
    border-color: transparent !important;
}

.transparency-card {
    background: linear-gradient(
        135deg,
        var(--surface-strong),
        rgba(84, 110, 194, 0.08)
    );
    box-shadow:
        0 0 0 1px rgba(132, 156, 230, 0.12) inset,
        0 24px 48px -36px rgba(36, 48, 88, 0.45);
}

.projects-cta-card {
    background: linear-gradient(
        165deg,
        var(--surface-strong),
        rgba(84, 110, 194, 0.14)
    );
    box-shadow:
        0 0 0 1px rgba(143, 160, 206, 0.2) inset,
        0 32px 68px -42px rgba(84, 102, 150, 0.35);
}

.vscode-window {
    box-shadow: 0 24px 48px -24px rgba(0, 0, 0, 0.65);
}

.project-card:hover .project-media {
    transform: scale(1.025);
    filter: saturate(1.12);
}

.project-media {
    transition: transform 420ms ease, filter 420ms ease;
}

.project-media img {
    transition: transform 420ms ease;
}

.service-card:hover {
    box-shadow:
        0 0 0 1px rgba(132, 156, 230, 0.16) inset,
        0 30px 55px -34px rgba(34, 45, 86, 0.45);
}

.pricing-card {
    position: relative;
    isolation: isolate;
    border: 1px solid color-mix(in srgb, var(--border) 75%, transparent);
    background: color-mix(in srgb, var(--surface) 38%, transparent);
    backdrop-filter: blur(14px) saturate(1.1);
    -webkit-backdrop-filter: blur(14px) saturate(1.1);
}
```

```
transition:
  transform 420ms cubic-bezier(0.22, 1, 0.36, 1),
  box-shadow 420ms cubic-bezier(0.22, 1, 0.36, 1),
  border-color 300ms ease,
  opacity 300ms ease;
}

.pricing-card-inner {
  position: relative;
  z-index: 2;
}

.pricing-card-secondary {
  opacity: 0.92;
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--ring) 6%, transparent) inset,
    0 16px 40px -32px rgba(20, 24, 40, 0.35);
}

.pricing-card-secondary:hover {
  opacity: 1;
  transform: translateY(-4px);
  border-color: color-mix(in srgb, var(--ring) 28%, var(--border));
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--accent) 14%, transparent) inset,
    0 28px 56px -34px color-mix(in srgb, var(--hero-glow) 55%, transparent);
}

.pricing-card-featured-shell {
  position: relative;
  border-radius: 1.2rem;
  padding: 2px;
  background: var(--pricing-gold);
  overflow: hidden;
  box-shadow:
    0 0 48px -12px color-mix(in srgb, var(--pricing-gold) 44%, transparent),
    0 24px 56px -36px color-mix(in srgb, var(--pricing-gold-soft) 55%, var(--hero-glow));
  transition:
    transform 420ms cubic-bezier(0.22, 1, 0.36, 1),
    box-shadow 420ms cubic-bezier(0.22, 1, 0.36, 1);
}

.pricing-card-featured-shell:hover {
  transform: translateY(-4px);
  box-shadow:
    0 0 64px -8px color-mix(in srgb, var(--pricing-gold) 52%, transparent),
    0 32px 64px -34px color-mix(in srgb, var(--pricing-gold-soft) 64%, var(--hero-glow));
}

.pricing-card-featured {
  position: relative;
  border: none;
  border-radius: calc(1.2rem - 2px);
  overflow: hidden;
  background: transparent;
  box-shadow: none;
}

.pricing-card-featured:hover {
  transform: none;
  box-shadow: none;
}

.pricing-card-featured-bg {
  position: absolute;
  inset: 0;
  z-index: 0;
```



```

pointer-events: none;
border-radius: inherit;
overflow: hidden;
backdrop-filter: blur(14px) saturate(1.1);
-webkit-backdrop-filter: blur(14px) saturate(1.1);
background: linear-gradient(
  165deg,
  color-mix(in srgb, var(--surface-strong) 90%, transparent) 0%,
  color-mix(in srgb, var(--accent) 8%, var(--surface)) 50%,
  color-mix(in srgb, var(--pricing-gold-soft) 35%, var(--surface)) 100%
);
}

.pricing-gold-particles {
  opacity: 0.6;
  mix-blend-mode: screen;
}

.pricing-card-featured-glow {
  position: absolute;
  inset: -30% -20% auto;
  height: 70%;
  background: radial-gradient(
    ellipse at 50% 0%,
    color-mix(in srgb, var(--pricing-gold) 35%, transparent),
    color-mix(in srgb, var(--pricing-gold) 15%, transparent) 38%,
    transparent 72%
  );
  filter: blur(28px);
  opacity: 0.8;
}

.pricing-card-featured-light {
  position: absolute;
  inset: 0;
  background: radial-gradient(
    120% 80% at 50% -10%,
    color-mix(in srgb, var(--pricing-gold) 23%, transparent),
    transparent 55%
  );
  opacity: 0.72;
}

[data-theme="light"] .pricing-card-featured-shell {
  background: color-mix(in srgb, var(--pricing-gold) 72%, #c4b48a);
  box-shadow:
    0 0 32px -18px color-mix(in srgb, var(--pricing-gold) 22%, transparent),
    0 18px 44px -30px rgba(148, 124, 72, 0.1);
}

[data-theme="light"] .pricing-card-featured-shell:hover {
  box-shadow:
    0 0 40px -14px color-mix(in srgb, var(--pricing-gold) 28%, transparent),
    0 22px 48px -28px rgba(148, 124, 72, 0.14);
}

[data-theme="light"] .pricing-card-featured-bg {
  backdrop-filter: none;
  -webkit-backdrop-filter: none;
  background: linear-gradient(
    168deg,
    #ffffff 0%,
    #fdfbf7 42%,
    color-mix(in srgb, #f7f2e8 88%, var(--pricing-gold-soft)) 100%
  );
}

```

```
[data-theme="light"] .pricing-gold-particles {
  opacity: 0.42;
  mix-blend-mode: multiply;
}

[data-theme="light"] .pricing-card-featured-bg .pricing-card-featured-glow {
  inset: 0;
  height: auto;
  filter: none;
  opacity: 0.42;
  background: radial-gradient(
    ellipse at 50% 0%,
    color-mix(in srgb, var(--pricing-gold) 18%, transparent),
    color-mix(in srgb, var(--pricing-gold) 8%, transparent) 40%,
    transparent 72%
  );
}

[data-theme="light"] .pricing-card-featured-bg .pricing-card-featured-light {
  opacity: 0.38;
  background: radial-gradient(
    120% 75% at 50% -8%,
    color-mix(in srgb, var(--pricing-gold) 12%, transparent),
    transparent 52%
  );
}

[data-theme="light"] .pricing-popular-badge {
  border-color: color-mix(in srgb, var(--pricing-gold) 38%, #e8dcc0);
  background: color-mix(in srgb, #faf6ee 75%, var(--pricing-gold-soft));
  color: color-mix(in srgb, var(--pricing-gold) 80%, #7a6535);
  box-shadow: 0 0 14px -8px color-mix(in srgb, var(--pricing-gold) 45%, transparent);
}

[data-theme="light"] .pricing-feature-icon-featured {
  border-color: color-mix(in srgb, var(--pricing-gold) 28%, var(--border));
  background: color-mix(in srgb, #faf6ee 70%, var(--pricing-gold-soft));
  color: color-mix(in srgb, var(--pricing-gold) 75%, #6b5830);
}

[data-theme="light"] .pricing-featured-note {
  border-color: color-mix(in srgb, var(--pricing-gold) 22%, #e8dcc0) !important;
  background: color-mix(in srgb, #faf6ee 82%, var(--pricing-gold-soft)) !important;
  color: color-mix(in srgb, var(--foreground) 88%, #5c4e30) !important;
}

.pricing-popular-badge {
  display: inline-flex;
  align-items: center;
  gap: 0.25rem;
  border-radius: 9999px;
  border: 1px solid color-mix(in srgb, var(--pricing-gold) 50%, var(--ring));
  background: color-mix(in srgb, var(--pricing-gold-soft) 70%, var(--surface));
  padding: 0.15rem 0.55rem;
  font-size: 0.58rem;
  font-weight: 700;
  letter-spacing: 0.07em;
  text-transform: uppercase;
  color: var(--pricing-gold);
  box-shadow: 0 0 18px -6px color-mix(in srgb, var(--pricing-gold) 80%, transparent);
}

.pricing-price {
  font-family: var(--font-display), var(--font-body), system-ui, sans-serif;
  font-size: clamp(1.85rem, 3.5vw, 2.65rem);
  line-height: 1;
  letter-spacing: -0.04em;
```

```
    font-weight: 600;
    color: var(--foreground);
}

.pricing-price-suffix {
  margin-bottom: 0.2rem;
  font-size: 0.8125rem;
  color: var(--muted);
  font-weight: 500;
}

.pricing-feature-icon {
  border: 1px solid var(--border);
  background: color-mix(in srgb, var(--surface-strong) 80%, transparent);
  color: var(--muted);
}

.pricing-feature-icon-featured {
  border-color: color-mix(in srgb, var(--pricing-gold) 35%, var(--ring));
  background: color-mix(in srgb, var(--pricing-gold-soft) 55%, var(--surface));
  color: var(--foreground);
}

.pricing-cta-featured {
  box-shadow:
    0 0 0 1px rgba(255, 255, 255, 0.12) inset,
    0 24px 48px -24px color-mix(in srgb, var(--pricing-gold) 40%, var(--hero-glow));
}

.pricing-cta-secondary:hover {
  border-color: color-mix(in srgb, var(--accent) 40%, var(--border));
  transform: translateY(-1px);
}

.pricing-section-badge,
.pricing-toggle {
  background: color-mix(in srgb, var(--surface) 55%, transparent);
  backdrop-filter: blur(10px);
  -webkit-backdrop-filter: blur(10px);
}

.pricing-comparison {
  background: color-mix(in srgb, var(--surface) 40%, transparent);
  backdrop-filter: blur(10px);
  -webkit-backdrop-filter: blur(10px);
}

.pricing-comparison-pro {
  background: linear-gradient(
    180deg,
    color-mix(in srgb, var(--pricing-gold-soft) 35%, transparent),
    color-mix(in srgb, var(--accent-soft) 25%, transparent)
  );
  box-shadow: inset 0 0 0 1px color-mix(in srgb, var(--pricing-gold) 12%, transparent);
}

.pricing-guarantee {
  backdrop-filter: blur(10px);
  -webkit-backdrop-filter: blur(10px);
}

.pricing-faq-item:focus-within {
  border-color: color-mix(in srgb, var(--ring) 55%, transparent);
}

.hero-word-emphasis {
  font-family: var(--font-display), var(--font-body), system-ui, sans-serif;
```

```
    font-weight: 600;
    letter-spacing: -0.03em;
  }

.priority-list-headline {
  font-size: clamp(2rem, 4.8vw, 3.35rem);
  line-height: 1.06;
}

.priority-list-hero-glow {
  background: radial-gradient(
    ellipse at 50% 50%,
    color-mix(in srgb, var(--accent) 22%, transparent),
    transparent 68%
  );
  filter: blur(32px);
  opacity: 0.85;
}

.priority-list-subtext {
  font-family: var(--font-body), system-ui, sans-serif;
  letter-spacing: -0.015em;
}

.priority-list-badge {
  background: color-mix(in srgb, var(--surface) 55%, transparent);
  backdrop-filter: blur(8px);
  -webkit-backdrop-filter: blur(8px);
  box-shadow: 0 0 0 1px color-mix(in srgb, var(--ring) 10%, transparent) inset;
}

.priority-list-card {
  position: relative;
  isolation: isolate;
  border: 1px solid color-mix(in srgb, var(--border) 70%, transparent);
  background: color-mix(in srgb, var(--surface) 22%, transparent);
  backdrop-filter: blur(12px) saturate(1.12);
  -webkit-backdrop-filter: blur(12px) saturate(1.12);
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--ring) 14%, transparent) inset,
    0 1px 0 color-mix(in srgb, white 6%, transparent) inset,
    0 28px 64px -40px color-mix(in srgb, var(--hero-glow) 45%, transparent);
}

.priority-list-card::before {
  content: "";
  position: absolute;
  inset: 0;
  border-radius: inherit;
  background: linear-gradient(
    145deg,
    color-mix(in srgb, white 7%, transparent) 0%,
    transparent 45%,
    color-mix(in srgb, var(--accent) 6%, transparent) 100%
  );
  pointer-events: none;
}

.priority-list-card > * {
  position: relative;
  z-index: 1;
}

[data-theme="light"] .priority-list-card {
  background: color-mix(in srgb, var(--surface-strong) 26%, transparent);
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--ring) 10%, transparent) inset,
```

```

    0 1px 0 rgba(255, 255, 255, 0.45) inset,
    0 24px 56px -38px color-mix(in srgb, var(--hero-glow) 28%, transparent);
}

.priority-list-success {
  animation: priority-success-in 0.5s cubic-bezier(0.22, 1, 0.36, 1) both;
}

@keyframes priority-success-in {
  from {
    opacity: 0;
    transform: translateY(10px);
  }
  to {
    opacity: 1;
    transform: translateY(0);
  }
}

.pricing-highlight {
  box-shadow:
    0 0 0 1px rgba(143, 160, 206, 0.26) inset,
    0 32px 68px -42px rgba(84, 102, 150, 0.35);
}

.pricing-highlight::after {
  content: "";
  position: absolute;
  inset: -35% auto auto -20%;
  width: 75%;
  height: 70%;
  background: radial-gradient(circle, rgba(116, 138, 196, 0.18), transparent 70%);
  pointer-events: none;
  filter: blur(16px);
  opacity: 0.75;
}

@keyframes drift {
  from {
    transform: translate3d(0, -1%, 0) scale(1);
  }
  to {
    transform: translate3d(0, 1.3%, 0) scale(1.03);
  }
}

/* ??? Responsive: tablet & mobile only (desktop lg+ unchanged) ??? */

.touch-target {
  min-height: 2.75rem;
}

.touch-target-sm {
  min-height: 2.5rem;
  min-width: 2.5rem;
}

@media (max-width: 1023px) {
  section[id] {
    scroll-margin-top: 5.25rem;
  }

  .site-header {
    backdrop-filter: blur(12px) saturate(1.05);
    -webkit-backdrop-filter: blur(12px) saturate(1.05);
  }
}

```

```

.mobile-nav-panel {
  backdrop-filter: blur(16px) saturate(1.1);
  -webkit-backdrop-filter: blur(16px) saturate(1.1);
}

.pricing-card-featured-bg,
.pricing-section-badge,
.pricing-toggle,
.pricing-guarantee,
.priority-list-card,
.priority-list-badge {
  backdrop-filter: blur(8px) saturate(1.05);
  -webkit-backdrop-filter: blur(8px) saturate(1.05);
}

.hero-display {
  font-size: clamp(2rem, 8vw, 3.5rem);
}

.priority-list-headline {
  font-size: clamp(1.85rem, 7vw, 2.75rem);
}

.pricing-price {
  font-size: clamp(2rem, 7vw, 2.75rem);
}
}

@media (max-width: 767px) {
  section[id] {
    scroll-margin-top: 4.75rem;
  }

  .touch-target {
    min-height: 3rem;
  }

  .hero-display {
    font-size: clamp(1.85rem, 9vw, 2.65rem);
    line-height: 1.08;
  }

  .priority-list-headline {
    font-size: clamp(1.65rem, 8.5vw, 2.35rem);
  }

  .pricing-comparison-mobile .pricing-comparison-pro {
    background: linear-gradient(
      180deg,
      color-mix(in srgb, var(--pricing-gold-soft) 35%, transparent),
      color-mix(in srgb, var(--accent-soft) 25%, transparent)
    );
    box-shadow: inset 0 0 0 1px color-mix(in srgb, var(--pricing-gold) 12%, transparent);
  }

  .concept-project-card .hero-stat-card,
  .hero-visual-card .hero-stat-card {
    backdrop-filter: none;
    -webkit-backdrop-filter: none;
  }
}

/* Hide preview toolbar inside iframe preview */
html:has(body[data-preview-frame="true"]) .responsive-preview-toolbar,
html:has(body[data-preview-frame="true"]) .responsive-preview-workbench {
  display: none !important;
}

```

```
/* Demo themes ? palan first; apex last so `.apex-root` tokens win on /demos/apex-advisory */  
@import "../demos/palan-capital/palan-capital.css";  
@import "../demos/apex-advisory/apex-advisory.css";
```

app/layout.tsx

```
import type { Metadata } from "next";
import { Geist_Mono, Inter, Space_Grotesk } from "next/font/google";
import { ResponsivePreviewShell } from "@components/responsive-preview-shell";
import "../premium-motion.css";
import "../globals.css";

const inter = Inter({
  variable: "--font-body",
  subsets: ["latin"],
  display: "swap",
});

const spaceGrotesk = Space_Grotesk({
  variable: "--font-display",
  subsets: ["latin"],
  display: "swap",
});

const geistMono = Geist_Mono({
  variable: "--font-geist-mono",
  subsets: ["latin"],
});

export const metadata: Metadata = {
  title: "Nocta Agency - Agence Web Premium",
  description:
    "Nocta Agency crée des sites web modernes, performants et haut de gamme pour restaurants, freelances et PME.",
};

export default function RootLayout({
  children,
}: Readonly<{
  children: React.ReactNode;
}>) {
  return (
    <html
      lang="fr"
      data-theme="dark"
      suppressHydrationWarning
      className={` ${inter.variable} ${spaceGrotesk.variable} ${geistMono.variable} h-full antialiased`}
    >
      <body className="min-h-full flex flex-col" suppressHydrationWarning>
        <ResponsivePreviewShell>{children}</ResponsivePreviewShell>
      </body>
    </html>
  );
}
```


app/page.full.tsx

```
/**
 * BACKUP ? page d'accueil complète (animations, sections, hooks).
 * Pour restaurer : copier ce fichier vers app/page.tsx
 * ou renommer : mv app/page.full.tsx app/page.tsx
 */
"use client";

import { Code2, Handshake, SearchCheck, WandSparkles } from "lucide-react";
import { useEffect, useState } from "react";
import { AmbientParticles } from "@/components/motion/ambient-particles";
import { CinematicReveal } from "@/components/motion/cinematic-reveal";
import { FloatBlobs } from "@/components/motion/float-blobs";
import { GsapStagger } from "@/components/motion/gsap-stagger";
import { ParallaxLayer } from "@/components/motion/parallax-layer";
import { Card, CardContent } from "@/components/ui/card";
import { PriorityListSection } from "@/components/priority-list-section";
import { ConceptProjectsSection } from "@/components/concept-projects-section";
import { HeroSection } from "@/components/hero-section";
import { PricingSection } from "@/components/pricing-section";
import { SiteHeader } from "@/components/site-header";
import { isPreviewFrame } from "@/hooks/use-responsive-preview";

const services = [
  {
    title: "Création de sites web",
    description:
      "Un site moderne adapté à votre activité (restaurant, freelance, artisan, etc.).",
    icon: Code2,
  },
  {
    title: "Refonte de sites existants",
    description:
      "Modernisation complète pour améliorer votre image et vos résultats.",
    icon: WandSparkles,
  },
  {
    title: "Optimisation mobile",
    description: "Site rapide et parfaitement adapté aux téléphones.",
    icon: SearchCheck,
  },
  {
    title: "Maintenance & suivi",
    description: "Mises à jour et support pour garder un site toujours performant.",
    icon: Handshake,
  },
];

export default function Home() {
  const [theme, setTheme] = useState<"dark" | "light">("dark");

  useEffect(() => {
    document.documentElement.setAttribute("data-theme", theme);
    localStorage.setItem("nocta-theme", theme);
  }, [theme]);

  useEffect(() => {
    if (!isPreviewFrame()) return;
    document.body.setAttribute("data-preview-frame", "true");
    return () => document.body.removeAttribute("data-preview-frame");
  }, []);

  const scrollTo = (sectionId: string) => {
    document.getElementById(sectionId)?.scrollIntoView({ behavior: "smooth" });
  };
}
```

```

return (
  <div className="relative min-h-screen overflow-x-hidden bg-[var(--background)] text-[var(--foreground)]">
    <AmbientParticles />
    <FloatBlobs />
    <ParallaxLayer speed={0.35} className="pointer-events-none absolute inset-0">
      <div className="hero-gradient absolute inset-0 opacity-70 max-lg:opacity-50" />
    </ParallaxLayer>
    <ParallaxLayer
      speed={0.55}
      className="pointer-events-none absolute -top-32 left-1/2 h-[16rem] w-[16rem] -translate-x-1/2 md:max-lg:h-[22rem] md:max-lg:w-[22rem] lg:h-[35rem] lg:w-[35rem]"
    >
      <div className="size-full rounded-full bg-[var(--glow-soft)] blur-3xl max-lg:blur-2xl" />
    </ParallaxLayer>

    <SiteHeader
      theme={theme}
      onToggleTheme={() => setTheme(theme === "dark" ? "light" : "dark")}
      onNavigate={scrollTo}
    />

    <main className="relative z-10 mx-auto flex w-full max-w-6xl flex-col gap-16 px-4 pb-8 pt-[4.75rem] max-md:gap-14 max-md:px-4 max-md:pb-8 max-md:pt-[4.5rem] md:max-lg:gap-20 md:px-10 md:pb-20 md:pt-28 lg:gap-28">
      <HeroSection
        onContact={() => scrollTo("contact")}
        onProjects={() => scrollTo("projects")}
      />

      <ConceptProjectsSection onContact={() => scrollTo("contact")} />

      <section id="services" className="space-y-7 max-md:space-y-6 md:max-lg:space-y-8 lg:space-y-9">
        <CinematicReveal className="space-y-3">
          <h2 className="text-[1.75rem] font-semibold leading-tight tracking-[-0.02em] max-md:text-[1.65rem] md:text-5xl">
            Ce que nous proposons.
          </h2>
          <p className="max-w-2xl text-base leading-7 text-[var(--muted)] max-md:leading-8 md:text-lg">
            Des services clairs pour créer un site utile, professionnel et facile à gérer.
          </p>
        </CinematicReveal>
        <GsapStagger className="grid gap-5 max-md:gap-4 md:max-lg:grid-cols-2 md:max-lg:gap-6 md:grid-cols-2">
          {services.map((service) => (
            <div key={service.title} data-stagger-item>
              <Card className="service-card premium-interactive h-full">
                <CardContent className="space-y-4 p-5 max-md:p-5 md:p-7">
                  <div className="flex size-10 items-center justify-center rounded-xl border border-[var(--border)] bg-[var(--surface-strong)]">
                    <service.icon className="size-[18px] text-[var(--foreground)]" />
                  </div>
                  <h3 className="text-lg font-semibold">{service.title}</h3>
                  <p className="text-sm leading-7 text-[var(--muted)]">{service.description}</p>
                </CardContent>
              </Card>
            </div>
          )))}
        </GsapStagger>
      </section>

      <PricingSection onContact={() => scrollTo("contact")} />

      <section id="about" className="space-y-5 max-md:space-y-4">
        <CinematicReveal>
          <h2 className="text-[1.75rem] font-semibold leading-tight tracking-[-0.02em] max-md:text-[1.65rem] md:text-5xl">
            L&apos;agence
          </h2>
        </CinematicReveal>
        <CinematicReveal delay={0.06}>
          <Card className="premium-interactive">

```

```

        <CardContent className="max-w-3xl p-5 text-base leading-8 text-[var(--muted)] max-md:p-6 max-md:leading-8 md:p-8 md:text-lg">
          Nocta Agency accompagne les entreprises locales, indépendants et
          PME dans la création de sites web modernes, performants et
          orientés résultats. Notre objectif : renforcer votre présence en
          ligne et transformer vos visiteurs en clients grâce à une
          expérience digitale soignée.
        </CardContent>
      </Card>
    </CinematicReveal>
  </section>

  <PriorityListSection />
</main>
</div>
);
}
```

app/page.tsx

```
"use client";

import { Code2, Handshake, SearchCheck, WandSparkles } from "lucide-react";
import { useEffect, useState } from "react";
import { CinematicReveal } from "@/components/motion/cinematic-reveal";
import { FloatBlobs } from "@/components/motion/float-blobs";
import { GsapStagger } from "@/components/motion/gsap-stagger";
import { PageSection } from "@/components/motion/page-section";
import { SubtleParallax } from "@/components/motion/subtle-parallax";
import { Card, CardContent } from "@/components/ui/card";
import { CardHoverGlow } from "@/components/ui/card-hover-glow";
import { PriorityListSection } from "@/components/priority-list-section";
import { ConceptProjectsSection } from "@/components/concept-projects-section";
import { HeroSection } from "@/components/hero-section";
import { PricingSection } from "@/components/pricing-section";
import { SiteHeader } from "@/components/site-header";
import { isPreviewFrame } from "@/hooks/use-responsive-preview";

const services = [
  {
    title: "Création de sites web",
    description:
      "Un site moderne adapté à votre activité (restaurant, freelance, artisan, etc.).",
    icon: Code2,
  },
  {
    title: "Refonte de sites existants",
    description:
      "Modernisation complète pour améliorer votre image et vos résultats.",
    icon: WandSparkles,
  },
  {
    title: "Optimisation mobile",
    description: "Site rapide et parfaitement adapté aux téléphones.",
    icon: SearchCheck,
  },
  {
    title: "Maintenance & suivi",
    description: "Mises à jour et support pour garder un site toujours performant.",
    icon: Handshake,
  },
];

export default function Home() {
  const [theme, setTheme] = useState<"dark" | "light">("dark");

  useEffect(() => {
    document.documentElement.setAttribute("data-theme", theme);
    localStorage.setItem("nocta-theme", theme);
  }, [theme]);

  useEffect(() => {
    if (!isPreviewFrame()) return;
    document.body.setAttribute("data-preview-frame", "true");
    return () => document.body.removeAttribute("data-preview-frame");
  }, []);

  const scrollTo = (sectionId: string) => {
    document.getElementById(sectionId)?.scrollIntoView({ behavior: "smooth" });
  };

  return (
    <div className="relative min-h-screen overflow-x-hidden bg-[var(--background)] text-[var(--foreground)]">
      <div className="pointer-events-none absolute inset-0 overflow-hidden">
        <div className="hero-gradient absolute inset-0 opacity-70 max-lg:opacity-50" />
      </div>
    </div>
  );
}
```

```

<SubtleParallax
  maxOffset={8}
  className="absolute -top-32 left-1/2 h-[16rem] w-[16rem] -translate-x-1/2 md:max-lg:h-[22rem] md:max-lg:w-[22rem] lg:h-[35rem] lg:w-[35rem]"
>
  <div className="size-full rounded-full bg-[var(--glow-soft)] blur-3xl max-lg:blur-2xl" />
</SubtleParallax>
</div>
<FloatBlobs />

<SiteHeader
  theme={theme}
  onToggleTheme={() => setTheme(theme === "dark" ? "light" : "dark")}
  onNavigate={scrollTo}
/>

<main className="relative z-10 mx-auto flex w-full max-w-6xl flex-col gap-16 px-4 pb-8 pt-[4.75rem] max-md:gap-14 max-md:px-4 max-md:pb-8 max-md:pt-[4.5rem] md:max-lg:gap-20 md:px-10 md:pb-20 md:pt-28 lg:gap-28">
  <HeroSection
    onContact={() => scrollTo("contact")}
    onProjects={() => scrollTo("projects")}
  />

  <PageSection as="div">
    <ConceptProjectsSection onContact={() => scrollTo("contact")} />
  </PageSection>

  <PageSection id="services" className="space-y-7 max-md:space-y-6 md:max-lg:space-y-8 lg:space-y-9">
    <CinematicReveal className="space-y-3">
      <h2 className="text-[1.75rem] font-semibold leading-tight tracking-[-0.02em] max-md:text-[1.65rem] md:text-5xl">
        Ce que nous proposons.
      </h2>
      <p className="max-w-2xl text-base leading-7 text-[var(--muted)] max-md:leading-8 md:text-lg">
        Des services clairs pour créer un site utile, professionnel et facile à gérer.
      </p>
    </CinematicReveal>
    <GsapStagger className="grid gap-5 max-md:gap-4 md:max-lg:grid-cols-2 md:max-lg:gap-6 md:grid-cols-2">
      {services.map((service) => (
        <div key={service.title} data-stagger-item>
          <CardHoverGlow className="h-full rounded-3xl">
            <Card className="service-card premium-interactive h-full">
              <CardContent className="space-y-4 p-5 max-md:p-5 md:p-7">
                <div className="flex size-10 items-center justify-center rounded-xl border border-[var(--border)] bg-[var(--surface-strong)]">
                  <service.icon className="size-[18px] text-[var(--foreground)]" />
                </div>
                <h3 className="text-lg font-semibold">{service.title}</h3>
                <p className="text-sm leading-7 text-[var(--muted)]">{service.description}</p>
              </CardContent>
            </Card>
          </CardHoverGlow>
        </div>
      )))}
    </GsapStagger>
  </PageSection>

  <PricingSection onContact={() => scrollTo("contact")} />

  <PageSection id="about" className="space-y-5 max-md:space-y-4">
    <CinematicReveal>
      <h2 className="text-[1.75rem] font-semibold leading-tight tracking-[-0.02em] max-md:text-[1.65rem] md:text-5xl">
        L'agence
      </h2>
    </CinematicReveal>
    <CinematicReveal delay={0.08}>
      <CardHoverGlow className="rounded-3xl">
        <Card className="premium-interactive">
          <CardContent className="max-w-3xl p-5 text-base leading-8 text-[var(--muted)] max-md:p-6 max-md:leading-8 md:p-8 md:text-lg">

```

```
        Nocta Agency accompagne les entreprises locales, indépendants et
        PME dans la création de sites web modernes, performants et
        orientés résultats. Notre objectif : renforcer votre présence en
        ligne et transformer vos visiteurs en clients grâce à une
        expérience digitale soignée.
    </CardContent>
</Card>
</CardHoverGlow>
</CinematicReveal>
</PageSection>

<PageSection as="div">
    <PriorityListSection />
</PageSection>
</main>
</div>
);
}
```

app/premium-motion.css

```
/* Premium motion ? CSS only, no infinite loops, no permanent RAF */
```

```
.reveal-on-scroll {
  opacity: 0;
  transform: translateY(18px);
  transition:
    opacity 0.75s cubic-bezier(0.22, 1, 0.36, 1),
    transform 0.75s cubic-bezier(0.22, 1, 0.36, 1);
  transition-delay: var(--reveal-delay, 0ms);
  will-change: opacity, transform;
}

.reveal-on-scroll.is-visible {
  opacity: 1;
  transform: translateY(0);
}

.reveal-stagger > .reveal-stagger-item {
  opacity: 0;
  transform: translateY(16px);
  transition:
    opacity 0.65s cubic-bezier(0.22, 1, 0.36, 1),
    transform 0.65s cubic-bezier(0.22, 1, 0.36, 1);
  transition-delay: calc(var(--stagger-index, 0) * 75ms);
}

.reveal-stagger.is-visible > .reveal-stagger-item {
  opacity: 1;
  transform: translateY(0);
}

.reveal-words .reveal-word {
  opacity: 0;
  transform: translateY(14px);
  transition:
    opacity 0.55s cubic-bezier(0.22, 1, 0.36, 1),
    transform 0.55s cubic-bezier(0.22, 1, 0.36, 1);
  transition-delay: calc(var(--word-index, 0) * 55ms + 80ms);
}

.reveal-words.reveal-on-scroll.is-visible .reveal-word {
  opacity: 1;
  transform: translateY(0);
}

.page-section {
  opacity: 0.98;
  transform: translateY(10px);
  transition:
    opacity 0.85s cubic-bezier(0.22, 1, 0.36, 1),
    transform 0.85s cubic-bezier(0.22, 1, 0.36, 1);
}

.page-section.is-section-visible {
  opacity: 1;
  transform: translateY(0);
}

.premium-interactive {
  transition:
    transform 380ms cubic-bezier(0.22, 1, 0.36, 1),
    box-shadow 380ms cubic-bezier(0.22, 1, 0.36, 1),
    border-color 300ms ease;
}
```

```
.premium-interactive:hover {
  transform: translateY(-4px) scale(1.01);
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--ring) 18%, transparent) inset,
    0 22px 48px -28px color-mix(in srgb, var(--hero-glow) 38%, transparent);
}

.magnetic-btn {
  transition: transform 200ms cubic-bezier(0.22, 1, 0.36, 1);
  will-change: transform;
}

.magnetic-btn:hover {
  box-shadow:
    0 0 0 1px color-mix(in srgb, var(--ring) 20%, transparent) inset,
    0 20px 44px -24px color-mix(in srgb, var(--hero-glow) 42%, transparent);
}

.card-hover-glow {
  position: relative;
  isolation: isolate;
}

.card-hover-glow::before {
  content: "";
  position: absolute;
  inset: 0;
  z-index: 0;
  border-radius: inherit;
  pointer-events: none;
  opacity: 0;
  background: radial-gradient(
    520px circle at var(--glow-x, 50%) var(--glow-y, 40%),
    color-mix(in srgb, var(--accent) 22%, transparent),
    transparent 58%
  );
  transition: opacity 420ms ease;
}

.card-hover-glow:hover::before {
  opacity: 1;
}

.card-hover-glow > * {
  position: relative;
  z-index: 1;
}

.pricing-card-featured.group:hover .pricing-card-featured-bg::after {
  opacity: 1;
}

.pricing-card-featured-bg::after {
  content: "";
  position: absolute;
  inset: 0;
  border-radius: inherit;
  pointer-events: none;
  opacity: 0;
  background: radial-gradient(
    420px circle at var(--glow-x, 50%) var(--glow-y, 35%),
    color-mix(in srgb, var(--pricing-gold) 28%, transparent),
    transparent 62%
  );
  transition: opacity 450ms ease;
}
```



```
.subtle-parallax-layer {
  will-change: transform;
  transform: translate3d(0, 0, 0);
}

@media (prefers-reduced-motion: reduce) {
  .reveal-on-scroll,
  .reveal-stagger > .reveal-stagger-item,
  .reveal-words .reveal-word,
  .page-section {
    opacity: 1 !important;
    transform: none !important;
    transition: none !important;
  }

  .premium-interactive:hover {
    transform: none;
  }

  .magnetic-btn {
    transform: none !important;
  }

  .subtle-parallax-layer {
    transform: none !important;
  }
}
```

components/concept-project-modals.tsx

```
"use client";

import { AnimatePresence, motion } from "framer-motion";
import { FileCode2, X } from "lucide-react";
import { useEffect, useState } from "react";
import type { CodeLine, ConceptProject } from "@/lib/concept-projects";
import { cn } from "@/lib/utils";

const tokenClasses: Record<CodeLine["tokens"][number]["type"], string> = {
  keyword: "text-[#c586c0]",
  string: "text-[#ce9178]",
  tag: "text-[#569cd6]",
  attr: "text-[#9cdcfe]",
  function: "text-[#dcdcaa]",
  comment: "text-[#6a9955]",
  plain: "text-[#d4d4d4]",
  number: "text-[#b5cea8]",
  type: "text-[#4ec9b0]",
};

type ModalShellProps = {
  open: boolean;
  onClose: () => void;
  title: string;
  subtitle?: string;
  children: React.ReactNode;
  wide?: boolean;
};

function ModalShell({
  open,
  onClose,
  title,
  subtitle,
  children,
  wide,
}: ModalShellProps) {
  useEffect(() => {
    if (!open) return;
    const onKeyDown = (event: KeyboardEvent) => {
      if (event.key === "Escape") onClose();
    };
    document.body.style.overflow = "hidden";
    window.addEventListener("keydown", onKeyDown);
    return () => {
      document.body.style.overflow = "";
      window.removeEventListener("keydown", onKeyDown);
    };
  }, [open, onClose]);

  return (
    <AnimatePresence>
      {open ? (
        <motion.div
          className="fixed inset-0 z-[100] flex items-start justify-center overflow-y-auto p-4 pb-6 pt-[5.5rem] sm:items-center sm:py-8 sm:pt-8"
          initial={{ opacity: 0 }}
          animate={{ opacity: 1 }}
          exit={{ opacity: 0 }}
        >
          <button
            type="button"
            aria-label="Fermer la fenêtre"
            className="fixed inset-0 bg-black/70 backdrop-blur-sm"
            onClick={onClose}
          />

```

```

<motion.div
  role="dialog"
  aria-modal="true"
  aria-labelledby="modal-title"
  initial={{ opacity: 0, y: 20, scale: 0.98 }}
  animate={{ opacity: 1, y: 0, scale: 1 }}
  exit={{ opacity: 0, y: 12, scale: 0.98 }}
  transition={{ duration: 0.25, ease: "easeOut" }}
  className={cn(
    "relative z-10 my-auto flex w-full flex-col overflow-hidden rounded-2xl border border-[var(--border)] bg-[var(--surface-strong)] shadow-[0_40px_80
px_-40px_rgba(0,0,0,0.8)] sm:rounded-3xl",
    "max-h-[min(calc(100dvh-6.5rem),42rem)]",
    wide ? "max-w-5xl" : "max-w-2xl",
  )}
>
<div className="sticky top-0 z-20 flex shrink-0 items-start justify-between gap-4 border-b border-[var(--border)] bg-[var(--surface-strong)] px-5 py
-4 sm:px-6 sm:py-5">
  <div className="min-w-0 pr-2">
    <h3 id="modal-title" className="text-lg font-semibold sm:text-xl">
      {title}
    </h3>
    {subtitle ? (
      <p className="mt-1 text-sm text-[var(--muted)]">{subtitle}</p>
    ) : null}
  </div>
  <button
    type="button"
    onClick={onClose}
    className="shrink-0 rounded-xl border border-[var(--border)] bg-[var(--surface)] p-2 text-[var(--muted)] transition hover:bg-[var(--surface-stro
ng)] hover:text-[var(--foreground)]"
    aria-label="Fermer"
  >
    <X className="size-4" />
  </button>
</div>
<div className="min-h-0 flex-1 overflow-y-auto overscroll-contain px-5 py-4 sm:px-6 sm:py-5">
  {children}
</div>
</motion.div>
</motion.div>
) : null}
</AnimatePresence>
);
}

type CaseStudyModalProps = {
  project: ConceptProject | null;
  open: boolean;
  onClose: () => void;
};

export function CaseStudyModal({ project, open, onClose }: CaseStudyModalProps) {
  if (!project) return null;

  const sections = [
    { label: "Objectifs du projet", items: project.caseStudy.objectives },
    { label: "Réflexion UX/UI", items: project.caseStudy.uxUi },
    { label: "Choix techniques", items: project.caseStudy.technical },
  ];

  return (
    <ModalShell
      open={open}
      onClose={onClose}
      title="Étude de cas"
      subtitle={` ${project.name} · ${project.sector}`}
    >

```

```

<div className="mb-5 rounded-2xl border border-[var(--border)] bg-[var(--surface)] px-4 py-3 text-sm text-[var(--muted)]">
  {project.highlight}
</div>
<div className="space-y-7">
  {sections.map((section) => (
    <div key={section.label}>
      <h4 className="mb-3 text-sm font-semibold uppercase tracking-[0.12em] text-[var(--primary-strong)]">
        {section.label}
      </h4>
      <ul className="space-y-2.5">
        {section.items.map((item) => (
          <li
            key={item}
            className="flex gap-3 text-sm leading-7 text-[var(--muted)]"
          >
            <span className="mt-2 size-1.5 shrink-0 rounded-full bg-[var(--ring)]" />
            {item}
          </li>
        ))}
      </ul>
    </div>
  ))}
  <div className="rounded-2xl border border-[var(--border)] bg-[var(--surface)] p-5">
    <h4 className="mb-2 text-sm font-semibold uppercase tracking-[0.12em] text-[var(--primary-strong)]">
      Résultat attendu
    </h4>
    <p className="text-sm leading-7 text-[var(--muted)]">
      {project.caseStudy.expectedResult}
    </p>
  </div>
</div>
</ModalShell>
  );
}

function CodeEditor({ filename, lines }: { filename: string; lines: CodeLine[] }) {
  return (
    <div className="vscode-window overflow-hidden rounded-2xl border border-[#2d2d2d]">
      <div className="flex items-center gap-2 border-b border-[#2d2d2d] bg-[#1e1e1e] px-4 py-3">
        <span className="size-3 rounded-full bg-[#ff5f57]" />
        <span className="size-3 rounded-full bg-[#feb22e]" />
        <span className="size-3 rounded-full bg-[#28c840]" />
        <div className="ml-3 flex items-center gap-2 rounded-md bg-[#252526] px-3 py-1 text-xs text-[#cccccc]">
          <FileCode2 className="size-3.5 text-[#569cd6]" />
          {filename}
        </div>
      </div>
      </div>
      <div className="max-h-[min(38dvh,22rem)] overflow-auto bg-[#1e1e1e] p-4 font-mono text-[13px] leading-6 sm:max-h-[min(42dvh,24rem)]">
        <table className="w-full border-collapse">
          <tbody>
            {lines.map((line) => (
              <tr key={line.number}>
                <td className="select-none pr-4 text-right align-top text-[#858585]">
                  {line.number}
                </td>
                <td className="whitespace-pre">
                  {line.tokens.length === 0 ? (
                    <span>&nbsp;</span>
                  ) : (
                    line.tokens.map((token, index) => (
                      <span
                        key={` ${line.number}-${index}`}
                        className={tokenClasses[token.type]}
                      >
                        {token.text}
                      </span>
                    ))
                  )}
                </td>
              </tr>
            ))}
          </tbody>
        </table>
      </div>
    </div>
  );
}

```

```

    }}
  </td>
</tr>
  )}}
</tbody>
</table>
</div>
<div className="border-t border-[#2d2d2d] bg-[#007acc] px-4 py-1.5 text-xs text-white/90">
  TypeScript React · UTF-8 · Espaces: 2
</div>
</div>
  );
}

type CodeModalProps = {
  project: ConceptProject | null;
  open: boolean;
  onClose: () => void;
};

export function CodeModal({ project, open, onClose }: CodeModalProps) {
  const [activeFile, setActiveFile] = useState(0);

  useEffect(() => {
    if (open) setActiveFile(0);
  }, [open, project?.id]);

  if (!project) return null;

  const currentFile = project.codeFiles[activeFile] ?? project.codeFiles[0];

  return (
    <ModalShell
      open={open}
      onClose={onClose}
      title="Aperçu technique"
      subtitle={`Architecture & composants · ${project.name}`}
      wide
    >
      {project.codeFiles.length > 1 ? (
        <div className="mb-4 flex flex-wrap gap-2">
          {project.codeFiles.map((file, index) => (
            <button
              key={file.filename}
              type="button"
              onClick={() => setActiveFile(index)}
              className={cn(
                "rounded-lg border px-3 py-1.5 font-mono text-xs transition",
                activeFile === index
                  ? "border-[var(--ring)] bg-[var(--surface)] text-[var(--foreground)]"
                  : "border-[var(--border)] text-[var(--muted)] hover:text-[var(--foreground)]",
              )}
            >
              {file.filename}
            </button>
          )}}
        </div>
      ) : null}
      {currentFile ? (
        <CodeEditor filename={currentFile.filename} lines={currentFile.lines} />
      ) : null}
      <p className="mt-4 text-sm leading-7 text-[var(--muted)]">
        Extraits représentatifs du code de la démonstration. Ils illustrent
        l'architecture, les composants et les fonctionnalités clés du projet
        type ? stack Next.js, React et TypeScript.
      </p>
    </ModalShell>
  )
}

```


components/concept-projects-section.tsx

```
"use client";

import { motion } from "framer-motion";
import { ArrowRight, BookOpen, Check, Code2, ExternalLink } from "lucide-react";
import Image from "next/image";
import { useState } from "react";
import { CinematicReveal } from "@components/motion/cinematic-reveal";
import { GsapStagger } from "@components/motion/gsap-stagger";
import { TiltCard } from "@components/motion/tilt-card";
import { Button } from "@components/ui/button";
import { Card, CardContent } from "@components/ui/card";
import { CardHoverGlow } from "@components/ui/card-hover-glow";
import { MagneticButton } from "@components/ui/magnetic-button";
import { CaseStudyModal, CodeModal } from "@components/concept-project-modals";
import { conceptProjects, type ConceptProject } from "@lib/concept-projects";

type ConceptProjectsSectionProps = {
  onContact: () => void;
};

export function ConceptProjectsSection({ onContact }: ConceptProjectsSectionProps) {
  const [caseStudyProject, setCaseStudyProject] = useState<ConceptProject | null>(
    null,
  );
  const [codeProject, setCodeProject] = useState<ConceptProject | null>(null);

  return (
    <>
      <section id="projects" className="space-y-10 max-md:space-y-8 md:max-lg:space-y-11 lg:space-y-12">
        <CinematicReveal className="space-y-4">
          <p className="inline-flex rounded-full border border-[var(--border)] bg-[var(--surface)] px-4 py-1.5 text-xs tracking-[0.08em] text-[var(--muted)]">
            Portfolio · Démonstrations
          </p>
          <h2 className="text-[1.75rem] font-semibold leading-tight tracking-[-0.02em] max-md:text-[1.65rem] md:text-5xl">
            Projets Conceptuels
          </h2>
          <p className="max-w-3xl text-base leading-7 text-[var(--muted)] max-md:leading-8 md:text-lg">
            Des démonstrations illustrant notre approche design, conversion et
            expérience utilisateur. Ces projets types ont été créés pour montrer
            différentes solutions adaptées à des secteurs d'activité réels.
          </p>
          <p className="max-w-3xl rounded-2xl border border-[var(--border)] bg-[var(--surface)] px-4 py-3 text-sm leading-7 text-[var(--muted)]">
            <span className="font-medium text-[var(--foreground)]/90">
              Format Starter · 1 page :
            </span>{" "}
            chaque démo regroupe toutes les sections en une seule page défilante
            (modèle le plus accessible). Selon votre abonnement Pro ou Premium,
            votre site peut comporter plusieurs pages distinctes avec navigation
            complète.
          </p>
        </CinematicReveal>

        <GsapStagger className="grid gap-6 max-md:gap-5 md:max-lg:grid-cols-2 md:max-lg:gap-6 lg:grid-cols-3 lg:gap-7">
          {conceptProjects.map((project) => (
            <div key={project.id} data-stagger-item className="h-full">
              <TiltCard className="h-full">
                <CardHoverGlow className="h-full rounded-3xl">
                  <Card className="concept-project-card group relative h-full overflow-hidden border-0 shadow-none">
                    <div className="pointer-events-none absolute inset-x-0 top-0 h-px bg-gradient-to-r from-transparent via-[var(--ring)] to-transparent opacity-0
                      transition-opacity duration-500 group-hover:opacity-100" />
                    <CardContent className="flex h-full flex-col gap-5 p-0">
                      <button
                        type="button"
                        onClick={() =>
                          window.open(project.demoPath, "_blank", "noopener,noreferrer")
                        }
                      </button>
                    </CardContent>
                  </Card>
                </CardHoverGlow>
              </TiltCard>
            </div>
          ))}
        </GsapStagger>
      </section>
    </>
  );
}
```

```

    }
    className="concept-project-media project-media group/image relative aspect-[16/10] w-full overflow-hidden text-left"
    aria-label={`Ouvrir la démo ${project.name}`}
  >
  <div className="concept-project-media-frame absolute inset-0">
    <Image
      src={project.image}
      alt={`Aperçu du projet conceptuel ${project.name}`}
      fill
      className="concept-project-thumb object-cover object-top"
      sizes="(max-width: 768px) 100vw, (max-width: 1024px) 50vw, 33vw"
    />
  </div>
  <div className="concept-project-color-overlay" aria-hidden />
  <div className="concept-project-light-wash" aria-hidden />
  <div className="pointer-events-none absolute inset-0 z-[3] bg-gradient-to-t from-[var(--background)]/95 via-[var(--background)]/30 to-tran
sparent" />
  <div className="absolute inset-0 z-[4] flex items-center justify-center bg-black/0 opacity-0 transition-all duration-300 group-hover/image
: bg-black/25 group-hover/image:opacity-100">
    <span className="inline-flex items-center gap-2 rounded-full border border-white/25 bg-black/50 px-4 py-2 text-xs font-medium text-white
backdrop-blur-sm">
      Voir la démo
      <ExternalLink className="size-3.5" />
    </span>
  </div>
  <span className="concept-badge absolute left-4 top-4 z-[5]">
    Projet Conceptuel
  </span>
</button>

<div className="flex flex-1 flex-col gap-5 px-5 pb-5 max-md:px-4 max-md:pb-4 md:px-6 md:pb-6">
  <div className="space-y-2">
    <p className="text-xs uppercase tracking-[0.16em] text-[var(--muted)]">
      {project.sector}
    </p>
    <h3 className="text-2xl font-semibold tracking-tight">
      {project.name}
    </h3>
    <p className="text-xs font-medium text-[var(--primary-strong)]">
      {project.highLight}
    </p>
    <p className="text-sm leading-7 text-[var(--muted)]">
      {project.description}
    </p>
  </div>

  <div className="space-y-3">
    <p className="text-xs font-medium uppercase tracking-[0.14em] text-[var(--foreground)]/80">
      Fonctionnalités
    </p>
    <ul className="grid gap-2 sm:grid-cols-2 lg:grid-cols-1">
      {project.features.map((feature) => (
        <li
          key={feature}
          className="flex items-center gap-2 text-sm text-[var(--muted)]"
        >
          <Check className="size-3.5 shrink-0 text-[var(--ring)]" />
          {feature}
        </li>
      ))}
    </ul>
  </div>

  <div className="space-y-2">
    <p className="text-xs font-medium uppercase tracking-[0.14em] text-[var(--foreground)]/80">
      Technologies
    </p>

```



```

    <div className="flex flex-wrap gap-2">
      {project.technologies.map((tech) => (
        <span key={tech} className="tech-pill">
          {tech}
        </span>
      ))}
    </div>
  </div>

  <div className="mt-auto flex flex-col gap-2 pt-2 max-md:gap-2.5 sm:grid sm:grid-cols-2">
    <Button
      size="sm"
      variant="outline"
      className="case-study-btn touch-target-sm min-h-11 min-w-0 px-3 text-xs sm:text-xs"
      onClick={() => setCaseStudyProject(project)}
    >
      <span className="truncate">Étude de cas</span>
      <BookOpen className="size-3 shrink-0" />
    </Button>
    <Button
      size="sm"
      variant="outline"
      className="touch-target-sm min-h-11 min-w-0 px-3 text-xs sm:text-xs"
      onClick={() => setCodeProject(project)}
    >
      <Code
        <Code2 className="size-3 shrink-0" />
      </Button>
    </div>
  </div>
</CardContent>
</Card>
</CardHoverGlow>
</TiltCard>
</div>
  )}
</GsapStagger>

<CinematicReveal delay={0.05}>
  <Card className="transparency-card premium-interactive">
    <CardContent className="space-y-3 p-6 max-md:p-6 md:p-10">
      <h3 className="text-xl font-semibold md:text-2xl">
        Une approche transparente
      </h3>
      <p className="max-w-3xl text-sm leading-7 text-[var(--muted)] md:text-base">
        Ces projets sont des démonstrations créées pour présenter le
        niveau de qualité, de design et de finition que Nocta propose à
        ses clients. Chaque démo correspond au format{" "}
        <span className="font-medium text-[var(--foreground)]/90">
          Starter (1 page)
        </span>{" "}
        ? l&apos;offre la plus accessible. Les formules Pro et Premium
        permettent d&apos;étendre le site sur plusieurs pages.
      </p>
    </CardContent>
  </Card>
</CinematicReveal>

<CinematicReveal delay={0.08}>
  <Card className="projects-cta-card premium-interactive overflow-hidden">
    <CardContent className="relative flex flex-col gap-6 p-6 max-md:p-6 md:flex-row md:items-center md:justify-between md:p-10">
      <div className="pointer-events-none absolute -right-8 -top-8 size-40 rounded-full bg-[var(--glow-soft)] blur-3xl" />
      <div className="relative space-y-3">
        <h3 className="text-2xl font-semibold md:text-3xl">
          Votre projet pourrait être le prochain
        </h3>
        <p className="max-w-2xl text-sm leading-7 text-[var(--muted)] md:text-base">

```

```

        Nocta accompagne actuellement ses premiers partenaires pour
        concevoir des sites web modernes, rapides et optimisés pour la
        conversion.
    </p>
</div>
<MagneticButton size="lg" onClick={onContact} className="relative w-full shrink-0 touch-target md:w-auto">
    Discuter de mon projet
    <ArrowRight className="size-4" />
</MagneticButton>
</CardContent>
</Card>
</CinematicReveal>
</section>

<CaseStudyModal
    project={caseStudyProject}
    open={caseStudyProject !== null}
    onClose={() => setCaseStudyProject(null)}
/>
<CodeModal
    project={codeProject}
    open={codeProject !== null}
    onClose={() => setCodeProject(null)}
/>
</>
);
}

```

components/hero-section.tsx

```
"use client";

import {
  ArrowRight,
  CheckCircle2,
  Sparkles,
  TrendingUp,
  Zap,
} from "lucide-react";
import { HeroHeadline } from "@components/motion/hero-headline";
import { ScrollReveal } from "@components/motion/scroll-reveal";
import { Button } from "@components/ui/button";
import { Card } from "@components/ui/card";
import { CardHoverGlow } from "@components/ui/card-hover-glow";
import { MagneticButton } from "@components/ui/magnetic-button";

type HeroSectionProps = {
  onContact: () => void;
  onProjects: () => void;
};

const headlineWords = [
  { text: "Créez" },
  { text: "un" },
  { text: "site" },
  { text: "web" },
  { text: "plus", breakAfter: true },
  { text: "intelligent", className: "hero-text-gradient font-semibold" },
  { text: "qui" },
  { text: "convertit.", className: "hero-text-accent font-bold" },
];

const socialProofItems = [
  "Restaurants & cafés",
  "Freelances & créateurs",
  "Artisans & PME locales",
];

export function HeroSection({ onContact, onProjects }: HeroSectionProps) {
  return (
    <section
      id="hero"
      className="relative grid items-center gap-10 pt-6 max-md:gap-8 max-md:pt-4 md:grid-cols-[1.05fr_0.95fr] md:gap-12 md:pt-14 lg:gap-16"
    >
      <div className="relative space-y-7 max-md:space-y-6 md:space-y-9">
        <div
          aria-hidden
          className="hero-title-glow pointer-events-none absolute -left-8 top-16 h-36 w-[min(100%,24rem)] max-md:h-28 max-md:w-[min(100%,18rem)]
          md:-left-12 md:top-20 md:h-56 md:w-[min(100%,28rem)]"
        />

        <ScrollReveal delay={0.05}>
          <span
            className="hero-badge inline-flex items-center gap-2 rounded-full border border-[var(--border)] bg-[var(--surface)]/90 px-4 py-1.5 text-xs font-
            medium tracking-[0.04em] text-[var(--muted)] backdrop-blur-md"
          >
            <Sparkles
              className="size-3.5 text-[var(--accent)]"
              aria-hidden
            />
            Agence web premium · IA-ready
          </span>
        </ScrollReveal>

        <div className="relative">
          <HeroHeadline words={headlineWords} />
        </div>

        <ScrollReveal delay={0.15}>
          <div
            className="hero-divider h-px w-full max-w-md"
            aria-hidden
          />
        </ScrollReveal>

        <ScrollReveal delay={0.2}>
```

```

<p className="hero-body max-w-xl text-[1.05rem] leading-8 text-[var(--muted)] max-md:text-base max-md:leading-8 md:text-lg md:leading-8">
  Nocta conçoit des expériences web{" "}
  <span className="hero-highlight-span font-medium text-[var(--foreground)]/95">
    rapides, élégantes et orientées conversion
  </span>
  . Design sur mesure, performance optimisée et intégrations IA pour
  transformer vos visiteurs en clients.
</p>
</ScrollReveal>

<ScrollReveal delay={0.28}>
  <div className="flex flex-col gap-3 max-md:gap-2.5 sm:flex-row sm:flex-wrap sm:items-center">
    <MagneticButton
      size="lg"
      onClick={onContact}
      className="hero-cta-primary group w-full min-w-0 touch-target sm:min-w-[11rem] sm:w-auto shadow-[0_0_1px_rgba(255,255,255,0.14)]_inset,0_28px_56px_28px_var(--hero-glow)]"
    >
      Lancer mon projet
      <ArrowRight className="size-4 transition-transform duration-300 group-hover:translate-x-0.5" />
    </MagneticButton>
    <MagneticButton
      size="lg"
      variant="outline"
      onClick={onProjects}
      className="hero-cta-secondary w-full min-w-0 touch-target sm:min-w-[11rem] sm:w-auto"
    >
      Voir les réalisations
    </MagneticButton>
  </div>
</ScrollReveal>

<ScrollReveal delay={0.36}>
  <div className="space-y-4 pt-1">
    <p className="flex items-center gap-2 text-xs font-medium uppercase tracking-[0.08em] text-[var(--muted)]">
      <CheckCircle2 className="size-3.5 text-[var(--accent)]" aria-hidden />
      Confié par des professionnels locaux
    </p>
    <div className="flex flex-wrap gap-2">
      {socialProofItems.map((item) => (
        <span key={item} className="hero-proof-pill">
          {item}
        </span>
      ))}
    </div>
  </div>
</ScrollReveal>
</div>

<ScrollReveal delay={0.12} threshold={0.15} className="relative mx-auto w-full max-w-lg max-md:max-w-[min(100%,22rem)] md:max-w-none">
  <div aria-hidden className="hero-visual-glow pointer-events-none absolute inset-0 scale-110 blur-3xl" />
  <CardHoverGlow className="h-full rounded-3xl">
    <Card className="hero-visual-card relative overflow-hidden border-[var(--border)] p-0 shadow-none">
      <div className="hero-visual-chrome flex items-center gap-2 border-b border-[var(--border)] px-4 py-3">
        <span className="size-2.5 rounded-full bg-[#ff5f57]" />
        <span className="size-2.5 rounded-full bg-[#feb2e2]" />
        <span className="size-2.5 rounded-full bg-[#28c840]" />
        <span className="ml-2 text-[10px] tracking-wide text-[var(--muted)]">
          nocta.studio / dashboard
        </span>
      </div>
    </div>

    <div className="space-y-5 p-5 md:p-6">
      <div className="flex items-start justify-between gap-3">
        <div>
          <p className="text-[11px] uppercase tracking-[0.08em] text-[var(--muted)]">
            Performance

```

```

    </p>
    <p className="hero-display mt-1 text-2xl font-semibold tracking-[-0.03em] md:text-3xl">
      +127<span className="text-[var(--accent)]">%</span>
    </p>
    <p className="mt-0.5 text-xs text-[var(--muted)]">Trafic qualifié ce mois</p>
  </div>
  <div className="hero-metric-icon flex size-10 items-center justify-center rounded-xl border border-[var(--border)] bg-[var(--surface-strong)]">
    <TrendingUp className="size-4 text-[var(--accent)]" />
  </div>
</div>

<div className="hero-chart relative h-24 overflow-hidden rounded-xl border border-[var(--border)] bg-[var(--background)]/40 p-3">
  <div className="absolute inset-x-3 bottom-3 flex items-end justify-between gap-1.5">
    {[38, 52, 44, 68, 58, 82, 74, 96].map((h, i) => (
      <div
        key={i}
        className="hero-chart-bar w-full rounded-sm"
        style={{ height: `${h}%`, animationDelay: `${i * 80}ms` }}
      />
    )]}
  </div>
</div>

<div className="grid gap-3 sm:grid-cols-2">
  <div className="hero-stat-card rounded-xl border border-[var(--border)] bg-[var(--surface)]/80 p-4 backdrop-blur-sm">
    <div className="flex items-center gap-2 text-[var(--muted)]">
      <Zap className="size-3.5 text-[var(--accent)]" />
      <span className="text-[11px]">Temps de chargement</span>
    </div>
    <p className="hero-display mt-2 text-xl font-semibold tracking-[-0.02em]">
      0.8s
    </p>
  </div>
  <div className="hero-stat-card rounded-xl border border-[var(--border)] bg-[var(--surface)]/80 p-4 backdrop-blur-sm">
    <div className="flex items-center gap-2 text-[var(--muted)]">
      <CheckCircle2 className="size-3.5 text-[var(--accent)]" />
      <span className="text-[11px]">Taux de conversion</span>
    </div>
    <p className="hero-display mt-2 text-xl font-semibold tracking-[-0.02em]">
      4.2x
    </p>
  </div>
</div>

  <div className="flex items-center justify-between rounded-xl border border-[var(--border)] bg-[linear-gradient(135deg,var(--surface-strong),color-
mix(in_srgb,var(--accent)_8%,transparent))] px-4 py-3">
    <p className="text-xs text-[var(--muted)]">Prochaine livraison estimée</p>
    <p className="text-sm font-semibold text-[var(--foreground)]">510 jours</p>
  </div>
</div>
</Card>
</CardHoverGlow>
</ScrollReveal>
</section>
);
}

```

components/motion/ambient-particles.tsx

```
"use client";

import { useEffect, useRef } from "react";
import { useMotionEnabled } from "@hooks/use-motion-prefs";
import { usePageVisible } from "@hooks/use-page-visible";

type Particle = {
  x: number;
  y: number;
  vx: number;
  vy: number;
  r: number;
  alpha: number;
};

const PARTICLE_COUNT = 24;

export function AmbientParticles() {
  const canvasRef = useRef<HTMLCanvasElement>(null);
  const motionEnabled = useMotionEnabled();
  const pageVisible = usePageVisible();

  useEffect(() => {
    if (!motionEnabled || !pageVisible) return;

    const el = canvasRef.current;
    if (!el) return;

    const context = el.getContext("2d");
    if (!context) return;

    let raf = 0;
    let particles: Particle[] = [];
    let w = 0;
    let h = 0;

    function resize() {
      const dpr = Math.min(window.devicePixelRatio || 1, 1.25);
      w = window.innerWidth;
      h = window.innerHeight;
      el!.width = Math.floor(w * dpr);
      el!.height = Math.floor(h * dpr);
      el!.style.width = `${w}px`;
      el!.style.height = `${h}px`;
      context!.setTransform(dpr, 0, 0, dpr, 0, 0);
    }

    function init() {
      particles = Array.from({ length: PARTICLE_COUNT }, () => ({
        x: Math.random() * w,
        y: Math.random() * h,
        vx: (Math.random() - 0.5) * 0.18,
        vy: (Math.random() - 0.5) * 0.18,
        r: Math.random() * 1.4 + 0.4,
        alpha: Math.random() * 0.35 + 0.08,
      }));
    }

    function tick() {
      context!.clearRect(0, 0, w, h);
      const isDark = document.documentElement.getAttribute("data-theme") !== "light";
      const color = isDark ? "148, 168, 220" : "90, 110, 170";

      for (const p of particles) {
        p.x += p.vx;
```

```

        p.y += p.vy;
        if (p.x < 0) p.x = w;
        if (p.x > w) p.x = 0;
        if (p.y < 0) p.y = h;
        if (p.y > h) p.y = 0;

        context!.beginPath();
        context!.arc(p.x, p.y, p.r, 0, Math.PI * 2);
        context!.fillStyle = `rgba(${color}, ${p.alpha})`;
        context!.fill();
    }

    raf = requestAnimationFrame(tick);
}

resize();
init();
tick();

const onResize = () => {
    resize();
    init();
};
window.addEventListener("resize", onResize);

return () => {
    cancelAnimationFrame(raf);
    window.removeEventListener("resize", onResize);
};
}, [motionEnabled, pageVisible]));

if (!motionEnabled) return null;

return (
    <canvas
        ref={canvasRef}
        aria-hidden
        className="pointer-events-none fixed inset-0 z-[1] opacity-[0.55]"
    />
);
}

```

components/motion/cinematic-reveal.tsx

```
"use client";

import { ScrollReveal } from "@components/motion/scroll-reveal";
import type { ElementType, ReactNode } from "react";

type CinematicRevealProps = {
  children: ReactNode;
  className?: string;
  delay?: number;
  as?: "div" | "section";
};

/** Scroll-triggered reveal (IntersectionObserver + CSS). */
export function CinematicReveal({
  children,
  className,
  delay = 0,
  as = "div",
}: CinematicRevealProps) {
  return (
    <ScrollReveal
      as={as as ElementType}
      className={className}
      delay={delay}
    >
      {children}
    </ScrollReveal>
  );
}
```


components/motion/float-blobs.tsx

```
"use client";

import { useHeavyMotionEnabled } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

/** Static blurred orbs ? avoids infinite Framer + blur-3xl repaint loops. */
export function FloatBlobs({ className }: { className?: string }) {
  const heavy = useHeavyMotionEnabled();

  if (!heavy) return null;

  return (
    <div className={cn("pointer-events-none absolute inset-0 overflow-hidden", className)}>
      <div
        aria-hidden
        className="float-blob float-blob-a absolute -left-24 top-1/4 size-72 rounded-full bg-[var(--glow-soft)] blur-3xl"
      />
      <div
        aria-hidden
        className="float-blob float-blob-b absolute -right-16 top-1/3 size-96 rounded-full bg-[var(--glow)]/30 blur-3xl"
      />
      <div
        aria-hidden
        className="float-blob float-blob-c absolute bottom-0 left-1/3 size-64 rounded-full bg-[var(--ring)]/10 blur-3xl"
      />
    </div>
  );
}
```

components/motion/float-motion.tsx

```
"use client";

import { useHeavyMotionEnabled, usePrefersReducedMotion } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

type FloatMotionProps = {
  children: React.ReactNode;
  className?: string;
  amplitude?: number;
  duration?: number;
};

export function FloatMotion({ children, className }: FloatMotionProps) {
  const reduced = usePrefersReducedMotion();
  const heavy = useHeavyMotionEnabled();

  if (reduced || !heavy) {
    return <div className={cn(className)}>{children}</div>;
  }

  return <div className={cn("float-motion-idle", className)}>{children}</div>;
}
```

components/motion/gsap-stagger.tsx

```
"use client";

import { ScrollRevealGroup } from "@components/motion/scroll-reveal-group";
import type { ReactNode } from "react";

type GsapStaggerProps = {
  children: ReactNode;
  className?: string;
  itemSelector?: string;
};

/** Staggered scroll reveal (CSS + IntersectionObserver, no GSAP). */
export function GsapStagger({
  children,
  className,
  itemSelector = "[data-stagger-item]",
}: GsapStaggerProps) {
  return (
    <ScrollRevealGroup className={className} itemSelector={itemSelector}>
      {children}
    </ScrollRevealGroup>
  );
}
```

components/motion/hero-headline.tsx

```
"use client";

import { ScrollReveal } from "@components/motion/scroll-reveal";
import { cn } from "@lib/utils";

type WordToken = {
  text: string;
  className?: string;
  breakAfter?: boolean;
};

type HeroHeadlineProps = {
  words: WordToken[];
  className?: string;
  as?: "h1" | "h2";
};

export function HeroHeadline({
  words,
  className,
  as: Tag = "h1",
}: HeroHeadlineProps) {
  return (
    <ScrollReveal as="div" className="reveal-words" threshold={0.2}>
      <Tag className={cn("hero-display text-balance", className)}>
        {words.map((word, i) => (
          <span key={` ${word.text}-${i}`} className="inline">
            <span
              className={cn("reveal-word inline-block", word.className)}
              style={{ "--word-index": i } as React.CSSProperties}
            >
              {word.text}
            </span>
            {i < words.length - 1 ? "\u00A0" : ""}
            {word.breakAfter ? <br className="hidden sm:block" /> : null}
          </span>
        ))}
      </Tag>
    </ScrollReveal>
  );
}
```

components/motion/page-section.tsx

```
"use client";

import {
  createElement,
  useEffect,
  useRef,
  type ElementType,
  type ReactNode,
} from "react";
import { usePrefersReducedMotion } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

type PageSectionProps = {
  children: ReactNode;
  className?: string;
  id?: string;
  as?: "section" | "div";
};

export function PageSection({
  children,
  className,
  id,
  as: Tag = "section",
}: PageSectionProps) {
  const ref = useRef<HTMLElement>(null);
  const reduced = usePrefersReducedMotion();

  useEffect(() => {
    const el = ref.current;
    if (!el) return;

    if (reduced) {
      el.classList.add("is-section-visible");
      return;
    }

    const observer = new IntersectionObserver(
      ([entry]) => {
        if (entry.isIntersecting) {
          el.classList.add("is-section-visible");
          observer.disconnect();
        }
      },
      { threshold: 0.06, rootMargin: "0px 0px -8% 0px" },
    );

    observer.observe(el);
    return () => observer.disconnect();
  }, [reduced]);

  return createElement(
    Tag,
    {
      ref,
      id,
      className: cn("page-section", className),
    },
    children,
  );
}
```

components/motion/parallax-layer.tsx

```
"use client";

import { cn } from "@/lib/utils";

type ParallaxLayerProps = {
  children: React.ReactNode;
  className?: string;
  speed?: number;
};

/** Parallax disabled ? scroll-linked transforms caused sustained layout/paint cost. */
export function ParallaxLayer({ children, className }: ParallaxLayerProps) {
  return <div className={cn(className)}>{children}</div>;
}
```

components/motion/pricing-gold-particles.tsx

```
"use client";

import { useEffect, useRef } from "react";
import { useInView } from "@hooks/use-in-view";
import { useMotionEnabled } from "@hooks/use-motion-prefs";
import { usePageVisible } from "@hooks/use-page-visible";

type Particle = {
  x: number;
  y: number;
  vx: number;
  vy: number;
  r: number;
  alpha: number;
  twinkle: number;
};

const PARTICLE_COUNT = 18;

export function PricingGoldParticles() {
  const canvasRef = useRef<HTMLCanvasElement>(null);
  const hostRef = useRef<HTMLDivElement>(null);
  const motionEnabled = useMotionEnabled();
  const pageVisible = usePageVisible();
  const inView = useInView(hostRef);
  const shouldAnimate = motionEnabled && pageVisible && inView;

  useEffect(() => {
    if (!shouldAnimate) return;

    const el = canvasRef.current;
    const parent = hostRef.current;
    if (!el || !parent) return;

    const context = el.getContext("2d");
    if (!context) return;

    let raf = 0;
    let particles: Particle[] = [];
    let w = 0;
    let h = 0;

    function resize() {
      const dpr = Math.min(window.devicePixelRatio || 1, 1.25);
      const rect = parent!.getBoundingClientRect();
      w = rect.width;
      h = rect.height;
      el!.width = Math.floor(w * dpr);
      el!.height = Math.floor(h * dpr);
      el!.style.width = `${w}px`;
      el!.style.height = `${h}px`;
      context!.setTransform(dpr, 0, 0, dpr, 0, 0);
    }

    function init() {
      particles = Array.from({ length: PARTICLE_COUNT }, () => ({
        x: Math.random() * w,
        y: Math.random() * h,
        vx: (Math.random() - 0.5) * 0.22,
        vy: (Math.random() - 0.5) * 0.16 - 0.04,
        r: Math.random() * 1.6 + 0.35,
        alpha: Math.random() * 0.55 + 0.15,
        twinkle: Math.random() * Math.PI * 2,
      }));
    }
  })
}
```

```

function tick() {
  context!.clearRect(0, 0, w, h);
  const isLight =
    document.documentElement.getAttribute("data-theme") === "light";
  const fillCore = isLight ? "160, 130, 78" : "219, 200, 138";
  const alphaScale = isLight ? 0.55 : 1;

  for (const p of particles) {
    p.x += p.vx;
    p.y += p.vy;
    p.twinkle += 0.035;

    if (p.x < -4) p.x = w + 4;
    if (p.x > w + 4) p.x = -4;
    if (p.y < -4) p.y = h + 4;
    if (p.y > h + 4) p.y = -4;

    const pulse = 0.55 + Math.sin(p.twinkle) * 0.45;
    const alpha = p.alpha * pulse * alphaScale;

    context!.beginPath();
    context!.arc(p.x, p.y, p.r, 0, Math.PI * 2);
    context!.fillStyle = `rgba(${fillCore}, ${alpha})`;
    context!.fill();
  }

  raf = requestAnimationFrame(tick);
}

resize();
init();
tick();

const observer = new ResizeObserver(() => {
  resize();
  init();
});
observer.observe(parent);

return () => {
  cancelAnimationFrame(raf);
  observer.disconnect();
};
}, [shouldAnimate]);

if (!motionEnabled) return null;

return (
  <div ref={hostRef} className="absolute inset-0" aria-hidden>
    <canvas
      ref={canvasRef}
      className="pricing-gold-particles pointer-events-none absolute inset-0 z-[1]"
    />
  </div>
);
}

```


components/motion/scroll-reveal-group.tsx

```
"use client";

import { useEffect, useRef, type ReactNode } from "react";
import { usePrefersReducedMotion } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

type ScrollRevealGroupProps = {
  children: ReactNode;
  className?: string;
  itemSelector?: string;
  threshold?: number;
};

export function ScrollRevealGroup({
  children,
  className,
  itemSelector = "[data-stagger-item]",
  threshold = 0.1,
}: ScrollRevealGroupProps) {
  const ref = useRef<HTMLDivElement>(null);
  const reduced = usePrefersReducedMotion();

  useEffect(() => {
    const root = ref.current;
    if (!root) return;

    const items = root.querySelectorAll(itemSelector);
    items.forEach((item, index) => {
      (item as HTMLElement).classList.add("reveal-stagger-item");
      (item as HTMLElement).style.setProperty("--stagger-index", String(index));
    });

    if (reduced) {
      root.classList.add("is-visible");
      return;
    }

    const observer = new IntersectionObserver(
      ([entry]) => {
        if (entry.isIntersecting) {
          root.classList.add("is-visible");
          observer.disconnect();
        }
      },
      { threshold, rootMargin: "0px 0px -4% 0px" },
    );

    observer.observe(root);
    return () => observer.disconnect();
  }, [reduced, itemSelector, threshold]);

  return (
    <div ref={ref} className={cn("reveal-stagger", className)}>
      {children}
    </div>
  );
}
```

components/motion/scroll-reveal.tsx

```
"use client";

import {
  createElement,
  useEffect,
  useRef,
  type CSSProperties,
  type ElementType,
  type ReactNode,
} from "react";
import { usePrefersReducedMotion } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

type ScrollRevealProps = {
  children: ReactNode;
  className?: string;
  delay?: number;
  as?: ElementType;
  threshold?: number;
};

export function ScrollReveal({
  children,
  className,
  delay = 0,
  as: Tag = "div",
  threshold = 0.12,
}: ScrollRevealProps) {
  const ref = useRef<HTMLElement>(null);
  const reduced = usePrefersReducedMotion();

  useEffect(() => {
    const el = ref.current;
    if (!el) return;

    if (reduced) {
      el.classList.add("is-visible");
      return;
    }

    const observer = new IntersectionObserver(
      ([entry]) => {
        if (entry.isIntersecting) {
          el.classList.add("is-visible");
          observer.disconnect();
        }
      },
      { threshold, rootMargin: "0px 0px -6% 0px" },
    );

    observer.observe(el);
    return () => observer.disconnect();
  }, [reduced, threshold]);

  return createElement(
    Tag,
    {
      ref,
      className: cn("reveal-on-scroll", className),
      style: { "--reveal-delay": `${delay}s` } as CSSProperties,
    },
    children,
  );
}
```

components/motion/subtle-parallax.tsx

```
"use client";

import { useCallback, useRef, type ReactNode } from "react";
import { useThrottledScroll } from "@hooks/use-throttled-scroll";
import { usePrefersReducedMotion } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

type SubtleParallaxProps = {
  children: ReactNode;
  className?: string;
  maxOffset?: number;
};

export function SubtleParallax({
  children,
  className,
  maxOffset = 8,
}: SubtleParallaxProps) {
  const ref = useRef<HTMLDivElement>(null);
  const reduced = usePrefersReducedMotion();

  const update = useCallback(() => {
    const el = ref.current;
    if (!el) return;

    const rect = el.getBoundingClientRect();
    const viewport = window.innerHeight;
    const center = rect.top + rect.height * 0.5;
    const progress = 1 - center / (viewport + rect.height * 0.5);
    const clamped = Math.max(0, Math.min(1, progress));
    const y = (clamped - 0.5) * 2 * maxOffset;

    el.style.transform = `translate3d(0, ${y.toFixed(2)}px, 0)`;
  }, [maxOffset]);

  useThrottledScroll(update, !reduced);

  return (
    <div
      ref={ref}
      className={cn("subtle-parallax-layer", className)}
      style={reduced ? undefined : undefined}
    >
      {children}
    </div>
  );
}
```

components/motion/tilt-card.tsx

```
"use client";

import { useRef, useState } from "react";
import { useMotionEnabled } from "@hooks/use-motion-prefs";
import { cn } from "@lib/utils";

type TiltCardProps = {
  children: React.ReactNode;
  className?: string;
  maxTilt?: number;
};

export function TiltCard({ children, className, maxTilt = 5 }: TiltCardProps) {
  const clipRef = useRef<HTMLDivElement>(null);
  const motionEnabled = useMotionEnabled();
  const [transform, setTransform] = useState("");
  const [glow, setGlow] = useState({ x: 50, y: 50, opacity: 0 });

  function onMove(e: React.MouseEvent<HTMLDivElement>) {
    if (!motionEnabled || !clipRef.current) return;
    const rect = clipRef.current.getBoundingClientRect();
    const x = e.clientX - rect.left;
    const y = e.clientY - rect.top;
    const px = x / rect.width - 0.5;
    const py = y / rect.height - 0.5;
    const rotateX = -py * maxTilt;
    const rotateY = px * maxTilt;

    setTransform(
      `perspective(900px) rotateX(${rotateX}deg) rotateY(${rotateY}deg) translateY(-3px)`
    );
    setGlow({ x: (x / rect.width) * 100, y: (y / rect.height) * 100, opacity: 1 });
  }

  function onLeave() {
    setTransform("");
    setGlow({ x: 50, y: 50, opacity: 0 });
  }

  if (!motionEnabled) {
    return <div className={cn("h-full", className)}>{children}</div>;
  }

  return (
    <div
      ref={clipRef}
      className={cn("tilt-card-clip relative h-full overflow-hidden rounded-3xl", className)}
      onMouseMove={onMove}
      onMouseLeave={onLeave}
    >
      <div
        aria-hidden
        className="tilt-card-glow pointer-events-none absolute inset-0 z-[1] rounded-3xl transition-opacity duration-300"
        style={{
          opacity: glow.opacity,
          background: `radial-gradient(320px circle at ${glow.x}% ${glow.y}%, color-mix(in srgb, var(--accent) 32%, transparent), transparent 72%)`,
        }}
      />
      <div
        className="tilt-card-wrap relative z-[2] h-full rounded-3xl"
        style={{
          transform: transform || undefined,
          transition:
            "transform 400ms cubic-bezier(0.22, 1, 0.36, 1), box-shadow 400ms ease",
        }}
      >
        {children}
      </div>
    </div>
  );
}
```

```
    >
    {children}
  </div>
</div>
);
}
```

components/pricing-section.tsx

```
"use client";

import { AnimatePresence, motion } from "framer-motion";
import {
  ArrowRight,
  Check,
  ChevronDown,
  Minus,
  ShieldCheck,
  Sparkles,
  Star,
  Zap,
} from "lucide-react";
import { useState } from "react";
import { CinematicReveal } from "@components/motion/cinematic-reveal";
import { GsapStagger } from "@components/motion/gsap-stagger";
import { PageSection } from "@components/motion/page-section";
import { SubtleParallax } from "@components/motion/subtle-parallax";
import { Button } from "@components/ui/button";
import { CardHoverGlow } from "@components/ui/card-hover-glow";
import { MagneticButton } from "@components/ui/magnetic-button";
import {
  comparisonRows,
  pricingFaqs,
  pricingPlans,
  type BillingMode,
  type PricingPlan,
} from "@lib/pricing";
import { cn } from "@lib/utils";

type PricingSectionProps = {
  onContact: () => void;
};

function formatPrice(amount: number, mode: BillingMode) {
  if (mode === "monthly") {
    return { value: `${amount}?`, suffix: "/mois" };
  }
  return {
    value: `${amount.toLocaleString("fr-FR")}?`,
    suffix: "",
  };
};

function ComparisonCell({ value }: { value: string | boolean }) {
  if (typeof value === "boolean") {
    return value ? (
      <Check className="mx-auto size-4 text-emerald-500" aria-label="Inclus" />
    ) : (
      <Minus className="mx-auto size-4 text-[var(--muted)]/50" aria-label="Non inclus" />
    );
  }
  return <span className="text-sm text-[var(--foreground)]/90">{value}</span>;
}

function FaqItem({
  question,
  answer,
  open,
  onHover,
  onLeave,
  onToggle,
} : {
  question: string;
  answer: string;
```

```

open: boolean;
onHover: () => void;
onLeave: () => void;
onToggle: () => void;
}) {
  return (
    <div
      className="pricing-faq-item overflow-hidden rounded-2xl border border-[var(--border)] bg-[var(--surface)]/60"
      onMouseEnter={onHover}
      onMouseLeave={onLeave}
    >
      <button
        type="button"
        onClick={onToggle}
        className="flex w-full touch-target-sm cursor-default items-center justify-between gap-4 px-5 py-4 text-left transition-colors hover:bg-[var(--surface-s
trong)]/50 max-md:py-4"
        aria-expanded={open}
      >
        <span className="text-sm font-medium md:text-base">{question}</span>
        <ChevronDown
          className={cn(
            "size-4 shrink-0 text-[var(--muted)] transition-transform duration-300",
            open && "rotate-180",
          )}
        />
      </button>
      <AnimatePresence initial={false}>
        {open ? (
          <motion.div
            initial={{ height: 0, opacity: 0 }}
            animate={{ height: "auto", opacity: 1 }}
            exit={{ height: 0, opacity: 0 }}
            transition={{ duration: 0.28, ease: [0.22, 1, 0.36, 1] }}
          >
            <p className="border-t border-[var(--border)] px-5 pb-4 pt-3 text-sm leading-7 text-[var(--muted)]">
              {answer}
            </p>
          </motion.div>
        ) : null}
      </AnimatePresence>
    </div>
  );
}

```

```

function setFeaturedGlow(event: React.MouseEvent<HTMLDivElement>, reset = false) {
  const bg = event.currentTarget.querySelector<HTMLElement>(".pricing-card-featured-bg");
  if (!bg) return;
  if (reset) {
    bg.style.setProperty("--glow-x", "50%");
    bg.style.setProperty("--glow-y", "35%");
    return;
  }
  const rect = event.currentTarget.getBoundingClientRect();
  const x = ((event.clientX - rect.left) / rect.width) * 100;
  const y = ((event.clientY - rect.top) / rect.height) * 100;
  bg.style.setProperty("--glow-x", `${x}%`);
  bg.style.setProperty("--glow-y", `${y}%`);
}

```

```

function PricingPlanCard({
  plan,
  billingMode,
  onContact,
}): {
  plan: PricingPlan;
  billingMode: BillingMode;
  onContact: () => void;
}

```

```

})) {
  const price = billingMode === "monthly" ? plan.monthlyPrice : plan.projectPrice;
  const formatted = formatPrice(price, billingMode);
  const isFeatured = plan.highlighted;

  const cardInner = (
    <div className="pricing-card-inner flex h-full flex-col gap-4 p-5 md:p-6">
      <div className="space-y-3">
        <div className="space-y-1.5">
          <div className="flex flex-wrap items-center gap-2">
            <p
              className={cn(
                "text-xs font-semibold uppercase tracking-[0.1em]",
                isFeatured ? "text-[var(--accent)]" : "text-[var(--muted)]",
              )}
            >
              {plan.name}
            </p>
            {isFeatured ? (
              <>
                <Zap className="size-3.5 text-[var(--pricing-gold)]" aria-hidden />
                <span className="pricing-popular-badge">
                  <Star className="size-2.5 fill-[var(--pricing-gold)] text-[var(--pricing-gold)]" />
                  {plan.badge}
                </span>
              </>
            ) : null}
          </div>
          <p
            className={cn(
              "text-sm leading-6",
              isFeatured ? "text-[var(--foreground)]/88" : "text-[var(--muted)]",
            )}
          >
            {plan.tagline}
          </p>
        </div>

        <div className="pricing-price-block">
          <div className="flex flex-wrap items-end gap-x-1.5 gap-y-0.5">
            <span className="pricing-price tabular-nums" aria-label={`Prix ${plan.name}`}>
              {formatted.value}
            </span>
            {formatted.suffix ? (
              <span className="pricing-price-suffix">{formatted.suffix}</span>
            ) : null}
          </div>
        </div>

        {plan.featuredNote ? (
          <p className="pricing-featured-note rounded-lg border border-[var(--ring)]/35 bg-[var(--accent-soft)] px-3 py-2 text-[11px] leading-5 text-[var(--foreground)]/85">
            {plan.featuredNote}
          </p>
        ) : null}
      </div>

      <ul className="pricing-features flex-1 space-y-2 border-t border-[var(--border)]/80 pt-3.5">
        {plan.features.map((feature) => (
          <li key={feature} className="flex items-start gap-2.5 text-[13px] leading-5">
            <span
              className={cn(
                "pricing-feature-icon mt-0.5 flex size-[1.15rem] shrink-0 items-center justify-center rounded-full",
                isFeatured && "pricing-feature-icon-featured",
              )}
            >
              <Check className="size-2.5" strokeWidth={2.5} />

```



```

        </span>
        <span
          className={cn(
            isFeatured ? "text-[var(--foreground)]/92" : "text-[var(--foreground)]/78",
          )}
        >
          {feature}
        </span>
      </li>
    )}
  </ul>

  <MagneticButton
    variant={isFeatured ? "default" : "outline"}
    size="default"
    className={cn(
      "pricing-cta w-full touch-target",
      isFeatured && "pricing-cta-featured hero-cta-primary",
      !isFeatured && "pricing-cta-secondary",
    )}
    onClick={onContact}
  >
    {plan.ctaLabel ?? (isFeatured ? "Choisir Pro" : "Demander un devis")}
    <ArrowRight className="size-4" />
  </MagneticButton>
</div>
);

if (isFeatured) {
  return (
    <div className="pricing-card-featured-shell h-full">
      <div
        className="pricing-card-featured group relative h-full"
        onMouseMove={(e) => setFeaturedGlow(e)}
        onMouseLeave={(e) => setFeaturedGlow(e, true)}
      >
        <div aria-hidden className="pricing-card-featured-bg">
          <div className="pricing-card-featured-glow" />
          <div className="pricing-card-featured-light" />
        </div>
        {cardInner}
      </div>
    </div>
  );
}

return (
  <CardHoverGlow className="h-full rounded-[1.2rem]">
    <div className="pricing-card pricing-card-secondary group relative h-full overflow-hidden rounded-[1.2rem]">
      {cardInner}
    </div>
  </CardHoverGlow>
);
}

export function PricingSection({ onContact }: PricingSectionProps) {
  const [billingMode, setBillingMode] = useState<BillingMode>("monthly");
  const [openFaq, setOpenFaq] = useState<number | null>(null);

  return (
    <PageSection id="pricing" className="relative space-y-10 max-md:space-y-9 md:max-lg:space-y-12 lg:space-y-14">
      <div
        aria-hidden
        className="pointer-events-none absolute -right-20 top-0 z-0 h-56 w-56 opacity-40 max-lg:hidden"
      >
        <SubtleParallax maxOffset={6} className="size-full">
          <div className="size-full rounded-full bg-[var(--glow-soft)] blur-3xl" />

```

```

    </SubtleParallax>
  </div>

  <div className="relative z-[1] space-y-10 max-md:space-y-9 md:max-lg:space-y-12 lg:space-y-14">
    <CinematicReveal className="mx-auto max-w-3xl space-y-5 text-center">
      <p className="pricing-section-badge inline-flex items-center gap-2 rounded-full border border-[var(--border)] px-4 py-1.5 text-xs tracking-[0.08em] text-[var(--muted)]">
        <Sparkles className="size-3.5 text-[var(--accent)]" />
        Tarifs transparents
      </p>
      <h2 className="hero-display text-[1.75rem] tracking-[-0.03em] max-md:text-[1.65rem] md:text-5xl">
        Des offres claires, pensées pour convertir
      </h2>
      <p className="text-base leading-7 text-[var(--muted)] max-md:leading-8 md:text-lg">
        Choisissez &apos;offre adaptée à votre ambition. Chaque formule inclut un
        accompagnement professionnel et des révisions pour un résultat qui vous
        ressemble.
      </p>

      <div className="pricing-toggle inline-flex w-full max-w-sm items-center gap-1 rounded-full border border-[var(--border)] p-1 max-md:max-w-none">
        <button
          type="button"
          onClick={() => setBillingMode("monthly")}
          className={cn(
            "touch-target-sm flex-1 rounded-full px-4 py-2.5 text-sm font-medium transition-all duration-300 max-md:py-3",
            billingMode === "monthly"
              ? "bg-[var(--foreground)] text-[var(--background)] shadow-sm"
              : "text-[var(--muted)] hover:text-[var(--foreground)]",
          )}
        >
          Mensuel
        </button>
        <button
          type="button"
          onClick={() => setBillingMode("project")}
          className={cn(
            "touch-target-sm flex-1 rounded-full px-4 py-2.5 text-sm font-medium transition-all duration-300 max-md:py-3",
            billingMode === "project"
              ? "bg-[var(--foreground)] text-[var(--background)] shadow-sm"
              : "text-[var(--muted)] hover:text-[var(--foreground)]",
          )}
        >
          Achat
        </button>
      </div>
      <p className="text-xs text-[var(--muted)]">
        {billingMode === "monthly"
          ? "Hébergement, maintenance et mises à jour inclus."
          : "Païement unique ? sans abonnement mensuel."}
      </p>
    </CinematicReveal>

    <GsapStagger className="grid items-stretch gap-4 md:max-lg:grid-cols-2 lg:grid-cols-3">
      {pricingPlans.map((plan) => (
        <div
          key={plan.id}
          data-stagger-item
          className={cn("h-full", plan.highlighted && "md:max-lg:col-span-2")}
        >
          <PricingPlanCard plan={plan} billingMode={billingMode} onContact={onContact} />
        </div>
      ))}
    </GsapStagger>

    <CinematicReveal delay={0.04}>
      <div className="pricing-guarantee flex flex-col items-start gap-4 rounded-2xl border border-[var(--border)] bg-[var(--surface)]/70 p-5 max-md:p-5 md:flex
x-row md:items-center md:justify-between md:p-8">

```

```

<div className="flex items-start gap-4">
  <div className="flex size-11 shrink-0 items-center justify-center rounded-xl border border-[var(--border)] bg-[var(--surface-strong)]">
    <ShieldCheck className="size-5 text-emerald-500" />
  </div>
  <div>
    <p className="font-semibold">Garantie satisfaction</p>
    <p className="mt-1 max-w-xl text-sm leading-7 text-[var(--muted)]">
      Révisions incluses sur chaque offre. Si le résultat ne correspond pas
      à ce qui a été validé ensemble, nous ajustons jusqu'à votre
      satisfaction ? sans frais cachés.
    </p>
  </div>
  <div>
    <MagneticButton variant="outline" onClick={onContact} className="w-full touch-target md:w-auto">
      Discuter de mon projet
    </MagneticButton>
  </div>
</CinematicReveal>

<CinematicReveal delay={0.06} className="space-y-5">
  <div className="space-y-2">
    <h3 className="text-xl font-semibold tracking-[-0.02em] md:text-2xl">
      Comparer les offres
    </h3>
    <p className="text-sm text-[var(--muted)] md:text-base">
      Vue d'ensemble pour choisir en toute confiance.
    </p>
  </div>

  <div className="pricing-comparison hidden overflow-x-auto rounded-2xl border border-[var(--border)] lg:block">
    <table className="pricing-table w-full min-w-[640px] border-collapse text-left">
      <thead>
        <tr className="border-b border-[var(--border)]">
          <th className="px-5 py-4 text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
            Fonctionnalité
          </th>
          <th className="px-5 py-4 text-center text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
            Starter
          </th>
          <th className="px-5 py-4 text-center text-xs font-medium uppercase tracking-[0.06em] text-[var(--foreground)]">
            Pro
            <span className="mt-1 block text-[10px] font-normal normal-case text-[var(--pricing-gold)]">
              Most Popular
            </span>
          </th>
          <th className="px-5 py-4 text-center text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
            Premium
          </th>
        </tr>
      </thead>
      <tbody>
        {comparisonRows.map((row, index) => (
          <tr>
            <td>
              <div>
                key={row.label}
                className={cn(
                  "border-b border-[var(--border)]/70 transition-colors last:border-0 hover:bg-[var(--surface-strong)]/30",
                  index % 2 === 0 && "bg-[var(--background)]/20",
                )}
              </div>
            </td>
            <td className="px-5 py-3.5 text-sm font-medium">{row.label}</td>
            <td className="px-5 py-3.5 text-center opacity-80">
              <ComparisonCell value={row.starter} />
            </td>
            <td className="pricing-comparison-pro px-5 py-3.5 text-center">
              <ComparisonCell value={row.pro} />
            </td>
            <td className="px-5 py-3.5 text-center opacity-80">

```

```

        <ComparisonCell value={row.premium} />
      </td>
    </tr>
  )}
</tbody>
</table>
</div>

<div className="pricing-comparison-mobile space-y-3 lg:hidden">
  {comparisonRows.map((row) => (
    <div
      key={row.label}
      className="rounded-2xl border border-[var(--border)] bg-[var(--surface)]/60 p-4"
    >
      <p className="mb-3 text-sm font-semibold">{row.label}</p>
      <div className="grid grid-cols-3 gap-2 text-center text-xs">
        <div className="space-y-1 rounded-xl bg-[var(--background)]/30 p-2">
          <p className="font-medium uppercase tracking-wide text-[var(--muted)]">Starter</p>
          <ComparisonCell value={row.starter} />
        </div>
        <div className="pricing-comparison-pro space-y-1 rounded-xl p-2">
          <p className="font-medium uppercase tracking-wide text-[var(--foreground)]">Pro</p>
          <ComparisonCell value={row.pro} />
        </div>
        <div className="space-y-1 rounded-xl bg-[var(--background)]/30 p-2">
          <p className="font-medium uppercase tracking-wide text-[var(--muted)]">Premium</p>
          <ComparisonCell value={row.premium} />
        </div>
      </div>
    </div>
  )})
</div>
</CinematicReveal>

<CinematicReveal delay={0.08} className="space-y-5">
  <div className="space-y-2">
    <h3 className="text-xl font-semibold tracking-[-0.02em] md:text-2xl">
      Questions fréquentes
    </h3>
    <p className="text-sm text-[var(--muted)] md:text-base">
      Tout ce qu&apos;il faut savoir avant de démarrer.
    </p>
  </div>

  <div className="space-y-3">
    {pricingFaqs.map((faq, index) => (
      <FaqItem
        key={faq.question}
        question={faq.question}
        answer={faq.answer}
        open={openFaq === index}
        onHover={() => setOpenFaq(index)}
        onLeave={() => setOpenFaq(null)}
        onToggle={() => setOpenFaq(openFaq === index ? null : index)}
      />
    )})
  </div>
</CinematicReveal>
</div>
</PageSection>
);
}

```

components/priority-list-hero.tsx

```
"use client";

import { HeroHeadline } from "@/components/motion/hero-headline";
import { ScrollReveal } from "@/components/motion/scroll-reveal";

const headlineWords = [
  { text: "Réservez", className: "hero-text-gradient font-semibold" },
  { text: "votre" },
  { text: "place", className: "hero-word-emphasis" },
  { text: "parmi", breakAfter: true },
  { text: "les" },
  { text: "premières", className: "hero-text-gradient hero-word-emphasis" },
  { text: "entreprises", className: "hero-text-accent font-bold" },
  { text: "accompagnées.", className: "hero-word-emphasis" },
];

export function PriorityListHero() {
  return (
    <div className="priority-list-hero relative mx-auto max-w-3xl space-y-7 text-center">
      <div aria-hidden className="priority-list-hero-glow pointer-events-none absolute inset-x-0 top-8 mx-auto h-40 w-[min(100%,24rem)]" />

      <ScrollReveal delay={0.05}>
        <p className="priority-list-badge relative inline-flex items-center gap-2 rounded-full border border-[var(--border)] px-4 py-1.5 text-xs font-medium tracking-[0.04em] text-[var(--muted)]">
          <span aria-hidden>?</span>
          Ouverture prochaine
        </p>
      </ScrollReveal>

      <div className="relative">
        <HeroHeadline as="h2" words={headlineWords} className="priority-list-headline" />
      </div>

      <ScrollReveal delay={0.12} className="hero-divider mx-auto h-px w-full max-w-sm">
        <span className="sr-only">Séparateur</span>
      </ScrollReveal>

      <ScrollReveal delay={0.2}>
        <p className="priority-list-subtext mx-auto max-w-2xl text-base leading-8 text-[var(--muted)] md:text-lg md:leading-8">
          Nocta sélectionne actuellement{" "}
          <span className="hero-text-accent font-semibold">quelques entreprises</span> pour ses{" "}
          <span className="hero-word-emphasis text-[var(--foreground)]/90">
            premières refontes web
          </span>{" "}
          et futurs accompagnements digitaux.{ " "}
          <span className="hero-text-gradient font-semibold">Rejoignez la liste prioritaire</span>{" "}
          pour être informé en avant-première lors de l'ouverture officielle.
        </p>
      </ScrollReveal>
    </div>
  );
}
```

components/priority-list-section.tsx

```
"use client";

import { AnimatePresence, motion } from "framer-motion";
import { ArrowRight, Check, Sparkles } from "lucide-react";
import { useState } from "react";
import { CinematicReveal } from "@components/motion/cinematic-reveal";
import { PriorityListHero } from "@components/priority-list-hero";
import { MagneticButton } from "@components/ui/magnetic-button";
import { Input } from "@components/ui/input";
import { Textarea } from "@components/ui/textarea";
import {
  priorityListConfirmation,
  priorityListReassurance,
  submitPriorityList,
  type PriorityListSubmission,
} from "@lib/priority-list";

type FormState = "idle" | "submitting" | "success" | "error";

const initialForm: PriorityListSubmission = {
  name: "",
  email: "",
  company: "",
  website: "",
  need: "",
};

export function PriorityListSection() {
  const [form, setForm] = useState(initialForm);
  const [state, setState] = useState<FormState>("idle");
  const [errorMessage, setErrorMessage] = useState("");

  function updateField(field: keyof PriorityListSubmission, value: string) {
    setForm((prev) => ({ ...prev, [field]: value }));
  }

  async function handleSubmit(event: React.FormEvent<HTMLFormElement>) {
    event.preventDefault();
    if (state === "submitting") return;

    setState("submitting");
    setErrorMessage("");

    try {
      await submitPriorityList({
        ...form,
        website: form.website?.trim() || undefined,
      });
      setState("success");
      setForm(initialForm);
    } catch (error) {
      setState("error");
      setErrorMessage(
        error instanceof Error
          ? error.message
          : "Une erreur est survenue. Réessayez dans un instant.",
      );
    }
  }

  return (
    <section id="contact" className="space-y-7 pb-6 max-md:space-y-6 md:max-lg:space-y-8 lg:space-y-8">
      <PriorityListHero />

      <CinematicReveal delay={0.06}>
```

```

<div className="priority-list-card mx-auto max-w-2xl rounded-3xl p-5 max-md:p-5 md:p-9">
  <AnimatePresence mode="wait">
    {state === "success" ? (
      <motion.div
        key="success"
        initial={{ opacity: 0, y: 12 }}
        animate={{ opacity: 1, y: 0 }}
        exit={{ opacity: 0, y: -8 }}
        transition={{ duration: 0.45, ease: [0.22, 1, 0.36, 1] }}
        className="priority-list-success flex flex-col items-center gap-4 py-8 text-center"
      >
        <div className="flex size-12 items-center justify-center rounded-full border border-[var(--ring)] bg-[var(--accent-soft)]">
          <Check className="size-5 text-[var(--accent)]" aria-hidden />
        </div>
        <p className="max-w-md text-base leading-8 text-[var(--foreground)]/95 md:text-lg">
          {priorityListConfirmation}
        </p>
      </motion.div>
    ) : (
      <motion.form
        key="form"
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        onSubmit={handleSubmit}
        className="space-y-5"
      >
        <div className="grid gap-4 md:grid-cols-2">
          <label className="space-y-2 text-left">
            <span className="text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
              Nom
            </span>
            <Input
              name="name"
              placeholder="Jean Dupont"
              value={form.name}
              onChange={(e) => updateField("name", e.target.value)}
              required
              autoComplete="name"
            />
          </label>
          <label className="space-y-2 text-left">
            <span className="text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
              Email professionnel
            </span>
            <Input
              name="email"
              type="email"
              placeholder="contact@votre-entreprise.fr"
              value={form.email}
              onChange={(e) => updateField("email", e.target.value)}
              required
              autoComplete="email"
            />
          </label>
        </div>

        <label className="block space-y-2 text-left">
          <span className="text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
            Entreprise
          </span>
          <Input
            name="company"
            placeholder="Nom de votre entreprise"
            value={form.company}
            onChange={(e) => updateField("company", e.target.value)}
            required
          />
        </label>
      </motion.form>
    )}
  </AnimatePresence>
</div>

```

```

      autoComplete="organization"
    />
  </label>

  <label className="block space-y-2 text-left">
    <span className="text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
      Site web actuel{" "}
      <span className="normal-case tracking-normal text-[var(--muted)]/80">
        (optionnel)
      </span>
    </span>
    <input
      name="website"
      type="url"
      placeholder="https://votre-site.fr"
      value={form.website}
      onChange={(e) => updateField("website", e.target.value)}
      autoComplete="url"
    />
  </label>

  <label className="block space-y-2 text-left">
    <span className="text-xs font-medium uppercase tracking-[0.06em] text-[var(--muted)]">
      Besoin principal
    </span>
    <textarea
      name="need"
      placeholder="Refonte de site, création vitrine, optimisation conversion?"
      value={form.need}
      onChange={(e) => updateField("need", e.target.value)}
      required
      className="min-h-32"
    />
  </label>

  {state === "error" && errorMessage ? (
    <p className="rounded-xl border border-red-400/30 bg-red-400/8 px-4 py-3 text-sm text-red-300">
      {errorMessage}
    </p>
  ) : null}

  <MagneticButton
    type="submit"
    size="lg"
    className="hero-cta-primary group w-full touch-target sm:w-auto"
    disabled={state === "submitting"}
  >
    {state === "submitting" ? "Envoi en cours?" : "Rejoindre la liste prioritaire"}
    <ArrowRight className="size-4 transition-transform duration-300 group-hover:translate-x-0.5" />
  </MagneticButton>
</motion.form>
  )}
</AnimatePresence>

{state !== "success" ? (
  <ul className="priority-list-reassurance mt-7 grid gap-3 border-t border-[var(--border)] pt-6 max-md:grid-cols-1 sm:grid-cols-3">
    {priorityListReassurance.map((item) => (
      <li
        key={item}
        className="flex items-start gap-2 text-xs leading-6 text-[var(--muted)] sm:text-sm"
      >
        <Check className="mt-0.5 size-3.5 shrink-0 text-[var(--accent)]" aria-hidden />
        {item}
      </li>
    ))}
  </ul>
) : null}

```



```
    </div>
  </CinematicReveal>

  <CinematicReveal delay={0.1} className="flex justify-center">
    <p className="inline-flex items-center gap-2 text-xs text-[var(--muted)]">
      <Sparkles className="size-3.5 text-[var(--accent)]" aria-hidden />
      Nocta Agency · Lancement en préparation
    </p>
  </CinematicReveal>
</section>
);
}
```

components/responsive-preview-shell.tsx

```
"use client";

import { Monitor, Smartphone, Tablet } from "lucide-react";
import { usePathname, useSearchParams } from "next/navigation";
import { Suspense, useMemo } from "react";
import {
  isPreviewFrame,
  PREVIEW_WIDTHS,
  useResponsivePreview,
  type PreviewMode,
} from "@hooks/use-responsive-preview";
import { isResponsivePreviewAvailable } from "@lib/responsive-preview-config";
import { cn } from "@lib/utils";

const previewEnabled = isResponsivePreviewAvailable();

function PreviewToolbar({
  mode,
  setMode,
}: {
  mode: PreviewMode;
  setMode: (mode: PreviewMode) => void;
}) {
  const options: { id: PreviewMode; label: string; icon: typeof Monitor }[] = [
    { id: "full", label: "Desktop", icon: Monitor },
    { id: "tablet", label: "Tablette", icon: Tablet },
    { id: "mobile", label: "Mobile", icon: Smartphone },
  ];

  return (
    <div
      className="responsive-preview-toolbar fixed bottom-5 left-1/2 z-[100] flex -translate-x-1/2 items-center gap-1 rounded-2xl border border-[var(--border)] b
g-[var(--surface-strong)]/95 p-1.5 shadow-2xl backdrop-blur-md"
      role="toolbar"
      aria-label="Simulation responsive"
    >
      {options.map(({ id, label, icon: Icon }) => (
        <button
          key={id}
          type="button"
          onClick={() => setMode(id)}
          className={cn(
            "inline-flex items-center gap-2 rounded-xl px-3 py-2 text-xs font-medium transition-all",
            mode === id
              ? "bg-[var(--foreground)] text-[var(--background)]"
              : "text-[var(--muted)] hover:bg-[var(--surface)] hover:text-[var(--foreground)]",
          )}
          aria-pressed={mode === id}
        >
          <Icon className="size-3.5" aria-hidden />
          <span className="hidden sm:inline">{label}</span>
        </button>
      ))}
    </div>
  );
}

function PreviewFrame({ mode }: { mode: Exclude<PreviewMode, "full"> }) {
  const src = useMemo(() => {
    if (typeof window === "undefined") return "/?preview-frame=1";
    const url = new URL(window.location.href);
    url.searchParams.set("preview-frame", "1");
    return url.pathname + url.search;
  }, []);
}
```

```

const width = PREVIEW_WIDTHS[mode];

return (
  <div className="responsive-preview-workbench fixed inset-0 z-[90] flex flex-col items-center overflow-auto bg-[#0d0d12] px-4 pb-24 pt-6">
    <div className="mb-4 flex items-center gap-3 text-xs text-white/60">
      <span className="rounded-full border border-white/15 bg-white/5 px-3 py-1">
        {mode === "mobile" ? "iPhone · 390px" : "iPad · 834px"}
      </span>
      <span>Les breakpoints réels s'appliquent dans le cadre</span>
    </div>
    <div
      className="responsive-preview-device relative shrink-0 overflow-hidden rounded-[2rem] border border-white/15 bg-[var(--background)] shadow-[0_40px_80px_-20px_rgba(0,0,0,0.65)]"
      style={{ width }}
    >
      <div className="pointer-events-none absolute inset-x-0 top-0 z-10 flex justify-center pt-2">
        <div className="h-1 w-16 rounded-full bg-black/20" aria-hidden />
      </div>
      <iframe
        title={`Aperçu ${mode}`}
        src={src}
        className="block w-full border-0"
        style={{ height: "min(90vh, 844px)", minHeight: "640px" }}
      />
    </div>
  </div>
);
}

function ResponsivePreviewInner({ children }: { children: React.ReactNode }) {
  const { mode, setMode, mounted } = useResponsivePreview();
  const pathname = usePathname();
  const searchParams = useSearchParams();
  const inFrame = searchParams.has("preview-frame") || isPreviewFrame();
  const isDemoRoute = pathname?.startsWith("/demos");

  if (!previewEnabled || isDemoRoute) {
    return <>{children}</>;
  }

  if (inFrame) {
    return <>{children}</>;
  }

  if (!mounted) {
    return <>{children}</>;
  }

  return (
    <>
      {mode === "full" ? children : null}
      {mode === "mobile" || mode === "tablet" ? <PreviewFrame mode={mode} /> : null}
      <PreviewToolbar mode={mode} setMode={setMode} />
    </>
  );
}

export function ResponsivePreviewShell({ children }: { children: React.ReactNode }) {
  if (!previewEnabled) {
    return <>{children}</>;
  }

  return (
    <Suspense fallback={children}>
      <ResponsivePreviewInner>{children}</ResponsivePreviewInner>
    </Suspense>
  );
}

```


components/site-header.tsx

```
"use client";

import { AnimatePresence, motion } from "framer-motion";
import { Menu, Moon, Sun, X } from "lucide-react";
import { useEffect, useState } from "react";
import { Button } from "@/components/ui/button";
import { cn } from "@/lib/utils";

type SiteHeaderProps = {
  theme: "dark" | "light";
  onToggleTheme: () => void;
  onNavigate: (sectionId: string) => void;
};

const navLinks = [
  { id: "projects", label: "Projets" },
  { id: "services", label: "Services" },
  { id: "pricing", label: "Tarifs" },
  { id: "about", label: "Agence" },
  { id: "contact", label: "Contact" },
];

export function SiteHeader({ theme, onToggleTheme, onNavigate }: SiteHeaderProps) {
  const [menuOpen, setMenuOpen] = useState(false);

  useEffect(() => {
    document.body.style.overflow = menuOpen ? "hidden" : "";
    return () => {
      document.body.style.overflow = "";
    };
  }, [menuOpen]);

  function navigate(sectionId: string) {
    setMenuOpen(false);
    onNavigate(sectionId);
  }

  return (
    <>
      <div className="site-header-shell fixed inset-x-0 top-0 z-50 px-4 pt-4 md:px-6 md:pt-5">
        <motion.header
          initial={{ opacity: 0, y: -12 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ duration: 0.6, ease: [0.22, 1, 0.36, 1] }}
          className="site-header mx-auto flex h-14 max-w-6xl items-center justify-between rounded-3xl px-5 md:h-[3.75rem] md:rounded-[1.75rem] md:px-7">
          >
            <button
              type="button"
              onClick={() => navigate("hero")}
              className="text-xl font-semibold tracking-tight transition-opacity hover:opacity-80">
              >
                Nocta Agency
            </button>

            {/* Desktop nav ? unchanged at lg+ */}
            <div className="hidden items-center gap-2 lg:flex">
              <Button variant="ghost" size="sm" onClick={() => navigate("pricing")}>
                Tarifs
              </Button>
              <Button variant="outline" size="sm" onClick={() => navigate("contact")}>
                Devis rapide
              </Button>
              <Button
                variant="outline"
                size="sm"
              >
            </div>
          </div>
    </>
  );
}
```

```

        onClick={onToggleTheme}
        aria-label="Changer le thème"
      >
        {theme === "dark" ? (
          <Sun className="size-4" aria-hidden="true" />
        ) : (
          <Moon className="size-4" aria-hidden="true" />
        )}
      </Button>
    </div>

    {/ * Mobile / tablet controls */}
    <div className="flex items-center gap-2 lg:hidden">
      <Button
        variant="outline"
        size="sm"
        onClick={onToggleTheme}
        aria-label="Changer le thème"
        className="touch-target-sm"
      >
        {theme === "dark" ? (
          <Sun className="size-4" aria-hidden="true" />
        ) : (
          <Moon className="size-4" aria-hidden="true" />
        )}
      </Button>
      <Button
        variant="outline"
        size="sm"
        onClick={() => setMenuOpen((open) => !open)}
        aria-expanded={menuOpen}
        aria-controls="mobile-nav"
        aria-label={menuOpen ? "Fermer le menu" : "Ouvrir le menu"}
        className="touch-target-sm"
      >
        {menuOpen ? (
          <X className="size-4" aria-hidden="true" />
        ) : (
          <Menu className="size-4" aria-hidden="true" />
        )}
      </Button>
    </div>
  </motion.header>
</div>

<AnimatePresence>
  {menuOpen ? (
    <>
      <motion.button
        type="button"
        aria-label="Fermer le menu"
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        transition={{ duration: 0.2 }}
        className="mobile-nav-backdrop fixed inset-0 z-40 bg-black/50 backdrop-blur-sm lg:hidden"
        onClick={() => setMenuOpen(false)}
      />
      <motion.nav
        id="mobile-nav"
        initial={{ x: "100%" }}
        animate={{ x: 0 }}
        exit={{ x: "100%" }}
        transition={{ duration: 0.32, ease: [0.22, 1, 0.36, 1] }}
        className="mobile-nav-panel fixed inset-y-0 right-0 z-50 flex w-[min(100%,20rem)] flex-col gap-2 border-l border-[var(--border)] bg-[var(--surface
-strong)] p-6 pt-24 shadow-2xl lg:hidden"
      >

```

```

    <p className="mb-2 text-xs font-medium uppercase tracking-[0.1em] text-[var(--muted)]">
      Navigation
    </p>
    {navLinks.map((link) => (
      <button
        key={link.id}
        type="button"
        onClick={() => navigate(link.id)}
        className={cn(
          "mobile-nav-link touch-target rounded-xl px-4 py-3.5 text-left text-base font-medium",
          "transition-colors hover:bg-[var(--surface)]",
        )}
      >
        {link.label}
      </button>
    ))}
    <div className="mt-auto space-y-3 border-t border-[var(--border)] pt-6">
      <Button
        size="lg"
        className="hero-cta-primary w-full"
        onClick={() => navigate("contact")}
      >
        Devis rapide
      </Button>
      <Button
        size="lg"
        variant="outline"
        className="w-full"
        onClick={() => navigate("pricing")}
      >
        Voir les tarifs
      </Button>
    </div>
  </motion.nav>
</>
) : null}
</AnimatePresence>
</>
);
}

```

components/ui/button.tsx

```
import * as React from "react";
import { cn } from "@lib/utils";

type ButtonProps = React.ButtonHTMLAttributes<HTMLButtonElement> & {
  variant?: "default" | "outline" | "ghost";
  size?: "default" | "sm" | "lg";
};

const variantClasses: Record<Nullable<ButtonProps["variant"]>, string> = {
  default:
    "relative overflow-hidden border border-[var(--border)] bg-[linear-gradient(135deg,var(--primary),var(--primary-strong))] text-[var(--button-foreground)] shadow-[0_0_0_1px_rgba(255,255,255,0.12)_inset,0_20px_34px_-20px_var(--glow)] before:absolute before:inset-y-0 before:-left-1/2 before:w-1/2 before:skew-x-[-24deg] before:bg-white/18 before:opacity-0 before:blur-md before:transition-all before:duration-500 hover:scale-[1.012] hover:brightness-105 hover:before:left-[130%] hover:before:opacity-100",
  outline:
    "border border-[var(--border)] bg-[var(--surface)]/86 text-[var(--foreground)] shadow-[0_14px_26px_-22px_rgba(21,29,58,0.45)] hover:bg-[var(--surface-strong)] hover:border-[color:var(--ring)]",
  ghost:
    "border border-transparent text-[var(--foreground)] hover:border-[var(--border)] hover:bg-[var(--surface)]/70",
};

const sizeClasses: Record<Nullable<ButtonProps["size"]>, string> = {
  default: "h-11 px-6 text-sm",
  sm: "h-9 px-4 text-sm",
  lg: "h-12 px-7 text-base",
};

export const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
  ({ className, variant = "default", size = "default", ...props }, ref) => {
    return (
      <button
        ref={ref}
        className={cn(
          "inline-flex items-center justify-center gap-2 rounded-xl font-medium tracking-[0.01em] transition-all duration-300 disabled:pointer-events-none disabled:opacity-40",
          variantClasses[variant],
          sizeClasses[size],
          className,
        )}
        {...props}
      />
    );
  },
);

Button.displayName = "Button";
```


components/ui/card-hover-glow.tsx

```
"use client";

import { useRef, type ReactNode } from "react";
import { cn } from "@/lib/utils";

type CardHoverGlowProps = {
  children: ReactNode;
  className?: string;
};

export function CardHoverGlow({ children, className }: CardHoverGlowProps) {
  const ref = useRef<HTMLDivElement>(null);

  function handleMove(event: React.MouseEvent<HTMLDivElement>) {
    const el = ref.current;
    if (!el) return;
    const rect = el.getBoundingClientRect();
    const x = ((event.clientX - rect.left) / rect.width) * 100;
    const y = ((event.clientY - rect.top) / rect.height) * 100;
    el.style.setProperty("--glow-x", `${x}%`);
    el.style.setProperty("--glow-y", `${y}%`);
  }

  function handleLeave() {
    ref.current?.style.setProperty("--glow-x", "50%");
    ref.current?.style.setProperty("--glow-y", "40%");
  }

  return (
    <div
      ref={ref}
      className={cn("card-hover-glow", className)}
      onMouseMove={handleMove}
      onMouseLeave={handleLeave}
    >
      {children}
    </div>
  );
}
```

components/ui/card.tsx

```
import * as React from "react";
import { cn } from "@lib/utils";

export function Card({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) {
  return (
    <article
      className={cn(
        "rounded-3xl border border-[var(--border)] bg-[var(--surface)] backdrop-blur-xl shadow-[0_30px_70px_-45px_rgba(2,8,23,0.9)] transition-all duration-300"
      )}
      {...props}
    />
  );
}

export function CardContent({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) {
  return <div className={cn("p-6", className)} {...props} />;
}
```

components/ui/input.tsx

```
import * as React from "react";
import { cn } from "@/lib/utils";

export const Input = React.forwardRef<
  HTMLInputElement,
  React.InputHTMLAttributes<HTMLInputElement>
>(({ className, ...props }, ref) => {
  return (
    <input
      ref={ref}
      className={cn(
        "h-11 w-full rounded-xl border border-[var(--border)] bg-[var(--surface)] px-4 text-sm text-[var(--foreground)] outline-none placeholder:text-[var(--muted)] premium-input focus:border-[var(--ring)]",
        className,
      )}
      {...props}
    />
  );
});

Input.displayName = "Input";
```

components/ui/magnetic-button.tsx

```
"use client";

import { useRef, type ComponentProps } from "react";
import { usePrefersReducedMotion } from "@hooks/use-motion-prefs";
import { Button } from "@components/ui/button";
import { cn } from "@lib/utils";

type MagneticButtonProps = ComponentProps<typeof Button> & {
  strength?: number;
};

export function MagneticButton({
  className,
  strength = 0.18,
  children,
  ...props
}: MagneticButtonProps) {
  const ref = useRef<HTMLButtonElement>(null);
  const reduced = usePrefersReducedMotion();

  function handleMove(event: React.MouseEvent<HTMLButtonElement>) {
    if (reduced || !ref.current) return;
    const rect = ref.current.getBoundingClientRect();
    const x = (event.clientX - rect.left - rect.width / 2) * strength;
    const y = (event.clientY - rect.top - rect.height / 2) * strength;
    ref.current.style.transform = `translate(${x.toFixed(2)}px, ${y.toFixed(2)}px)`;
  }

  function reset() {
    if (!ref.current) return;
    ref.current.style.transform = "";
  }

  return (
    <Button
      ref={ref}
      className={cn("magnetic-btn", className)}
      onMouseMove={handleMove}
      onMouseLeave={reset}
      onBlur={reset}
      {...props}
    >
      {children}
    </Button>
  );
}
```

components/ui/textarea.tsx

```
import * as React from "react";
import { cn } from "@lib/utils";

export const Textarea = React.forwardRef<
  HTMLTextAreaElement,
  React.TextareaHTMLAttributes<HTMLTextAreaElement>
>(({ className, ...props }, ref) => {
  return (
    <textarea
      ref={ref}
      className={cn(
        "min-h-28 w-full rounded-xl border border-[var(--border)] bg-[var(--surface)] px-4 py-3 text-sm text-[var(--foreground)] outline-none placeholder:text-[var(--muted)] premium-input focus:border-[var(--ring)]",
        className,
      )}
      {...props}
    />
  );
});

Textarea.displayName = "Textarea";
```

eslint.config.mjs

```
import { defineConfig, globalIgnores } from "eslint/config";
import nextVitals from "eslint-config-next/core-web-vitals";
import nextTs from "eslint-config-next/typescript";
```

```
const eslintConfig = defineConfig([
  ...nextVitals,
  ...nextTs,
  // Override default ignores of eslint-config-next.
  globalIgnores([
    // Default ignores of eslint-config-next:
    ".next/**",
    "out/**",
    "build/**",
    "next-env.d.ts",
  ]),
]);
```

```
export default eslintConfig;
```

hooks/use-in-view.ts

```
"use client";

import { useEffect, useState, type RefObject } from "react";

/** True when the element intersects the viewport (for pausing off-screen canvas). */
export function useInView<T extends Element>({
  ref: RefObject<T | null>,
  options?: IntersectionObserverInit,
}) {
  const [inView, setInView] = useState(false);

  useEffect(() => {
    const el = ref.current;
    if (!el) return;

    const observer = new IntersectionObserver(
      ([entry]) => setInView(entry.isIntersecting),
      { rootMargin: "80px", threshold: 0, ...options },
    );
    observer.observe(el);
    return () => observer.disconnect();
    // eslint-disable-next-line react-hooks/exhaustive-deps -- stable observer per mount
  }, [ref]);

  return inView;
}
```

hooks/use-motion-prefs.ts

```
"use client";

import { useEffect, useState } from "react";

export function usePrefersReducedMotion() {
  const [reduced, setReduced] = useState(false);

  useEffect(() => {
    const mq = window.matchMedia("(prefers-reduced-motion: reduce)");
    const update = () => setReduced(mq.matches);
    update();
    mq.addEventListener("change", update);
    return () => mq.removeEventListener("change", update);
  }, []);

  return reduced;
}

export function useIsMobile(breakpoint = 768) {
  const [mobile, setMobile] = useState(false);

  useEffect(() => {
    const mq = window.matchMedia(`(max-width: ${breakpoint - 1}px)`);
    const update = () => setMobile(mq.matches);
    update();
    mq.addEventListener("change", update);
    return () => mq.removeEventListener("change", update);
  }, [breakpoint]);

  return mobile;
}

export function useIsBelowDesktop(breakpoint = 1024) {
  const [below, setBelow] = useState(false);

  useEffect(() => {
    const mq = window.matchMedia(`(max-width: ${breakpoint - 1}px)`);
    const update = () => setBelow(mq.matches);
    update();
    mq.addEventListener("change", update);
    return () => mq.removeEventListener("change", update);
  }, [breakpoint]);

  return below;
}

export function useMotionEnabled() {
  const reduced = usePrefersReducedMotion();
  const mobile = useIsMobile();
  return !reduced && !mobile;
}

export function useHeavyMotionEnabled() {
  const reduced = usePrefersReducedMotion();
  const belowDesktop = useIsBelowDesktop();
  return !reduced && !belowDesktop;
}
```


hooks/use-page-visible.ts

```
"use client";

import { useEffect, useState } from "react";

/** False when the tab is in the background ? use to pause RAF / heavy effects. */
export function usePageVisible() {
  const [visible, setVisible] = useState(true);

  useEffect(() => {
    const update = () => setVisible(document.visibilityState === "visible");
    update();
    document.addEventListener("visibilitychange", update);
    return () => document.removeEventListener("visibilitychange", update);
  }, []);

  return visible;
}
```

hooks/use-responsive-preview.ts

```
"use client";

import { useCallback, useEffect, useState } from "react";

export type PreviewMode = "full" | "mobile" | "tablet";

const STORAGE_KEY = "nocta-preview-mode";

export function useResponsivePreview() {
  const [mode, setModeState] = useState<PreviewMode>("full");
  const [mounted, setMounted] = useState(false);

  useEffect(() => {
    setMounted(true);
    const stored = localStorage.getItem(STORAGE_KEY) as PreviewMode | null;
    if (stored === "mobile" || stored === "tablet" || stored === "full") {
      setModeState(stored);
    }
  }, []);

  const setMode = useCallback((next: PreviewMode) => {
    setModeState(next);
    localStorage.setItem(STORAGE_KEY, next);
  }, []);

  return { mode, setMode, mounted };
}

export function isPreviewFrame(): boolean {
  if (typeof window === "undefined") return false;
  return new URLSearchParams(window.location.search).has("preview-frame");
}

export const PREVIEW_WIDTHS: Record<Exclude<PreviewMode, "full">, number> = {
  mobile: 390,
  tablet: 834,
};
```

hooks/use-scroll-progress.ts

```
"use client";

import { useEffect, useState, type RefObject } from "react";
import { usePrefersReducedMotion } from "@hooks/use-motion-prefs";

type ScrollProgressOptions = {
  /** Viewport ratio where progress begins (0 = top, 1 = bottom). */
  start?: number;
  /** Viewport ratio where progress completes. */
  end?: number;
};

function clamp(value: number, min = 0, max = 1) {
  return Math.min(max, Math.max(min, value));
}

/**
 * Scroll-driven progress (0?1) for an element. rAF-throttled, passive listeners.
 */
export function useScrollProgress(
  ref: RefObject<HTMLElement | null>,
  { start = 0.82, end = 0.28 }: ScrollProgressOptions = {},
) {
  const reduced = usePrefersReducedMotion();
  const [progress, setProgress] = useState(reduced ? 1 : 0);

  useEffect(() => {
    const el = ref.current;
    if (!el) return;

    if (reduced) {
      setProgress(1);
      return;
    }

    let frame = 0;

    const update = () => {
      frame = 0;
      const rect = el.getBoundingClientRect();
      const vh = window.innerHeight;
      const startY = vh * start;
      const endY = vh * end;
      const span = rect.height + startY - endY;
      const raw = span <= 0 ? 1 : (startY - rect.top) / span;
      setProgress(clamp(raw));
    };

    const onScroll = () => {
      if (frame) return;
      frame = requestAnimationFrame(update);
    };

    update();
    window.addEventListener("scroll", onScroll, { passive: true });
    window.addEventListener("resize", onScroll, { passive: true });

    return () => {
      if (frame) cancelAnimationFrame(frame);
      window.removeEventListener("scroll", onScroll);
      window.removeEventListener("resize", onScroll);
    };
  }, [ref, reduced, start, end]);

  return progress;
}
```

```
}

export function stepProgress(overall: number, index: number, total: number) {
  if (total <= 0) return 1;
  const segment = 1 / total;
  const pad = segment * 0.12;
  const start = index * segment;
  const local = (overall - start + pad) / (segment + pad * 0.5);
  return clamp(local);
}

export function lineProgress(step: number, lineIndex: number, lineCount: number) {
  if (lineCount <= 0) return 1;
  const slot = 1 / lineCount;
  const offset = lineIndex * slot * 0.55;
  return clamp((step - offset) / (slot * 0.85));
}

export function emphasisProgress(step: number, delay = 0.35) {
  return clamp((step - delay) / 0.45);
}
```

hooks/use-throttled-scroll.ts

```
"use client";

import { useEffect } from "react";

/** Passive scroll listener, max one RAF callback per frame. */
export function useThrottledScroll(onScroll: () => void, enabled = true) {
  useEffect(() => {
    if (!enabled) return;

    let ticking = false;

    const handleScroll = () => {
      if (ticking) return;
      ticking = true;
      requestAnimationFrame(() => {
        onScroll();
        ticking = false;
      });
    };

    handleScroll();
    window.addEventListener("scroll", handleScroll, { passive: true });
    return () => window.removeEventListener("scroll", handleScroll);
  }, [onScroll, enabled]);
}
```

lib/concept-projects.ts

```
import {
  bellaVistaCode,
  novaHabitatCode,
  titanFitnessCode,
} from "../project-code-samples";

export type CaseStudy = {
  objectives: string[];
  uxUi: string[];
  technical: string[];
  expectedResult: string;
};

export type CodeToken = {
  text: string;
  type:
    | "keyword"
    | "string"
    | "tag"
    | "attr"
    | "function"
    | "comment"
    | "plain"
    | "number"
    | "type";
};

export type CodeLine = {
  number: number;
  tokens: CodeToken[];
};

export type CodeFile = {
  filename: string;
  lines: CodeLine[];
};

export type ConceptProject = {
  id: string;
  name: string;
  sector: string;
  image: string;
  description: string;
  features: string[];
  technologies: string[];
  demoPath: string;
  caseStudy: CaseStudy;
  codeFiles: CodeFile[];
  highlight: string;
};

const demoBase = process.env.NEXT_PUBLIC_DEMO_BASE_URL?.replace(/\/$/, "");

function buildDemoPath(slug: string) {
  if (demoBase) return `${demoBase}/${slug}`;
  return `/demos/${slug}`;
}

export const conceptProjects: ConceptProject[] = [
  {
    id: "bella-vista",
    name: "Bella Vista",
    sector: "Restaurant gastronomique",
    image: "/projects/bella-vista.png",
    description:
```

```

    "Expérience immersive pour un restaurant italien premium. Design luxueux, réservation en ligne et galerie visuelle pour valoriser l'art culinaire.",
    features: [
      "Réservation en ligne",
      "Galerie immersive",
      "Présentation du chef",
      "Témoignages clients",
      "Carte interactive",
      "Animations au scroll",
    ],
    technologies: [
      "Next.js",
      "React",
      "TypeScript",
      "Tailwind CSS",
      "Framer Motion",
    ],
    demoPath: buildDemoPath("bella-vista"),
    highlight: "Design premium + expérience utilisateur",
    caseStudy: {
      objectives: [
        "Augmenter les réservations en ligne sans friction.",
        "Créer une image Michelin : luxe, élégance, immersion.",
        "Mettre en valeur le chef, le menu et l'ambiance du lieu.",
      ],
      uxUi: [
        "Palette noir profond, blanc cassé et touches dorées pour un positionnement haut de gamme.",
        "Hero plein écran avec CTA de réservation immédiatement visible.",
        "Typographie serif (Cormorant) + sans-serif pour un contraste élégant.",
        "Parcours one-page fluide : menu ? chef ? galerie ? réservation.",
      ],
      technical: [
        "Architecture composants modulaires avec animations Framer Motion.",
        "Images optimisées via next/image (Unsplash, lazy loading).",
        "Formulaire de réservation avec états loading/success.",
        "Navigation sticky responsive avec menu mobile animé.",
      ],
      expectedResult:
        "Un site qui donne l'impression d'un restaurant étoilé et incite à réserver en moins de 30 secondes.",
    },
    codeFiles: bellaVistaCode,
  },
  {
    id: "titan-fitness",
    name: "Titan Fitness",
    sector: "Salle de sport premium",
    image: "/projects/titan-fitness.png",
    description:
      "Landing dynamique inspirée des startups fitness américaines. Outils interactifs de conversion pour transformer les visiteurs en abonnés.",
    features: [
      "Calculateur IMC",
      "Simulateur d'objectif sportif",
      "FAQ interactive",
      "Cartes d'abonnement",
      "Formulaire d'essai gratuit",
      "Témoignages transformations",
    ],
    technologies: [
      "Next.js",
      "React",
      "TypeScript",
      "Tailwind CSS",
      "Framer Motion",
    ],
    demoPath: buildDemoPath("titan-fitness"),
    highlight: "Marketing + conversion + design moderne",
    caseStudy: {
      objectives: [

```

```

    "Convertir les visiteurs en abonnés via des CTA impactants.",
    "Démontrer une offre premium avec preuve sociale et résultats.",
    "Engager l'utilisateur avec des outils interactifs (IMC, objectifs).",
  ],
  uxUi: [
    "Design énergique dark + accent lime, inspiré des startups fitness US.",
    "Sections à fort impact visuel : hero, stats, programmes, tarifs.",
    "Cartes d'abonnement avec plan Pro mis en avant (best seller).",
    "FAQ accordion et formulaire d'essai gratuit en fin de parcours.",
  ],
  technical: [
    "Calculateur IMC et simulateur d'objectif en logique client pure.",
    "Composants réutilisables : cards, stats bar, pricing tiers.",
    "Animations scroll reveal et micro-interactions sur les CTA.",
    "Mobile-first avec navigation sticky et menu hamburger.",
  ],
  expectedResult:
    "Une vitrine qui ressemble à une startup fitness valorisée plusieurs millions, orientée conversion.",
},
codeFiles: titanFitnessCode,
},
{
  id: "nova-habitat",
  name: "Nova Habitat",
  sector: "Rénovation & travaux",
  image: "/projects/nova-habitat.png",
  description:
    "Plateforme de génération de leads pour une entreprise de rénovation. Devis avancé, estimation automatique et assistant IA simulé.",
  features: [
    "Formulaire de devis avancé",
    "Galerie avant/après",
    "Estimation automatique",
    "Chatbot IA simulé",
    "Calculateur de budget",
    "Carte zone d'intervention",
  ],
  technologies: [
    "Next.js",
    "React",
    "TypeScript",
    "Tailwind CSS",
    "Framer Motion",
  ],
},
demoPath: buildDemoPath("nova-habitat"),
highlight: "Fonctionnalités business + IA + automatisation",
caseStudy: {
  objectives: [
    "Générer des demandes de devis qualifiées.",
    "Rassurer les prospects avec preuves sociales et transparence.",
    "Automatiser la première étape commerciale (estimation, orientation).",
  ],
  uxUi: [
    "Design professionnel clair : navy + bleu, inspiré des leaders du BTP.",
    "Galerie avant/après interactive pour prouver l'expertise.",
    "Double parcours : devis détaillé + calculateur budget rapide.",
    "Chatbot flottant pour répondre aux questions fréquentes 24/7.",
  ],
  technical: [
    "Estimation dynamique basée sur type de projet et surface (m²).",
    "Chatbot IA simulé avec matching par mots-clés (devis, délai, prix).",
    "Slider budget avec niveaux de finition (standard/premium/luxe).",
    "Formulaire multi-champs avec validation et état de succès.",
  ],
  expectedResult:
    "Un site qui positionne Nova Habitat comme leader du secteur et capture des leads qualifiés.",
},
codeFiles: novaHabitatCode,

```


lib/demo-images.ts

```
const u = {id: string, w = 2400} =>
`https://images.unsplash.com/${id}?auto=format&fit=crop&w=${w}&q=80`;
```

```
/** IDs vérifiés (HTTP 200) */
export const images = {
  bellaVista: {
    hero: u("photo-1414235077428-338989a2e8c0"),
    dish1: u("photo-1565299624946-b28f40a0ae38"),
    dish2: u("photo-1544025162-d76694265947"),
    dish3: u("photo-1567620905732-2d1ec7ab7445"),
    dish4: u("photo-1555939594-58d7cb561ad1"),
    dish5: u("photo-1504674900247-0877df9cc836"),
    dish6: u("photo-1540189549336-e6e99c3679fe"),
    interior: u("photo-1517248135467-4c7edcad34c4"),
    chef: u("photo-1551218808-94e220e084d2"),
    map: u("photo-1523906834658-6e24ef2386f9", 1600),
    gallery: [
      u("photo-1424847651672-bf20a4b0982b", 1600),
      u("photo-1504674900247-0877df9cc836", 1600),
      u("photo-1540189549336-e6e99c3679fe", 1600),
      u("photo-1517248135467-4c7edcad34c4", 1600),
      u("photo-1555939594-58d7cb561ad1", 1600),
      u("photo-1565299624946-b28f40a0ae38", 1600),
    ],
  },
  titanFitness: {
    hero: u("photo-1534438327276-14e5300c3a48"),
    program1: u("photo-1571019613454-1cb2f99b2d8b"),
    program2: u("photo-1517836357463-d25dfeac3438"),
    program3: u("photo-1518611012118-696072aa579a"),
    coach1: u("photo-1574680096145-d05b474e2155"),
    coach2: u("photo-1594381898411-846e7d193883"),
    coach3: u("photo-1506126613408-eca07ce68773"),
    transform1: u("photo-1534438327276-14e5300c3a48"),
    transform2: u("photo-1517836357463-d25dfeac3438"),
    transform3: u("photo-1571019613454-1cb2f99b2d8b"),
  },
  novaHabitat: {
    hero: u("photo-1600585154340-be6161a56a0c"),
    service1: u("photo-1600607687939-ce8a6c25118c"),
    service2: u("photo-1600566753190-17f0baa2a6c3"),
    service3: u("photo-1600210492493-0946911123ea"),
    before1: u("photo-1600585154526-990dced4db0d"),
    after1: u("photo-1600607687644-c7171b42498f"),
    before2: u("photo-1600585154340-be6161a56a0c"),
    after2: u("photo-1600566753190-17f0baa2a6c3"),
    before3: u("photo-1600607687939-ce8a6c25118c"),
    after3: u("photo-1600210492493-0946911123ea"),
  },
};
```

lib/notion-waitlist.ts

```
import type { WaitlistEntry } from "@lib/waitlist-types";
import { buildWaitlistRow } from "@lib/waitlist-row";

const NOTION_VERSION = "2022-06-28";
const DEFAULT_DATABASE_ID = "35356780-a3d8-40f2-afdf-667543feb15a";

function getNotionConfig() {
  const token = process.env.NOTION_TOKEN?.trim();
  const databaseId =
    process.env.NOTION_WAITLIST_DATABASE_ID?.trim() || DEFAULT_DATABASE_ID;
  const direct =
    process.env.NOTION_DIRECT_SYNC !== "false" &&
    process.env.NOTION_DIRECT_SYNC !== "0";

  if (!token || !direct) {
    return { enabled: false as const };
  }

  return { enabled: true as const, token, databaseId };
}

function richText(content: string) {
  return [{ type: "text" as const, text: { content: content.slice(0, 2000) } }];
}

function buildNotionProperties(entry: WaitlistEntry) {
  const row = buildWaitlistRow(entry);
  const props: Record<string, unknown> = {
    Nom: {
      title: richText(row.name || row.email.split("@")[0] || "Inscription"),
    },
    Email: { email: row.email },
    Priorité: { select: { name: "Moyenne" } },
  };

  if (row.company) {
    props.Entreprise = { rich_text: richText(row.company) };
  }

  if (row.website) {
    let url = row.website;
    if (!/^https?:\/\//.i.test(url)) url = `https://${url}`;
    props["Site actuel"] = { url };
  }

  if (row.need) {
    props.Besoin = { rich_text: richText(row.need) };
  }

  return props;
}

async function notionFetch(
  path: string,
  token: string,
  init?: RequestInit,
): Promise<Response> {
  return fetch(`https://api.notion.com/v1${path}`, {
    ...init,
    headers: {
      Authorization: `Bearer ${token}`,
      "Notion-Version": NOTION_VERSION,
      "Content-Type": "application/json",
      ...init?.headers,
    },
  });
}
```

```

    });
}

async function findPageByEmail(
  token: string,
  databaseId: string,
  email: string,
): Promise<string | null> {
  const res = await notionFetch(`/databases/${databaseId}/query`, token, {
    method: "POST",
    body: JSON.stringify({
      page_size: 1,
      filter: {
        property: "Email",
        email: { equals: email.trim().toLowerCase() },
      },
    }),
  });

  const data = (await res.json()) as { results?: { id: string }[]; message?: string };

  if (!res.ok) {
    console.error("[notion-waitlist] query failed:", res.status, data);
    return null;
  }

  return data.results?.[0]?.id ?? null;
}

export type NotionSyncResult =
  | { ok: true; pageId: string; updated: boolean }
  | { ok: false; skipped: true }
  | { ok: false; message: string };

export async function syncWaitlistToNotion(
  entry: WaitlistEntry,
): Promise<NotionSyncResult> {
  const config = getNotionConfig();
  if (!config.enabled) {
    console.info("[notion-waitlist] sync désactivé (NOTION_TOKEN ou NOTION_DIRECT_SYNC=false)");
    return { ok: false, skipped: true };
  }

  const email = entry.email.trim().toLowerCase();
  const properties = buildNotionProperties({ ...entry, email });

  console.info(
    "[notion-waitlist] envoi:",
    JSON.stringify({
      email,
      fields: {
        name: entry.name,
        company: entry.company,
        website: entry.website,
        need: entry.need,
      },
    }),
  );

  try {
    const existingId = await findPageByEmail(
      config.token,
      config.databaseId,
      email,
    );

    if (existingId) {

```

```

const res = await notionFetch(`/pages/${existingId}`, config.token, {
  method: "PATCH",
  body: JSON.stringify({ properties }),
});
const data = (await res.json()) as { id?: string; message?: string };
if (!res.ok) {
  console.error("[notion-waitlist] update failed:", res.status, data);
  return { ok: false, message: data.message ?? "Notion update failed" };
}
console.info("[notion-waitlist] update OK", { pageId: existingId, email });
return { ok: true, pageId: data.id ?? existingId, updated: true };
}

const res = await notionFetch("/pages", config.token, {
  method: "POST",
  body: JSON.stringify({
    parent: { database_id: config.databaseId },
    properties,
  }),
});

const data = (await res.json()) as { id?: string; message?: string };
if (!res.ok) {
  console.error("[notion-waitlist] create failed:", res.status, data);
  return { ok: false, message: data.message ?? "Notion create failed" };
}

console.info("[notion-waitlist] create OK", { pageId: data.id, email });
return { ok: true, pageId: data.id ?? "", updated: false };
} catch (err) {
  const message = err instanceof Error ? err.message : "Notion sync error";
  console.error("[notion-waitlist] exception:", err);
  return { ok: false, message };
}
}

```

lib/pricing.ts

```
export type BillingMode = "monthly" | "project";

export type PricingPlan = {
  id: "starter" | "pro" | "premium";
  name: string;
  tagline: string;
  monthlyPrice: number;
  projectPrice: number;
  features: string[];
  highlighted?: boolean;
  badge?: string;
  featuredNote?: string;
  ctaLabel?: string;
};

export const pricingPlans: PricingPlan[] = [
  {
    id: "starter",
    name: "Starter",
    tagline:
      "Pour les indépendants et petites activités qui veulent une présence professionnelle en ligne.",
    monthlyPrice: 19,
    projectPrice: 690,
    ctaLabel: "Démarrer avec Starter",
    features: [
      "Site vitrine jusqu'à 3 pages",
      "Design moderne et responsive",
      "Optimisation mobile",
      "Formulaire de contact",
      "Hébergement et maintenance inclus",
      "Optimisation des performances",
      "Intégration Google Maps et réseaux sociaux",
      "1 série de révisions",
    ],
  },
  {
    id: "pro",
    name: "Pro",
    tagline:
      "Pour les entreprises qui veulent transformer leurs visiteurs en prospects.",
    monthlyPrice: 39,
    projectPrice: 1490,
    highlighted: true,
    badge: "Most Popular",
    featuredNote:
      "Recommandé pour la plupart des entreprises ? le meilleur équilibre entre budget, design et conversion.",
    ctaLabel: "Choisir Pro",
    features: [
      "Tout ce qui est inclus dans Starter",
      "Site complet jusqu'à 8 pages",
      "Design premium personnalisé",
      "Animations modernes et micro-interactions",
      "SEO complet de base",
      "Optimisation de conversion (CTA, parcours utilisateur)",
      "Google Analytics et suivi des leads",
      "Fonctionnalités business (devis, réservation, prise de rendez-vous)",
      "Optimisation avancée des performances",
      "3 séries de révisions",
    ],
  },
  {
    id: "premium",
    name: "Premium",
    tagline:
      "Pour les entreprises qui veulent automatiser et se différencier.",
  }
];
```

```

    monthlyPrice: 49,
    projectPrice: 2490,
    ctaLabel: "Opter pour Premium",
    features: [
      "Tout ce qui est inclus dans Pro",
      "Intégration IA (chatbot, FAQ intelligente, assistant client)",
      "Automatisations IA simples avec outils gratuits",
      "Génération de leads assistée par IA",
      "Optimisation du contenu avec IA",
      "Audit UX approfondi",
      "Priorité sur les demandes d'évolution",
      "Révisions illimitées pendant la phase de création",
    ],
  },
];

```

```

export const comparisonRows = [
  {
    label: "Pages",
    starter: "Jusqu'à 3",
    pro: "Jusqu'à 8",
    premium: "Jusqu'à 8",
  },
  {
    label: "Design",
    starter: "Moderne & responsive",
    pro: "Premium personnalisé",
    premium: "Premium + IA",
  },
  {
    label: "Animations",
    starter: false,
    pro: true,
    premium: true,
  },
  {
    label: "SEO",
    starter: "Essentiel",
    pro: "Complet (base)",
    premium: "Contenu optimisé IA",
  },
  {
    label: "Conversion",
    starter: "Formulaire contact",
    pro: "CTA & parcours optimisés",
    premium: "Leads assistés IA",
  },
  {
    label: "Analytics & leads",
    starter: false,
    pro: true,
    premium: true,
  },
  {
    label: "Fonctionnalités business",
    starter: false,
    pro: true,
    premium: true,
  },
  {
    label: "Intégration IA",
    starter: false,
    pro: false,
    premium: true,
  },
  {
    label: "Révisions",

```

```

    starter: "1 série",
    pro: "3 séries",
    premium: "Illimitées (création)",
  },
] as const;

export const pricingFaqs = [
  {
    question: "Quelle différence entre abonnement mensuel et projet unique ?",
    answer:
      "L'abonnement mensuel inclut l'hébergement, la maintenance et les mises à jour courantes. L'achat correspond à un paiement unique pour la création du site  
? idéal si vous préférez éviter un abonnement.",
  },
  {
    question: "Puis-je changer d'offre plus tard ?",
    answer:
      "Oui. Vous pouvez faire évoluer votre site vers une offre supérieure à tout moment. Nous adaptons le devis en fonction des fonctionnalités à ajouter.",
  },
  {
    question: "Que couvrent les révisions incluses ?",
    answer:
      "Les révisions portent sur le contenu, la mise en page et les ajustements visuels durant la phase de création. Les ajouts majeurs de fonctionnalités font  
l'objet d'un devis complémentaire transparent.",
  },
  {
    question: "Proposez-vous un accompagnement après la livraison ?",
    answer:
      "Oui. Avec l'abonnement mensuel, la maintenance et le support sont inclus. En projet unique, un forfait de suivi optionnel peut être mis en place selon vo  
s besoins.",
  },
  {
    question: "Comment se déroule le premier échange ?",
    answer:
      "Un appel ou échange par message pour comprendre votre activité, vos objectifs et votre budget. Vous recevez ensuite une proposition claire avant tout eng  
agement.",
  },
];

```


lib/priority-list.ts

```
export type PriorityListSubmission = {
  name: string;
  email: string;
  company: string;
  website?: string;
  need: string;
};

export type PriorityListResponse = {
  ok: boolean;
  message?: string;
};

/**
 * Envoie une inscription à la liste prioritaire (Supabase + Notion).
 */
export async function submitPriorityList(
  data: PriorityListSubmission,
): Promise<PriorityListResponse> {
  const body = {
    name: data.name.trim(),
    email: data.email.trim(),
    company: data.company.trim(),
    need: data.need.trim(),
    ...(data.website?.trim() ? { website: data.website.trim() } : {}),
  };

  if (process.env.NODE_ENV === "development") {
    console.info("[priority-list] fetch payload:", JSON.stringify(body));
  }

  const response = await fetch("/api/priority-list", {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify(body),
  });

  const result = (await response.json()) as PriorityListResponse;

  if (!response.ok || !result.ok) {
    throw new Error(result.message ?? "Impossible d'enregistrer votre demande.");
  }

  return result;
}

export const priorityListReassurance = [
  "Places limitées",
  "Sélection de quelques projets seulement",
  "Réponse prioritaire lors de l'ouverture",
] as const;

export const priorityListConfirmation =
  "Merci pour votre intérêt. Votre demande a bien été enregistrée dans la liste prioritaire.";
```

lib/responsive-preview-config.ts

```
/** Dev-only responsive preview ? never enabled in production unless explicitly opted in. */
export function isResponsivePreviewAvailable() {
  return (
    process.env.NODE_ENV === "development" ||
    process.env.NEXT_PUBLIC_ENABLE_RESPONSIVE_PREVIEW === "true"
  );
}
```

lib/supabase.ts

```
import { createClient, type SupabaseClient } from "@supabase/supabase-js";
import type { WaitlistEntry } from "@lib/waitlist-types";
import {
  buildWaitlistRow,
  buildWaitlistUpdateRow,
  logWaitlistRow,
  type WaitlistRow,
} from "@lib/waitlist-row";
```

```
type SupabaseConfig =
  | { ok: true; url: string; key: string; role: "service_role" | "anon" }
  | { ok: false; error: string };
```

```
function resolveSupabaseConfig(): SupabaseConfig {
  const url = process.env.SUPABASE_URL?.trim();
  const serviceKey = process.env.SUPABASE_SERVICE_ROLE_KEY?.trim();
  const anonKey = process.env.SUPABASE_ANON_KEY?.trim();
  const key = serviceKey || anonKey;
```

```
  if (!url || !key) {
    return {
      ok: false,
      error:
        "Variables manquantes : SUPABASE_URL et SUPABASE_ANON_KEY (ou SUPABASE_SERVICE_ROLE_KEY) dans .env.local / Vercel.",
    };
  }
```

```
  if (!url.includes("supabase.co")) {
    return {
      ok: false,
      error: `SUPABASE_URL invalide : "${url}". Utilise l'URL ?supabase.co du dashboard.` ,
    };
  }
```

```
  return {
    ok: true,
    url,
    key,
    role: serviceKey ? "service_role" : "anon",
  };
}
```

```
let client: SupabaseClient | null = null;
let clientRole: "service_role" | "anon" | null = null;
```

```
function getSupabase(): SupabaseClient {
  const config = resolveSupabaseConfig();
  if (!config.ok) {
    throw new Error(config.error);
  }

  if (!client || clientRole !== config.role) {
    client = createClient(config.url, config.key, {
      auth: { persistSession: false, autoRefreshToken: false },
    });
    clientRole = config.role;
    console.info("[supabase] client initialisé", { role: config.role });
  }
```

```
  return client;
}
```

```
export type WaitlistInsertResult =
  | { ok: true; row?: WaitlistRow; action?: "insert" | "update" }
  | { ok: false; message: string; code?: string; hint?: string };
```

```

function mapSupabaseError(error: {
  code?: string;
  message?: string;
  hint?: string | null;
}): WaitlistInsertResult {
  if (error.code === "PGRST205" || error.message?.includes("Could not find the table")) {
    return {
      ok: false,
      code: error.code,
      hint: "table",
      message:
        "Table waitlist introuvable. Exécute supabase/waitlist-setup.sql dans Supabase ? SQL Editor.",
    };
  }

  if (
    error.code === "PGRST204" ||
    error.message?.includes("Could not find") ||
    error.message?.includes("column")
  ) {
    return {
      ok: false,
      code: error.code,
      hint: "columns",
      message:
        "Colonnes manquantes. Exécute supabase/waitlist-migrate.sql dans Supabase ? SQL Editor.",
    };
  }

  if (error.code === "42501" || error.message?.toLowerCase().includes("row-level security")) {
    return {
      ok: false,
      code: error.code,
      hint: "RLS",
      message:
        "Accès Supabase refusé (RLS). Ajoute SUPABASE_SERVICE_ROLE_KEY sur Vercel, ou exécute supabase/waitlist-rls.sql.",
    };
  }
}

const devDetail =
  process.env.NODE_ENV === "development"
    ? ` ${error.code ?? "?"}: ${error.message}`
    : "";

return {
  ok: false,
  code: error.code,
  hint: error.hint ?? undefined,
  message: `Impossible d'enregistrer votre demande.${devDetail}`,
};
}

export async function insertWaitlistEntry(
  entry: WaitlistEntry,
): Promise<WaitlistInsertResult> {
  const config = resolveSupabaseConfig();
  if (!config.ok) {
    console.error("[supabase] config:", config.error);
    return { ok: false, message: config.error, hint: "env" };
  }

  const row = buildWaitlistRow(entry);
  const updateRow = buildWaitlistUpdateRow(entry);
  logWaitlistRow("INSERT row", row);
  logWaitlistRow("UPDATE row (si email existant)", updateRow);

  try {

```

```

const db = getSupabase();

const { data: inserted, error: insertError } = await db
  .from("waitlist")
  .insert([row])
  .select()
  .single();

if (!insertError) {
  console.info("[supabase] insert OK", { email: row.email, data: inserted });
  return { ok: true, row, action: "insert" };
}

if (insertError.code !== "23505") {
  console.error("[supabase] insert failed:", {
    role: config.role,
    code: insertError.code,
    message: insertError.message,
    details: insertError.details,
    hint: insertError.hint,
    row,
  });
  return mapSupabaseError(insertError);
}

console.info("[supabase] email déjà présent, update", { email: row.email });

const { data: updated, error: updateError } = await db
  .from("waitlist")
  .update(updateRow)
  .eq("email", row.email)
  .select()
  .single();

if (!updateError) {
  console.info("[supabase] update OK", { email: row.email, data: updated });
  return { ok: true, row, action: "update" };
}

console.error("[supabase] update failed:", {
  role: config.role,
  code: updateError.code,
  message: updateError.message,
  details: updateError.details,
  hint: updateError.hint,
  updateRow,
});

return mapSupabaseError(updateError);
} catch (err) {
  console.error("[supabase] unexpected:", err);

  const message = err instanceof Error ? err.message : String(err);

  if (message.includes("ENOTFOUND") || message.includes("fetch failed")) {
    return {
      ok: false,
      message:
        "Connexion Supabase impossible. Vérifie SUPABASE_URL, puis redémarre le serveur.",
    };
  }
}

return {
  ok: false,
  message:
    process.env.NODE_ENV === "development"
      ? message

```

```
        : "Impossible d'enregistrer votre demande. Réessayez plus tard.",
    });
  }
}

export async function insertWaitlistEmail(email: string): Promise<WaitlistInsertResult> {
  return insertWaitlistEntry({
    email,
    source: "waitlist_email",
  });
}
```

lib/utlis.ts

```
import { clsx, type ClassValue } from "clsx";
import { twMerge } from "tailwind-merge";

export function cn(...inputs: ClassValue[]) {
  return twMerge(clsx(inputs));
}

export function scrollToId(id: string) {
  document.getElementById(id)?.scrollIntoView({ behavior: "smooth" });
}
```

lib/waitlist-row.ts

```
import type { WaitlistEntry } from "@lib/waitlist-types";

/** Colonnes alignées sur la table Supabase `waitlist`. */
export type WaitlistRow = {
  email: string;
  name?: string;
  company?: string;
  website?: string;
  need?: string;
  source?: string;
};

export type WaitlistUpdateRow = Omit<WaitlistRow, "email">;

/**
 * Ligne complète pour INSERT ? sans clés null/vides.
 */
export function buildWaitlistRow(entry: WaitlistEntry): WaitlistRow {
  const row: WaitlistRow = {
    email: entry.email.trim().toLowerCase(),
    source: entry.source?.trim() || "priority_list",
  };

  const name = entry.name?.trim();
  const company = entry.company?.trim();
  const website = entry.website?.trim();
  const need = entry.need?.trim();

  if (name) row.name = name;
  if (company) row.company = company;
  if (website) row.website = website;
  if (need) row.need = need;

  return row;
}

/**
 * Champs pour UPDATE uniquement ? jamais d'email, jamais de null écrasant.
 */
export function buildWaitlistUpdateRow(entry: WaitlistEntry): WaitlistUpdateRow {
  const update: WaitlistUpdateRow = {
    source: entry.source?.trim() || "priority_list",
  };

  const name = entry.name?.trim();
  const company = entry.company?.trim();
  const website = entry.website?.trim();
  const need = entry.need?.trim();

  if (name) update.name = name;
  if (company) update.company = company;
  if (website) update.website = website;
  if (need) update.need = need;

  return update;
}

export function logWaitlistRow(label: string, row: WaitlistRow | WaitlistUpdateRow) {
  console.info(`[waitlist] ${label}:`, JSON.stringify(row));
}
```


lib/waitlist-types.ts

```
export type WaitlistEntry = {  
  email: string;  
  name?: string;  
  company?: string;  
  website?: string;  
  need?: string;  
  source?: string;  
};
```

next.config.ts

```
import type { NextConfig } from "next";
import path from "path";

/** Force Turbopack root to this app (avoids parent ~/package-lock.json hijacking). */
const appRoot = path.resolve(__dirname);

const nextConfig: NextConfig = {
  // Autorise les assets dev (CSS/JS) quand le site est consulté via ngrok.
  allowedDevOrigins: [
    "*.ngrok-free.dev",
    "*.ngrok-free.app",
    "*.ngrok.app",
    "*.ngrok.io",
  ],
  turbopack: {
    root: appRoot,
  },
  images: {
    remotePatterns: [
      {
        protocol: "https",
        hostname: "images.unsplash.com",
      },
    ],
  },
};

export default nextConfig;
```

package.json

```
{
  "name": "portfolio",
  "version": "0.1.0",
  "private": true,
  "scripts": {
    "dev": "next dev",
    "dev:share": "bash scripts/share-dev.sh",
    "tunnel": "bash scripts/tunnel.sh",
    "tunnel:url": "bash scripts/tunnel-url.sh",
    "ngrok:install": "bash scripts/install-ngrok.sh",
    "build": "next build",
    "food-assets:fetch": "node scripts/fetch-food-assets-3d.mjs",
    "start": "next start",
    "lint": "eslint"
  },
  "dependencies": {
    "@supabase/ssr": "^0.10.3",
    "@supabase/supabase-js": "^2.106.2",
    "clsx": "^2.1.1",
    "framer-motion": "^12.40.0",
    "gsap": "^3.15.0",
    "lenis": "^1.3.23",
    "lucide-react": "^1.17.0",
    "next": "16.2.6",
    "react": "19.2.4",
    "react-dom": "19.2.4",
    "stripe": "^22.2.0",
    "tailwind-merge": "^3.6.0"
  },
  "devDependencies": {
    "@tailwindcss/postcss": "^4",
    "@types/node": "^20",
    "@types/react": "^19",
    "@types/react-dom": "^19",
    "eslint": "^9",
    "eslint-config-next": "16.2.6",
    "tailwindcss": "^4",
    "typescript": "^5"
  }
}
```

postcss.config.mjs

```
const config = {  
  plugins: {  
    "@tailwindcss/postcss": {},  
  },  
};  
  
export default config;
```

supabase/waitlist-migrate.sql

```
-- À exécuter dans Supabase (projet Nocta Agency OS) ? SQL Editor
-- Ajoute les colonnes pour le formulaire liste prioritaire + sync Notion

alter table public.waitlist add column if not exists name text;
alter table public.waitlist add column if not exists company text;
alter table public.waitlist add column if not exists website text;
alter table public.waitlist add column if not exists need text;
alter table public.waitlist add column if not exists source text default 'website';
```

supabase/waitlist-rls.sql

```
-- Politiques + grants pour waitlist (formulaire Next.js avec clé anon)
-- Exécuter dans Supabase ? SQL Editor (projet Nocta Agency OS)

alter table public.waitlist enable row level security;

-- Nettoyage anciennes politiques
drop policy if exists "allow insert" on public.waitlist;
drop policy if exists "allow update" on public.waitlist;
drop policy if exists "waitlist_anon_insert" on public.waitlist;
drop policy if exists "waitlist_anon_update" on public.waitlist;

-- Droits SQL (en plus des politiques RLS)
grant usage on schema public to anon, authenticated;
grant select, insert, update on table public.waitlist to anon, authenticated;

-- INSERT (nouvelle inscription)
create policy "waitlist_anon_insert"
on public.waitlist
for insert
to anon, authenticated
with check (true);

-- UPDATE (email déjà inscrit ? formulaire complet)
create policy "waitlist_anon_update"
on public.waitlist
for update
to anon, authenticated
using (true)
with check (true);
```

supabase/waitlist-setup.sql

```
-- Exécuter dans Supabase ? SQL Editor (nouveau projet ou table absente)
```

```
create table if not exists public.waitlist (  
  id uuid primary key default gen_random_uuid(),  
  email text not null unique,  
  name text,  
  company text,  
  website text,  
  need text,  
  source text default 'website',  
  created_at timestampz not null default now()  
);  
  
alter table public.waitlist enable row level security;  
  
drop policy if exists "allow insert" on public.waitlist;  
drop policy if exists "allow update" on public.waitlist;  
drop policy if exists "waitlist_anon_insert" on public.waitlist;  
drop policy if exists "waitlist_anon_update" on public.waitlist;  
  
grant usage on schema public to anon, authenticated;  
grant select, insert, update on table public.waitlist to anon, authenticated;  
  
create policy "waitlist_anon_insert"  
on public.waitlist  
for insert  
to anon, authenticated  
with check (true);  
  
create policy "waitlist_anon_update"  
on public.waitlist  
for update  
to anon, authenticated  
using (true)  
with check (true);
```

tsconfig.json

```
{
  "compilerOptions": {
    "target": "ES2017",
    "lib": ["dom", "dom.iterable", "esnext"],
    "allowJs": true,
    "skipLibCheck": true,
    "strict": true,
    "noEmit": true,
    "esModuleInterop": true,
    "module": "esnext",
    "moduleResolution": "bundler",
    "resolveJsonModule": true,
    "isolatedModules": true,
    "jsx": "react-jsx",
    "incremental": true,
    "plugins": [
      {
        "name": "next"
      }
    ],
    "paths": {
      "@/*": ["./*"]
    }
  },
  "include": [
    "next-env.d.ts",
    "**/*.ts",
    "**/*.tsx",
    ".next/types/**/*.ts",
    ".next/dev/types/**/*.ts",
    "**/*.mts"
  ],
  "exclude": ["node_modules", "vittrines-demo"]
}
```