Done

Our First Tables

Host: pg.pg4e.com

Port: 5432

Database: pg4e_402ae32925

User: pg4e_402ae32925

Password: (hide/show copy)

Check Answer

Here is the the **psql** command to access your database:

```
psql -h pg.pg4e.com -p 5432 -U pg4e_402ae32925 pg4e_402ae32925
```

Log in to your database and create the following tables.

The **pg4e_debug** table will let you see the queries that were run by the auto grader as it is grading your assignment. It is cleared out at the beginning of each autograder attempt.

```
CREATE TABLE pg4e_debug (
  id SERIAL,
  query VARCHAR(4096),
  result VARCHAR(4096),
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY(id)
);
```

You can view the contents of this table after running the autograder with this command:

```
SELECT query, result, created_at FROM pg4e_debug;
```

Creating the **pg4e_result** table is optional in the case you do not want to store any of your Personally Identifiable Information (PII) on a third party server.

If you create the **pg4e_result** table, the auto-graders will store a copy of the grades you receive from each assignment along with some error message detail if something goes wrong. These scores are also sent to your learning system of record so changing or deleting your scores in this table will not accomplish anything :).

Done

```
CREATE TABLE pg4e_result (
  id SERIAL,
  link_id INTEGER UNIQUE,
  score FLOAT,
  title VARCHAR(4096),
  note VARCHAR(4096),
  debug_log VARCHAR(8192),
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
  updated_at TIMESTAMP
);
```

Note: You will see a **pg4e_meta** table in your database that is used internally by the autograder to pass information from one assignment to another assignment. The autograder will store mysterious stuff in this table and look at it later. Leave this table alone. If this table does not exist or you change the data the autograder puts in this table, the autograder may refuse to grade your assignments.