Done

Loading JSON from PokéAPI

In this assignment, you will load the first 100 Pokémon JSON documents from the PokéAPI (https://pokeapi.co/) and store them in a table.

Host: pg.pg4e.com

Port: 5432

Database: pg4e_402ae32925

User: pg4e_402ae32925

Password: (hide/show copy)

Check Answer

Here is the the **psql** command to access your database:

```
psql -h pg.pg4e.com -p 5432 -U pg4e_402ae32925 pg4e_402ae32925
```

Here is the table to create:

```
CREATE TABLE IF NOT EXISTS pokeapi (id INTEGER, body JSONB);
```

This assignment is **not** an adaptation of any of the sample code we provide. You will probably have to write this assignment from scratch. You can look at the code for https://www.pg4e.com/code/swapi.py (https://www.pg4e.com/code/swapi.py?PHPSESSID=60bfd83a378910cd25e6e03d1a857166) and use it to help you write your application - but your application will be much simpler than the **swapi.py** application.

What you need to do is loop through the PokéAPI (https://pokeapi.co/) and retrieve the JSON data for urls ending in 1..100 and store it in the above table. Here is an example URL that ends in `1`: `https://pokeapi.co/api/v2/pokemon/1` . You may find that the Pokemon API supports other URL patterns to retrieve the data, which is fine! But a simple approach wouuld be to loop through the numbers 1..100 and modify this URL to retrieve the data for that item.

The autograder will run a query that looks for data from the API has been successfully inserted into rows in the `pokeapi` table.

There is no need to have a status field or have a restartable process for this assignment. Just get the first 100 JSON items and store them in the above table.

Optionally, but not required by the autograder, feel free to paste your Python code in the space below the assignment to share with reviewers.

Done

Please enter your Python code here: