CHUNK_ID: pneumatic-leak-scenario
TITLE: Demo fault: pressure loss / suspected pneumatic leak
ORIGIN: DEMO_FICTION
SOURCE: A4S authored scenario v1; all numeric values synthetic

CONTENT
The synthetic air-pressure signal starts at 6.0 bar. After 8 seconds it drops by 0.13 bar per second, down to 3.8 bar. Warning is below 5.2 bar; a fault is raised after pressure remains below 4.8 bar for 3 seconds. The fictional failure mechanism is a leaking pneumatic connector: available pressure falls, the press cannot remain ready, the synthetic collective fault becomes true, and order A requires a maintenance hold. Turning-over readiness stays true and conveyor speed is 0 in the fault state. This is a simulated hypothesis, not a measured diagnosis, calibrated threshold or PLC alarm.
END CONTENT

CHUNK_ID: maintenance-playbook
TITLE: Demo maintenance review and business response
ORIGIN: DEMO_FICTION
SOURCE: A4S scenario v1 / MaintenanceInstructions application profile based on IDTA 02018

CONTENT
On the simulated pressure alarm, retrieve technical context and preserve the signal history. Report suspected air leakage as the scenario hypothesis. A qualified operator assesses the pneumatic connection under approved site isolation and maintenance procedures; the agent does not issue physical repair instructions or operate the PLC.
Read OpenMES orders, dry-run a blocking TOOL_FAILURE issue on A, then compare moving the not-yet-started B to the simulated backup. Each business mutation requires approval and read-back. The demo planning allowance for operator review is 30 minutes; it is an invented scheduling assumption, not a predicted or guaranteed repair time.
END CONTENT