

[qlog]

structured event logging

The philosophical update

Robin Marx robin.marx@kuleuven.be

The story so far

[qlog] = QUIC Logging

Log events directly inside the endpoint implementations

- Packet captures require full decryption → worse for privacy/security
- Can add additional information (e.g., congestion window)

Protocol agnostic in 3 parts:

- Main schema
- QUIC and TLS events
- HTTP/3 and QPACK events

<https://github.com/quicwg/qlog>

What do we actually **standardize** and **why**?

Part 1: what does it look like?



Part 1: what does it look like?

draft-01: csv + JSON

```
{
  "event_fields": [
    "relative_time",
    "category",
    "event",
    "data"
  ],
  "events": [
    [
      2,
      "transport",
      "packet_received",
      { header: {...}, frames: {...} }
    ],
    ...
  ]
}
```

← "column" names

- mvfst
- aioquic
- quicly / H2O
- f5
- neqo
- picoquic
- ats
- ...

Part 1: what does it look like?

draft-01: csv + JSON

```
{
  "event_fields": [
    "relative_time",
    "category",
    "event",
    "data"
  ],
  "events": [
    [
      2,
      "transport",
      "packet_received",
      { header: {...}, frames: {...} }
    ],
    ...
  ]
}
```

← **"column" names**

- mvfst
- aioquic
- quicly / H2O
- f5
- neqo
- picoquic
- ats
- ...

draft-02: JSON

```
{
  "events": [
    {
      "time": 2,
      "name": "transport:packet_received",
      "data": {
        header: {...},
        frames: {...}
      }
    },
    ...
  ]
}
```

- quic-go
- ngtcp2
- quiche
- haskell
- kwik

Part 1: what does it look like?

draft-01: csv + JSON

```
{
  "event_fields": [
    "relative_time",
    "category",
    "event",
    "data"
  ],
  "events": [
    [
      2,
      "transport",
      "packet_received",
      { header: {...}, frames: {...} }
    ],
    ...
  ]
}
```

← **"column" names**

draft-02: JSON + NDJSON

```
{
  "events": [
    {
      "time": 2,
      "name": "transport:packet_received",
      "data": {
        header: {...},
        frames: {...}
      }
    },
    ...
  ]
}
```

- mvfst
- aioquic
- quicly / H2O
- f5

- neqo
- picoquic
- ats
- ...

- quic-go
- ngtcp2
- quiche
- haskell
- kwik

Part 1: The JSON in the room

JSON pros:

- Broadly supported → browser-based tooling, scripting libraries
- Plaintext → re-use existing tools (jq, sed/awk/grep/..., **YOU**), `fprintf("%s")`

JSON cons:

- Slow
- Verbose
- *NDJSON isn't actually standardized anywhere yet*

Alternatives:

- CBOR
- Protobuffers/flatbuffers/...
- PCAPNG
- ...

Part 1: What is the goal for qlog?

Optimize for interoperable/**reusable tools**?

VS

Optimize for direct **output/storage/transfer**?

Part 1: What is the goal for qlog?

Optimize for interoperable/**reusable tools**?

VS

Optimize for direct **output/storage/transfer**?

Is this even needed?

- Direct 2 JSON is feasible
 - mvfst, quic-go
- Log optimized, **convert**
 - quicly, picoquic
 - chromium (kind of)

- **Compress**

500MB_0ms_Isquic

format	raw (MB)	%	gzip6 (MB)	%	brtl4 (MB)	%
pcap	561.57	203.45	529.01	191.65	528.85	191.60
qlog	276.02	100.00	19.15	6.94	19.40	7.03
cbor	215.53	78.08	17.78	6.44	18.90	6.85
qlog_lookup	155.89	56.48	17.25	6.25	17.99	6.52
cbor_lookup	90.85	32.91	15.18	5.50	13.18	4.77
protobuf	66.15	23.96	14.56	5.27	10.71	3.88



<https://crates.io/crates/qlog>

<https://github.com/quicwg/qlog/issues/30>

<https://github.com/quicwg/qlog/issues/144#issuecomment-815018003>

Part 1: Proposal

Prioritize tools, stick to JSON + NDJSON

- Other documents can later define CBOR/PCAPNG/Protobuf/... if needed
- We do need to define NDJSON proper ourselves then...
- *Implies switch to CDDL to describe events in drafts*
 - *Currently, we're using a custom DDL based on TypeScript*
- Even loading large JSON files should be feasible
 - Not in qvis/browser, but surely in native apps

Part 2: what's inside it?



Part 2: What we have now

wire image

```
{
  "time": 15000,
  "name": "transport:packet_received",
  "data": {
    "header": {
      "packet_type": "1rtt",
      "packet_number": 25
    },
    "frames": [
      {
        "frame_type": "ack",
        "acked_ranges": [
          [10,15],
          [17,20]
        ]
      }
    ]
  }
}
```

internal state

```
{
  "time": 15001,
  "name": "recovery:metrics_updated",
  "data": {
    "min_rtt": 25,
    "smoothed_rtt": 30,
    "latest_rtt": 25,

    "congestion_window": 60,
    "bytes_in_flight": 77000,
  }
}
```

+ Custom events!

Tools MUST deal with unknown events

Part 2: What we also have now

wire image

```
{
  "time": 15000,
  "name": "transport:packet_received",
  "data": {
    "header": {
      "packet_type": "1rtt",
      "packet_number": 25
    },
    "frames": [
      {
        "frame_type": "ack",
        "acked_ranges": [
          [10,15],
          [17,20]
        ]
      }
    ]
  }
}
```

state changes

```
{
  "time": 15000,
  "name": "transport:packets_acked",
  "data": {
    "packet_numbers": [17,20]
  }
}
```

Only newly
ACKed

Part 2: What we also have now

wire image

```
{
  "time": 15000,
  "name": "transport:packet_received",
  "data": {
    "header": {
      "packet_type": "1rtt",
      "packet_number": 25
    },
    "frames": [
      {
        "frame_type": "ack",
        "acked_ranges": [
          [10,15],
          [17,20]
        ]
      }
    ]
  }
}
```

state changes

```
{
  "time": 15000,
  "name": "transport:packets_acked",
  "data": {
    "packet_numbers": [17,20]
  }
}
```

Only newly
ACKed

partial wire image

```
{
  "time": 15000,
  "name": "transport:frames_processed",
  "data": {
    "frames": {
      "frame_type": "ack",
      "acked_ranges": [
        [10,15],
        [17,20]
      ]
    }
  }
}
```

No packet
header

Part 2: What people are proposing

wire image

```
{
  "time": 15000,
  "name": "transport:packet_received",
  "data": {
    "header": {
      "packet_type": "1rtt",
      "packet_number": 25
    },
    "frames": [
      {
        "frame_type": "ack",
        "acked_ranges": [
          [10, 15],
          [17, 20]
        ]
      }
    ]
  }
}
```

"optimized" partial wire image

```
{
  "time": 15000,
  "name": "transport:frames_created",
  "data": {
    "default_frame": {
      "frame_type": "stream",
      "stream_id": 0,
      "length": 1000
    },
    "frames": [
      {"offset": 2000 },
      {"offset": 3000 },
      {"offset": 4000, "length": 500}
    ]
  }
}
```

Often
sending
similar
STREAM
frames



Part 2: Explosion of events

All useful, but **confusing**

- qlog implementers: what to log when/where?
- Tool creators: which events to use? What if contradictions?
 - *If tools only support a subset, what's the use of standardizing more?*

We need **guidelines**/design philosophy

When should something be a new event / re-use event / **be custom event**?

Part 2: Re-use event types

```
{
  "time": 15000,
  "name": "transport:packet_received",
  "data": {
    "header": {
      "packet_type": "1rtt",
      "packet_number": 25
    }
  }
}
```

Tool
couples
based on
PN

```
{
  "time": 15000,
  "name": "transport:packet_received",
  "data": {
    "header": {
      "packet_number": 25
    },
    "frames": [
      {
        "frame_type": "ack",
        "acked_ranges": [
          [10, 15],
          [17, 20]
        ]
      }
    ]
  }
}
```

When handling header

When handling payload

Part 2: Proposal

Pragmatism: rules with exceptions

1. Stay as close to wire image as possible
 - Only deviate for internal state
 - *Makes tools mostly usable on pcaps as well*
2. Prevent duplicate info logging
 - Only deviate for non-trivial internal state changes
 - *packets_acked would be a good "exception to the rule"*
 - *QPACK wire image vs "dynamic_table_contents"*

If implementations need split (re-used) events/other logic:

→ Write **custom converter** to "proper" qlog for tools that don't support those

In short



Proposal 1: JSON + NDJSON

Proposal 2: limit event options, similar to draft-01

- TODO: not sure if we can call for “consensus” here, but really would like to hear the thoughts in the room about this
 - Not sure how to best approach that
 - Don't want to be left in limbo AGAIN → been bringing this up for 9 months, need decision or clear involvement in discussion