API Reference

Stats -- Initiate Processing

Stats -- Initiate Processing

Copy Page

POST https://dialpad.com/api/v2/stats

Begins processing statistics asynchronously, returning a request id to get the status and retrieve the results by calling GET /stats/{request_id}.

Stats for the whole company will be processed by default. An office_id can be provided to limit stats to a single office. A target_id and target_type can be provided to limit stats to a single target.

Added on May 3, 2018 for API v2.

Rate limit: 200 per hour.

Body Params

coaching_group boolean | null

Whether or not the the statistics should be for trainees of the coach group with the given target_id.

coaching_team boolean | null

Whether or not the the statistics should be for trainees of the coach team with the given target_id.

days_ago_end int64 | null Defaults to 30

End of the date range to get statistics for.

This is the number of days to look back relative to the current day. Used in conjunction with days_ago_start to specify a range.

30

days_ago_start int64 | null Defaults to 1

Start of the date range to get statistics for.

This is the number of days to look back relative to the current day. Used in conjunction with days_ago_end to specify a range.

1

export_type string | null enum required

Whether to return aggregated statistics (stats), or individual rows for each record (records).

NOTE: For stat_type "csat" or "dispositions", only "records" is supported.

Allowed: `records` `stats`

records

group_by string | null enum

This param is only applicable when the stat_type is specified as call. For call stats, group calls by user per day (default), get total metrics by day, or break down by department and call center (office only).

Allowed: `date` `group` `user`

is_today boolean | null

Whether or not the statistics are for the current day.

NOTE: days_ago_start and days_ago_end are ignored if this is passed in.

office_id int64 | null

ID of the office to get statistics for.

If a target_id and target_type are passed in this value is ignored and instead the target is used.

LANGUAGE

Shell Node Ruby PHP Python

CREDENTIALS BEARER

Bearer token

Log in to use your API keys

URL

Base URL https://dialpad.com/api/v2/stats

cURL Request Examples

```
curl --request POST \
     --url https://dialpad.com/api/v2/stats \
     --header 'accept: application/json' \
     --header 'content-type: application/json' \
     --data '
{
  "days_ago_end": 30,
  "days_ago_start": 1,
  "export_type": "records",
  "stat_type": "calls",
  "timezone": "UTC"
}
'
```

Try It!

RESPONSE

Click Try It! to start a request and see the response here! Or choose an example:

application/json

– 200

stat_type string | null enum required

calls

The type of statistics to be returned.

NOTE: if the value is "csat" or "dispositions", target_id and target_type must be specified.

+ Show 8 enum values

target_id int64 | null

The target's id.

target_type string | null enum

Target's type.

+ Show 9 enum values

timezone string | null Defaults to UTC

UTC

Timezone using a tz database name.

Response

200

A successful response

RESPONSE BODY

object

already_started boolean | null

A boolean indicating whether this request has already begun processing.

request_id string | null

The processing request ID.

Updated 5 months ago

← Stats -- Get Result

subscriptions →

Did this page help you? Yes No