


# Ring Light Series

V2.6





## Applications

- 2-dimension code
- Character recognition
- PCB components positioning



High-intensity bright field illumination. LEDs are arranged in flexible circuit boards, getting the high illumination intensity by mainly radiating the central area.

## Technical specifications

|                                                    |                          |                                                                                                                                                                                      |
|----------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Light color</b>                                 | White (W)                | 6500 – 8500K                                                                                                                                                                         |
|                                                    | Red (R)                  | 620 – 630nm                                                                                                                                                                          |
|                                                    | Green (G)                | 520 – 530nm                                                                                                                                                                          |
|                                                    | Blue (B)                 | 460 – 475nm                                                                                                                                                                          |
|                                                    | Infrared (IR)            | On request                                                                                                                                                                           |
|                                                    | Ultraviolet (UV)         | On request                                                                                                                                                                           |
| <b>Connector</b>                                   | JST-SMR-03V-B<br>(FCB-3) |  1<br>2<br>3  |
|                                                    |                          | 1 : +24V<br>2: NC<br>3: GND                                                                                                                                                          |
| <b>Operating environment</b>                       | Temperature              | 0~40 °C                                                                                                                                                                              |
|                                                    | Humidity                 | 20~85 %                                                                                                                                                                              |
| <b>Certification</b>                               | CE / RoHS                |                                                                                                                                                                                      |
| <b>Accessories</b>                                 | VA-CABLE-MVL-FCB3-1m     | 1 meter extension cable                                                                                                                                                              |
|                                                    | VA-CABLE-MVL-FCB3-3m     | 3 meter extension cable                                                                                                                                                              |
|                                                    | VA-CABLE-MVL-FCB3-OE-3m  | 3 meter open end cable                                                                                                                                                               |
|                                                    | VA-CABLE-MVL-FCB3-5m     | 5 meter extension cable                                                                                                                                                              |
| <b>Compatible Power Supply (Dimmable/ Trigger)</b> | VA-PS2-A4-60W-24V        | Analog 4 Channel / 24V / Total 60W / Max. 36W per channel                                                                                                                            |
|                                                    | VA-PS2-A2-200W-24V       | Analog 2 Channel / 24V / Total 200W / Max. 96W per channel                                                                                                                           |
|                                                    | VA-PS2-A4-200W-24V       | Analog 4 Channel / 24V / Total 200W / Max. 64W per channel                                                                                                                           |
|                                                    | VA-PS5-D4-200W-24V       | Digital 4 Channel / 24V / Total 200W / Max. 72W per channel                                                                                                                          |
| <b>Compatible Power Supply (Continuous)</b>        | VA-PS6-2CH-65W-24V       | 2 Channel / 24V / Total 65W                                                                                                                                                          |
|                                                    | VA-PS6-4CH-90W-24V       | 4 Channel / 24V / Total 90W                                                                                                                                                          |
|                                                    | VA-PS6-4CH-150W-24V      | 4 Channel / 24V / Total 150W                                                                                                                                                         |



**Strobe operation: 48 V maximum, 2 ms maximum pulse width, 50% duty cycle (2 ms on / 2 ms off minimum).**

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substituted for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation, and testing of the products with respect to the relevant specific application or use thereof. Neither VA Imaging nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein or incorrect information in this document.

## Product table



| Model         | Color<br>○ ● ● ● | LED<br>Rows | Voltage | Angle | Power<br>(R)* | Power<br>(W/B/G)<br>* | Dimensions<br>ODxIDxH<br>(mm) | Weight<br>(gram) | Express<br>Stock |
|---------------|------------------|-------------|---------|-------|---------------|-----------------------|-------------------------------|------------------|------------------|
| VA-RL3-43-70  | W/R/G/B          | 2           | 24V     | 70    | 1.3           | 2.3                   | 34x10x16                      | 30               | No               |
| VA-RL3-37-90  | W/R/G/B          | 2           | 24V     | 90    | 0.9           | 1.8                   | 37x14x18                      | 35               | No               |
| VA-RL3-42-65  | W/R/G/B          | 2           | 24V     | 65    | 1.8           | 2.3                   | 42x18x18                      | 42               | No               |
| VA-RL3-50-45  | W/R/G/B          | 3           | 24V     | 45    | 3.1           | 3.6                   | 50x20x19                      | 54               | No               |
| VA-RL3-50-60  | W/R/G/B          | 2           | 24V     | 60    | 2.2           | 2.6                   | 50x24x16                      | 46               | No               |
| VA-RL3-50-75  | W/R/G/B          | 2           | 24V     | 75    | 1.8           | 2.6                   | 50x28x16                      | 44               | No               |
| VA-RL3-50-90  | W/R/G/B          | 2           | 24V     | 90    | 1.8           | 3.1                   | 50x25x19                      | 52               | No               |
| VA-RL3-60-60  | W/R/G/B          | 2           | 24V     | 60    | 2.6           | 3                     | 60x33.5x16                    | 60               | No               |
| VA-RL3-66-60  | W/R/G/B          | 3           | 24V     | 60    | 4.4           | 4.4                   | 66x30x17                      | 87               | No               |
| VA-RL3-70-45  | W/R/G/B          | 3           | 24V     | 45    | 4.8           | 5.1                   | 70x38x21                      | 100              | No               |
| VA-RL3-70-60  | W/R/G/B          | 3           | 24V     | 60    | 4.4           | 4.9                   | 70x30x20                      | 114              | No               |
| VA-RL3-70-90  | W/R/G/B          | 3           | 24V     | 90    | 4.4           | 5.8                   | 70x35x22                      | 113              | No               |
| VA-RL3-74-60  | W/R/G/B          | 3           | 24V     | 60    | 5.2           | 5.4                   | 74x35x20                      | 114              | No               |
| VA-RL3-90-45  | W/R/G/B          | 3           | 24V     | 45    | 6             | 6.1                   | 90x56x20.5                    | 129              | No               |
| VA-RL3-90-70  | W/R/G/B          | 4           | 24V     | 70    | 6.3           | 6.3                   | 90x50x20                      | 151              | Yes              |
| VA-RL3-100-90 | W/R/G/B          | 5           | 24V     | 90    | 7             | 7.1                   | 100x40x20                     | 229              | No               |
| VA-RL3-110-65 | W/R/G/B          | 5           | 24V     | 65    | 9             | 9                     | 110x60x25                     | 266              | No               |
| VA-RL3-120-50 | W/R/G/B          | 4           | 24V     | 50    | 9.8           | 9.8                   | 120x80x21                     | 215              | No               |
| VA-RL3-120-75 | W/R/G/B          | 5           | 24V     | 75    | 11.4          | 11.4                  | 120x65x17                     | 240              | No               |
| VA-RL3-120-90 | W/R/G/B          | 6           | 24V     | 90    | 11            | 11.3                  | 120x50x18                     | 311              | No               |
| VA-RL3-150-90 | W/R/G/B          | 9           | 24V     | 90    | 13.6          | 13.7                  | 150x25x22.5                   | 603              | No               |
| VA-RL3-180-60 | W/R/G/B          | 5           | 24V     | 60    | 18.9          | 19                    | 180x126x33                    | 488              | No               |
| VA-RL3-210-60 | W/R/G/B          | 6           | 24V     | 60    | 28.8          | 28.8                  | 210x145x25                    | 691              | No               |

\*Tolerance +/- 10%


The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.

This documentation is not intended as a substituted for and is not to be used for determining suitability or reliability of these products for specific user applications.


It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation, and testing of the products with respect to the relevant specific application or use thereof.

Neither VA Imaging nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein or incorrect information in this document.


## Technical drawing




**VA-RL3-34-70**




**VA-RL3-37-90**




**VA-RL3-42-65**




**VA-RL3-50-45**




**VA-RL3-50-60**




**VA-RL3-50-75**




**VA-RL3-50-90**




**VA-RL3-60-60**




**VA-RL3-66-60**




**VA-RL3-70-45**




**VA-RL3-70-60**




**VA-RL3-70-90**




**VA-RL3-74-60**




**VA-RL3-90-45**




**VA-RL3-90-70**




**VA-RL3-100-90**




**VA-RL3-110-65**




**VA-RL3-120-50**




**VA-RL3-120-75**




**VA-RL3-120-90**




**VA-RL3-150-90**



**VA-RL3-180-60**



**VA-RL3-210-60**



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.

This documentation is not intended as a substituted for and is not to be used for determining suitability or reliability of these products for specific user applications.

It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation, and testing of the products with respect to the relevant specific application or use thereof.

Neither VA Imaging nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein or incorrect information in this document.

## Product number

| VA – RL3 | - | Diameter | - | Angle | - | Color |
|----------|---|----------|---|-------|---|-------|
|          |   | 34       |   | 45    |   | W     |
|          |   | 50       |   | 60    |   | R     |
|          |   | .....    |   | 65    |   | G     |
|          |   |          |   | 70    |   | B     |
|          |   |          |   | 90    |   | IR    |
|          |   |          |   |       |   | UV    |