

姓名：蔡佩津

学号：78066011

### 第三作业

1.答：综合统一，高度非过程化，面向集合的操作方式，语言简洁，易学易用，已同一语法结构提供两种使用方式（自含式，嵌入式）。

3.答：(1)SELECT \* FROM S WHERE A=10

(2)SELECT DISTINCT A,B FROM S

(3)SELECT A,B,S.C,S.D,E,F FROM S,T WHERE S.C=T.C AND S.D=T.D

(4)SELECT A,B,S.C,S.D,T.C,T.D,E,F FROM S,T WHERE S.C=T.C

(5)SELECT A,B,S.C,S.D,T.C,T.D,E,F FROM S,T WHERE A<E

(6)SELECT S1.C,S1.D,T.C,T.D,E,F FROM T,(select DISTINCT C,D FROM S) AS S1

4.答：建 S 表：

S (SNO,SNAME,STATUS,CITY) ;

CREATE TABLE S

(SNO CHAR(3), SNAME CHAR(10),STATUS CHAR(2),CITY CHAR(10));

建 P 表：

P (PNO,PNAME,COLOR,WEIGHT) ;

CREATE TABLE P

(PNO CHAR(3), PNAME CHAR(10),COLOR CHAR(4),WEIGHT INT);

建 J 表：

J (JNO,JNAME,CITY) ;

CREATE TABLE J

(JNO CHAR(3), JNAME CHAR(10),CITY CHAR(10));

建 SPJ 表：

SPJ (SNO,PNO,JNO,QTY) ;

CREATE TABLE SPJ

(SNO CHAR(3), PNO CHAR(3),JNO CHAR(3),QTY INT);

5.答: (1)SELECT SNAME,CITY //pg 36

FROM S

SNAME	CITY
精益	天津
盛锡	北京
东方红	北京
丰泰盛	天津
为民	上海

(2)SELECT PNAME,COLOR,WEIGHT

FROM P

PNAME	COLOR	WEIGHT
螺母	红	12
螺栓	绿	17
螺丝刀	蓝	14
螺丝刀	红	14
凸轮	蓝	40
齿轮	红	30

(3)SELECT JNO

FROM SPJ

WHERE SNO='S1';

JNO
J1
J3
J4
J2

(4)SELECT P.PNAME,SPJ.QTY

FROM P,SPJ

WHERE P.PNO=SPJ.PNO

AND SPJ.JNO='J2';

PNAME	QTY
螺栓	100
螺丝刀	200
凸轮	100
齿轮	200

(5)SELECT DISTINCT PNO

FROM SPJ

WHERE SNO IN

(SELECT SNO

FROM S

WHERE CITY='上海');

PNO
P2
P3
P6

(6) SELECT JNAME

FROM J,SPJ,S

WHERE J.JNO=SPJ.JNO

AND SPJ.SNO=S.SNO

AND S.CITY='上海';

1	SELECT JNAME
2	FROM J,SPJ,S
3	WHERE J.JNO=SPJ.JNO
4	AND SPJ.SNO=S.SNO
5	AND S.CITY='上海';
6	
JNAME	
三建	
一汽	
造船广	
造船广	

```

(7) SELECT JNO
      FROM J
      WHERE NOT EXISTS
      (SELECT *
      FROM SPJ
      WHERE SPJ.JNO=J.JNO
      AND SNO IN
      (SELECT SNO
      FROM S
      WHERE CITY='天津'));

```

JNO
J5
J6
J7

```

(8) UPDATE P
SET COLOR='蓝'
WHERE COLOR='红';

```

PNO	PNAME	COLOR	WEIGHT
P1	螺母	蓝	12
P2	螺栓	绿	17
P3	螺丝刀	蓝	14
P4	螺丝刀	蓝	14
P5	凸轮	蓝	40
P6	齿轮	蓝	30

```

(9) UPDATE SPJ
SET SNO='S3'
WHERE SNO='S5'
AND JNO='J4'

```

AND PNO='P6';

SNO	PNO	JNO	QTY
S5	P2	J4	100
S5	P3	J1	200
S5	P6	J2	200
S3	P6	J4	500

(10)DELETE

FROM SPJ

WHERE SNO='S2';

DELETE

FROM S

WHERE SNO='S2';

SNO	SNAME	STATUS	CITY
S1	精益	20	天津
S3	东方红	30	北京
S4	丰泰盛	20	天津
S5	为民	30	上海

6.答：基本表式本身独立存在的表，在 SQL 中一个关系就对应一个基本表。

视图是从一个或几个基本表导出的表。

视图本身不存在独立存储在数据库中，是一个虚表。即数据库中只存放视图的定义而不存放视图对应的数据，这些数据仍然存放在导出视图的基本表中。视图在概念上基本与表等同。视图在概念上与基本表等同，用户可以在基本表那样使用视图，可以在视图上再定义视图。

9.答：创建视图：

1) CREATE VIEW V\_SPJ AS

SELECT SNO,PNO,QTY

FROM SPJ

WHERE JNO=

(SELECT JNO FROM J WHERE JNAME='三建');

对该视图查询：

```
1) SELECT PNO,QTY  
    FROM V_SPJ;
```

```
2) SELECT PNO,QTY  
    FROM V_SPJ  
    WHERE SNO='S1';
```