



Vimba

Vimba GigE TL Features Manual

1.8.0

Legal Notice

Trademarks

Unless stated otherwise, all trademarks appearing in this document are brands protected by law.

Warranty

The information provided by Allied Vision is supplied without any guarantees or warranty whatsoever, be it specific or implicit. Also excluded are all implicit warranties concerning the negotiability, the suitability for specific applications or the non-breaking of laws and patents. Even if we assume that the information supplied to us is accurate, errors and inaccuracy may still occur.

Copyright

All texts, pictures and graphics are protected by copyright and other laws protecting intellectual property.

All rights reserved.

Headquarters:
Allied Vision Technologies GmbH
Taschenweg 2a
D-07646 Stadtroda, Germany
Tel.: +49 (0)36428 6770
Fax: +49 (0)36428 677-28
e-mail: info@alliedvision.com

Contents

1	Contacting Allied Vision	8
2	Document history and conventions	9
2.1	Document history	10
2.2	Conventions used in this manual	10
2.2.1	Styles	11
2.2.2	Symbols	11
3	VimbaGigETL - Overview	12
4	VimbaGigETL System Features	13
4.1	SystemInformation	14
4.1.1	TLID	14
4.1.2	TLVendorName	14
4.1.3	TLModelName	15
4.1.4	TLVersion	15
4.1.5	TLDisplayName	16
4.1.6	TLPath	16
4.1.7	TLType	16
4.1.8	GenTLVersionMajor	17
4.1.9	GenTLVersionMinor	17
4.1.10	GevVersionMajor	18
4.1.11	GevVersionMinor	18
4.2	InterfaceEnumeration	18
4.2.1	InterfaceUpdateList	19
4.2.2	InterfaceCount [Allied Vision]	19
4.2.3	InterfaceSelector	19
4.2.4	InterfaceID	20
4.2.5	GevInterfaceMACAddress	20
4.2.6	GevInterfaceDefaultIPAddress	20
4.2.7	GevInterfaceDefaultSubnetMask	21
4.3	CameraAddressForcing [Allied Vision]	21
4.3.1	GevDeviceForceMACAddress [Allied Vision]	21
4.3.2	GevDeviceForceIPAddress [Allied Vision]	22
4.3.3	GevDeviceForceSubnetMask [Allied Vision]	22
4.3.4	GevDeviceForceGateway [Allied Vision]	22
4.3.5	GevDeviceForceIP [Allied Vision]	23
4.4	ActionControl	23
4.4.1	ActionCommand [Allied Vision]	23
4.4.2	ActionDeviceKey [Allied Vision]	24

4.4.3	ActionGroupKey [Allied Vision]	24
4.4.4	ActionGroupMask [Allied Vision]	24
4.4.5	GevActionDestinationIPAddress [Allied Vision]	25
5	VimbaGigETL Interface Features	26
5.1	InterfaceInformation	27
5.1.1	InterfaceID	27
5.1.2	InterfaceDisplayName	28
5.1.3	InterfaceType	28
5.2	DeviceEnumeration	28
5.2.1	DeviceUpdateList	29
5.2.2	DeviceCount [Allied Vision]	29
5.2.3	DeviceSelector	29
5.2.4	DeviceID	30
5.2.5	DeviceVendorName	30
5.2.6	DeviceModelName	30
5.2.7	DeviceType [Allied Vision]	31
5.2.8	DeviceDisplayName [Allied Vision]	31
5.2.9	DeviceAccessStatus	31
5.3	Gev [Allied Vision]	32
5.3.1	GevInterfaceMACAddress	32
5.3.2	GevInterfaceSubnetIPAddress	32
5.3.3	GevInterfaceSubnetMask	33
5.3.4	GevDeviceIPAddress	33
5.3.5	GevDeviceSubnetMask	33
5.3.6	GevDeviceMACAddress	34
5.3.7	GevDeviceForceIPAddress	34
5.3.8	GevDeviceForceSubnetMask	34
5.3.9	GevDeviceForceGateway	35
5.3.10	GevDeviceForceIP	35
5.4	Settings [Allied Vision]	35
5.4.1	InterfaceBeatRate [Allied Vision]	35
5.4.2	InterfaceHailPace [Allied Vision]	36
5.4.3	InterfacePingPace [Allied Vision]	36
5.4.4	DiscoveryMode [Allied Vision]	37
5.4.5	DiscoveryBroadcastMode [Allied Vision]	37
5.5	ActionControl	37
5.5.1	ActionCommand	38
5.5.2	ActionDeviceKey	38
5.5.3	ActionGroupKey	38
5.5.4	ActionGroupMask	39

5.5.5	GevActionDestinationIPAddress	39
6	VimbaGigETL Device Features	40
6.1	DeviceInformation	41
6.1.1	DeviceID	41
6.1.2	DeviceVendorName	41
6.1.3	DeviceModelName	42
6.1.4	DeviceType	42
6.1.5	DeviceDisplayName	43
6.2	Gev [Allied Vision]	43
6.2.1	GevDeviceIPAddress	43
6.2.2	GevDeviceSubnetMask	43
6.2.3	GevDeviceMACAddress	44
6.2.4	GevDeviceGateway	44
6.2.5	DeviceEndiannessMechanism	45
6.3	StreamEnumeration	45
6.3.1	StreamCount [Allied Vision]	45
6.3.2	StreamSelector	46
6.3.3	StreamID	46
6.4	GigE [Allied Vision]	47
6.5	GVCP [Allied Vision]	47
6.5.1	GevHeartbeatTimeout	47
6.5.2	GevHeartbeatInterval [Allied Vision]	47
6.5.3	GVCPCmdTimeout [Allied Vision]	48
6.5.4	GVCPCmdRetries [Allied Vision]	48
7	VimbaGigETL Stream Features	49
7.1	StreamInformation	50
7.1.1	StreamID	50
7.1.2	StreamType	51
7.2	BufferHandlingControl	51
7.2.1	StreamAnnouncedBufferCount	51
7.2.2	StreamBufferHandlingMode	52
7.2.3	StreamAnnounceBufferMinimum	52
7.3	Stream [Allied Vision]	52
7.4	Multicast [Allied Vision]	52
7.4.1	MulticastEnable [Allied Vision]	53
7.4.2	MulticastIPAddress [Allied Vision]	53
7.5	Info [Allied Vision]	53
7.5.1	GVSPFilterVersion [Allied Vision]	54
7.6	Settings [Allied Vision]	54
7.6.1	GVSPTimeout [Allied Vision]	54

7.6.2	GVSPDriver [Allied Vision]	54
7.6.3	GVSPHostReceiveBuffers [Allied Vision]	55
7.6.4	GVSPBurstSize [Allied Vision]	55
7.6.5	GVSPMaxLookBack [Allied Vision]	56
7.6.6	GVSPMaxRequests [Allied Vision]	56
7.6.7	GVSPMissingSize [Allied Vision]	56
7.6.8	GVSP TiltingSize [Allied Vision]	57
7.6.9	GVSPMaxWaitSize [Allied Vision]	57
7.6.10	GVSPPacketSize [Allied Vision]	57
7.6.11	GVSPAdjustPacketSize [Allied Vision]	58
7.7	Statistics [Allied Vision]	58
7.7.1	StatFrameDelivered [Allied Vision]	58
7.7.2	StatFrameDropped [Allied Vision]	59
7.7.3	StatFrameUnderrun [Allied Vision]	59
7.7.4	StatFrameShoved [Allied Vision]	59
7.7.5	StatFrameRescued [Allied Vision]	60
7.7.6	StatPacketReceived [Allied Vision]	60
7.7.7	StatPacketMissed [Allied Vision]	61
7.7.8	StatPacketErrors [Allied Vision]	61
7.7.9	StatPacketRequested [Allied Vision]	61
7.7.10	StatPacketResent [Allied Vision]	62
7.7.11	StatFrameRate [Allied Vision]	62
7.7.12	StatLocalRate [Allied Vision]	62
7.7.13	StatTimeElapsed [Allied Vision]	63
8	Vimba functional extensions to GenTL	64
8.1	Custom Transport Layer events	65
8.1.1	Additions to EVENT_TYPE_LIST	65
8.1.2	Additions to EVENT_DATA_INFO_CMD_LIST	65
8.1.3	Additional enumeration IFCHANGE_WHAT_LIST	65
8.2	Additional URL information	66
8.2.1	Additions to URL_INFO_CMD_LIST	66

Listings

1	Event types	65
2	Change Events	65
3	Change Event options	66
4	URL information	66

1 Contacting Allied Vision

Contact information on our website

<https://www.alliedvision.com/en/meta-header/contact-us>

Find an Allied Vision office or distributor

<https://www.alliedvision.com/en/about-us/where-we-are>

Email

info@alliedvision.com

support@alliedvision.com

Sales Offices

EMEA: +49 36428-677-230

North and South America: +1 978 225 2030

California: +1 408 721 1965

Asia-Pacific: +65 6634-9027

China: +86 (21) 64861133

Headquarters

Allied Vision Technologies GmbH

Taschenweg 2a

07646 Stadtroda

Germany

Tel: +49 (0)36428 677-0

Fax: +49 (0)36428 677-28

Managing Directors (Geschäftsführer): Andreas Gerke, Peter Tix

2 Document history and conventions



This chapter includes:

2.1	Document history	10
2.2	Conventions used in this manual	10
2.2.1	Styles	11
2.2.2	Symbols	11

2.1 Document history

Version	Date	Changes
1.0	2013-02-25	Initial version
1.1	2013-03-07	Different generation of document, small layout changes
1.2	2013-05-13	Refined some descriptions, changed the layout of document and feature tables, removed the exemplary camera features
1.3	2014-07-09	Changed the referenced GenTL version to 1.3, small corrections
1.4.1	2015-11-09	Renamed several Vimba components and documents ("AVT" no longer in use), links to new Allied Vision website
1.4.2	2016-02-27	New document layout
1.5.0	2016-02-27	Added Action Commands, updated document layout
1.5.3	2018-05-02	Bug fixes
1.6.0	June 2019	Bug fixes
1.7.0	October 2019	GenTL 1.5 support
1.8.0	October 2020	Added GevUseExtendedIDs feature, provided standard-compliant ForceIP feature

2.2 Conventions used in this manual

To give this manual an easily understood layout and to emphasize important information, the following typographical styles and symbols are used:

2.2.1 Styles

Style	Function	Example
Emphasis	Programs, or highlighting important things	Emphasis
Publication title	Publication titles	Title
Web reference	Links to web pages	Link
Document reference	Links to other documents	Document
Output	Outputs from software GUI	Output
Input	Input commands, modes	Input
Feature	Feature names	Feature

2.2.2 Symbols



Practical Tip



Safety-related instructions to avoid malfunctions

Instructions to avoid malfunctions



Further information available online

3 VimbaGigETL - Overview

The VimbaGigETL (Vimba GigE Transport Layer) transports the data from the network card to an application. It is a module according to the GenTL specification and complies to GenICam applications providing a GenTL consumer interface. It consists of several parts: the functional interface and the feature maps for the transport layer and for the camera.


The **functional interface** is needed for dynamically controlling GigE cameras and it covers the functionality described in [GenTL specification 1.5](#). There is additional functionality, which is described in chapter 8, **Vimba extensions to the functional GenTL interface**.

The **features** exposed by XML files are GenAPI-conforming features described in the locations:

- Features of the GenTL **System module** in chapter 4. The System is a module for handling multiple GenTL Interfaces in one transport layer.
- Features of the GenTL **Interface module** in chapter 5. The Interface is a module for handling multiple GenTL Devices.
- Features of the GenTL **Device module** in chapter 6. The Device module is a host-side representation of the Camera aka "Remote Device".
- Features of the GenTL **Data Stream module** in chapter 7. The Data Stream module allows handling all streaming-related operations.
- Camera (**Remote Device**) features in [GigE_Features_Reference.pdf](#).

The **configuration file**, which is named VimbaGigETL.xml (according to the name of the VimbaGigETL.cti), must be located in the same directory as the Transport Layer file. The configuration options are described in the comments of the file itself.

4 VimbaGigETL System Features



This chapter includes:

4.1	SystemInformation	14
4.1.1	TLID	14
4.1.2	TLVendorName	14
4.1.3	TLModelName	15
4.1.4	TLVersion	15
4.1.5	TLDisplayName	16
4.1.6	TLPath	16
4.1.7	TLType	16
4.1.8	GenTLVersionMajor	17
4.1.9	GenTLVersionMinor	17
4.1.10	GevVersionMajor	18
4.1.11	GevVersionMinor	18
4.2	InterfaceEnumeration	18
4.2.1	InterfaceUpdateList	19
4.2.2	InterfaceCount [Allied Vision]	19
4.2.3	InterfaceSelector	19
4.2.4	InterfaceID	20
4.2.5	GevInterfaceMACAddress	20
4.2.6	GevInterfaceDefaultIPAddress	20
4.2.7	GevInterfaceDefaultSubnetMask	21
4.3	CameraAddressForcing [Allied Vision]	21
4.3.1	GevDeviceForceMACAddress [Allied Vision]	21
4.3.2	GevDeviceForceIPAddress [Allied Vision]	22
4.3.3	GevDeviceForceSubnetMask [Allied Vision]	22
4.3.4	GevDeviceForceGateway [Allied Vision]	22
4.3.5	GevDeviceForceIP [Allied Vision]	23
4.4	ActionControl	23
4.4.1	ActionCommand [Allied Vision]	23
4.4.2	ActionDeviceKey [Allied Vision]	24
4.4.3	ActionGroupKey [Allied Vision]	24
4.4.4	ActionGroupMask [Allied Vision]	24
4.4.5	GevActionDestinationIPAddress [Allied Vision]	25

This chapter lists features that are potentially available in this module. Some features are only available under certain circumstances.

The following categories can be found below the Root category:

- SystemInformation
- InterfaceEnumeration
- CameraAddressForcing
- ActionControl

4.1 SystemInformation

Category that contains all System Information features of the System module.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.1 TLID

Name	TL ID
Interface	IString
Access	Read
Visibility	Beginner

Unique identifier of the GenTL Producer like a GUID.
Corresponds to the TL_INFO_ID command of TLGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.2 TLVendorName

Name	TL Vendor Name
Interface	IString
Access	Read
Visibility	Beginner

Name of the GenTL Producer vendor.

Corresponds to the TL_INFO_VENDOR command of TLGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.3 TLModelName

Name	TL Model Name
Interface	IString
Access	Read
Visibility	Beginner

Name of the GenTL Producer to distinguish different kinds of GenTL Producer implementations from one vendor.

Corresponds to the TL_INFO_MODEL command of TLGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.4 TLVersion

Name	TL Version
Interface	IString
Access	Read
Visibility	Beginner

Vendor specific version string.

Corresponds to the TL_INFO_VERSION command of TLGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.5 TLDisplayName

Name	TL Display Name
Interface	IString
Access	Read
Visibility	Beginner

User readable name of the GenTL Producer.

Corresponds to the TL_INFO_DISPLAYNAME command of TLGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.6 TLPath

Name	TL Path
Interface	IString
Access	Read
Visibility	Beginner

Full path to the GenTL Producer driver including name and extension.

Corresponds to the TL_INFO_PATHNAME command of TLGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.7 TLType

Name	TL Type
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	GEV

Transport layer type of the GenTL Producer implementation.
Corresponds to the TL_INFO_TLTYPE command of TLGetInfo function.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.8 GenTLVersionMajor

Name	GenTL Version Major
Interface	Integer
Access	Read
Visibility	Expert

Major version number of the GenTL specification the GenTL Producer implementation complies with.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.9 GenTLVersionMinor

Name	GenTL Version Minor
Interface	Integer
Access	Read
Visibility	Expert

Minor version number of the GenTL specification the GenTL Producer implementation complies with.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.10 GevVersionMajor

Name	GEV Major Version Number
Interface	Integer
Access	Read
Visibility	Beginner

Major version number of the GigE Vision specification the GenTL Producer implementation complies to.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.1.11 GevVersionMinor

Name	GEV Minor Version Number
Interface	Integer
Access	Read
Visibility	Beginner

Minor version number of the GigE Vision specification the GenTL Producer implementation complies to.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2 InterfaceEnumeration

Category that contains all Interface Enumeration features of the System module.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2.1 InterfaceUpdateList

Name	Interface Update List
Interface	ICommand
Access	Read/Write
Visibility	Beginner

Update the internal interface list on this GenTL Producer.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2.2 InterfaceCount [Allied Vision]

Name	Interface Count
Interface	Integer
Access	Read/Write
Visibility	Beginner

Number of interfaces on this GenTL Producer.

4.2.3 InterfaceSelector

Name	Interface Selector
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Selector for the different GenTL Producer interfaces.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2.4 InterfaceID

Name	Interface ID
Interface	QString
Access	Read
Visibility	Beginner

GenTL Producer wide unique identifier of the selected interface.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2.5 GevInterfaceMACAddress

Name	Interface MAC Address
Interface	Integer
Access	Read/Write
Visibility	Expert

48-bit MAC address of the interface.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2.6 GevInterfaceDefaultIPAddress

Name	Interface IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert

IP address of the interface.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.2.7 GevInterfaceDefaultSubnetMask

Name	Interface Subnet Mask
Interface	Integer
Access	Read/Write
Visibility	Expert

Subnet mask of the interface.

See [GenTL specification 1.5 chapter 7](#) for more details.

4.3 CameraAddressForcing [Allied Vision]

Category that contains all features of the System module for forcing access to cameras that are otherwise not detectable.

4.3.1 GevDeviceForceMACAddress [Allied Vision]

Name	Gev Device Force MAC Address
Interface	Integer
Access	Read/Write
Visibility	Expert

48-bit MAC address of the GEV camera to force IP setup.

4.3.2 GevDeviceForceIPAddress [Allied Vision]

Name	Gev Device Force IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert

IP address of the GEV camera to be forced.

4.3.3 GevDeviceForceSubnetMask [Allied Vision]

Name	Gev DeviceForce Subnet Mask
Interface	Integer
Access	Read/Write
Visibility	Expert

Subnet mask of the GEV camera to be forced.

4.3.4 GevDeviceForceGateway [Allied Vision]

Name	Gev Device Force Gateway
Interface	Integer
Access	Read/Write
Visibility	Expert

Gateway of the GEV camera to be forced.

4.3.5 GevDeviceForceIP [Allied Vision]

Name	Gev Device Force IP
Interface	ICommand
Access	Read/Write
Visibility	Expert

Send the force address command on all interfaces.

4.4 ActionControl

Category that contains all features of the System module for creating and sending Action Commands.
See [GenTL specification 1.5 chapter 7](#) for more details.

4.4.1 ActionCommand [Allied Vision]

Name	Action Command
Interface	ICommand
Access	Read/Write
Visibility	Expert

Send created Action Command.

4.4.2 ActionDeviceKey [Allied Vision]

Name	Action Device Key
Interface	Integer
Access	Read/Write
Visibility	Expert

The Device Key for the Action Command to be created.
This Key has to match Action Device Key within desired device(s).

4.4.3 ActionGroupKey [Allied Vision]

Name	Action Group Key
Interface	Integer
Access	Read/Write
Visibility	Expert

The Group Key for the Action Command to be created.
This Key has to match Action Group Key within desired device(s).

4.4.4 ActionGroupMask [Allied Vision]

Name	Action Group Mask
Interface	Integer
Access	Read/Write
Visibility	Expert


The Group Mask Key for the Action Command to be created.
This Key has to match Action Group Mask Key within desired device(s).

4.4.5 GevActionDestinationIPAddress [Allied Vision]

Name	Gev Action Destination IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert

Specifies destination the IP address for the Action Command.

5 VimbaGigETL Interface Features



This chapter includes:

5.1	InterfaceInformation	27
5.1.1	InterfaceID	27
5.1.2	InterfaceDisplayName	28
5.1.3	InterfaceType	28
5.2	DeviceEnumeration	28
5.2.1	DeviceUpdateList	29
5.2.2	DeviceCount [Allied Vision]	29
5.2.3	DeviceSelector	29
5.2.4	DeviceID	30
5.2.5	DeviceVendorName	30
5.2.6	DeviceModelName	30
5.2.7	DeviceType [Allied Vision]	31
5.2.8	DeviceDisplayName [Allied Vision]	31
5.2.9	DeviceAccessStatus	31
5.3	Gev [Allied Vision]	32
5.3.1	GevInterfaceMACAddress	32
5.3.2	GevInterfaceSubnetIPAddress	32
5.3.3	GevInterfaceSubnetMask	33
5.3.4	GevDeviceIPAddress	33
5.3.5	GevDeviceSubnetMask	33
5.3.6	GevDeviceMACAddress	34
5.3.7	GevDeviceForceIPAddress	34
5.3.8	GevDeviceForceSubnetMask	34
5.3.9	GevDeviceForceGateway	35
5.3.10	GevDeviceForceIP	35
5.4	Settings [Allied Vision]	35
5.4.1	InterfaceBeatRate [Allied Vision]	35
5.4.2	InterfaceHailPace [Allied Vision]	36
5.4.3	InterfacePingPace [Allied Vision]	36
5.4.4	DiscoveryMode [Allied Vision]	37
5.4.5	DiscoveryBroadcastMode [Allied Vision]	37
5.5	ActionControl	37
5.5.1	ActionCommand	38
5.5.2	ActionDeviceKey	38
5.5.3	ActionGroupKey	38
5.5.4	ActionGroupMask	39
5.5.5	GevActionDestinationIPAddress	39

This chapter lists features that are potentially available in this module. Some features are only available under certain circumstances.

The following categories can be found below the Root category:

- InterfaceInformation
- DeviceEnumeration
 - Gev
- Settings
- ActionControl

5.1 InterfaceInformation

Category that contains all Interface Information features of the Interface module.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.1.1 InterfaceID

Name	Interface ID
Interface	IString
Access	Read
Visibility	Beginner

GenTL Producer wide unique identifier of the selected interface.

Corresponds to the INTERFACE_INFO_ID command of IFGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.1.2 InterfaceDisplayName

Name	Interface Display Name
Interface	IString
Access	Read
Visibility	Beginner

User readable name of the selected interface.

Corresponds to the INTERFACE_INFO_DISPLAYNAME command of IFGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.1.3 InterfaceType

Name	Interface Type
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	GEV

Identifies the transport layer technology of the interface.

Corresponds to the INTERFACE_INFO_TLTYPE command of IFGetInfo function.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.2 DeviceEnumeration

Category that contains all Device Enumeration features of the Interface module.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.2.1 DeviceUpdateList

Name	Device Update List
Interface	ICommand
Access	Read/Write
Visibility	Beginner

Updates the internal device list.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.2.2 DeviceCount [Allied Vision]

Name	Device Count
Interface	Integer
Access	Read/Write
Visibility	Beginner

Number of found devices.

5.2.3 DeviceSelector

Name	Device Selector
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Selector for the different devices on this interface.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.2.4 DeviceID

Name	Device ID
Interface	QString
Access	Read
Visibility	Beginner

Interface wide unique identifier of the selected device.
See [GenTL specification 1.5 chapter 7](#) for more details.

5.2.5 DeviceVendorName

Name	Device Vendor Name
Interface	QString
Access	Read
Visibility	Beginner

Name of the device vendor.
See [GenTL specification 1.5 chapter 7](#) for more details.

5.2.6 DeviceModelName

Name	Device Model Name
Interface	QString
Access	Read
Visibility	Beginner

Name of the device model.
See [GenTL specification 1.5 chapter 7](#) for more details.

5.2.7 DeviceType [Allied Vision]

Name	Device Type
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	GEV

Identifies the transport layer technology of the device.
Possible values:

- GEV: GigE Vision

5.2.8 DeviceDisplayName [Allied Vision]

Name	Device Display Name
Interface	IString
Access	Read
Visibility	Beginner

User readable name of the selected device.

5.2.9 DeviceAccessStatus

Name	Device Access Status
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	Unknown, ReadWrite, ReadOnly, NoAccess

Gives the device's access status at the moment of the last execution of "DeviceUpdateList".

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3 Gev [Allied Vision]

5.3.1 GevInterfaceMACAddress

Name	Interface MAC Address
Interface	Integer
Access	Read/Write
Visibility	Expert

48-bit MAC address of this interface.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.2 GevInterfaceSubnetIPAddress

Name	Interface IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert

IP address of the selected subnet of this interface.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.3 GevInterfaceSubnetMask

Name	Interface Subnet Mask
Interface	Integer
Access	Read/Write
Visibility	Expert

Subnet mask of the selected subnet of this interface.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.4 GevDeviceIPAddress

Name	Device IP Address
Interface	Integer
Access	Read/Write
Visibility	Beginner

Current IP address of the GVCP interface of the selected remote device.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.5 GevDeviceSubnetMask

Name	Device Subnet Mask
Interface	Integer
Access	Read/Write
Visibility	Beginner

Current subnet mask of the GVCP interface of the selected remote device.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.6 GevDeviceMACAddress

Name	Device MAC Address
Interface	Integer
Access	Read/Write
Visibility	Beginner

48-bit MAC address of the GVCP interface of the selected remote device.
See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.7 GevDeviceForceIPAddress

Name	Gev Device Force IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert

IP address of the GEV camera to be forced.
See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.8 GevDeviceForceSubnetMask

Name	Gev DeviceForce Subnet Mask
Interface	Integer
Access	Read/Write
Visibility	Expert

Subnet mask of the GEV camera to be forced.
See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.9 GevDeviceForceGateway

Name	Gev Device Force Gateway
Interface	Integer
Access	Read/Write
Visibility	Expert

Gateway of the GEV camera to be forced.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.3.10 GevDeviceForceIP

Name	Gev Device Force IP
Interface	ICommand
Access	Read/Write
Visibility	Expert

Send the force address command on all interfaces.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.4 Settings [Allied Vision]

5.4.1 InterfaceBeatRate [Allied Vision]

Name	Interface Beat Rate
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	10..10000

Rate (in ms) at which the interface will perform device discovery.

5.4.2 InterfaceHailPace [Allied Vision]

Name	Interface Hail Pace
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	1..10

Pace (as in every X beats) at which the interface will hail for devices to reply.

5.4.3 InterfacePingPace [Allied Vision]

Name	Interface Ping Pace
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	1..10

Pace (as in every X beats) at which the interface will ping detected devices.

5.4.4 DiscoveryMode [Allied Vision]

Name	Devices Discovery Mode
Interface	IEnumeration
Access	Read/Write
Visibility	Beginner
Values	Off, Auto, Once

Defines how the interface should discover connected devices.

5.4.5 DiscoveryBroadcastMode [Allied Vision]

Name	Devices Discovery Broadcast Mode
Interface	IEnumeration
Access	Read/Write
Visibility	Beginner
Values	Local, Subnet

Defines how the interface should send its discovery broadcast.

5.5 ActionControl

Category that contains all features of the Interface module for creating and sending Action Commands.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.5.1 ActionCommand

Name	Action Command
Interface	ICommand
Access	Read/Write
Visibility	Expert

Send created Action Command.

See [GenTL specification 1.5 chapter 7](#) for more details.

5.5.2 ActionDeviceKey

Name	Action Device Key
Interface	Integer
Access	Read/Write
Visibility	Expert

The Device Key for the Action Command to be created.

This Key has to match Action Device Key within desired device(s).

See [GenTL specification 1.5 chapter 7](#) for more details.

5.5.3 ActionGroupKey

Name	Action Group Key
Interface	Integer
Access	Read/Write
Visibility	Expert

The Group Key for the Action Command to be created.

This Key has to match Action Group Key within desired device(s).

See [GenTL specification 1.5 chapter 7](#) for more details.

5.5.4 ActionGroupMask

Name	Action Group Mask
Interface	Integer
Access	Read/Write
Visibility	Expert

The Group Mask Key for the Action Command to be created.

This Key has to match Action Group Mask Key within desired device(s).

See [GenTL specification 1.5 chapter 7](#) for more details.


5.5.5 GevActionDestinationIPAddress

Name	Gev Action Destination IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert

Specifies destination the IP address for the Action Command.

See [GenTL specification 1.5 chapter 7](#) for more details.

6 VimbaGigETL Device Features



This chapter includes:

6.1	DeviceInformation	41
6.1.1	DeviceID	41
6.1.2	DeviceVendorName	41
6.1.3	DeviceModelName	42
6.1.4	DeviceType	42
6.1.5	DeviceDisplayName	43
6.2	Gev [Allied Vision]	43
6.2.1	GevDeviceIPAddress	43
6.2.2	GevDeviceSubnetMask	43
6.2.3	GevDeviceMACAddress	44
6.2.4	GevDeviceGateway	44
6.2.5	DeviceEndiannessMechanism	45
6.3	StreamEnumeration	45
6.3.1	StreamCount [Allied Vision]	45
6.3.2	StreamSelector	46
6.3.3	StreamID	46
6.4	GigE [Allied Vision]	47
6.5	GVCP [Allied Vision]	47
6.5.1	GevHeartbeatTimeout	47
6.5.2	GevHeartbeatInterval [Allied Vision]	47
6.5.3	GVCPCmdTimeout [Allied Vision]	48
6.5.4	GVCPCmdRetries [Allied Vision]	48

This chapter lists features that are potentially available in this module. Some features are only available under certain circumstances.

The following categories can be found below the Root category:

- DeviceInformation
 - Gev
- StreamEnumeration
- GigE
 - GVCP

6.1 DeviceInformation

Category that contains all Device Information features of the Device module.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.1.1 DeviceID

Name	Device ID
Interface	IString
Access	Read
Visibility	Beginner

Interface-wide unique identifier of this device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.1.2 DeviceVendorName

Name	Device Vendor Name
Interface	IString
Access	Read
Visibility	Beginner

Name of the device vendor.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.1.3 DeviceModelName

Name	Device Model Name
Interface	IString
Access	Read
Visibility	Beginner

Name of the device model.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.1.4 DeviceType

Name	Device Type
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	GEV

Identifies the transport layer technology of the device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.1.5 DeviceDisplayName

Name	Device Display Name
Interface	QString
Access	Read
Visibility	Beginner

User readable name of the device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.2 Gev [Allied Vision]

6.2.1 GevDeviceIPAddress

Name	Device IP address
Interface	Integer
Access	Read/Write
Visibility	Beginner

Current IP address of the GVCP interface of the remote device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.2.2 GevDeviceSubnetMask

Name	Device Subnet Mask
Interface	Integer
Access	Read/Write
Visibility	Beginner

Current subnet of the GVCP interface of the selected remote device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.2.3 GevDeviceMACAddress

Name	Device MAC Address
Interface	Integer
Access	Read/Write
Visibility	Beginner

48-bit MAC address of the GVCP interface of the selected remote device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.2.4 GevDeviceGateway

Name	Device Gateway
Interface	Integer
Access	Read/Write
Visibility	Beginner

Current gateway of the GVCP interface of the selected remote device.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.2.5 DeviceEndiannessMechanism

Name	Device Endianness Mechanism
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	Legacy

Identifies the endianness mode.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.3 StreamEnumeration

Category that contains all Stream Enumeration features of the Device module.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.3.1 StreamCount [Allied Vision]

Name	Stream Count
Interface	Integer
Access	Read/Write
Visibility	Beginner

Number of available streams.

6.3.2 StreamSelector

Name	Stream Selector
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Selector for the different stream channels.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.3.3 StreamID

Name	Stream ID
Interface	IString
Access	Read
Visibility	Beginner

Device unique ID for the stream.

See [GenTL specification 1.5 chapter 7](#) for more details.

6.4 GigE [Allied Vision]

6.5 GVCP [Allied Vision]

6.5.1 GevHeartbeatTimeout

Name	Heartbeat Timeout
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	..10000

Interval of time (in ms) after which a device rejects control by a host if no heartbeat activity is registered. See [GenTL specification 1.5 chapter 7](#) for more details.

6.5.2 GevHeartbeatInterval [Allied Vision]

Name	Heartbeat Interval
Interface	Integer
Access	Read/Write
Visibility	Expert

Interval of time (in ms) after which a heartbeat is sent by the host.

6.5.3 GVCPCmdTimeout [Allied Vision]

Name	Command Timeout
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	100..1000


Timeout waiting for an answer from the device.

6.5.4 GVCPCmdRetries [Allied Vision]

Name	Command Retries
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	1..9

Number of time a particular command to the device will be resent when no answer is being received.

7 VimbaGigETL Stream Features



This chapter includes:

7.1	StreamInformation	50
7.2	BufferHandlingControl	51
7.3	Stream [Allied Vision]	52
7.4	Multicast [Allied Vision]	52
7.5	Info [Allied Vision]	53
7.6	Settings [Allied Vision]	54
7.7	Statistics [Allied Vision]	58

This chapter lists features that are potentially available in this module. Some features are only available under certain circumstances.

The following categories can be found below the Root category:

- StreamInformation
- BufferHandlingControl
- Stream
 - Multicast
 - Info
 - Settings
 - Statistics

7.1 StreamInformation

Category that contains all Stream Information features of the Data Stream module.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.1.1 StreamID

Name	Stream ID
Interface	IString
Access	Read
Visibility	Beginner

Device unique identifier for this data stream.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.1.2 StreamType

Name	Stream Type
Interface	IEnumeration
Access	Read
Visibility	Beginner
Values	GEV

Identifies the transport layer technology of the stream.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.2 BufferHandlingControl

Contains all features of the Data Stream module that control the used buffers.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.2.1 StreamAnnouncedBufferCount

Name	Stream Announced Buffer Count
Interface	Integer
Access	Read/Write
Visibility	Beginner

Number of announced (known) buffers on this stream.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.2.2 StreamBufferHandlingMode

Name	Stream Buffer Handling Mode
Interface	IEnumeration
Access	Read/Write
Visibility	Beginner
Values	Default

Available buffer handling modes of this stream.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.2.3 StreamAnnounceBufferMinimum

Name	Stream Announce Buffer Minimum
Interface	Integer
Access	Read
Visibility	Beginner

Minimal number of buffers to announce to enable selected acquisition mode.

See [GenTL specification 1.5 chapter 7](#) for more details.

7.3 Stream [Allied Vision]

7.4 Multicast [Allied Vision]

Category for features dealing with multicast.

7.4.1 MulticastEnable [Allied Vision]

Name	Multicast Enable
Interface	IBoolean
Access	Read/Write
Visibility	Expert

Enable multicast streaming.

7.4.2 MulticastIPAddress [Allied Vision]

Name	Multicast IP Address
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	224..4294967279

IP address of the target multicasting group.

7.5 Info [Allied Vision]

Category for Stream information features.

7.5.1 GVSPFilterVersion [Allied Vision]

Name	GVSP Filter Version
Interface	IString
Access	Read
Visibility	Expert

Version of the GVSP Filter driver.

7.6 Settings [Allied Vision]

7.6.1 GVSPTimeout [Allied Vision]

Name	GVSP Timeout
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	10..5000

Timeout (in ms) used for stream packets.

7.6.2 GVSPDriver [Allied Vision]

Name	GVSP Driver Selector
Interface	IEnumeration
Access	Read/Write
Visibility	Expert
Values	Socket, Filter

Streaming driver to be used.

7.6.3 GVSPHostReceiveBuffers [Allied Vision]

Name	GVSP Host Receive Buffers
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	256..2048

Number of receive buffers to be used by the OS' socket (hint).

7.6.4 GVSPBurstSize [Allied Vision]

Name	GVSP Burst Size
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	1..256

Maximum number of GVSP packets to be processed in a burst.

7.6.5 GVSPMaxLookBack [Allied Vision]

Name	GVSP Max Look Back
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	1..1024

Size of the missing GVSP packets detection windows.

7.6.6 GVSPMaxRequests [Allied Vision]

Name	GVSP Max Requests
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..512

Maximum number of requests (to the device) for a missing GVSP packet.

7.6.7 GVSPMissingSize [Allied Vision]

Name	GVSP Missing Size
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..1024

Maximum number of simultaneous missing GVSP packets before dropping the frame (0 = OFF).

7.6.8 GVSP TiltingSize [Allied Vision]

Name	GVSP Tilting Size
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..1024

Maximum number GVSP packets received from a following frame before dropping the frame (0 = OFF).

7.6.9 GVSPMaxWaitSize [Allied Vision]

Name	GVSP Max Wait Size
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	8..1024

Maximum number of received GVSP packets following a resend request to wait before requesting again.

7.6.10 GVSPPacketSize [Allied Vision]

Name	GVSP Packet Size
Interface	Integer
Access	Read/Write
Visibility	Expert

GVSP Packet size (in bytes).

7.6.11 GVSPAdjustPacketSize [Allied Vision]

Name	GVSP Adjust Packet Size
Interface	ICommand
Access	Read/Write
Visibility	Expert

Request the packet size used to be adjusted automatically.

7.7 Statistics [Allied Vision]

Category for Stream statistics features.

7.7.1 StatFrameDelivered [Allied Vision]

Name	Stat Frames Delivered
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Number of error-free frames that have been delivered to the TL consumer.

7.7.2 StatFrameDropped [Allied Vision]

Name	Stat Frames Dropped
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Number of incomplete (due to missing packets) frames received by the host (not including shoved frames).

7.7.3 StatFrameUnderrun [Allied Vision]

Name	Stat Frames Underrun
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..

Number of frames missed due to the non-availability of a user supplied buffer (buffer underrun).

7.7.4 StatFrameShoved [Allied Vision]

Name	Stat Frames Shoved
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..

Number of frames dropped because the transfer of a following frame was completed earlier.

7.7.5 StatFrameRescued [Allied Vision]

Name	Stat Frames Rescued
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..

Number of frames that initially had missing packets but were successfully completed after packet resend.

7.7.6 StatPacketReceived [Allied Vision]

Name	Stat Packets Received
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Number of error-free packets received and processed by the host (including successfully resent packets).

7.7.7 StatPacketMissed [Allied Vision]

Name	Stat Packets Missed
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Number of packets expected and not received by the host (not including successfully resent packets).

7.7.8 StatPacketErrors [Allied Vision]

Name	Stat Packets Errors
Interface	Integer
Access	Read/Write
Visibility	Expert
Values	0..

Number of received packets that are erroneous (usually signal an hardware issue on the device).

7.7.9 StatPacketRequested [Allied Vision]

Name	Stat Packets Requested
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Number of missing packets that were requested for resend from the device.

7.7.10 StatPacketResent [Allied Vision]

Name	Stat Packets Resent
Interface	Integer
Access	Read/Write
Visibility	Beginner
Values	0..

Number of missing packets that were resent by the device after having been requested.

7.7.11 StatFrameRate [Allied Vision]

Name	Stat Frame Rate
Interface	IFloat
Access	Read/Write
Visibility	Beginner
Values	0.0..

Rate (frames/s) at which the device is sending frames to the host (derived from the frame timestamps).

7.7.12 StatLocalRate [Allied Vision]

Name	Stat Local Rate
Interface	IFloat
Access	Read/Write
Visibility	Expert
Values	0.0..


Rate (frames/s) at which (complete and incomplete) frames have been received by the host (derived from the host clock).

7.7.13 StatTimeElapsed [Allied Vision]

Name	Stat Time Elapsed
Interface	IFloat
Access	Read/Write
Visibility	Expert
Values	0.0..

Elapsed time (in s) since the streaming was started.

8 Vimba functional extensions to GenTL



This chapter includes:

8.1	Custom Transport Layer events	65
8.1.1	Additions to EVENT_TYPE_LIST	65
8.1.2	Additions to EVENT_DATA_INFO_CMD_LIST	65
8.1.3	Additional enumeration IFCHANGE_WHAT_LIST	65
8.2	Additional URL information	66
8.2.1	Additions to URL_INFO_CMD_LIST	66

Vimba transport layers provide additional functionality to the general GenTL interface. The provided extensions to Transport Layer Events allow monitoring system changes. Other extensions allow comfortable access to additional URL information.

8.1 Custom Transport Layer events

Custom additions to the following Enumerations are available:

- EVENT_TYPE_LIST (used in GCRegisterEvent and GCUnregisterEvent)
- EVENT_DATA_INFO_CMD_LIST (used in EventGetDataInfo)

Additionally, an enumeration for determining the type of a change is provided: IFCHANGE_WHAT_LIST

These extensions allow the users of Vimba transport layers to get informed about changes to either the interface list or the camera list.

8.1.1 Additions to EVENT_TYPE_LIST

Listing 1: Event types

```
enum EVENT_TYPE_LIST_VIMBA
{
    EVENT_SYSTEM_CHANGE          = 1000, // System detected some change
    EVENT_INTERFACE_CHANGE       = 1001  // Interface detected some change
}
```

8.1.2 Additions to EVENT_DATA_INFO_CMD_LIST

Listing 2: Change Events

```
enum EVENT_DATA_INFO_CMD_LIST_VIMBA
{
    // for event type EVENT_SYSTEM_CHANGE
    EVENT_DATA_SYSTEM_IFCOUNT = 1000, // UINT32    Number of detected interfaces

    // for event type EVENT_INTERFACE_CHANGE
    EVENT_DATA_IFCHANGE_DUID    = 1001, // STRING    Device UID
    EVENT_DATA_IFCHANGE_WHAT    = 1002, // UINT32    Bitfield of what has changed
                                   // (IFCHANGE_WHAT_LIST)
    EVENT_DATA_IFCHANGE_DATA    = 1003  // UINT32    Bitfield of current state of
                                   // the device (IFCHANGE_WHAT_LIST)
};
```

8.1.3 Additional enumeration IFCHANGE_WHAT_LIST

Listing 3: Change Event options

```
enum IFCHANGE_WHAT_LIST
{
    IFCHANGE_WHAT_VISIBILITY    = 1,    // Device visibility has changed
    IFCHANGE_WHAT_REACHABILITY  = 2    // Device reachability has changed
};
```

8.2 Additional URL information

For the following Enumeration, extensions are available:

- URL_INFO_CMD_LIST (used in GCGetPortURLInfo)

The extensions allow the user of the Vimba transport layers to access URL information without having to parse the URL string.

8.2.1 Additions to URL_INFO_CMD_LIST

Listing 4: URL information

```
enum URL_INFO_CMD_LIST_VIMBA
{
    URL_INFO_FILENAME          = 1000,  // STRING    Filename of the port XML file
    URL_INFO_ADDRESS           = 1001,  // UINT64    Start address of the XML file
    URL_INFO_LENGTH            = 1002,  // SIZE_T    XML file length (in bytes)
    URL_INFO_ZIPPED            = 1003,  // BOOL      Is the XML file zipped
};
```