

Technical Test Result

DESCRIPTION	STATUS
Attempted Questions	15
Blank Answer	0
Basic Correct	13
Optional Correct	0

1.   **Which search method takes less memory**

- ☒ (A) Depth-First search
- ☐ (B) Breadth-First search ✓
- ☐ (C) Linear Search
- ☐ (D) Optimal Search

2.   **Which algorithm is used for solving temporal probabilistic reasoning?**

- ☐ (A) Hill-climbing search
- ☒ (B) Hidden markov model ✓
- ☐ (C) Depth-first search
- ☐ (D) Breadth-first search

3.   **Where does the Hidden Markov Model is used?**

- ☒ (A) Speech recognition ✓
- ☐ (B) Understanding of real world
- ☐ (C) Both Speech recognition & Understanding of real world
- ☐ (D) None of the mentioned

★
★
4. ☆ Web Crawler is a/an

- ☒ (A) Intelligent goal-based agent ✓
- ☐ (B) Problem-solving agent
- ☐ (C) Simple reflex agent
- ☐ (D) Model based agent

★
★
5. ★ Which data structure is used to give better heuristic estimates?

- ☐ (A) Forwards state-space
- ☐ (B) Backward state-space
- ☒ (C) Planning graph algorithm ✓
- ☐ (D) None of the mentioned

★
★
6. ☆ How many types of recognition are there in artificial intelligence

- ☐ (A) 1
- ☐ (B) 2
- ☒ (C) 3 ✓
- ☐ (D) 4

★
★
7. ☆ Which object recognition process is an error-prone process

- ☒ (A) Bottom-up segmentation ✓
- ☐ (B) Top-down segmentation
- ☐ (C) Both Bottom-up & Top-down segmentation
- ☐ (D) None of the mentioned

★
★
8. ☆ What can't be done in the semantic interpretation?

- ☐ (A) Logical term
- ☐ (B) Complete logical sentence
- ☒ (C) Both Logical term & Complete logical sentence ✓
- ☐ (D) None of the mentioned

★
★
9. ★ Which of the following machine learning algorithm can be used for imputing missing values of both categorical and continuous variables?

- ☒ (A) K-NN ✓

- ☐ (B) Linear Regression
- ☐ (C) Logistic Regression
- ☐ (D)

10. ★ In k-NN it is very likely to overfit due to the curse of dimensionality. Which of the following option would you consider to handle such problem?

- ☐ (A) Dimensionality
- ☐ (B) Feature selection
- ☒ (C) A and B ✓
- ☐ (D) None of these

11. ★ Which of the following algorithm doesn't use learning Rate as one of its hyperparameter?

- ☒ (A) Random Forest ✓
- ☐ (B) Gradient Boosting
- ☐ (C) AdaBoost
- ☐ (D)

12. ★ When you use the boosting algorithm you always consider the weak learners. Which of the following is the main reason for having weak learners?

- ☒ (A) To prevent overfitting ✓
- ☐ (B) To prevent under fitting
- ☐ (C) To prevent overfitting and underfitting
- ☐ (D) None of these

13. ★ A perceptron is:

- ☒ (A) a single layer feed-forward neural network with pre-processing ✓
- ☐ (B) an auto-associative neural network
- ☐ (C) a double layer auto-associative neural network
- ☐ (D) a neural network that contains feedback

14. ★ A 4-input neuron has weights 1, 2, 3 and 4. The transfer function is linear with the constant of proportionality being equal to 2. The inputs are 4, 10, 5 and 20 respectively. The output will be:

- ☒ (A) 238 ✓
- ☐ (B) 76
- ☐ (C) 119
- ☐ (D) 123

15. ★★ ☆ One of the main challenge/s of NLP is _

- ☐ (A) Handling Ambiguity of Sentences ✓
- ☐ (B) Handling Tokenization
- ☐ (C) Handling POS-Tagging
- ☒ (D) All of the mentioned