

Installation Guide

Technical installation, configuration, verification, startup, backup, and recovery instructions.

ProcuraFlow Professional Edition | Issued 11 August 2026

1. Prerequisites

1. Windows 10/11 or Windows Server with PowerShell.
2. Node.js 18 or later and npm.
3. Write access to the ProcuraFlow application directory.
4. Approved company identity, hostname, JWT secret, and protected backup location for production.

2. Application Layout

Install the application in an approved directory named ProcuraFlow, for example C:\ProcuraFlow. The primary database is backend\procuraflo.db. Uploaded evidence is stored in backend\uploads. Frontend and backend source code are kept in their respective src directories.

3. Install the Backend

1. Open PowerShell and change directory to ProcuraFlow\backend.
2. Copy .env.example to .env.
3. Run npm install.
4. Run npm run build.
5. Run npm start for the compiled service, or npm run dev for development.

4. Install the Frontend

1. Open a second PowerShell window and change directory to ProcuraFlow\frontend.
2. Run npm install.
3. Run npm run build to verify the release.
4. Run npm run dev for local operation.
5. Open http://localhost:5173 in a supported browser.

5. Production Configuration

1. Replace JWT_SECRET with a long, random, confidential value.
2. Set DB_PATH to ./procuraflo.db or an approved absolute path.
3. Set LICENSED_COMPANY_NAME and LICENSED_HOSTNAMES for the purchased installation.
4. Set CORS_ORIGINS to the exact permitted frontend origins.
5. Use HTTPS and restrict operating-system access to the database, uploads, environment file, and backups.

6. Release Verification

1. Open <http://localhost:4000/api/health> and confirm ProcuraFlow Professional Edition.
2. Run `npm run audit:db` in backend to verify SQLite integrity, foreign keys, stock, FIFO, totals, and master-code controls.
3. Run `npm run build` in both backend and frontend; resolve errors before go-live.
4. Sign in with a named employee account and confirm role-specific navigation and warehouse scope.

7. Backup and Recovery

1. Use System Settings > Download Database Backup for controlled operational backups.
2. Keep backups outside the application directory with restricted access and retention controls.
3. Use restore staging to validate a candidate SQLite file before replacement.
4. After restoration, run the database audit and verify balances and source documents.
5. For a filesystem copy, stop the backend cleanly before copying `procurafLOW.db`.

8. Startup and Shutdown

1. Start the backend first, then the frontend.
2. Confirm ports 4000 and 5173 are listening and complete the health check.
3. Stop frontend and backend cleanly so SQLite checkpoints current data.
4. Never delete `.db-wal` or `.db-shm` while the backend is running.