SoK: Reusing Defense Evidence in LLM and Agent Side Channels

***Abstract*—This SoK examines mitigation results reported in empirically attack-evaluated LLM and agent studies. The C1–C5 source frame contains 31 privacy or attribution mitigation records from 19 families; it does not census the full defense literature. We organize evidence by the receiving view, executed intervention and evaluation condition. Functional quality is required when an intervention can change generation, computation or component quality; lossless framing and exact logical preservation instead support a narrower function claim. Under this rule, three of eight applicable families bind a quality measurement, increasing to four when partial evidence is accepted; eleven families are exempt from that quality query. Four agent-associated families provide no linked same-condition end-to-end task score, but their trace, transport and generation interventions require different outcome claims. Configuration-level examples show how to retain measured quality/cost packages and preservation witnesses while separating costs from another primitive. A decision procedure makes these retained claims and remaining deployment measurements explicit; controlled examples also demonstrate attacker-dependent recovery after an apparent reduction.**

1. Introduction

Encryption conceals message content, yet LLM serving and agents expose packet sizes, cache timing, destinations and tool sequences [1], [2], [3], [4], [5], [6]. Padding, cache isolation and decoy actions address different parts of this problem. Choosing among them requires both a protection result and evidence of what the protected system still does, at what cost.

What the selected studies support. Our 19-family inventory concerns mitigation results in studies with empirical attack-inference evaluations. Output-preserving transport should retain its narrow functional claim, while a changed prompt, approximate computation or added execution needs outcome-specific evidence. After resolving that applicability, functional quality is explicitly bound in 3/8 families, or 4/8 with partial evidence; eleven families are exempt from that quality query. For agent-associated interventions, a task score must also match the executed condition. The practical question is: *which evidence supports the chosen intervention, and what measurement does its proposed deployment require?*

One example, three decisions. Consider a serving operator choosing a cache-reuse defense. Early Bird evaluates a prefix-recovery oracle and separately measures semantic-cache deidentification overhead [3, V-A–B]. CachePrune evaluates direct and contextual recovery and links its default configuration to generation quality and serving cost [7, 5.1–5.6]. Prefix and direct-recovery results inform a shortlist for a shared token-recovery threat. Early Bird's semantic-cache overhead prices a different mechanism, whereas CachePrune's shared package informs feasibility at its tested configuration. A changed workload then identifies the next workload and cost measurements. This example connects the reporting pattern to a concrete selection decision.

The 82-family map supplies context. Within the attack-evaluation frame, the privacy and attribution synthesis covers 31 records from 19 families; two evasion records and six contextual records retain comparison boundaries. We classify mitigations by mechanism and generation layer, and changes by *observed signal*, *executed intervention* and *evaluation setting*. A cover action can change the environment, and component output quality can differ from task success.

Contributions.

- **A source-framed mitigation synthesis.** A mechanism-by-layer map locates evaluated interventions and unmapped privacy/attribution families. The inspected-source inventory separates quality-changing interventions from preservation witnesses and links inference, adaptation and cost, with status and denominator sensitivities (§§4–5).
- **Configuration-level comparison and positive reuse.** The record atlas separates costs measured for another mechanism and retains outcomes measured together, including the CachePrune package and SparLeak's intensity-specific inference/quality pairs. Exact record identities make each combination reconstructable in this PDF (§5).
- **Deployment measurement plans.** The holdout synthesis separates attack generalization from tested defense transfer. A reusable reporting card and filled examples translate a changed signal, intervention or setting into retained evidence and a specific next measurement (§§6–8.1).

The synthesis builds on website-fingerprinting and adaptive-attack evaluation practice [8], [9], [10], [11]. It connects that practice to the measured objects in LLM/agent systems, where serving primitives, tool state and planner utility coexist. Worked applications illustrate the resulting decisions. A matched attacker comparison makes one boundary concrete: a reduction against an unadapted classifier can disappear after fitting on defended data.

TABLE 1. RESEARCH QUESTIONS, SOURCE-BASED FINDINGS AND DEPLOYMENT CONSEQUENCES.

Question	Synthesis finding	Concrete use / evidential basis
RQ1: landscape	Indexed attack-evaluation sources link mitigation records to 10/22 pure service-layer families, 1/8 pure hardware and 2/13 attribution families.	Target underrepresented settings within the empirical core map; preserve its C1–C5 eligibility.
RQ2: comparability	Five of eight families with explicit inference and cost place them in different records.	Keep Early Bird prefix recovery on the shortlist while obtaining a cost for that primitive.
RQ3: joint evidence	Quality is measured in 3/8 applicable families, or 4/8 with partial evidence; ten have narrow function exemptions. Four agent-associated families have no linked same-condition task score.	Retain lossless-content evidence; measure changed function and executed tasks; preserve the CachePrune package.
RQ4: transfer	Three model and two topology holdouts concern attack generalization.	Reuse the tested attacker coverage; separately establish source-to-target defense-calibration outcomes.

Reading the findings. Counts describe bindings located in the inspected sources, under the stated applicability rules. An unreported binding is an open measurement for the proposed reuse; it does not establish that the source authors never performed the experiment.

2. Scope and Systematization Method

2.1. Research questions, eligibility and threat polarity

We organize the systematization around four questions. **RQ1 (landscape):** which hidden targets, threat polarities and auxiliary observables appear across LLM and agent systems, and where is each signal generated versus observed? **RQ2 (comparability):** when do two reported defense results measure the same target, receiver, intervention and cost object? **RQ3 (joint evidence):** which results bind protection, utility and cost at one evaluated operating point? **RQ4 (transfer):** which evidence distinguishes attack generalization, defended-condition evaluation and defense transfer across tasks, models, topologies and hardware? RQ1 supplies the field context; RQ2–RQ4 correspond to the three contributions.

Our mitigation statistics describe results in studies selected through an empirical attack-evaluation frame, rather than all defense research. Core inclusion requires five conjunctive criteria: (C1) LLM or agent execution, (C2) a hidden target property, (C3) an execution-dependent auxiliary observable rather than ordinary output semantics alone, (C4) specified observer permissions, and (C5) an empirical inference evaluation. Consequently, defense-oriented work without a qualifying C1–C5 result does not enter this denominator. The frame includes both attack-oriented and defense-oriented studies; it does not classify every included paper as an attack-first paper. Mixed-feature papers qualify only if they isolate an auxiliary-only C3 component; thus coding fingerprints, WildAuth, ZeroPrint, endpoint-content fingerprints and StepFinder remain adjacent boundary comparators [12], [13], [14], [15], [16]. Table 2 states the observable eligibility rules. For C3, the extraction must name an execution mechanism and an evaluated observable separate from ordinary linguistic meaning. A filter qualifies when its accept/reject behavior or differential response is the measured oracle for a hidden property; merely analyzing a reply's wording or style does not. If a mixed paper does not isolate that mechanism, its membership stays adjacent. This operational distinction concerns the measured signal, not whether the output is text.

TABLE 2. OBSERVABLE-BASED ELIGIBILITY. A HIDDEN TARGET ALONE DOES NOT MAKE A SEMANTIC ATTACK A SIDE CHANNEL.

Observed input	Decision and required distinction
Length, timing, cache response	Core when measured execution dependence supports hidden-target inference.
Own-site actions	Core attribution with site permission; no automatic access to other sites or private tool logs.
Reply states the secret	Direct disclosure; adjacent, not auxiliary-channel evidence.
Reply style/content identifies a user	Adjacent unless a separately evaluated auxiliary mechanism is established. WildAuth stays a mixed-view comparator.
Output-filter membership oracle	Core only for an isolated accept/reject or differential-response oracle tied to filter execution; semantic content alone remains adjacent.
Privileged loop/fault logs	Separate diagnostic component when C1–C5 hold; does not increase confidentiality evidence.

We use four narrative groupings of objectives and observer roles, not mutually exclusive classes. An unauthorized identity inference can be both attribution and a confidentiality concern. Each record separately specifies the inference target, observer, authorization relation and protected interest: **Type I** concerns confidentiality/privacy; **Type II** concerns model, harness or identity attribution; **Type III** concerns evasion of a platform's human–agent detector; **Type IV** concerns authorized operator diagnostics. Types can overlap. WRA protects research intent (I); UI Traces attributes agents (II); AHB evades a defensive detector (III); ClawGuard diagnoses loops (IV) [6], [5], [17], [18]. These roles are mapped per core family, alongside generating and receiving layers, in Table 7.




Figure 1. Receiving views and execution boundaries. A content-aware frontend can emit a new trace; admitted cover actions can change state. Evidence must describe the object a deployment will expose or execute.

2.2. Corpus construction and reconciliation

Forty seeds, venue-targeted proceedings screening and one-hop citation snowballing produced an initial map of 60 families (43 core, 17 adjacent). A supplementary database and bulk keyword search returned 615 occurrences and 565 unique records; auditing its 204 exclusions rerouted four records, and the search added 15 core and seven adjacent families. The final collection has 58 core and 24 adjacent families. The completed search frames, closed on October 21, 2026, combine Semantic Scholar and native arXiv queries with venue-targeted screening of S&P, USENIX Security, NDSS, CCS and PMLR. C1–C5 screening and version deduplication operate on records before family reconciliation; the supplement retains queries, dispositions and excluded incomplete search frames. Architecture and hardware venues were not comprehensively screened; the finite frame is not an exhaustive census.

2.3. Source-bound result records

Each record links its target, observation boundary and operating point to a source version and section/table/figure locator. The authors report reviewing the classification of all 82 families using titles, abstracts and experimental sections, and checking all 39 result records and 180 family-audit cells against source locators. The subsequent 351-cell record audit and 133 within-question pair decisions retain author-assigned reasons; executable checks establish their accounting consistency. Candidate fields produced with AI assistance were subject to this author review.

Appendices B and F contain the record index, comparison summary and query memberships in this PDF. The ledger also separates cited publication status, inspected version, measurement mode and remaining binding uncertainty. Published status increases traceability of venue review but does not establish the correctness of a result; a preprint's observations remain provisional at their inspected scope.

SoK Takeaway 1 (Map evidence to the receiving deployment). A family-level label does not identify which signal, observer permission or protected objective a result supports. The complete core map separates signal origin from receiving access; the result ledger then binds each comparison to a source version and operating point.

TABLE 3. A SINGLE RESULT RECORD. ONLY FIELDS RELEVANT TO THE REQUESTED COMPARISON MUST ALIGN; UNAVAILABLE REQUIRED FIELDS REMAIN UNRESOLVED.

Record field	Required meaning
Source	Family/result ID, version, source locator, reading scope and hash.
Target	Hidden property, inference goal and protection relation: confidentiality, attribution, human/agent distinction or authorized diagnosis.
Receiver	Actual permission and released representation, including session/document linkage and any auxiliary inputs.
Intervention	Where protection ends; whether edits affect stored traces, transmission or executed actions.
Attacker	Fit/calibration condition, test population, training access and adaptation budget.
Workload	Task, system, topology/hardware and grouping/holdout.
Outcomes	Inference metric / denominator; objective or proxy utility; applicable cost object; uncertainty and field states.

3. Result Records and Comparability Rules

The atomic unit of our systematization is one *evaluated result record*, rather than a whole paper or a single headline score. A result record binds a source version and locator to seven structured fields: Source, Target (and threat polarity Types I–IV), Receiver projection, Intervention boundary, Attacker training/calibration (D_0: clean-condition fit; D_2: protected-condition fit), Workload/holdout, and Outcomes (inference metric, task/component utility, and cost object; Table 3). A record is a comparison unit with a source-indexed parameter grid, not an independent trial. We split when a change of primitive, execution mode, target/receiver contract or separately measured cost object would alter what a result can support. We retain models, datasets, parameter values and repetitions as coordinates within that unit; numerical joins must preserve those coordinates. Source versions are reconciled within a family before extraction.

Indexing schema and comparison contracts. The index names the hidden property, measured channel, observer permissions, intervention and evaluation provenance. Generating layers span hardware (P1), serving (P2), transport (P3), application/API (P4), orchestration (P5), tools/MCP (P6), environment (P7) and multi-agent communication (P8). We

TABLE 4. COMPARISON RULES. A KNOWN MISMATCH AND A MISSING BINDING HAVE DIFFERENT CONSEQUENCES.

Requirement	Condition and resulting license
Descriptive comparison	Identify the shared target and receiving view. Describe differing populations or metrics separately; numerical cost comparisons additionally require aligned cost objects. Token payload and wire bytes cannot be ranked as the same cost.
Paired effect	Compare the same defended test units and outcome. A known test-unit mismatch makes that subtraction incompatible; an unverified fit binding leaves the effect unresolved.
Deployment transfer	Establish a bridge for the changed receiver, intervention, workload, topology or hardware. A demonstrated violation blocks the proposed transfer; an untested bridge leaves it unresolved. Permit only the range and endpoints actually covered.

TABLE 5. FILLED RECORD AND ITS LICENSED JUDGMENT. VALUES ARE SOURCE-REPORTED; NO CROSS-MODE EFFECT IS COMPUTED.

Join key / field	Entry
Family / result	Dangol workflow / `DANGOL-livebinding`.
Version / locator	arXiv:2606.07150v3, §9.7, live-protocol paragraph after Table 5 [19].
Target / view	Workflow classification from live Oblivious HTTP (OHTTP)/Agent-to-Agent (A2A) traffic; not GUI-state observation.
Intervention	Live fixed-rate cover with fresh per-session identifiers, distinct from transformed stored captures.
Workload / testbed	Workflow classes with client, relay, gateway and agent co-located on one loopback host.
Outcome / cost	Accuracy 0.30; about $13\times$ bytes and $11\times$ latency in that condition.
Unresolved fields	Objective terminal task utility U; precise paired live-refit comparison ?.
Licensed judgment	These costs describe this live protocol condition. They neither price dummy GUI actions nor prove task preservation. A matched objective endpoint is needed for the latter.

apply three claim-specific comparison contracts (Table 4). For the requested claim, a comparison is *compatible* when its required fields align, *incompatible* when a required object conflicts, and *unresolved* when a required binding is unreported (U), unavailable (A) or unverified (?). In the audit, B means explicitly bound, P partial and – inapplicable. A common inference topic permits a scoped description while costs or populations remain separate; comparing costs requires an aligned cost object. Table 5 illustrates a complete record-to-judgment lineage.

Record boundaries and coverage. The 39-record ledger retains 31 privacy/attribution mitigation records from 19 families, two Type III evasion records and six contextual controls. The mitigation synthesis within this C1–C5 source frame uses the first 31; the evasion records illustrate a different protected objective. A defense discussion without a scoped evaluated result stays in the map. Appendix B indexes the source scopes and split decisions. Three examples fix the granularity:

TABLE 6. TAXONOMY OF CHANGES RELEVANT TO EVIDENCE REUSE.

Changed object	Typical transition	Evidence to carry or renew
Observed signal	Receiver, released representation, hidden target	Keep the target and permissions; measure the actual receiving trace.
Executed intervention	Prefix/semantic cache; transformed trace/live scheduler; read/write cover	Keep mechanism and state boundary; bind function and cost to the executed configuration.
Evaluation setting	Attacker fit, workload, model, hardware or network	Keep training/test provenance; establish the proposed holdout and relevant baseline.

- **Split:** Early Bird's K-prefix recovery oracle and semantic-cache processing benchmark change both primitive and measured object; their numbers cannot form one protection–cost point.
- **Retain coordinates:** SparLeak's model-by-replacement-intensity ASR/ROUGE grid remains one mitigation record. Each intensity's inference/quality pair must be retained together; selecting the lowest ASR and highest ROUGE from different rows is disallowed.
- **Split outcome, share package:** CachePrune's direct recovery and contextual guessing require two target contracts. They reference one shared default quality/cost package, counted once when joining configurations.

Question cohorts precede compatibility judgments. Records enter one declared comparison question by the intervention and receiving object, not by score or verdict: delivered traffic, service-cache reuse, local memory/resource behavior, behavioral humanization, generator fingerprinting or fixed instructions. Three contextual singletons concern access gates, contention and filter-created views. Appendix F lists all 39 assignments. When a mechanism spans several questions, retain the primary extracted question and document the alternative; a new cross-cohort question requires a new inventory. A shared cohort admits a pair for inspection; it does not make different targets or costs compatible. The archived pair index records a scoped match, a different-object witness or an unresolved binding for its stated comparison. A different-object label prohibits substituting that witness object, not every possible comparison between the papers. It is not an assessment of all three contracts. Appendix F varies record granularity and retains the original judgments. The reporting-pattern synthesis in Section 5 uses item availability and within-record bindings directly.

A taxonomy of reuse changes. The categories below describe what changes between a source result and a deployment question; several can apply together. The mechanism-by-layer matrix in Section 4 adds the defense design space. The nine audit items identify the evidence needed to evaluate a selected mechanism at its receiver and execution boundary.

From contracts to an audit. Section 5 operationalizes these contracts as nine reuse items with a shared evidence-status alphabet (Table 10) and applies them to every mitigation family (Table 12).

4. Corpus Map Across 82 Study Families

4.1. Generating layers, receiving projections and threat polarities

Table 7 maps all 58 core families by signal-generating layers, receiving projections and threat polarity. Multi-layer families retain every reported layer in their generating and observing sets.

Cross-layer synthesis. A remote network observer, a same-site script and a privileged diagnostic hook expose different views even when they share an attribution target. WRA's read-only privacy decoys, AHB's stateful evasion and SplitDecoy's exposed return path illustrate why receiving permissions and protected objectives must accompany the generating layer [6], [17], [36].

Layer incidence highlights where the systematization's comparison problem arises. In the 58-family map, signal-generation labels cluster at P2 serving/runtime (32 families) and P5 orchestration (19); receiving views cluster at P4 application/API (18), P1 hardware (16), and P3 transport (14). Generation at P3/P4 is rare (one family each), despite frequent observation at those layers. This source/receiver asymmetry makes the transfer question concrete: protection at a frequent source layer cannot be presumed to cover a different receiving projection. The map records layer sets, so it does not assign a causal edge to each source/receiver pair.

Purpose labels further show why a single "agent side channel" category is insufficient: Type I appears 41 times, Type II 13, Type III 2, and Type IV 5. The 32 map-only families extend coverage beyond mitigation comparisons: 15 list serving origins, 11 hardware and 11 orchestration; 19 concern confidentiality, nine attribution, one evasion and all five authorized-diagnostic families. Mapping these families locates privacy targets, operator capabilities and candidate validation environments even when no scoped mitigation record enters the ledger. Counts are overlapping family-label incidences; the audit then applies its reuse rules to the 39 scoped result records.

Linked mitigation evidence in the attack-evaluation map. Table 8 organizes the 19 privacy/attribution mitigation families by mechanism and generating layer. Within this empirically attack-evaluated 52-family Type I/II union, mitigation records are linked to 1/8 pure hardware families, 4/7 hardware/service, 10/22 service-only, 3/13 workflow and 1/2 other cross-layer families. Two of 13 attribution families have such a record. Appendix G lists the other 33 families. These are gaps in the inspected C1–C5 frame; defense-only work outside that frame is not counted. The receiving view and remaining channel determine which mechanism and additional measurement are relevant.

4.2. Relationship to prior systematizations

Prior surveys map compound-system threats, TEE boundaries and privacy contracts [68], [69], [70]. WF already supplies feature leakage analysis, cost trade-offs and environment-shift tests [71], [8], [72], [73]. Mathews et al. re-evaluate nine defenses with stronger attacks and an on-network DynaFlow implementation [9]. Adaptive attacks and online-cost evaluation are established foundations.

Adaptive evaluation and benchmarking. Tramèr et al. show why defense-specific adaptive attacks require more than applying an unchanged attack; Carlini et al. set out robustness-evaluation practices; RobustBench standardizes the evaluated threat and test interface [10], [11], [74]. These works already motivate protected-data evaluation and reproducible benchmarks. Our R4/R5 items instantiate that discipline. The LLM/agent-specific question is whether a refit, cost or functional result belongs to the same prefix policy, content-aware emitter or state-changing action under discussion.

What this synthesis adds. Our unit is a *scoped result*, so execution mode, protected state and cost remain attached when one paper reports several mechanisms. The 39-record atlas documents these distinct measurement objects; the 82-family holdout matrix separates evidence for each transfer axis. This connects evidence that earlier taxonomies organize by attack or mechanism: one family can contain several execution modes, a receiving projection can cross system layers, and utility/cost can belong to a different operating point from inference. The synthesis preserves these distinctions when translating a reported result into a deployment decision.

Formal guarantees and runtime measurements. The mitigation inventory covers evaluated runtime results, not the complete literature on privacy proofs. Differential privacy constrains releases for a specified adjacency relation and privacy budget [75]; information-flow measures distinguish mutual information from single-guess vulnerability [76]. Constant-time verification and oblivious memory protect stated traces under their own leakage models [77], [78]. These guarantees can supply stronger source-scoped evidence than a low empirical attack score. Their scope still matters: a guarantee for model weights need not include a serving trace, and hiding addresses need not hide access counts. TDXRay and OTRO connect these foundations to the indexed LLM components. For reuse, retain the stated adjacency, leakage model and execution assumptions. Attack-refitting items are inapplicable to a purely formal proof; absence of a classifier experiment does not count against that guarantee.

TABLE 7. COMPLETE MAP OF THE 58 CORE STUDY FAMILIES. EACH FAMILY APPEARS ONCE; LAYER AND TYPE LABELS MAY BE MULTIPLE AND DO NOT IMPLY ONE-TO-ONE CAUSAL PATHS. THE BLOCKS GROUP SOURCE LAYERS, NOT EVIDENTIAL QUALITY.

Core family	$G \to O$	Type
hardware generation, P1 (8)		
Edge EM leakage [20]	$1 \to 1$	I
Energon [21]	$1 \to 1$	II
MoEcho [22]	$1 \to 1$	I
I Know What You Said [23]	$1 \to 1$	I
Behind Bars [24]	$1 \to 1$	I
PAGE404 [25]	$1 \to 1$	I
Spill the Beans [26]	$1 \to 1$	I
ArchSnoop [27]	$1 \to 1$	II
hardware and service, P1/P2 (8)		
SparLeak [28]	$1,2 \to 1$	I
Shape and Substance [29]	$1,2 \to 1$	I
TDXRay [30]	$1,2 \to 1$	I
SparSEEty [31]	$1,2 \to 1$	I
OTRO [32]	$1,2 \to 1$	I
Detokenization Leaks [33]	$1,2 \to 1$	I
LLM-WFIN [34]	$1,2 \to 1,3$	I
LLM-serving RCA [35]	$1,2 \to 2$	IV
service generation, P2 (first 13 of 22)		
SplitDecoy [36]	$2 \to 2$	I
KVGov [37]	$2 \to 2,4$	I
LLMs Have Rhythm [38]	$2 \to 3$	II
Remote timing [39]	$2 \to 3$	I
NetEcho [40]	$2 \to 3$	I
Prompt Echo [41]	$2 \to 3$	I
Speculative decoding [42]	$2 \to 3$	I
Remote keylogging [1]	$2 \to 3$	I
Whisper Leak [43]	$2 \to 3$	I
Cache contention [44]	$2 \to 4$	I
Routing metadata [45]	$2 \to 4$	I
SafeKV [46]	$2 \to 4$	I
ML privacy channels [47]	$2 \to 4$	I
service generation, P2 (remaining 9 of 22)		
Early Bird [3]	$2 \to 4$	I
Prompt-cache audit [48]	$2 \to 4$	I
InputSnatch [49]	$2 \to 4$	I
Leaky Language Models [50]	$2 \to 4$	I
PromptPeek [2]	$2 \to 4$	I
SpliceLeak [51]	$2 \to 4$	I
Time Will Tell [52]	$2 \to 4$	I
CachePrune [7]	$2 \to 4$	I
MoE prompt stealing [53]	$2 \to 4$	I
cross-layer sources (5)		
ClawGuard [18]	$1,5 \to 1$	IV
MIRAGE [54]	$2,5 \to 2$	IV
Cloud traffic benchmark [55]	$2,5,8 \to 3$	I, II
Web-agent unmasking [56]	$3,7 \to 3,7$	II, III
LumiMAS [57]	$4,5 \to 4,6$	IV
orchestration/workflow sources (15)		
AgentPrint [4]	$5 \to 3$	I, II
Cycle detection [58]	$5 \to 4,6$	IV
SIGLEAK [59]	$5,6 \to 4,6$	I
ProcGrep [60]	$5,6 \to 4,6$	II
AgentProv [61]	$5,6 \to 6$	II
Lidar [62]	$5,6 \to 6$	II
Dangol workflow [19]	$5,6,8 \to 3,6,8$	I
Campaign attribution [63]	$5,6,8 \to 6,8$	II
WRA [6]	$5,7 \to 3$	I
PersonaFingerprint [64]	$5,7 \to 3$	I
Whose Agent? [65]	$5,7 \to 7$	II
AgentTell [66]	$5,7 \to 7$	I
UI Traces [5]	$5,7 \to 7$	II
FP-Agent [67]	$5,7 \to 7$	II
AHB [17]	$5,7 \to 7$	III

G denotes signal-generation layers and O the receiving observation layers. Layer indices: 1 hardware; 2 serving/runtime; 3 transport; 4 application/API; 5 orchestration; 6 tools; 7 browser/environment; 8 multi-agent communication. Types: I confidentiality/privacy; II attribution; III human–agent distinction/evasion; IV authorized diagnostics. These are objectives and observer roles, not mutually exclusive security guarantees. Privileged operator receivers and physical receivers are marked by the layer they inspect. Source versions, locators and normalization of prose-only layer descriptions are in the artifact.

5. Mitigation Evidence in Attack-Evaluated Studies

5.1. Source frame and outcome-specific applicability

The C1–C5 attack-evaluation frame links 19 privacy/attribution families to 31 mitigation records, including defense-oriented systems. Two AHB evasion records and six contextual controls remain outside this synthesis. Tables 8 and 9 organize mechanisms and receiving views.

R8 resolves the claimed function before asking for a quality score. Changed prompts, sampling, approximate computation or component coverage need matched quality evidence. Lossless framing, fixed-trace transformations and exact logical preservation instead support a narrow content/function claim. Delay, resources, timeouts and task completion remain separate outcomes for both classes.

5.2. Quality evidence depends on what the intervention changes

Eleven records can affect quality, 18 have scoped preservation witnesses, and two are standalone cost/calibration units. Eight families have a quality-applicable intervention; eleven are exempt. Explicit quality evidence is bound in 3/8, or 4/8 accepting partial evidence. Appendix F supplies every current record code.

CachePrune's approximate reuse binds default-package quality; TDXRay binds vocabulary coverage; SparLeak pairs reconstruction with ROUGE by replacement intensity. NetEcho/Whisper framing, SPEC aggregation and OTRO's token preservation are exempt only for their scoped function [7], [30], [28], [40], [43], [42], [32]. Table 11 keeps inference, cost and fitting populations separate. Source-removal and partial-evidence sensitivities appear in S44.

TABLE 8. PRIVACY AND ATTRIBUTION INTERVENTIONS INDEXED BY MECHANISM AND SIGNAL-GENERATION LAYER. A CELL NAMES FAMILIES WITH A QUALIFYING MITIGATION RECORD IN THE C1–C5 ATTACK-EVALUATED SOURCE FRAME; MULTIPLE MECHANISMS MAY OCCUR IN ONE FAMILY. LETTERS DENOTE THE EVIDENCE PRESENT IN THE INDEXED RECORD, NOT A UNIVERSAL SECURITY GUARANTEE: E = EMPIRICAL PROTECTED-VIEW OR SIMULATED ATTACK OUTCOME; C = COMPONENT COST OR PROPOSAL/ESTIMATE WITHOUT A BOUND ATTACK OUTCOME IN THAT INDEXED RECORD. THE TABLE DOES NOT ADJUDICATE WHETHER EACH SOURCE ALSO PROVES A FORMAL GUARANTEE.

Mechanism	P1 only	P1/P2	P2 only	Workflow	Other cross-layer
Traffic framing / rate	–	–	NetEcho, Whisper, SPEC, Remote, Time [40], [43], [42], [39], [52] (E/C)	Dangol [19] (E)	–
Cache isolation, policy or timing	–	–	Early Bird, SpliceLeak, SafeKV, KV-Gov, CachePrune [3], [51], [46], [37], [7] (E/C)	–	–
Memory access / isolation	Gao [23] (C)	TDXRay, OTRO [30], [32] (C/E)	–	–	–
Model computation or output shaping	–	SparLeak, Shape [28], [29] (E/C)	–	–	–
Decoys, timing edits, or input changes	–	–	–	WRA, UI Traces [6], [5] (E)	Cloud benchmark [55] (E)

Cells concern the mapped generating layer, not necessarily the intervention layer. Residual observations are receiver-specific: grouped or re-emitted traffic can remain after framing; timing can remain after a cache-policy change; access counts can remain after address hiding; and action types/order can remain after timestamp edits. A dash means no matching indexed record in this collection, not that the mechanism cannot apply or that no external defense exists. Type III evasion and Type IV authorized diagnostics are boundary cases, not privacy-protection results.

5.3. Agent-associated interventions need distinct task claims

Four map-selected families require distinct outcomes. UI preserves saved action order; Dangol preserves fixed message bodies; WRA returns only the real output despite concurrent research decoys. These support narrow preservation claims. The cloud prompt/temperature interventions remain generation-quality-applicable (0/1 B, 1/1 accepting P). None of the four binds an explicit same-condition end-to-end task score. WRA is the sole added-call example (0/1 matched task score); its usefulness judgment uses another condition. The 0/4 task inventory therefore spans different interventions [5], [6], [19], [55].

5.4. Family-level inference and cost often describe different records

Eight families have explicit inference and explicit cost somewhere in their evaluations. In five—Early Bird, SpliceLeak, Time Will Tell, KVGov and OTRO—no individual record carries both. The distinctions are concrete: prefix policy versus semantic processing; background-load mitigation versus QCP; a length instruction versus a padding estimate; partial flushing versus HMAC; and padded versus unpadded ORAM. SPEC, Dangol and CachePrune supply the five same-record inference/cost results listed in Table 13. Appendix F lists all eight families' exact supporting records.

The separation remains five of seven after removing CachePrune and four of six after removing final-search additions; accepting P reduces it to three of 12. Mechanism/cost splitting contributes to these counts. The source examples identify which cost prices a proposed mechanism.

Positive combinations for deployment. The joint queries start from the same 31 source records. A quality join includes only an intervention for which quality is applicable; preservation witnesses provide a separately named functional route. Table 13 names every positive result; Appendix F supplies current record codes and query reconstruction. CachePrune's two target outcomes share one quality/cost package, while SparLeak provides intensity-specific inference/quality pairs. These examples support feasibility analysis at their measured configurations. R4/R5 concern protected-data fitting and a matched clean/protected fit. For non-learning attackers, their inapplicability leaves other defense-aware attacks open. Treating those cells as unknown broadens the query (Table 14). Explicit placement excludes SPEC's payload-cost record from the inference–cost query. Removing CachePrune removes the two measured-quality triple records; preservation-backed packages remain a distinct functional route.

5.5. Execution evidence is distributed across measurement modes

Among the 31 privacy/attribution records, 13 are executed collections/prototypes, five trace transformations, five simulations/derived estimates, six component/calibration measurements and two unresolved placements. The 12-record network-receiver subset contains six executed, four transformed and two unresolved records. These modes are a mixture rather than a predominance of network replay. An executed prototype still supplies only its measured local scope.

Comparison permissions as a supporting index. The question groups index 133 pairs, of which 17 retain a scoped object match. For example, Early Bird and CachePrune inform a token-recovery shortlist while keeping their costs separate. Appendix F reconstructs all labels and coarser projections. The reporting findings above derive directly from records and cells.

TABLE 9. SEVEN PRIVACY AND ATTRIBUTION INTERVENTION CATEGORIES ORGANIZED BY RECEIVING VIEW AND SUPPORTED DEPLOYMENT JUDGMENT. TYPE I PROTECTS CONFIDENTIALITY; TYPE II ADDRESSES PROVENANCE OR IDENTITY ATTRIBUTION.

Intervention & polarity	Evaluated view, target and source	Established result and applicable boundary
Padding / batching (Type I: confidentiality)	Network packet lengths and groups; topic inference. NetEcho and Whisper Leak [40], [43].	Collected padding traces retain inference signal; packet-group batching is evaluated by replay. A protected upstream length view does not cover downstream re-emission or residual grouping. Live incremental cost remains U.
Constant-rate / transport cover (Type I: confidentiality)	Network workflow fingerprint; Dangol's OHTTP testbed [19].	The co-located loopback setting yields 0.30 recovery at about $13\times$ bytes and $11\times$ latency. Transformed-capture results are separate; neither result supplies objective agent-task utility.
Concurrent query decoys (Type I: confidentiality)	Destination/domain observer; private prompt and trait inference. WRA [6].	Real/decoy research prompts execute in parallel as read-only queries whose decoy answers are discarded locally; interleaved-domain evaluation reduces one-decoy E_{func} from 0.770 to 0.610. Terminal decoy utility/cost are U.
Cache isolation / keying (Type I: confidentiality)	Co-tenant prefix timing; SafeKV, KVGov and CachePrune [46], [37], [7].	SafeKV reports post-trigger AUC near 0.5 and separate TTFT/throughput comparisons. KVGov's HMAC median 1.3 μs prices key computation, excluding lost reuse. CachePrune jointly binds marked-token protection, QA/summarization utility and serving performance.
Cache timing equalization (Type I: confidentiality)	Co-tenant cache-fusion timing; SpliceDefense [51].	Constant-Time Boundary Fusion (CTBF) suppresses the tested signal over 15 tasks/75 steps. Quantized Chunk Padding (QCP) adds mean 7.5 tokens and $<$ 5ms/$<$ 1% prefill time; this does not price combined deployment.
Timestamp perturbation (Type II: attribution)	Recorded website action metadata; model/agent attribution. UI Traces [5].	Fitting on delayed traces (D_2) recovers substantial attribution performance under offline timestamp edits that retain action types/order. Live execution delay and task outcomes are not measured by the trace transformation.
Oblivious / unshared memory (Type I: confidentiality)	Host or local resource observations; TDXRay, Gao et al. and OTRO [30], [23], [32].	TDXRay measures oblivious-map lookup cost; Gao measures loading/memory cost after disabling zero-copy. OTRO reduces conditional access-count information (3.94 to 0.04 bits) with separate unpadded TTFT (4.59%) and epoch-padding (2.8ms) bounds.

Authorized operator diagnostics (Type IV: ClawGuard, cycle detection, LumiMAS, LLM-serving RCA and MIRAGE) are baseline telemetry rather than privacy attacks or evasion defenses, and are cataloged separately.

SoK Takeaway 2 (Bind function and cost to protection). Resolve the requested function first. Preserve a source-bound content invariant for lossless framing; obtain quality evidence for changed content or behavior, and a task outcome for added execution. Protection, function and cost must retain their evaluated configuration within the selected attack-evaluation sources.

6. Which Evidence Supports Defense Transfer?

6.1. Separate the evaluated object before counting holdouts

RQ4 distinguishes three questions: does an *attack* recognize new inputs or systems; is a *defense condition* evaluated; and does a *fixed attacker or defense calibration* carry from a specified source to a target? Table 15 makes the distinction operational. Repeating a defense on several models can establish condition-specific outcomes without establishing a held-out model or transferring a fitted calibration.

The 82-family matrix in Appendix D is a discovery index for these questions. Its six axes are task/input/user, model, harness/topology, hardware, network/load and time. H marks reported separation, V condition variation/recalibration, X a scoped restriction, and ? unresolved extraction. The 13 task/input H entries include only four families in the 20-family extended mitigation inventory; all three model H entries concern attack/identification generalization outside that inventory. The two topology H entries occur in privacy/attribution mitigation families, but their held-out objects are workflow recognizers. The five model/topology H entries thus locate attack-generalization evidence, with no source-frozen defense-calibration transfer in those entries. The 13 task entries require their individual defended-condition linkage; they are not uniformly attack-only. S34 lists all H objects, while S38 retains their member identities. Varying or locally refitting a defense differs from transporting a source calibration.

6.2. A changed generator and a tested defense are different bindings

LLM-Fin, ArchSnoop and LeakyLMs evaluate recognition of unseen model variants or architectures [79], [27], [50]. This supplies attack-side model generalization. In the traffic benchmark, graph-to-star and star-to-graph classification explicitly move the fitted attacker across topologies; the prompt/temperature countermeasures are separate evaluations [55, V-B–C]. Dangol's leave-composition-out test likewise examines recognition of a novel workflow shape, separately from its protected-capture frontier [19, 9.8–9.12]. The reusable result in both topology entries is the recognizer's tested generalization.

There is nevertheless useful *defense-side variation* evidence. Time Will Tell applies the same fixed-length instruction to two models and reports different residual classification ASRs; this tests a common rule under changed generators [52, VII-B]. Whisper Leak evaluates mitigation conditions across provider-models, while its prompt holdout describes the classifier protocol [43, 3.2,6]. Preserve those per-condition results; a shared rule, a refitted local attack,

TABLE 10. CLAIM-CONDITIONED REUSE RULES. EACH ROW NAMES THE REQUESTED INFERENCE AND THE EVIDENCE NEEDED TO SUPPORT IT.

Item	Reuse query → required binding (**B**)
R1 Target	Same protected interest → explicit hidden property, inference goal and authorization relation.
R2 Receiver	Same observer protection → permissions, released view and auxiliary inputs.
R3 Intervention	Same executed mechanism → placement/mode: stored data, wire emission or actions.
R4 Protected fit	Resistance to protected-data fitting → identified protected training/calibration and testing.
R5 Matched adaptation	Effect of adaptation → clean/protected fits tested on the same defended population.
R6 Workload	Changed workload/system → tasks, configuration and the relevant holdout axis.
R7 Inference	Quantified protection → metric, denominator and scoped defended evaluation condition.
R8 Quality	Changed generation/computation → matched quality; a preservation witness exempts only that scoped quality query.
R9 Cost	Resource-budget feasibility → units, baseline and cost object at that operating point.

B: bound; **P**: partial binding; U: unreported in inspected scope; A: source unavailable; ?: binding unverified; –: inapplicable. For R4/R5, – means that a training-fit contrast is inapplicable; it does not establish that non-learning adaptive attacks are irrelevant or absent. For task timeliness or completion, content preservation alone is insufficient. First determine applicability, then assign evidence status. Family **B** means at least one scoped record satisfies the item, not that every result does.

TABLE 11. REPORTING IN THE C1–C5 ATTACK-EVALUATED SOURCE FRAME. R8 COUNTS ONLY FAMILIES WITH A POTENTIALLY CHANGED GENERATION, COMPUTATION OR COMPONENT OUTCOME; ELEVEN FAMILIES ARE EXEMPT FROM THAT NARROW QUALITY QUERY.

Requested evidence	B / applicable	B+P / applicable
Inference outcome (R7)	15/16	16/16
Cost (R9)	11/18	15/18
Functional quality (R8)	3/8	4/8
Protected fitting (R4)	4/10	8/10
Matched adaptation (R5)	2/10	2/10

a source-trained attack and a source-calibrated defense are four distinct comparisons.

Deployment decision. For the proposed change, name the source, target, held-out unit, quantities held fixed or refitted, and protected outcome. Carry forward only the corresponding binding. An attack-generalization result justifies including that attacker at the target; a defended-condition result supplies its local outcome; a source-to-target defense-calibration result supports only the stated transfer. This prevents both overclaiming portability and discarding useful local evidence. Unresolved hardware/time entries in the discovery matrix identify source follow-up, not absent experiments.

TABLE 12. MITIGATION-SOURCE BINDINGS IN THE ATTACK-EVALUATION FRAME. R8 EXEMPTS SCOPED PRESERVATION; COLUMNS CAN REFER TO DIFFERENT RECORDS.

Family	R1	R2	R3	R4	R5	R6	R7	R8	R9
UI Traces [5]	**B**	**P**	**B**	**B**	**B**	**B**	**B**	–	–
WRA [6]	**B**	**P**	**B**	–	–	**P**	**B**	–	U
NetEcho [40]	**B**	**B**	**B**	**B**	?	**B**	**B**	–	**P**
Early Bird [3]	**B**	**B**	**B**	**B**	?	**B**	**B**	U	**B**
Whisper Leak [43]	**B**	**B**	**B**	**P**	U	**B**	**B**	–	**P**
SpliceLeak [51]	**B**	**B**	**B**	–	–	**B**	**B**	U	**B**
Time Will Tell [52]	**B**	**B**	**B**	**P**	U	**B**	**B**	U	**B**
I Know What You Said [23]	**B**	**B**	**B**	–	–	**P**	–	–	**B**
Speculative decoding [42]	**B**	**B**	**P**	**P**	U	**B**	**B**	–	**B**
Dangol workflow [19]	**B**	**B**	**B**	**B**	**B**	**B**	**B**	–	**B**
Cloud traffic benchmark [55]	**B**	**P**	**B**	U	U	**P**	**B**	**P**	U
Remote timing [39]	**B**	**B**	**P**	–	–	**B**	–	–	**B**
TDXRay [30]	**B**	**B**	**B**	–	–	**B**	–	**B**	**B**
SafeKV [46]	**B**	**B**	**B**	–	–	**B**	**B**	–	**P**
KVGov [37]	**B**	**B**	**B**	–	–	**B**	**B**	–	**B**
CachePrune [7]	**B**	**B**	**B**	–	–	**B**	**B**	**B**	**B**
OTRO [32]	**B**	**B**	**B**	–	–	**B**	**B**	–	**B**
SparLeak [28]	**B**	**B**	**B**	**P**	U	**B**	**B**	**B**	U
Shape and Substance [29]	**B**	**B**	**P**	U	U	**B**	**P**	U	**P**
Bound	19	16	16	4	2	16	15	3	11
Applicable	19	19	19	10	10	19	16	8	18

B: bound; P: partial; U: unreported; ?: unverified; –: inapplicable to the named outcome. For R8, – supports only the stated functional object, not timeliness or task completion. Current record codes: Appendix F; source rationales: S44.

7. Synthesis: From Evidence to Reuse Decisions

The census (§5) covers all 39 records and the holdout matrix (§6) all 82 families. We now select three examples by the *comparison decision* they expose, not by effect size: a changed receiving path, cover with different state effects, and an adaptation/cost mismatch within a named mechanism. Their value is the decision they change: retain an aligned result, separate a wrongly joined package, or require a result at a changed execution boundary.

7.1. Case 1: bind the final target-bearing emitter

NetEcho's upstream packet-size shaping operates on a different projection from the tool-call sequence. Its plaintext-aware frontend then emits a new size trace (grouped token counts or character lengths), reopening a size channel after upstream protection [40]. SplitDecoy is a separate map-only return-path example, outside the 39-record mitigation ledger: the cloud sees nonzero gradient row support on every tested frame across nine seeds [36, Sections 5.1–5.3]. Both change the receiver boundary and therefore require a separately bound inference result.

The data processing inequality applies when the downstream output receives only the protected view Z; a frontend that also receives content X can re-emit a new signal $Y = f(Z, X)$ [80, Theorem 2.8.1]. NetEcho's source-backed re-emission example motivates capturing the final receiver view; the inequality alone is not a quantitative leakage estimate for that system.

TABLE 13. JOINT RESULTS IN THE SAME 31-RECORD SOURCE FRAME AFTER R8 APPLICABILITY IS RESOLVED. QUALITY QUERIES INCLUDE ONLY POTENTIALLY QUALITY-CHANGING RECORDS; A SCOPED PRESERVATION WITNESS SUPPLIES A SEPARATE FUNCTIONAL ROUTE.

Requested evidence	Bound records	Interpretation
Inference + measured quality (3/8)	CACHEPRUNE-context; CACHEPRUNE-selective; SPARLEAK-replacement	CachePrune shares one default package; SparLeak binds quality by intensity.
Inference + cost (5/21)	CACHEPRUNE-context; CACHEPRUNE-selective; DANGOL-capture; DANGOL-livebinding; SPEC-padding-REST	Payload, capture, loopback and serving costs remain distinct.
Adaptation + inference (2/15)	DANGOL-capture; UI-delay-offline	Matched clean/protected fitting on defended tests.
Inference + measured quality + cost (2/8)	CACHEPRUNE-context; CACHEPRUNE-selective	Two CachePrune outcomes, one configuration.
All five applicable checks (0/5)	None	No bound record for this scoped query.
Narrow preservation + inference/cost	DANGOL-capture; DANGOL-livebinding; SPEC-padding-REST	Fixed message/token content; no implied deadline or end-to-end task guarantee.

SPEC binds a payload-size ratio, not live wire cost; requiring explicit placement still leaves four of the 21 inference/cost-eligible records. A structural function witness and an empirical quality score are separate evidence types.

TABLE 14. FIT-SCOPE SENSITIVITY WITH THE CURRENT R8 QUALITY APPLICABILITY. BROADENING FIT-INAPPLICABLE CELLS GIVES UNKNOWN EVIDENCE.

Query	Fit scope	Broader unknown
Matched adaptation + inference	2/15	2/22
All five bindings	0/5	0/8
Inference + cost	5/21	4/21[†]

[†] Requires explicit R3 placement, or a wire-level cost rather than SPEC's payload ratio. R8 exemptions do not change this inference/cost query.

TABLE 15. THREE EVIDENCE OBJECTS FOR RQ4. THE SAME FAMILY MAY SUPPLY SEVERAL OBJECTS IN SEPARATE EXPERIMENTS.

Object	Required link	Permitted reuse
Attack generalization	Training/profiling source → held-out inputs or systems; attack outcome.	An attacker or recognition method covers the stated target domain.
Defended condition	Named mechanism, local fitting, defended test and outcome.	Retain that operating point; multi-model testing alone is not held-out transfer.
Defense transfer	Source-selected policy/calibration held fixed → target; local-calibration comparator and attacker fit specified.	Transport the evaluated policy only over the tested direction and scope.

7.2. Case 2: resolve the WRA versus AHB cover asymmetry

WRA discards decoy reads for Type I confidentiality; AHB's Type III evasion executes GUI events, a different objective and state contract [6], [17]. AHB has source-bound detection and task outcomes for its online wrapper; those bindings alone do not establish a matched causal effect between conditions. In our retail simulator, read-only and isolated-shadow cover preserve the reference database in 291/291 units, whereas a self-write inserted before the program changes it in 173/291 units (97 tasks, three selections; S9). These controlled units illustrate why discarding a response does not make an executed write inert. State equality is scoped to the simulator and does not establish production safety.

7.3. Case 3: bind adaptive retraining and cost objects

A matched adaptation contrast evaluates an attacker fitted on unprotected data (D_0) and one fitted on defended data (D_2) on identical defended tests. In the controlled transport examples, buffered 1024-byte buckets give 50.0% versus 70.8% accuracy; constant-sized eight-token batches give 50.0% versus 100.0%. A constant-event/count cap instead gives 50.0% for both (Appendix E). Thus a reduction against an unadapted attacker can disappear after adaptation, while another configuration retains the measured reduction. The reuse decision must retain the evaluated attacker as well as the mechanism. Early Bird's 6ms/4% semantic-processing cost separately does not price its K-prefix isolation; KVGov's 1.3 μs HMAC microcost omits lost reuse [3], [37]. CachePrune supplies a configuration-bound protection, quality and serving-cost package [7].

7.4. A positive reuse path: from comparison to a candidate configuration

The Early Bird K-prefix record and CachePrune's direct-recovery record form one of the 17 descriptive matches: both address sensitive-token recovery through cache-reuse probes [3, V-A], [7, 5.1–5.6]. This permits an analyst to retain both mechanisms as candidates for that threat, while keeping the oracle and executed-serving measurements separate. The joint audit then changes the next step. CachePrune supplies a default configuration package linking recovery, generation quality and serving cost; the analyst can use that package for a source-scoped feasibility assessment. Early Bird's semantic-cache overhead cannot price its K-prefix candidate, so that candidate still needs a serving-cost measurement. Neither a pooled recovery ranking nor a new-hardware guarantee follows from this comparison.

TABLE 16. CLAIM-CONDITIONED REUSE DECISIONS DERIVED FROM THE RECORD AND HOLDOUT AUDITS. EACH CHANGED BOUNDARY IDENTIFIES THE EVIDENCE THAT MUST BE BOUND BEFORE CARRYING A RESULT FORWARD.

Reuse question	Evidence decision	Retain or measure next
Emitter / representation	An upstream or buffered capture can differ from the final receiving trace and delivery schedule.	Bind inference to the final receiver; retain the emitter's overflow, byte and delivery-delay scope (R2/R3/R9; §7).
Read cover → writes	Discarding a reply does not establish unchanged commits, authorization or workflow outcomes.	Bind the protected state and utility to the executed intervention; include cover calls, quotas and failures (R3/R8/R9).
Customer / model calibration	A reported split can separate inputs without changing the generator or calibration population.	State held-out units and calibration provenance; separate local fitting variability from source/domain changes; evaluate the requested transfer axis (R5/R6; §6).
Attacker observation	An outcome for one projection or fitted attacker does not supply a result for a richer receiving view.	Evaluate comparable defended tests under the intended observation and adaptation contract; retain receiver-specific inference metrics (R2/R5/R7).
Stored trace → online path	A trace transformation or simulated span does not measure executed queues, completion or online latency.	Bind the receiver, harness and resource denominator to the online condition; establish the relevant topology/network holdout (R3/R6/R9).
Bound cache-reuse package	Early Bird prefix recovery and CachePrune direct recovery permit a scoped candidate comparison; CachePrune binds a shared utility/cost package.	Retain that package for its measured configuration; measure prefix-policy serving cost separately, and re-evaluate any changed workload/hardware.
Component → workflow utility	Component quality or logical state conformance does not determine a planner's response to scheduling and deadlines.	Report utility at the requested workflow boundary and the same intervention/configuration as protection and cost (R3/R8/R9).

What the three findings add. Record-level comparison turns a mechanism-level shortlist into scoped alternatives. Configuration-level binding distinguishes a reusable package from utility or cost measured elsewhere. Building on established WF and adaptive-attack practice [8], [9], [10], [11], the examples instantiate three LLM/agent joins: prefix versus semantic-cache primitives, discarded reads versus executed writes, and component quality versus planner outcomes. The examples identify specific measurements for a deployment; they do not establish that prior authors made a comparison error.

7.5. A deployment query determines the evidence to retain

Start with the intended receiver, protected outcome and intervention (Figure 2). Record-level comparison identifies whether the cited result measures that object. Configuration-level joint binding identifies which inference, utility and cost outcomes share its configuration. Deployment decisions use the holdout matrix to identify evidence for the proposed change and specify the remaining measurement. Table 16 makes these outputs operational: a new emitter needs a receiver-specific capture, writes need state/authorization checks, source-calibration comparisons need a local fitting-variability control, and an online scheduler needs its own planner utility and latency measurement. The calibration control follows from the comparison design: changing the source can also change the finite training sample used to fit the defense.

The following worked applications show how the procedure represents external reevaluations and internal examples. Appendix E retains the detailed controlled case study.

7.6. External worked applications: retain, separate, remeasure

We apply the procedure to a fixed external frame: both defenses in Deep Fingerprinting, all three in WFDefProxy, and all nine in Mathews et al.'s reevaluation, with DynaFlow's live implementation kept as a separate record [81], [82], [9]. The resulting 15 measurement records represent 14 defense–study pairs in three studies. The ledger retains favorable outcomes alongside weaknesses, fixes the Standard setting for the nine-defense table, and records a locator and a concrete measurement decision for every row (S35).

The worked output separates decisions that a mechanism name conflates (Table 18). Stronger protected-data fitting requires revisiting WTF-PAD's attack result, while Walkie-Talkie's symmetric-pairing result remains a valid scoped outcome. FRONT's live protection improves even as its bandwidth cost changes. A record-level audit therefore preserves the security observation and replaces the cost estimate separately. DynaFlow's live result needs a separate execution/workload record, preventing a simulated cost from being attached to a live attack result.

The 11 protected-fit/view requirements cover B01–B02 and B06–B14; the four execution/cost requirements cover B03–B05 and B15. Favorable controls overlap both groups: symmetric Walkie-Talkie B02 and one-split TrafficSliver B11, and live FRONT B03 and Tamaraw B04. Each row produces a retain, separate or remeasure decision. These retrospective examples encode established WF practice; their visible outcomes make them worked applications rather than a prediction-accuracy evaluation.




Figure 2. Decision path for a proposed defense reuse. The output identifies evidence to retain, an observed mismatch or a specific unresolved measurement.

TABLE 17. FILLED REPORTING CARDS FROM SOURCE RESULTS. EARLY BIRD IS VENUE-LINKED (INSPECTED AUTHOR VERSION); TDXRAY IS AN S&P PAPER; CACHEPRUNE IS A CITED PREPRINT AND SERVES AS THE RUNNING CONFIGURATION EXAMPLE. NO NEW BENCHMARK IS IMPLIED.

Field	Early Bird [3, V-A–B]	TDXRay [30, 6.1, Fig. 8, Table 3]	CachePrune [7, 5.1–5.6]
Receiver/target	Timing oracle; sensitive prefix recovery.	Memory-access view; oblivious lookup defense component.	Cache-reuse probes; direct and contextual token recovery.
Intervention	Prefix-granularity oracle; semantic-cache prototype separately.	Oblivious mapping microbenchmark.	Selective cache sharing at default configuration.
Attacker/test	Granularity-specific calibration; matched adaptation unresolved.	Component cost, no bound protected end-to-end inference row.	Recovery evaluation; default quality/cost package; matched training-fit contrast inapplicable; broader adaptive attacks unassessed.
Function	No bound prefix-policy utility.	No bound full-inference utility.	QA/summarization quality at stated configuration.
Cost	Semantic-cache overhead belongs to a different primitive.	Lookup microcost; not complete serving cost.	Serving throughput/cost; preserve default package.
Extension/action	Retain prefix candidate; measure its own serving cost.	Retain component cost; measure protected service and its function.	Retain scoped package; test changed workload/hardware.

TABLE 18. EXTERNAL APPLICATIONS: RETAIN A SCOPED RESULT, SEPARATE AN OUTCOME PACKAGE, OR REQUEST A SPECIFIC MEASUREMENT. FULL 15-RECORD LEDGER: S35. ACCURACY AND TPR RETAIN THEIR ORIGINAL POPULATIONS.

Published contrast	Evidence-reuse decision
B01 WTF-PAD [81]	Refit: DF accuracy 90.7%; prior attackers in the same table reach at most 69.0%.
B02 Walkie-Talkie [81]	Retain symmetric-pairing scope: DF accuracy 49.7%; do not inherit it for asymmetric pairing.
B03 FRONT [82]	Separate outcomes: live DF TPR improves, 72.06% to 42.79%, while data overhead rises, 52% to 75%.
B04 Tamaraw [82]	Retain low live TPR, 6.43%; use live bandwidth overhead 179%, rather than simulated 207/224%.
B15 DynaFlow [9]	Separate live record: 379% mean per-site time overhead; changed URLs/crawler prevent a matched simulation–live effect.

7.7. Internal case-study illustrations

Seven pre-specified judgments illustrate how changed receivers, attacks and source premises affect a comparison. Four have scoped counterexamples, one is partial, one has an unmet source premise and one remains unestablished. Appendix E and S35 retain their conditions and outcomes. These examples illustrate the decision procedure; they do not estimate its accuracy.

8. Implications and Ethics

8.1. Deployment and reporting implications

The decision table distinguishes receiving permissions from intervention capabilities. An access-network operator, VPC monitor and receiving tool service expose different views; remote paths can reveal destinations even with Encrypted ClientHello [83]. A result for one ingress projection therefore needs a separately bound claim before it is applied to host instrumentation or downstream commit logs.

Likewise, read queries, provider-isolated execution and gateway-routed cover have different state contracts. Kubernetes dry-run, Stripe sandboxes and transactional rollback offer isolation mechanisms with their own limits [84], [85], [86]; idempotence alone is insufficient, and sequence changes can survive rollback [87]. Evidence reuse requires the trusted boundary, authorization policy, resource quotas and protected outcome to accompany the mechanism name. The corpus's component outcomes remain useful when their execution and cost scopes match the intended query.

TABLE 19. REUSABLE REPORTING CARD. FILL EACH EVIDENCE CELL WITH A VERSION AND LOCATOR OR "UNKNOWN"; THE FINAL ACTION IS CONDITIONAL ON THE PROPOSED DEPLOYMENT.

Field	What to enter
Receiver/target	Hidden property, accessible signal and permissions.
Intervention	Primitive, execution mode, state and trust boundary.
Attacker/test	Training or calibration condition; defended test population.
Function	Component quality or task outcome; shared configuration.
Cost	Resource, units, denominator, baseline and included operations.
Extension	Changed workload/system axis; available holdout; retain, separate or measure next.

A usable reporting card. Table 19 is a reusable six-field template. Its last column asks for a deployment decision after recording the source evidence. Table 17 fills it for two venue-linked sources and the running cache example, preserving their different scopes. The editable artifact template includes an explicit unknown state and source-locator slot for every field.

8.2. Ethics and artifact scope

The audit uses public research sources. Stakeholders include tenants, tool providers and users whose activity may be inferred or whose state may change. Bot-detection evasion and research-intent privacy have different authorization relations [17], [6]. The case study uses cloned benchmark databases, simulated users and controlled sockets; it does not modify production accounts. Publishing attack methods may enable inference, while scoped results help practitioners assess defenses. The artifact records source locators, audit labels, protocols and aggregate results; release of traces is subject to privacy review, data rights and applicable API terms.

AI tools assisted candidate-field extraction, implementation, source reconciliation and prose revision. Review coverage is stated in §2. Source locators and recorded corrections enable inspection; aggregation and joins are recomputed from record cells. Authors retain responsibility for interpretation. The model case study examines agent behavior; replaying saved trajectories supports multiple controlled comparisons without repeating model calls.

9. Conclusion

This SoK synthesizes mitigation results within an empirical attack-evaluation source frame. Outcome-specific applicability separates source-supported preservation from interventions that can alter content or execution. Functional quality is explicitly bound in 3/8 applicable families, or 4/8 with partial evidence; eleven are exempt from that narrow query. The four agent-associated families leave same-condition end-to-end task scores unbound, with only WRA clearly adding executed decoy research calls.

CachePrune and SparLeak provide measured quality examples; lossless framing supplies a different, narrower functional witness. The decision procedure retains the receiving view, execution state and evaluation condition with each result. Controlled attacker comparisons show that a protection estimate can also change after fitting on defended data. These distinctions specify which result to retain and which deployment outcome to measure.

References

[1] R. Weiss, D. Ayzenshteyn, G. Amit, and Y. Mirsky, "What was your prompt? a remote keylogging attack on AI assistants," in *33rd USENIX Security Symposium*. USENIX Association, 2024, pp. 3367–3384. [Online]. Available: https://www.usenix.org/conference/usenixsecurity24/presentation/weiss

[2] G. Wu, Z. Zhang, Y. Zhang, W. Wang, J. Niu, Y. Wu, and Y. Zhang, "I know what you asked: Prompt leakage via KV-cache sharing in multi-tenant LLM serving," in *Network and Distributed System Security Symposium (NDSS)*, 2025. [Online]. Available: https://www.ndss-symposium.org/ndss-paper/i-know-what-you-asked-prompt-leakage-via-kv-cache-sharing-in-multi-tenant-llm-serving/

[3] L. Song, Z. Pang, W. Wang, Z. Wang, X. Wang, H. Chen, W. Song, Y. Jin, D. Meng, and R. Hou, "The early bird catches the leak: Unveiling timing side channels in LLM serving systems," *IEEE Transactions on Information Forensics and Security*, vol. 20, pp. 11 431–11 446, 2025, consulted arXiv:2409.20002v5; archived access 18 October 2026. [Online]. Available: https://ieeexplore.ieee.org/document/11206380/

[4] Y. Zhang, X. Deng, Z. Gu, Y. Chen, K. Xu, Q. Li, and J. Wu, "Exposing LLM user privacy via traffic fingerprint analysis: A study of privacy risks in LLM agent interactions," *arXiv preprint arXiv:2510.07176*, 2025. [Online]. Available: https://arxiv.org/abs/2510.07176

[5] W. Lugoloobi, S. Marro, J. Magomere, J. Wright, and C. Russell, "Known by their actions: Fingerprinting LLM browser agents via UI traces," *arXiv preprint arXiv:2605.14786*, 2026, consulted arXiv:2605.14786v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2605.14786v1

[6] H. Jeong, M. Teymoorianfard, A. Kumar, A. Houmansadr, and E. Bagdasarian, "Network-level prompt and trait leakage in local research agents," in *35th USENIX Security Symposium*. USENIX Association, 2026, pp. 6485–6504. [Online]. Available: https://www.usenix.org/conference/usenixsecurity26/presentation/jeong

[7] G. Wu, Z. Li, Y. Zhang, Z. Zhang, J. Niu, Y. Wu, and Y. Zhang, "Cacheprune: Privacy-aware and fine-grained KV cache sharing for efficient LLM inference," *arXiv preprint arXiv:2605.23640v1*, 2026, consulted 2605.23640v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2605.23640v1

[8] M. Juarez, S. Afroz, G. Acar, C. Diaz, and R. Greenstadt, "A critical evaluation of website fingerprinting attacks," in *Proceedings of the ACM SIGSAC Conference on Computer and Communications Security*, 2014, pp. 263–274.

[9] N. Mathews, J. K. Holland, S. E. Oh, M. S. Rahman, N. Hopper, and M. Wright, "SoK: A critical evaluation of efficient website fingerprinting defenses," in *IEEE Symposium on Security and Privacy*, 2023.

[10] F. Tramèr, N. Carlini, W. Brendel, and A. Madry, "On adaptive attacks to adversarial example defenses," in *Advances in Neural Information Processing Systems*, vol. 33, 2020. [Online]. Available: https://arxiv.org/abs/2002.08347v2

[11] N. Carlini, A. Athalye, N. Papernot, W. Brendel, J. Rauber, D. Tsipras, I. Goodfellow, A. Madry, and A. Kurakin, "On evaluating adversarial robustness," *arXiv preprint arXiv:1902.06705*, 2019. [Online]. Available: https://arxiv.org/abs/1902.06705v2

[12] T. A. Ghaleb, "Fingerprinting AI coding agents on GitHub," *arXiv preprint arXiv:2601.17406v1*, 2026, consulted arXiv:2601.17406v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2601.17406v1

[13] W. Wang, Z. Liu, H. Kou, X. Liu, and J. Shen, "The chatbot knows it's you: Dialogue attribution in unauthenticated human–LLM sessions," in *Proceedings of the ACM Web Conference 2026*, 2026, pp. 8797–8807. [Online]. Available: https://dl.acm.org/doi/10.1145/3774904.3793048

[14] S. Shao, Y. Li, H. Yao, Y. Chen, Y. Yang, and Z. Qin, "Reading between the lines: Towards reliable black-box LLM fingerprinting via zeroth-order gradient estimation," 2026, version 2, 21 January 2026. [Online]. Available: https://arxiv.org/html/2510.06605v2

[15] J. Leshin, M. Shah, I. Timmis, and D. Kang, "Behavioral fingerprints for LLM endpoint stability and identity," 2026, version 1, 19 March 2026. [Online]. Available: https://arxiv.org/html/2603.19022v1

[16] T. Zhu, Y. Wu, W. Jin, Y. Li, and G. Huang, "StepFinder: A temporal semantic framework for failure attribution in multi-agent systems," 2026, version 1, 2 June 2026. [Online]. Available: https://arxiv.org/html/2606.03467v1

[17] J. Zhu, L. Yang, R. Shan, C. Zheng, Z. Zheng, W. Liu, Y. Yu, W. Zhang, and J. Lin, "Turing test on screen: A benchmark for mobile GUI agent humanization," *arXiv preprint arXiv:2604.09574v1*, 2026, consulted arXiv:2604.09574v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/html/2604.09574v1

[18] L. L. Gan, J. Wu, L. Ge, L. Yang, Y. Song, J. Zhang, H. Jin, W. Wang, and G. Xue, "ClawGuard: Out-of-band detection of LLM agent workflow hijacking via EM side channel," *arXiv preprint arXiv:2605.06205v1*, 2026. [Online]. Available: https://arxiv.org/abs/2605.06205v1

[19] B. Dangol, "From privacy to workflow integrity: Communication-graph metadata in autonomous agent interoperability," *arXiv preprint arXiv:2606.07150v3*, 2026, consulted arXiv:2606.07150v3; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2606.07150v3

[20] N. Alhalawani, G. Acar, Z. Liu, and L. Batina, "Physical side-channel attacks on edge LLMs: Extracting output tokens and user prompts," *arXiv preprint arXiv:2610.14215v1*, 2026, consulted 2610.14215v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2610.14215v1

[21] A. Chaudhuri, S. Shukla, S. Bhattacharya, and D. Mukhopadhyay, "Energon: Unveiling transformers from GPU power and thermal side-channels," in *IEEE/ACM International Conference on Computer-Aided Design*, 2025. [Online]. Available: https://arxiv.org/abs/2508.01768v1

[22] R. Ding, T. Xu, X. Shen, A. A. Ding, and Y. Fei, "MoEcho: Exploiting side-channel attacks to compromise user privacy in mixture-of-experts LLMs," in *ACM SIGSAC Conference on Computer and Communications Security*, 2025, pp. 2159–2173. [Online]. Available: https://arxiv.org/abs/2508.15036v1

[23] Z. Gao, J. Hu, F. Guo, Y. Zhang, Y. Han, S. Liu, H. Li, and Z. Lv, "I know what you said: Unveiling hardware cache side-channels in local large language model inference," in *34th USENIX Security Symposium*, 2025, pp. 1649–1668. [Online]. Available: https://www.usenix.org/conference/usenixsecurity25/presentation/gao-zibo

[24] C. Gu, R. Levine, Z. Zhang, T. Sorensen, and Y. Guo, "Behind bars: A side-channel attack on NVIDIA MIG cache partitioning using memory barriers," in *35th USENIX Security Symposium*. USENIX Association, 2026, pp. 5373–5392. [Online]. Available: https://www.usenix.org/conference/usenixsecurity26/presentation/gu-cheng

[25] R. Nazaraliyev, Y. Zhang, and N. Abu-Ghazaleh, "Page404: Breaking GPU isolation through hardware-assisted page migration," *arXiv preprint arXiv:2610.20962v1*, 2026, consulted 2610.20962v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2610.20962v1

[26] A. Adiletta and B. Sunar, "Spill the beans: Exploiting CPU cache side-channels to leak tokens from large language models," *arXiv preprint arXiv:2505.00817*, 2025. [Online]. Available: https://arxiv.org/abs/2505.00817

[27] H. Weng, R. Zhou, Y. Qu, X. Ji, and W. Xu, "ArchSnoop: LLM architecture snooping via electromagnetic side-channel on edge devices," in *Proceedings of the 19th ACM Conference on Security and Privacy in Wireless and Mobile Networks*, 2026, pp. 51–62. [Online]. Available: https://dl.acm.org/doi/10.1145/3765613.3811673

[28] F. Chen, L. Du, J. Zhou, P. Li, and Z. Su, "Sparleak: Privacy leakage from sparse attention in LLM inference on shared gpus," *arXiv preprint arXiv:2609.38830v1*, 2026, consulted 2609.38830v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2609.38830v1

[29] E. Hadad and M. Guri, "Shape and substance: Dual-layer side-channel attacks on local vision-language models," *arXiv preprint arXiv:2603.25403v1*, 2026, consulted 2603.25403v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2603.25403v1

[30] T. Hornetz, H. Yavarzadeh, A. Cheu, A. Gascon, L. Gerlach, D. Moghimi, P. Schoppmann, M. Schwarz, and R. Zhang, "Tdxray: Microarchitectural side-channel analysis of Intel TDX for real-world workloads," in *IEEE Symposium on Security and Privacy*, 2026. [Online]. Available: https://tdxray.cpusec.org/assets/tdxray_sp26.pdf

[31] Y. Jo, J. Park, E. Lee, and D. Song, "Sparseety: Extracting tokens from sparsity-exploiting LLM serving systems via deterministic side channels," *arXiv preprint arXiv:2608.02995v1*, 2026, consulted 2608.02995v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2608.02995v1

[32] J. Lee, Y. Wang, R. Rajat, D. Wong, M. Li, and M. Annavaram, "Otro: Oblivious tokenization path with square-root oram," *arXiv preprint arXiv:2606.17358v1*, 2026, consulted 2606.17358v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2606.17358v1

[33] R. Weiss, B. Konstantinov, E. Sheetrit, T. Simon, and Y. Mirsky, "Detokenization leaks: Reconstructing local LLM outputs from cache traces," *arXiv preprint arXiv:2609.06674v1*, 2026. [Online]. Available: https://arxiv.org/abs/2609.06674v1

[34] J.-J. Jiao, H. Yang, and R. Wen, "Llm-wfin: A fine-grained large language model (LLM)-oriented website fingerprinting attack via fusing interrupt trace and network traffic," *Electronics*, vol. 14, no. 7, p. 1263, 2025, consulted publisher version 2025-03-23; source-scoped access 21 October 2026. [Online]. Available: https://doi.org/10.3390/electronics14071263

[35] D. Scheinert, A. Acker, T. Wittkopp, S. Becker, H. Yous, K. Reddy, I. Farhat, H. Hacid, and O. Kao, "Beyond microservices: Testing web-scale RCA methods on GPU-driven LLM workloads," 2026, version 1, 2 March 2026. [Online]. Available: https://arxiv.org/html/2603.02057v1

[36] G. Politis and E. Pappas, "Privacy failure in split-LLM training, the returned gradient nullifies the decoys," *arXiv preprint arXiv:2609.04382v1*, 2026, consulted 2609.04382v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2609.04382v1

[37] T. C. Addagada, "Governing the KV cache: Preventing timing side-channel leakage in multi-tenant LLM inference," *arXiv preprint arXiv:2608.09225*, 2026, consulted arXiv:2608.09225v1; archived access 19 October 2026. [Online]. Available: https://arxiv.org/abs/2608.09225v1

[38] S. Alhazbi, A. Hussain, G. Oligeri, and P. Papadimitratos, "LLMs have rhythm: Fingerprinting large language models using inter-token times and network traffic analysis," *IEEE Open Journal of the Communications Society*, vol. 6, pp. 5050–5071, 2025. [Online]. Available: https://arxiv.org/abs/2502.20589v1

[39] N. Carlini and M. Nasr, "Remote timing attacks on efficient language model inference," *arXiv preprint arXiv:2410.17175v1*, 2024. [Online]. Available: https://arxiv.org/abs/2410.17175v1

[40] Z. Zhang, G. Wu, S. Deng, S. Wang, and Y. Zhang, "Netecho: From real-world streaming side-channels to full LLM conversation recovery," *arXiv preprint arXiv:2510.25472*, 2025, consulted arXiv:2510.25472v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2510.25472v1

[41] S. Li, T. Cui, M. Chen, X. Lin, Z. Gu, X. Deng, K. Xu, and Q. Li, "From length to content: Token-length side-channel attacks on LLM api merged outputs," in *35th USENIX Security Symposium*, 2026, pp. 2187–2206. [Online]. Available: https://www.usenix.org/conference/usenixsecurity26/presentation/li-sijia

[42] J. Wei, A. Abdulrazzag, T. Zhang, A. Muursepp, and G. Saileshwar, "When speculation spills secrets: Side channels via speculative decoding in llms," *arXiv preprint arXiv:2411.01076*, 2024, consulted arXiv:2411.01076v4; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2411.01076v4

[43] G. McDonald and J. B. Or, "Whisper leak: a side-channel attack on large language models," *arXiv preprint arXiv:2511.03675*, 2025, consulted arXiv:2511.03675v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2511.03675v1

[44] R. A. Bakar, "Characterizing contention-induced reliability collapse in KV-cache timing side channels for multi-tenant LLM serving," *arXiv preprint arXiv:2609.06853v1*, 2026. [Online]. Available: https://arxiv.org/abs/2609.06853v1

[45] T.-R. Chen, "Sensitive-topic leakage through LLM routing metadata: Measurement and mitigation," *arXiv preprint arXiv:2610.09981v1*, 2026, consulted 2610.09981v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2610.09981v1

[46] K. Chu, Z. Lin, D. Xiang, Z. Shen, J. Su, C. Chu, Y. Yang, W. Zhang, W. Wu, and W. Zhang, "Selective KV-cache sharing to mitigate timing side-channels in LLM inference," *arXiv preprint arXiv:2508.08438v2*, 2026, consulted arXiv:2508.08438v2; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2508.08438v2

[47] E. Debenedetti, G. Severi, N. Carlini, C. A. Choquette-Choo, M. Jagielski, M. Nasr, E. Wallace, and F. Tramèr, "Privacy side channels in machine learning systems," in *33rd USENIX Security Symposium*. USENIX Association, 2024. [Online]. Available: https://www.usenix.org/conference/usenixsecurity24/presentation/debenedetti

[48] C. Gu, X. L. Li, R. Kuditipudi, P. Liang, and T. Hashimoto, "Auditing prompt caching in language model apis," in *International Conference on Machine Learning*, vol. 267, 2025, pp. 20 477–20 496. [Online]. Available: https://proceedings.mlr.press/v267/gu25b.html

[49] X. Zheng, H. Han, S. Shi, Q. Fang, Z. Du, X. Hu, and Q. Guo, "Inputsnatch: Stealing input in LLM services via cache-sharing timing side-channel attacks," in *Advanced Parallel Processing Technologies (APPT 2026)*, 2027, pp. 483–497, first online August 24, 2026; publisher citation year 2027. [Online]. Available: https://link.springer.com/chapter/10.1007/978-981-92-4805-6_32

[50] S. Majidi, N. Mireshghallah, and K. Taram, "Leaky language models: Stealing architecture and inference optimizations via per-token timing," *arXiv preprint arXiv:2607.20723*, 2026, consulted arXiv:2607.20723v1; archived access 19 October 2026. [Online]. Available: https://arxiv.org/abs/2607.20723v1

[51] H. Sun, S. Liu, S. Ma, J. Li, M. Xiao, and W. Jiang, "Agent-assisted side-channel attacks on non-prefix KV cache in rag," *arXiv preprint arXiv:2606.21842*, 2026, consulted arXiv:2606.21842v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2606.21842v1

[52] T. Zhang, G. Saileshwar, and D. Lie, "Time will tell: Timing side channels via output token count in large language models," *arXiv preprint arXiv:2412.15431*, 2024, consulted arXiv:2412.15431v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2412.15431v1

[53] I. Yona, I. Shumailov, J. Hayes, and N. Carlini, "Stealing user prompts from mixture of experts," *arXiv preprint arXiv:2410.22884v1*, 2024. [Online]. Available: https://arxiv.org/abs/2410.22884v1

[54] P. Revankar, K. Chauhan, J. Kim, S. N. Nur, V. Siu, and C.-G. Wang, "Mirage: A polarity-flipping encoding subspace in LLM agents," *arXiv preprint arXiv:2606.10304v1*, 2026, consulted 2606.10304v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2606.10304v1

[55] S. Pouryousef, J. Lopez, S. R. Nowmi, M. M. Kamol, M. Hossain, M. Tran, and M. S. Rahman, "A large-scale benchmark and risk assessment of traffic analysis attacks on cloud LLM services," *arXiv preprint arXiv:2609.31877v1*, 2026, consulted arXiv:2609.31877v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2609.31877v1

[56] I. Fayolle, S. Bouhenniche, S. Pélissier, P. Laperdrix, C. Maurice, and W. Rudametkin, "On the internet, nobody knows you're an LLM bot: Unmasking web agents with multi-layer fingerprinting," *arXiv preprint arXiv:2606.30119v1*, 2026, consulted 2606.30119v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2606.30119v1

[57] R. Solomon, Y. Y. Levi, L. Vaknin, E. Aizikovich *et al.*, "LumiMAS: A comprehensive framework for real-time monitoring and enhanced observability in multi-agent systems," *arXiv preprint arXiv:2508.12412v2*, 2026. [Online]. Available: https://arxiv.org/abs/2508.12412v2

[58] F. George, H. Kumar, D. Pathak, K. Ray, M. Verma, and P. Moogi, "Unsupervised cycle detection in agentic applications," *arXiv preprint arXiv:2511.10650v1*, 2025. [Online]. Available: https://arxiv.org/abs/2511.10650v1

[59] J. Geng, R. He, Z. Fei, B. Yi, R. Wang, Z. Liu, X. Hu, X. Wu, and Q. Zeng, "Agent skills matter: Inferring proprietary skills from execution trajectories," *arXiv preprint arXiv:2607.25560v1*, 2026, consulted arXiv:2607.25560v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2607.25560v1

[60] H. Oderinwale, "Agent trajectories as programs: fingerprinting and programming coding-agent behavior," *arXiv preprint arXiv:2606.16988v1*, 2026. [Online]. Available: https://arxiv.org/abs/2606.16988v1

[61] X. Wang, B. Zhao, M. Backes, F. Boenisch, and A. Dziedzic, "Agentprov: Auditing agentic LLM api providers via tool-use policy probes," *arXiv preprint arXiv:2609.00052v1*, 2026, consulted 2609.00052v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2609.00052v1

[62] C.-Y. Wang, X.-H. Xie, T.-Z. Wang, F.-C. Luo, and Y. Cui, "Who is behind the harness? fingerprinting LLMs through agentic behavior," *arXiv preprint arXiv:2609.28559v1*, 2026, consulted 2609.28559v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2609.28559v1

[63] S.-J. Park, M. Choi, J. Kim, and M.-S. Kang, "Cross-agent campaign attribution: Linking asynchronous attacks across LLM agents," *arXiv preprint arXiv:2607.18826v1*, 2026, consulted 2607.18826v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2607.18826v1

[64] C. Song, H. Wang, and R. Martin, "Personafingerprint: Measuring persona inference on modern websites with LLM-driven browsing," *arXiv preprint arXiv:2605.15962*, 2026. [Online]. Available: https://arxiv.org/abs/2605.15962

[65] D. Kang, H. Jeong, J. Sheffey, P. Datta, and A. Houmansadr, "Whose agent are you? multi-layer fingerprinting and attribution of autonomous web agents," *arXiv preprint arXiv:2606.20910v1*, 2026. [Online]. Available: https://arxiv.org/abs/2606.20910v1

[66] A. Shahriar, M. N. Rahman, S. Ahmed, F. Sadeque, and M. R. Parvez, "AgentTell: Behavioural side-channel leakage in browser-use agents," *arXiv preprint arXiv:2609.32915v1*, 2026, consulted arXiv:2609.32915v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2609.32915v1

[67] E. Wang, Z. Shafiq, and Y. Vekaria, "Fp-agent: Fingerprinting AI browsing agents," *arXiv preprint arXiv:2605.01247*, 2026, consulted arXiv:2605.01247v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2605.01247v1

[68] S. Banerjee, P. Sahu, M. Luo, A. Vahldiek-Oberwagner, N. J. Yadwadkar, and M. Tiwari, "SoK: A systems perspective on compound AI threats and countermeasures," *arXiv preprint arXiv:2411.13459v1*, 2024, consulted arXiv:2411.13459v1; inspected 20 October 2026. [Online]. Available: https://arxiv.org/abs/2411.13459v1

[69] J. Forough, M. Kogias, and H. Haddadi, "When agents handle secrets: A survey of confidential computing for agentic AI," *arXiv preprint arXiv:2605.03213v2*, 2026, consulted arXiv:2605.03213v2; inspected 20 October 2026. [Online]. Available: https://arxiv.org/abs/2605.03213v2

[70] O. Kotevska, S. Jha, A. Bellet, R. Hu, N. D. Bastian, R. F. da Silva, R. Madduri, and K. Kim, "Privacy foundations for multi-institutional scientific artificial intelligence," *arXiv preprint arXiv:2609.39787v1*, 2026, consulted 2609.39787v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2609.39787v1

[71] X. Cai, R. Nithyanand, T. Wang, R. Johnson, and I. Goldberg, "A systematic approach to developing and evaluating website fingerprinting defenses," in *ACM CCS*, 2014, pp. 227–238. [Online]. Available: https://doi.org/10.1145/2660267.2660362

[72] M. Juarez, M. Imani, M. Perry, C. Diaz, and M. Wright, "Toward an efficient website fingerprinting defense," in *ESORICS*, 2016, pp. 27–46. [Online]. Available: https://arxiv.org/abs/1512.00524

[73] T. Wang and I. Goldberg, "Walkie-talkie: An efficient defense against passive website fingerprinting attacks," in *26th USENIX Security Symposium*, 2017. [Online]. Available: https://www.usenix.org/conference/usenixsecurity17/technical-sessions/presentation/wang-tao

[74] F. Croce, M. Andriushchenko, V. Sehwag, E. Debenedetti, N. Flammarion, M. Chiang, P. Mittal, and M. Hein, "RobustBench: a standardized adversarial robustness benchmark," in *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, vol. 1, 2021. [Online]. Available: https://datasets-benchmarks-proceedings.neurips.cc/paper/2021/hash/a3c65c2974270fd093ee8a9bf8ae7d0b-Abstract-round2.html

[75] C. Dwork and A. Roth, "The algorithmic foundations of differential privacy," *Foundations and Trends in Theoretical Computer Science*, vol. 9, no. 3–4, pp. 211–407, 2014. [Online]. Available: https://www.cis.upenn.edu/~aaroth/Papers/privacybook.pdf

[76] G. Smith, "On the foundations of quantitative information flow," in *Foundations of Software Science and Computational Structures*, ser. LNCS, vol. 5504, 2009, pp. 288–302. [Online]. Available: https://link.springer.com/chapter/10.1007/978-3-642-00596-1_21

[77] J. B. Almeida, M. Barbosa, G. Barthe, F. Dupressoir, and M. Emmi, "Verifying Constant-Time implementations," in *25th USENIX Security Symposium*, 2016, pp. 53–70. [Online]. Available: https://www.usenix.org/conference/usenixsecurity16/technical-sessions/presentation/almeida

[78] E. Stefanov, M. van Dijk, E. Shi, C. Fletcher, L. Ren, X. Yu, and S. Devadas, "Path ORAM: An extremely simple oblivious RAM protocol," in *ACM SIGSAC Conference on Computer and Communications Security*, 2013, pp. 299–310. [Online]. Available: https://doi.org/10.1145/2508859.2516660

[79] N. Nazari, F. Xiang, C. Fang, H. M. Makrani, A. Puri, K. Patwari, H. Sayadi, S. Rafatirad, C.-N. Chuah, and H. Homayoun, "LLM-FIN: Large language models fingerprinting attack on edge devices," in *International Symposium on Quality Electronic Design*, 2024. [Online]. Available: https://web.cs.ucdavis.edu/~srafatir/pages/documents/llm_fingerprint.pdf

[80] T. M. Cover and J. A. Thomas, *Elements of Information Theory*, 2nd ed. Wiley-Interscience, 2006, theorem 2.8.1, Data-processing inequality. [Online]. Available: https://onlinelibrary.wiley.com/doi/book/10.1002/047174882X

[81] P. Sirinam, M. Imani, M. Juarez, and M. Wright, "Deep fingerprinting: Undermining website fingerprinting defenses with deep learning," in *ACM CCS*, 2018, pp. 1928–1943.

[82] J. Gong, W. Zhang, C. Zhang, and T. Wang, "WFDefProxy: Modularly implementing and empirically evaluating website fingerprinting defenses," arXiv:2111.12629v1, 2021. [Online]. Available: https://arxiv.org/abs/2111.12629v1

[83] E. Rescorla, K. Oku, N. Sullivan, and C. A. Wood, "TLS Encrypted Client Hello," RFC 9849, Mar. 2026. [Online]. Available: https://www.rfc-editor.org/rfc/rfc9849

[84] Kubernetes Authors, "Kubernetes API Concepts: Dry-run," https://kubernetes.io/docs/reference/using-api/api-concepts/#dry-run, accessed October 24, 2026.

[85] Stripe, "Sandboxes," https://docs.stripe.com/sandboxes, accessed October 24, 2026.

[86] PostgreSQL Global Development Group, "PostgreSQL 18 Documentation: ROLLBACK," https://www.postgresql.org/docs/18/sql-rollback.html, accessed October 24, 2026.

[87] ——, "PostgreSQL 18 Documentation: Sequence Manipulation Functions," https://www.postgresql.org/docs/18/functions-sequence.html, accessed October 24, 2026.

[88] R. H. Anwar, J. O. Weiss, T. Alves, S. Kundu, and M. T. Raza, "InferNet: Exploiting aggregate GPU profiles as side-channel for DNN architecture inference," *ACM Transactions on AI Security and Privacy*, 2026. [Online]. Available: https://rhasnainanwar.me/assets/pdf/2304.03388v2.pdf

[89] W. Cui, H. Zhang, Y. Huang, Q. Li *et al.*, "SymDiag: Explainable diagnosis for LLM reasoning via neuro-symbolic verification," in *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, 2026, consulted arXiv:2608.08786v1; archived access 18 October 2026. [Online]. Available: https://arxiv.org/abs/2608.08786v1

[90] N. Lahjouji and A. G. Colaco, "Agents that know too much: A data-centric survey of privacy in LLM agents," *arXiv preprint arXiv:2606.26627*, 2026, consulted arXiv:2606.26627v1; archived access 19 October 2026. [Online]. Available: https://arxiv.org/abs/2606.26627v1

[91] J. Roh, E. Bagdasarian, H. Haddadi, and A. S. Shamsabadi, "SPILLage: Agentic oversharing on the web," *arXiv preprint arXiv:2602.13516v1*, 2026. [Online]. Available: https://arxiv.org/abs/2602.13516v1

[92] G. Yu, Q. Wang, R. Lang, S. Su, and X. Wang, "PlanTwin: Privacy-preserving planning abstractions for cloud-assisted LLM agents," *arXiv preprint arXiv:2603.18377v2*, 2026. [Online]. Available: https://arxiv.org/abs/2603.18377v2

[93] J. Xu, L. Fan, Z. Wang, X. Li, and H. Liu, "Selection-invariant communication compilers for privacy-aware multi-agent LLM workflows," *arXiv preprint arXiv:2609.26076v1*, 2026. [Online]. Available: https://arxiv.org/abs/2609.26076v1

[94] Y. Qiao, D. Liu, H. Yang, W. Zhou, and S. Hu, "Agent tools orchestration leaks more: Dataset, benchmark, and mitigation," *arXiv preprint arXiv:2512.16310v4*, 2026, version 4. [Online]. Available: https://arxiv.org/abs/2512.16310v4

[95] M. Umar, A. P. Marathe, M. D. Gupta, S. J. Ghosh, G. E. Suh, and W. Xiong, "Efficient memory side-channel protection for embedding generation in machine learning," in *IEEE International Symposium on High-Performance Computer Architecture*, 2025. [Online]. Available: https://bearhw.ece.vt.edu/content/dam/bearhw_ece_vt_edu/publications/2025_HPCA_SecEmb.pdf

[96] L. Wu, C. Wang, T. Liu, Y. Zhao, and H. Wang, "From assistants to adversaries: Exploring the security risks of mobile LLM agents," *arXiv preprint arXiv:2505.12981v1*, 2025, version 1. [Online]. Available: https://arxiv.org/abs/2505.12981

[97] J. W. Kim, B. Min, K. Edemacu, Y. Choi, S.-H. Cho, and B. Jang, "Dp-memview: A memory interface for attribute-level transcript privacy in long-term LLM agents," *arXiv preprint arXiv:2608.03130v1*, 2026, consulted 2608.03130v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2608.03130v1

[98] M. Mudryi, M. Chaklosh, and G. M. Wójcik, "The hidden dangers of browsing AI agents," *arXiv preprint arXiv:2505.13076v1*, 2025, version 1. [Online]. Available: https://arxiv.org/abs/2505.13076

[99] Y.-M. Wang, Y.-X. Li, S.-L. Fan, Y.-H. Zheng, and T.-H. Chang, "Ask without telling: Local slms consult cloud LLMs without revealing task intent," *arXiv preprint arXiv:2609.32642v1*, 2026, consulted 2609.32642v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2609.32642v1

[100] A. Ukani, H. Haddadi, A. S. Shamsabadi, and P. Snyder, "Privacy practices of browser agents," *arXiv preprint arXiv:2512.07725*, 2025. [Online]. Available: https://arxiv.org/abs/2512.07725

[101] Z. Liu, S. van Hoek, P. Horváth, D. Lauret, X. Xu, and L. Batina, "Real-world edge neural network implementations leak private interactions through physical side channel," *arXiv preprint arXiv:2501.14512v1*, 2025, consulted 2501.14512v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2501.14512v1

[102] P. G. Pennas, K. Papaioannou, M. Guarnieri, and T. D. Doudali, "Cachesolidarity: Preventing prefix caching side channels in multi-tenant LLM serving systems," *arXiv preprint arXiv:2603.10726v1*, 2026, consulted 2603.10726v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2603.10726v1

[103] C.-Y. Zhou, Q.-L. Jiang, S.-N. Wu, and X.-H. Zhou, "The vision encoder as a privacy boundary: Visual-token side channels in encoder-free vision-language models," *arXiv preprint arXiv:2606.14783v1*, 2026, consulted 2606.14783v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2606.14783v1

[104] G. Politis and E. Pappas, "What gradients add to text leakage in split language models, counted per token and per document," *arXiv preprint arXiv:2610.04128v1*, 2026, consulted 2610.04128v1; source-scoped access 21 October 2026. [Online]. Available: https://arxiv.org/html/2610.04128v1

Appendix A. Audit Trail

The artifact preserves the 82-family map, 39-record ledger, 180 family cells and 351 record cells with source versions and locators. S33 publishes query membership and sensitivity checks. Case-study protocols, observations and uncertainty calculations retain their original cohorts and provenance.

Appendix B. Result-record index

Table 20 indexes all 39 records by measurement mode and source locator. Marks distinguish six contextual controls (‡) and six final-search additions (†); all enter the pair inventory. The ledger retains full locators, versions and hashes.

Appendix C. Case-Study Artifact Index

The artifact index maps the case to experiment keys; Supplement S11–S26 provides the associated methods and results. These keys preserve original task/customer memberships; S30 retains the corrected permutation/Holm tests and calibration resampling.

Appendix D. Family-Level Holdout Evidence

This is a family-level discovery index, not a count of defense-transfer tests. The three model H entries concern attack/identification generalization; even an H in a mitigation family must be linked to its defended condition before reuse. The main RQ4 table separates those evidence objects, and S34 identifies every H entry. Table 21 covers 82 families and 492 cells. Axes: T task/input/user; M model; C harness/topology; H hardware; N network/load; D time. Codes: H reported holdout; V condition comparison/recalibration; X scoped restriction; ? unresolved; – conceptual/inapplicable. Scope C/A denotes core/adjacent. H records separation, not transfer success; ? does not establish an absent experiment. S28 retains source locators and qualified interpretations.

Appendix E. Illustrative Case Study and Reconstruction Scope

This appendix explains the role of the archived implementation examples. They instantiate the same distinctions used in the literature atlas: final receiver versus upstream trace, executed state versus discarded responses, and online planner utility versus reused trajectories. They are illustrative applications, not validation data for the comparison rules. The complete numerical grids, negative outcomes, intervals and corrected tests remain unchanged in S11–S32.

The transport example has 48 saved responses on 24 topics (12 train/12 test). The public *retail* setting has 115 tasks from 53 customers; its frozen split contains 46 test tasks from 24 customers, including 5 cancellation-positive and 7 return-positive customers. The separate live planner example has 100 episodes: 37/50 baseline and 33/50 defended successes, a difference of -8.0 points with customer interval $[-23.9, 6.5]$. All eight calibration contrasts have Holm-adjusted $p = 1.000$; the original absolute protection screen remains unmet. Neither these unresolved contrasts nor resampling the same customers validates the framework.

Attacker-dependent recovery. On the same defended test outputs, buffered 1024-byte buckets give $D_0 = 50.0\%$ and $D_2 = 70.8\%$ accuracy (adapted accuracy interval 58.3–83.3%; S11). Constant-sized eight-token batches give 50.0% versus 100.0%, while a constant-event/count cap gives 50.0% for both (S12). The comparison fixes the outputs and defended view and changes fitting; it demonstrates

configuration-specific recovery, without implying that adaptation defeats every defense. The held-out sample contains 24 outputs from 12 topics.

The artifact separates *analysis reconstruction* from *new model collection*. Archived requests, responses, traces, calibration hashes and predictions permit the reported calculations to be reconstructed. Fresh calls to mutable Sol/Luna/MiniMax/GLM aliases, with documented unequal budgets, cannot reproduce an identical generator. No fixed-weight replication claim is made. Detailed protocols and model identities remain explicit in S14–S32; the literature synthesis does not depend on obtaining a favorable result from these examples.

Appendix F.
Reconstructing the Audit in This PDF

Table 22 gives the reporting-pattern sensitivity to removing CachePrune and final-search additions. The latter removes six records from four families (the † marker in the record index); six contextual ‡ controls are excluded throughout. Removing both CachePrune and all final-search additions equals the latter row. The removal table retains the archived measured-utility convention; the current R8 rule yields 3/8 quality-applicable families (4/8 accepting P), with eleven families exempt from that narrow query. S44 gives the source-linked rationale for each exemption. Task scores for added execution remain separate.

Table 23 supplies the current record-level R1–R9 codes and question assignments. Its R8 column incorporates the preservation exemptions; all other cells retain their source coding. To reproduce a joint query, retain the 31 Type I/II mitigation records (exclude both AHB records and six contextual controls), exclude records with an inapplicable required item, and count records with B for every requested item. The required items are R7/R8 for inference/utility, R7/R9 for inference/cost, R4/R5/R7 for matched fitting/inference, R7/R8/R9 for the triple, and R4/R5/R7/R8/R9 for all five. Table 24 identifies each family inference/cost witness. Appendix B supplies record names, modes and locators.

Pair inventory and granularity. Table 25 covers all 133 within-question pair decisions. The 105 different-object pairs and eight of 15 within-family pairs reflect the declared split and grouping rules; a normal difference in research scope is not a source-paper defect. Table 26 projects the unchanged judgments onto coarser units. Mixed edges retain all constituent statuses, and within-unit edges disappear from the index without being resolved. Family-only indexing yields 44 edges, eight mixed, and hides all 15 within-family pairs. Table 23 reconstructs the 133 labels; the pair CSV supplies the per-pair reasons and locators. These indexing sensitivities support audit reconstruction; the reporting findings use the record cells directly.

Appendix G.
Mapped Privacy Families without a Linked Mitigation Record

Within the frozen corpus, the union of Type I and II contains 52 families; 19 have a scoped mitigation record. The remaining 33 families are enumerated below so that this coverage statement can be audited against the core map. This is a statement about the record-selection rules and inspected sources: several have contextual guardrails, noise, filters, decoy boundaries, or unbound claims. It does not assert that none of their papers or subsequent work evaluates any defense.

The Type I families without a linked qualifying mitigation record are Edge EM leakage, MoEcho, Behind Bars, PAGE404, Spill the Beans, SparSEEty, Detokenization Leaks, LLM-WFIN, SplitDecoy, Prompt Echo, remote keylogging, cache contention, routing metadata, ML privacy channels, prompt-cache audit, InputSnatch, Leaky Language Models, PromptPeek, MoE prompt stealing, AgentPrint, SIGLEAK, PersonaFingerprint, and AgentTell [20], [22], [24], [25], [26], [31], [33], [34], [36], [41], [1], [44], [45], [47], [48], [49], [50], [2], [53], [4], [59], [64], [66].

The Type II families without a linked qualifying mitigation record are Energon, ArchSnoop, LLMs Have Rhythm, Web-agent unmasking, AgentPrint, ProcGrep, AgentProv, Lidar, Campaign attribution, Whose Agent?, and FP-Agent [21], [27], [38], [56], [4], [60], [61], [62], [63], [65], [67]. AgentPrint belongs to both lists and is counted once in the union.

TABLE 20. COMPLETE INDEX OF THE 39 RESULT RECORDS (26 FAMILIES). BOLD NUMBERS 01–39 BESIDE EACH BOUNDARY LINK TO THE CELL AND PAIR INDEX IN APPENDIX F. MODE IS THE PRIMARY MEASUREMENT MODE: EX EXECUTED COLLECTION/PROTOTYPE (20), TR TRACE TRANSFORMATION (6), SI SIMULATION/DERIVED ESTIMATE (5), CO COMPONENT/CALIBRATION MEASUREMENT (6), UN PLACEMENT UNRESOLVED (2). ‡: CONTEXTUAL RECORD (6); †: ADDED BY THE FINAL SEARCH (6). T=TABLE, F=FIGURE, APP.=APPENDIX; LOCATORS REFER TO THE CITED SOURCE.

Record ID / family	Mode	Boundary; source locator
UI-delay-offline [5]	Tr	**01**. Offline delay; no live task outcome. 6.1 F5; A.5
WRA-decoy-execution [6]	Ex	**02**. Executed decoys; usefulness proxy only. 8.1–8.3 T8–11
NET-upstream-local [40]	Ex	**03**. Protected deployment/local serving; topology scoped. IV-C–E TIII–IV
NET-dummy-padding-simulation [40]	Tr	**04**. Synthetic insert/pad; no live execution. VII TIX
EARLY-K-calibration-oracle [3]	Si	**05**. K-specific fit then oracle; not live KV trial. V-A TVI; IV-A
EARLY-semantic-deidentification [3]	Ex	**06**. GPTCache prototype cost; not KV-granularity cost. V-B
WHISPER-randompadding-capture [43]	Ex	**07**. New padded captures; rounded medians. 6.1 T3–4
WHISPER-batching-replay [43]	Tr	**08**. Offline batching; model-dependent result. 6.2 F7
WHISPER-injection-replay [43]	Tr	**09**. Synthetic packets; no live zero-delay claim. 6.3 T5
SPLICE-CTBF-signal [51]	Ex	**10**. Prototype background load; tested signal only. VII-C TII
SPLICE-QCP-cost [51]	Co	**11**. QCP component cost; excludes combined CTBF. VII-C TII
TIME-length-instruction [52]	Ex	**12**. Length instruction; unequal outputs remain. 7.2
TIME-padding-estimate [52]	Si	**13**. Analytic plaintext cost; not network bytes. 7.3
SPEC-padding-REST [42]	Un	**14**. Padding/aggregation; payload cost, placement unverified. 6.1 F6–7 T2
DANGOL-capture [19]	Tr	**15**. Capture transform; distinct from live population. 9.8–9.9 T6
DANGOL-livebinding [19]	Ex	**16**. Live loopback binding; do not join capture accuracy. 9.7, OHTTP paragraph after T5
SIG-common-guardrail‡ [59]	Ex	**17**. Common instruction; not a causal guardrail effect. 4.1–4.2; App. C
SAFE-post-trigger [46]	Ex	**18**. Post-trigger probes; detector cost not service TTFT. 7.2.4 F12; 7.3–7.4
AHB-online-executed [17]	Ex	**19**. Executed UI edits; task/state changes possible. 5.1.2 T1; E.1–E.3
AHB-offline [17]	Tr	**20**. Offline touch edits; no online task damage claim. T1 offline rows; E.1–E.3
KVGOV-partialflush-sim [37]	Si	**21**. Deterministic simulation; not live protected recovery. 5.1–5.3
KVGOV-hardware-gap [37]	Co	**22**. Hardware gap calibration; not protected ASR. 5.7–5.8
KVGOV-HMAC-cost [37]	Co	**23**. HMAC microcost; not cache reuse/task loss. 5.9
TRAFFIC-prompt-reformulation [55]	Ex	**24**. Collected prompt rewrites; task utility unmeasured. V-C1 F9a
TRAFFIC-temperature [55]	Ex	**25**. Collected decoding changes; no monotone benefit. V-C1 F9a
CARLINI-fixed-rate [39]	Un	**26**. Rate/replayed cost; per-token, not request delay. VII F11–12
GAO-zero-copy-off [23]	Co	**27**. Loader component costs; not end-to-end TTFT. 7.1
TDXRAY-oblivious-map [30]	Co	**28**. Lookup microbenchmark; not full inference cost. 6.1 F8 T3
AGENTTELL-fixed-instruction‡ [66]	Ex	**29**. Live local browser tasks; loaded/cold context contrast. 4.3.1; 5 Finding 1
FP-CLOUDFLARE‡ [67]	Ex	**30**. Live access control; not user confidentiality. 6.4 T5
BAR-co-running-noise‡ [24]	Ex	**31**. MIG noise test; not an LLM defense trial. 7.2–7.3 T8
RHYTHM-VPN‡ [38]	Ex	**32**. Live VPN shift; baseline-trained attacker only. VI-B; VII
DEB-filter-origin‡ [47]	Ex	**33**. Filter creates attack view; not mitigation of it. Threat model; 4.2
CACHEPRUNE-selective† [7]	Ex	**34**. Selective cache sharing; direct token recovery/quality. 3.1; 5.1–5.6; T1; App. A
CACHEPRUNE-context† [7]	Ex	**35**. Contextual guessing; distinct from direct recovery. 3.1; 5.1–5.6; T1; App. A
OTRO-unpadded† [32]	Co	**36**. ORAM TTFT/memory; access-count padding excluded. VII-C–E; TIII
OTRO-epochpad† [32]	Si	**37**. Epoch-padding estimate; not measured padded TTFT. VII-C–E; TIII
SPARLEAK-replacement† [28]	Ex	**38**. Sparse replacement/quality; attack cost is separate. 3.1; 4–7; T4
SHAPE-padding-estimate† [29]	Si	**39**. Constant-work proposal/estimate; no executed pair. IX-B1

TABLE 21. COMPLETE HOLDOUT-CODE MATRIX; CODES AND AXES ARE DEFINED IN APPENDIX D. SOURCE-QUALIFIED ROW NOTES ARE IN SUPPLEMENT S28.

Family	Scope	T	M	C	H	N	D	Family	Scope	T	M	C	H	N	D
F01 AgentPrint [4]	C	?	?	?	?	?	?	F42 ML privacy channels [47]	C	?	V	?	?	?	?
F02 UI Traces [5]	C	V	V	V	?	?	?	F43 MoE stealing [53]	C	?	?	?	?	?	?
F03 WRA [6]	C	H	?	?	?	?	?	F44 Energon [21]	C	?	V	?	?	?	?
F04 FP-Agent [67]	C	H	?	X	?	?	?	F45 SafeKV [46]	C	?	V	?	?	?	?
F05 Prompt length [1]	C	H	?	V	?	V	V	F46 InferNet [88]	A	?	V	?	V	?	?
F06 PromptPeek [2]	C	V	?	?	?	V	?	F47 ArchSnoop [27]	C	?	H	?	V	?	?
F07 NetEcho [40]	C	V	?	V	?	?	?	F48 Coding fingerprints [12]	A	X	?	X	?	?	X
F08 Early Bird [3]	C	?	V	?	?	?	?	F49 AHB [17]	C	?	?	X	?	?	?
F09 InputSnatch [49]	C	H	?	?	?	?	?	F50 WildAuth [13]	A	H	?	X	?	?	?
F10 Whisper Leak [43]	C	H	V	?	?	?	?	F51 Cycles [58]	C	X	?	X	?	?	X
F11 Spill the Beans [26]	C	V	?	?	?	?	?	F52 LumiMAS [57]	C	?	V	V	?	?	?
F12 SpliceLeak [51]	C	V	?	?	?	?	?	F53 SymDiag [89]	A	V	V	?	?	?	?
F13 Time Will Tell [52]	C	?	?	?	?	V	V	F54 LeakyLMs [50]	C	?	H	?	V	?	?
F14 Prompt Echo [41]	C	H	V	?	?	?	?	F55 KVGov [37]	C	?	?	?	V	?	?
F15 I Know What You Said [23]	C	H	V	V	V	?	?	F56 Data-centric survey [90]	A	-	-	-	-	-	-
F16 Speculation [42]	C	H	?	?	?	V	?	F57 Serving RCA [35]	C	?	?	X	?	?	?
F17 Behind Bars [24]	C	?	V	?	V	?	?	F58 ZeroPrint [14]	A	?	V	?	?	?	?
F18 Prompt caching [48]	C	?	V	?	?	?	V	F59 Endpoint fingerprints [15]	A	?	?	V	?	?	V
F19 Whose Agent [65]	C	?	?	?	?	?	?	F60 StepFinder [16]	A	H	?	?	?	?	?
F20 Workflow traffic [19]	C	?	?	H	?	?	?	F61 Web-agent detection [56]	C	?	V	?	?	?	?
F21 GPU contention [44]	C	?	?	V	?	V	?	F62 Cross-campaign [63]	C	V	?	V	?	?	?
F22 AgentTell [66]	C	V	?	?	?	V	?	F63 AgentProv [61]	C	?	V	?	?	?	?
F23 Traffic benchmark [55]	C	?	?	H	?	?	?	F64 LiDAR [62]	C	?	V	V	?	?	?
F24 Remote timing [39]	C	?	V	?	?	?	V	F65 LLM-WFIN [34]	C	V	?	?	?	?	?
F25 Persona fingerprint [64]	C	?	?	X	?	?	?	F66 MIRAGE [54]	C	V	V	?	?	?	?
F26 TDXRay [30]	C	?	?	?	?	?	?	F67 Routing metadata [45]	C	V	?	V	?	?	?
F27 Detokenization [33]	C	?	?	X	?	?	?	F68 Shape and Substance [29]	C	V	V	V	V	?	?
F28 Spillage [91]	A	V	?	?	?	?	?	F69 SplitDecoy [36]	C	?	?	?	?	?	?
F29 PlanTwin [92]	A	V	?	?	?	?	?	F70 PAGE404 [25]	C	V	V	?	?	?	?
F30 SICC [93]	A	?	?	?	?	?	?	F71 Edge EM [20]	C	H	?	?	?	?	?
F31 TOPR [94]	A	V	?	?	?	?	?	F72 SparLeak [28]	C	V	V	V	?	?	?
F32 ClawGuard [18]	C	?	?	V	?	?	V	F73 Sparseety [31]	C	V	V	V	?	?	?
F33 SIGLEAK [59]	C	V	?	?	?	?	?	F74 OTRO [32]	C	?	?	?	?	?	?
F34 ProcGrep [60]	C	H	?	V	?	?	?	F75 CachePrune [7]	C	V	V	?	?	?	?
F35 SecEmb [95]	A	?	X	?	?	?	?	F76 Privacy foundations [70]	A	-	-	-	-	-	-
F36 Mobile agents [96]	A	?	?	?	?	?	?	F77 DP-MemView [97]	A	?	?	?	?	?	?
F37 Hidden risks [98]	A	?	?	?	?	?	?	F78 PriCon [99]	A	?	?	?	?	?	?
F38 Browser privacy [100]	A	?	?	V	?	?	?	F79 SCAAR [101]	A	?	?	?	?	?	?
F39 LLMs Have Rhythm [38]	C	?	V	?	?	H	V	F80 CacheSolidarity [102]	A	?	?	?	?	?	?
F40 MoEcho [22]	C	H	V	?	?	V	?	F81 Vision encoder [103]	A	?	?	?	?	?	?
F41 LLM-Fin [79]	A	?	H	?	?	?	?	F82 Split gradients [104]	A	?	?	?	?	?	?

TABLE 22. SENSITIVITY OF REPORTING PATTERNS. FRACTIONS GIVE EXPLICIT / APPLICABLE FAMILY COUNTS; BRACKETED NUMERATORS ALSO ACCEPT P. REMOVING FINAL-SEARCH ADDITIONS EXCLUDES SIX RECORDS FROM FOUR FAMILIES; CONTEXTUAL CONTROLS ARE EXCLUDED IN EVERY ROW. IC SEPARATE MEANS NO SINGLE RECORD CARRIES BOTH EXPLICIT INFERENCE AND COST.

Inventory	R7	R9	R8	R4	R5	Agent R8	IC separate
All mitigation	16/17 [17]	11/19 [15]	4/17 [6]	4/11 [9]	2/11 [2]	0/4 [2]	5/8
Without CachePrune	15/16 [16]	10/18 [14]	3/16 [5]	4/11 [9]	2/11 [2]	0/4 [2]	5/7
Without final-search records	13/13 [13]	9/15 [12]	2/14 [4]	4/9 [8]	2/9 [2]	0/4 [2]	4/6

TABLE 23. COMPLETE CURRENT RECORD-CELL AND PAIR INDEX. R8 USES THE OUTCOME-SPECIFIC APPLICABILITY RULE; THE ORIGINAL 351 CELLS REMAIN ARCHIVED. NUMBERS FOLLOW APPENDIX B, READING THE LEFT BLOCK (01–20) THEN THE RIGHT BLOCK (21–39). EACH NINE-CHARACTER STRING GIVES R1–R9 IN ORDER; B/P/U/A/?/– USE TABLE 10. THE SINGLE HYPHEN IN A STRING MEANS INAPPLICABLE. COHORTS T TRAFFIC, C CACHE, L LOCAL MEMORY, B BEHAVIORAL, G GENERATOR, F FIXED INSTRUCTION, A ACCESS GATE, N CONTENTION, V FILTER-CREATED VIEW.

No.	Group	R1–R9	No.	Group	R1–R9	No.	Group	R1–R9	No.	Group	R1–R9
01	B	BPBBBBB-	11	C	BBB-B-UB	21	C	BBB-BB-U	31	N	BBB-BBUU
02	T	BPB-PB-U	12	T	BBBPUBBUU	22	C	BBB-B--	32	G	BBBUUBBUU
03	T	BBBB?BB-U	13	T	BBP-B-B	23	C	BBB-B-B	33	V	BBB-BBUU
04	T	BBB??BB-P	14	T	BBPPUBB-B	24	G	BPBUUPBPU	34	C	BBB-BBBB
05	C	BBBB?BB-P	15	T	BBBBBBB-B	25	G	BPBUUPBUU	35	C	BBB-BBBB
06	C	BBB-B-UB	16	T	BBB??BB-B	26	T	BBP-B-B	36	L	BBB-B-B
07	T	BBBPUBB-U	17	F	BBB-BBPU	27	L	BBB-P-B	37	L	BBB-BB-P
08	T	BBBPUBB-U	18	C	BBB-BB-P	28	L	BBB-B-BB	38	L	BBBPUBBBU
09	T	BBBPUBB-P	19	B	BBBPUBBBU	29	F	BBB-BBPU	39	L	BBPUUBPUP
10	C	BBB-BBUU	20	B	BBBPUBBU-	30	A	BBB-BBBU			

R1 target, R2 receiver, R3 intervention, R4 protected fitting, R5 matched fitting, R6 workload, R7 inference, R8 utility, R9 cost; B bound, P partial, U unreported, A unavailable, ? unverified, - inapplicable.

Within each nonsingleton group, every unordered pair is included. The 17 scoped-match pairs are: 03/04, 03/07, 03/08, 03/09, 04/07, 04/08, 04/09, 05/34, 07/08, 07/09, 08/09, 15/16, 18/21, 19/20, 24/25, 24/32, 25/32. The 11 unresolved pairs are: 02/12, 02/14, 05/18, 05/21, 12/14, 17/29, 18/34, 18/35, 21/34, 21/35, 37/38. The remaining 105 within-group pairs have a different-object witness; the three singleton groups yield no pairs. Match refers to the specified object, not universal equality of costs, populations or contracts.

The eight different-object pairs within a family are: 05/06, 10/11, 12/13, 21/22, 21/23, 22/23, 34/35, 36/37. All 351 cells and 133 within-group labels are recoverable here; individual source rationales remain in Supplement S29 and S34.

TABLE 24. EVERY FAMILY WITH B IN BOTH INFERENCE AND COST COLUMNS OF TABLE 12. SEPARATE COLUMN WITNESSES DO NOT AUTOMATICALLY FORM ONE ROW-LEVEL RESULT. IDS EXPAND IN APPENDIX B.

Family	Inference record(s)	Cost record(s)	Same-record inference + cost
[3]	EARLY-K-calibration-oracle	EARLY-semantic-deidentification	–
[51]	SPLICE-CTBF-signal	SPLICE-QCP-cost	–
[52]	TIME-length-instruction	TIME-padding-estimate	–
[42]	SPEC-padding-REST	SPEC-padding-REST	SPEC-padding-REST
[19]	DANGOL-capture; DANGOL-livebinding	DANGOL-capture; DANGOL-livebinding	DANGOL-capture; DANGOL-livebinding
[37]	KVGOV-partialflush-sim	KVGOV-HMAC-cost	–
[7]	CACHEPRUNE-selective; CACHEPRUNE-context	CACHEPRUNE-selective; CACHEPRUNE-context	CACHEPRUNE-selective; CACHEPRUNE-context
[32]	OTRO-epochpad	OTRO-unpadded	–

TABLE 25. THE 133 WITHIN-QUESTION INDEX LABELS; 608 OTHER PAIRS HAVE NO DECLARED COMPARISON. A DIFFERENT-OBJECT WITNESS LIMITS A SPECIFIED COMPARISON, NOT ALL COMPARISONS BETWEEN THE STUDIES.

Question	Scoped match	Different object	Unresolved
behavioral humanization	1	2	0
cache service	2	37	6
fixed instruction	0	0	1
generator fingerprint	3	0	0
local memory	0	14	1
traffic envelope	11	52	3
Total	17	105	11

TABLE 26. SENSITIVITY TO THE COMPARISON UNIT. M/D/U: UNANIMOUS SCOPED MATCH/DIFFERENT OBJECT/UNRESOLVED; MIX: CONSTITUENT JUDGMENTS DIFFER. HIDDEN: ORIGINAL WITHIN-QUESTION PAIRS ABSORBED INSIDE A UNIT. NO NEW PAIR IS ADJUDICATED.

Unit	Units	M	D	U	Mix	Hidden
Scoped result records	39	17	105	11	0	0
Shared configuration package	38	16	98	9	1	1
Family and measurement mode	35	10	83	9	1	4
Family only	26	2	31	3	8	15