

# Biometric Authentication

## Lecture 3

### Biometrics Technology: Image & Signal Processing

Biometric Authentication

Lecture 3- 1



## *Outline*

- Digital Image: Introduction
- Basic Processing Technologies:
  - Point (Pixel) Operations
  - Group (Neighborhood) Operations

Biometric Authentication

Lecture 3- 2


# Digital Image: Introduction

Biometric Authentication

Lecture 3- 3

## Digital Image Processing

- Brightness
- Contrast
- Noise reduction
- Edge enhancement
- Zooming
- Object trackers
- Object classification




Biometric Authentication

Lecture 3- 4

## Image Acquisition

- Source of imagery
  - Charge-coupled device (CCD) sensor
- Rectangular array of detectors
- Measure brightness (intensity) and colour
- **Intensity** determined via **sampling over region of pixel.**




Biometric Authentication

Lecture 3- 5

## Digital Image Representation

- Optical image denoted by  $A(x,y)$
- $x$  and  $y$  are spatial co-ordinates
- $A(x,y)$  is the brightness at position  $(x,y)$




The points at which an image is sampled are known as *picture elements*, or *pixels*.

Biometric Authentication

Lecture 3- 6

## Digital Image Representation




picture  
element  
(pixel)

Biometric Authentication

Lecture 3- 7

## Digital Image Representation



- An image is a **spatial presentation** of an object –  
*Matrix representing quantized intensity values.*

Biometric Authentication


Lecture 3- 8

## Image Resolution

- Image resolution: Measure of image quality (No. of pixels,  $M \times N$ )
  - 1280 x 960 (digital camera)
  - 512 x 512 (video camera)
  - 256 x 256 (reasonable processing quality)
- Dynamic range: Measure of the range of brightness values
  - 1 bit (binary image)
  - 8 bits (grey image: 0 for black, 255 for white)
  - 12 bits (medical imagery)
  - 16 bits (Astronomical imagery)
  - 24 bits (colour image)



High




Low

Biometric Authentication

Lecture 3- 9

## Gray-Level Quantisation




- For black and white images, a pixel is a single value integer or *floating point*.
- For display, normally 8 bits per pixel (bpp) is used.
- The human eye cannot resolve to this accuracy. 32 gray levels are usually sufficient (5 bpp).
- At 4 bpp and below, “false contouring” can become apparent.

Biometric Authentication

Lecture 3- 10

# Image Histograms



- Plot of  $N_j$  versus  $j$ : Shows the distribution of image pixels in terms of their gray levels.
- Gray levels  $j=0,1,\dots,255$
- $N_j$ = number of pixels in image with gray level  $j$

Biometric Authentication

Lecture 3- 11

# Bimodal Histograms

Light object(s) against a darker background - 'white hot'







Dark object(s) against a lighter background - 'black hot'



Bright object

Dark background



Lecture 3- 12

# Point (Pixel) Operations

Biometric Authentication


Lecture 3- 13

## Point (Pixel) Operation

- Point operation: A function is applied to every pixel in an image, which operates only on the pixel's current value.
- Thresholding - A mask may be created by setting a pixel value to 1 or 0 depending upon if the current value is above or below a certain threshold value.

Input pixel value,  $I$ , mapped to output pixel value,  $O$ , via transfer function  $T$ .


$$O = T(I)$$



Biometric Authentication

Lecture 3- 14


## Contrast Enhancement: Linear Stretching



Biometric Authentication

Lecture 3- 15

## Brightness



Biometric Authentication

Lecture 3- 16



## Contrast Enhancement: Power Law Function




$$O = I^\gamma$$

- $\gamma < 1$  to enhance contrast in dark regions
- $\gamma > 1$  to enhance contrast in bright regions.

Biometric Authentication

Lecture 3- 17




## Contrast Enhancement: Power Law Function ( $\gamma = 0.5$ )



Biometric Authentication

Lecture 3- 18

## Contrast Enhancement: Power Law Function ( $\gamma = 3.0$ )



Biometric Authentication

Lecture 3- 19

## Contrast Enhancement: Power Law Function

- Look-up Table
  - Transfer function implemented as a look-up table (LUT).
  - Implemented in hardware or software.

$$\gamma=2$$


$I$	$O$
0	0
0.10	0.01
0.20	0.04
0.30	0.09
0.40	0.16
0.50	0.25
0.60	0.36
0.70	0.49
0.80	0.64
0.90	0.81
1.00	1.00

Biometric Authentication

Lecture 3- 20

## Contrast Enhancement: Histogram Equalisation

- Image histograms consisting of peaks and low plains.
- Peaks = many pixels concentrated in a few grey levels
- Plains = small number of pixels distributed over a wider range of grey levels




Biometric Authentication

Figure 3- 21

## Histogram Equalisation

- Expand pixels in peaks over a wider range of gray-levels.
- “Squeeze” low plains pixels into a narrower range of gray levels.
- **Flat** histogram.



Biometric Authentication

Lecture 3- 22

## Contrast Enhancement: Comparison

Original



$\gamma > 1$



Histogram  
equalisation



Biometric Authentication


3- 23

## *Group (Neighborhood) Operations*

Biometric Authentication

Lecture 3- 24

## Why are Neighbourhoods Important?



- Provide context for individual pixels.
- Relationships between neighbours determine image features.

Biometric Authentication

Lecture 3- 25

## Neighbourhood Operations

Noise Reduction

Edge Enhancement



Zooming



Biometric Authentication

Lecture 3- 26

# Convolution

- Consists of filtering an image  $A$  using a filter (mask)  $B$ .
- Mask is a small image whose pixel values are called weights.
- Weights modify relationships between pixels.

Filter,  
mask or  
template **B**

$B_{1,1}$	$B_{1,2}$
$B_{2,1}$	$B_{2,2}$

$2 \times 2$

Input  
image **A**

$A_{1,1}$	$A_{1,2}$	$A_{1,3}$	$A_{1,4}$
$A_{2,1}$	$A_{2,2}$	$A_{2,3}$	$A_{2,4}$
$A_{3,1}$	$A_{3,2}$	$A_{3,3}$	$A_{3,4}$
$A_{4,1}$	$A_{4,2}$	$A_{4,3}$	$A_{4,4}$

$4 \times 4$

Convolved  
Image **C**

$C_{1,1}$	$C_{1,2}$	$C_{1,3}$
$C_{2,1}$	$C_{2,2}$	$C_{2,3}$
$C_{3,1}$	$C_{3,2}$	$C_{3,3}$

$3 \times 3$

=

Biometric Authentication

Lecture 3- 27

# Convolution

$B_{1,1}$	$B_{1,2}$	$A_{1,3}$	$A_{1,4}$
$B_{2,1}$	$B_{2,2}$	$A_{2,3}$	$A_{2,4}$
$A_{3,1}$	$A_{3,2}$	$A_{3,3}$	$A_{3,4}$
$A_{4,1}$	$A_{4,2}$	$A_{4,3}$	$A_{4,4}$

$A_{1,1} \times B_{1,1}$	$A_{1,2} \times B_{1,2}$
$A_{2,1} \times B_{2,1}$	$A_{2,2} \times B_{2,2}$

$$C_{1,1} = \boxed{A_{1,1} \times B_{1,1}} + \boxed{A_{1,2} \times B_{1,2}} + \boxed{A_{2,1} \times B_{2,1}} + \boxed{A_{2,2} \times B_{2,2}}$$

Biometric Authentication

Lecture 3- 28

# Convolution

$A_{1,1}$	$A_{1,2}$	$B_{1,1}$	$B_{1,2}$
$A_{2,1}$	$A_{2,2}$	$B_{2,1}$	$B_{2,2}$
$A_{3,1}$	$A_{3,2}$	$A_{3,3}$	$A_{3,4}$
$A_{4,1}$	$A_{4,2}$	$A_{4,3}$	$A_{4,4}$

$A_{1,3} \times B_{1,1}$	$A_{1,4} \times B_{1,2}$
$A_{2,3} \times B_{2,1}$	$A_{2,4} \times B_{2,2}$

$$C_{1,3} = \boxed{A_{1,3} \times B_{1,1}} + \boxed{A_{1,4} \times B_{1,2}} + \boxed{A_{2,3} \times B_{2,1}} + \boxed{A_{2,4} \times B_{2,2}}$$

Biometric Authentication

Lecture 3- 29

# Convolution

$A_{1,1}$	$A_{1,2}$	$A_{1,3}$	$A_{1,4}$
$B_{2,1}$	$B_{2,2}$	$A_{2,3}$	$A_{2,4}$
$B_{3,1}$	$B_{3,2}$	$A_{3,3}$	$A_{3,4}$
$A_{4,1}$	$A_{4,2}$	$A_{4,3}$	$A_{4,4}$

$A_{2,1} \times B_{1,1}$	$A_{2,2} \times B_{1,2}$
$A_{3,1} \times B_{2,1}$	$A_{3,2} \times B_{2,2}$

$$C_{2,1} = \boxed{A_{2,1} \times B_{1,1}} + \boxed{A_{2,2} \times B_{1,2}} + \boxed{A_{3,1} \times B_{2,1}} + \boxed{A_{3,2} \times B_{2,2}}$$

Biometric Authentication

Lecture 3- 30

## Mathematical Notation

$$C_{1,1} = \boxed{A_{1,1} \times B_{1,1}} + \boxed{A_{1,2} \times B_{1,2}} + \boxed{A_{2,1} \times B_{2,1}} + \boxed{A_{2,2} \times B_{2,2}}$$

$$B = M \times N$$

$$C_{k,l} = \sum_{i=k}^{k+M-1} \sum_{j=l}^{l+N-1} A_{i,j} \times B_{i-k+1,j-l+1}$$

$$\sum_{i=1}^2 i = 1 + 2$$

$$\sum_{i=1}^2 A_i = A_1 + A_2$$

$$\sum_{i=1}^2 \sum_{j=1}^2 A_{i,j} = \sum_{i=1}^2 (A_{i,1} + A_{i,2}) = A_{1,1} + A_{1,2} + A_{2,1} + A_{2,2}$$

Lecture 3- 31

## Summations

$$C_{k,l} = \sum_{i=k}^{k+M-1} \sum_{j=l}^{l+N-1} A_{i,j} \times B_{i-k+1,j-l+1}$$

$$C_{1,1} = \sum_{i=1}^{1+2-1} \sum_{j=1}^{1+2-1} A_{i,j} \times B_{i-1+1,j-1+1}$$

$$= \sum_{i=1}^2 \sum_{j=1}^2 A_{i,j} \times B_{i,j}$$

$$= \sum_{i=1}^2 A_{i,1} \times B_{i,1} + A_{i,2} \times B_{i,2}$$

$$= A_{1,1} \times B_{1,1} + A_{1,2} \times B_{1,2} + A_{2,1} \times B_{2,1} + A_{2,2} \times B_{2,2}$$

$$M=N=2$$

$$k=l=1$$

Biometric Authentication

Lecture 3- 32



# Convolution

Filter,  
mask or  
template

**B**

-1	2
-1	2

$2 \times 2$

Input  
image

**A**

4	4	7	9
4	3	8	9
3	5	9	9
3	6	10	9

$4 \times 4$

Convolved  
Image

**C**

6	23	21
9	26	19
16	27	17

$3 \times 3$

Biometric Authentication

Lecture 3- 33


# Convolution Size

Image size =  $M_1 \times N_1$

Mask size =  $M_2 \times N_2$

Convolution size =  
 $(M_1 - M_2 + 1) \times (N_1 - N_2 + 1)$

Typical Mask sizes  
=  $3 \times 3$ ,  $5 \times 5$ ,  $7 \times 7$ ,  
 $9 \times 9$ ,  $11 \times 11$




What is the convolved image size for a  $128 \times 128$  image and  $7 \times 7$  mask?

Biometric Authentication


Lecture 3- 34

# Noise

- Source of noise = CCD chip.
- Electronic signal fluctuations in detector.
- Caused by thermal energy.
- Worse for infra-red sensors.



image




noise





'grainy' image

# Noise

- Plot of image brightness.
- Vertical slice through image.
- Noise is additive.
- Noise fluctuations are rapid, i.e, high frequency.



## Noise Reduction





- Noise varies above and below uncorrupted image.

Biometric Authentication

Lecture 3- 37

## Noise Reduction-1st principles

- How do we reduce noise?
- Consider a uniform 1-d image  $A$  and add noise.
- Focus on a pixel neighbourhood.
- Central pixel has been increased and neighbouring pixels have decreased.




Biometric Authentication

Lecture 3- 38

## Noise Reduction-1st principles

- Averaging 'smoothes' the noise fluctuations.
- Consider the next pixel  $A_{i+1}$
- Repeat for remainder of pixels.

$$C_{i+1} = \frac{A_i + A_{i+1} + A_{i+2}}{3}$$



Biometric Authentication

Lecture 3- 39

## Noise Reduction- Neighborhood Operations

- All pixels can be averaged by convolving 1-d image  $A$  with mask  $B$  to give enhanced image  $C$ .
- Weights of  $B$  must equal one when added together.

$$\mathbf{C} = \mathbf{A} * \mathbf{B}$$

$$\mathbf{B} = \frac{1}{3} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

- Extend to two dimensions.

$$\mathbf{C} = \mathbf{A} * \mathbf{B}$$

$$\mathbf{B} = [B_1 \ B_2 \ B_3]$$

$$C_i = A_{i-1} \times B_1 + A_i \times B_2 + A_{i+1} \times B_3$$

$$B = \frac{1}{3} [1 \ 1 \ 1]$$


$$C_i = \frac{A_{i-1} + A_i + A_{i+1}}{3}$$

Biometric Authentication

Lecture 3- 40

## Noise Reduction

- Technique relies on high frequency noise fluctuations being 'blocked' by filter. Hence, low-pass filter.
- Fine detail in image may also be smoothed.
- Balance between keeping image fine detail and reducing noise.
- Example:
  - Saturn image coarse detail
  - Boat image contains fine detail
  - Noise reduced but fine detail also smoothed




Biometric Authentication

Lecture 3- 41

## Noise Reduction

- Consider a uniform 1-d image A with a step function.
- Step function corresponds to fine image detail such as an edge.
- Low-pass filter 'blurs' the edge.




Biometric Authentication

Lecture 3- 42

## Noise Reduction-1st principles

- How do we reduce noise without averaging?
- Consider a uniform 1-d image A and add noise.
- Focus on a pixel neighbourhood.
- Non-linear operator?

Median filter!



Biometric Authentication

Lecture 3- 43

## Noise Reduction- Neighborhood Operations

- All pixels can be replaced by neighbourhood median by convolving 1-d image A with median filter B to give enhanced image C.
- Extend to two dimensions.

$$\mathbf{C} = \mathbf{A} * \mathbf{B}$$

$$\mathbf{B} = [B_1 \quad B_2 \quad B_3]$$

$$C_i = \text{median}\{A_{i-1} \times B_1, A_i \times B_2, A_{i+1} \times B_3\}$$

$$\mathbf{B} = [1 \quad 1 \quad 1]$$

$$C_i = \text{median}\{A_{i-1}, A_i, A_{i+1}\}$$

$$C_{k,l} = \text{median}_{i=k:M-1, j=l:N-1} \{A_{i,j} \times B_{i-k+1, j-l+1}\}$$

$$B_{i,j} = 1 \text{ for all } i,j$$

Biometric Authentication

Lecture 3- 44

## Noise reduction

Original



Low-pass



Median




Biometric Authentication


Lecture 3- 45

## Noise reduction

Low-pass



Median



- Low-pass: fine detail smoothed by averaging
- Median: fine detail passed by filter

Biometric Authentication

Lecture 3- 46

# Filter Operations

## 1 Low-Pass Filter

- Class: Image Enhancement/Restoration
- Implementation: Pixel group process and smooth an image

1 1 1	1 1 1	1 2 1
1 1 1	1 2 1	2 4 2
1 1 1	1 1 1	1 2 1
/9	/10	/16

Biometric Authentication

Lecture 3- 47

# Filter Operations

## 2 High-Pass Filter

- Implementation: Pixel group process and sharpen an image

-1 -1 -1	0 -1 0	1 -2 1
-1 9 -1	-1 5 -1	-2 5 -2
-1 -1 -1	0 -1 0	1 -2 1

## 3 Sobel Edge Enhancement

- Implementation: Edge extraction

-1 0 1	-1 -2 -1
-2 0 2	0 0 0
-1 0 1	1 2 1
Vertical mask	Horizontal mask

Biometric Authentication

Lecture 3- 48



## Filter Operations

### 4 Shift and Difference Edge Enhancement

- Implementation: **Vertical, Horizontal and Diagonal Edge extraction**

$$\begin{bmatrix} 0 & 0 & 0 \\ -1 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Vertical

$$\begin{bmatrix} 0 & -1 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Horizontal

$$\begin{bmatrix} -1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Diagonal

### 5 Laplacian Edge Enhancement

- Implementation: **All Edge extraction**

$$\begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}$$

$$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 4 & -1 \\ 0 & -1 & 0 \end{bmatrix}$$

$$\begin{bmatrix} 1 & -2 & 1 \\ -2 & 4 & -2 \\ 1 & -2 & 1 \end{bmatrix}$$

Biometric Authentication

Lecture 3- 49

## Questions?

1. There are two operations (point and neighborhood) introduced by this lecture. How to use these two operations in our biometrics system?
2. Signal/image preprocessing is an important stage in biometrics system. Please list what problems we should solve during this stage.
3. There are some examples of filter operations. Please point out the difference of Low-pass filters, High-pass filters and Edge enhancement filters. Notice that the “0”-Sum mask for Edge enhancement filters and “1”-Sum for others.

Biometric Authentication

Lecture 3- 50

So much for today!



Thank you !!!

Biometric Authentication

Lecture 3- 51