

Министерство транспорта Российской Федерации

**Федеральное государственное автономное образовательное учреждение
высшего образования «Российский университет транспорта» РУТ
(МИИТ)**

Институт управления и цифровых технологий

**Кафедра Цифровые технологии управления транспортными
процессами»**

Отчет по Лабораторной Работе №3

Вариант 13

По дисциплине «Базы данных и экспертные системы»

На тему «SQL (DDL, DCL)»

Выполнил: Воробченко АА

Группа: УПМ-311

Проверил: доцент кафедры ЦТУТП

Козьяков П.О.

Москва

2025

I. Цель работы

Приобрести практические навыки проектирования структуры реляционной базы данных с использованием языка определения данных (DDL) и управления правами доступа с помощью языка контроля данных (DCL), а также развить способность обеспечивать целостность, безопасность и актуальность информации в многопользовательской среде.

II. Задание

1 Создать таблицу Residing (Проживающие)

№ п/п	Имя столбца	Описание	Тип данных	Ограничения целостности
1.	id_residing	id проживания	integer	первичный ключ
2.	id_warrant	id ордера проживания	integer	внешний ключ
3.	id_premises	id помещения	integer	
4.	d_start	дата начала	date	пустые значения запрещены
5.	d_end	дата окончания	date	
6.	id_bas_sal_date	дата перерасчета	date	не пусто

```
CREATE TABLE Residing (  
id_residing INTEGER PRIMARY KEY,  
id_warrant INTEGER,  
id_premises INTEGER,  
d_start DATE NOT NULL,  
d_end DATE,  
id_bas_sal_date INTEGER NOT NULL  
);
```

```
CREATE TABLE Residing (  
id_residing INTEGER PRIMARY KEY,  
id_warrant INTEGER,  
id_premises INTEGER,  
d_start DATE NOT NULL,  
d_end DATE,  
id_bas_sal_date INTEGER NOT NULL  
);
```





Table RESIDING created.

2 Создать таблицу Warrant (Ордер проживающего)

№ п/п	Имя столбца	Описание	Тип данных	Ограничения целостности
1.	id_warrant	id ордера проживания	integer	первичный ключ
2.	id_building	id здания	integer	внешний ключ
3.	id_settling	id заселения	integer	

```
CREATE TABLE Warrant (
    id_warrant INTEGER PRIMARY KEY,
    id_building INTEGER,
    id_settling INTEGER
);
```



3 Создать таблицу Building (Здания)

№ п/п	Имя столбца	Описание	Тип данных	Ограничения целостности
1.	id_building	id здания	integer	первичный ключ
2.	b_name	наименование	char(10)	
3.	b_start	дата начала	date	не пусто
4.	b_note	примечание	char(10)	

```
CREATE TABLE Building (
    id_building INTEGER PRIMARY KEY,
    b_name CHAR(100),
    b_start DATE NOT NULL,
    b_note CHAR(100)
);
```

```
CREATE TABLE Building (
    id_building INTEGER PRIMARY KEY,
    b_name CHAR(100),
    b_start DATE NOT NULL,
    b_note CHAR(100)
);
```

Script Output x Query Result x Query

Task completed in 0,07 seconds

Table BUILDING created.

4 Создать таблицу Premises (Помещения)

№ п/ п	Имя столбца	Описание	Тип данных	Ограничения целостности
1.	id_premises	id помещения	integer	первичный ключ
2.	p_name	название	varchar(30)	не пусто
3.	p_d_start	дата начала	date	не пусто
4.	id_building	id здания	integer	внешний ключ

```
CREATE TABLE Premises (
    id_premises INTEGER PRIMARY KEY,
    p_name VARCHAR(30) NOT NULL,
    p_d_start DATE NOT NULL,
    id_building INTEGER
);
```

```
CREATE TABLE Premises (
    id_premises INTEGER PRIMARY KEY,
    p_name VARCHAR(30) NOT NULL,
    p_d_start DATE NOT NULL,
    id_building INTEGER
);
```

Script Output x Query Result x Query

Task completed in 0,07 seconds

Table PREMISES created.

5 Создать таблицу Settling (Заселение)

№ п/п	Имя столбца	Описание	Тип данных	Ограничения целостности
1.	id_settling	id заселения	integer	первичный ключ
2.	id_e	id человека	varchar(30)	не пусто
3.	d_start	дата начала	date	

```
CREATE TABLE Settling (  
    id_settling INTEGER PRIMARY KEY,  
    id_e VARCHAR(30) NOT NULL,  
    d_start DATE  
);
```

```
CREATE TABLE Settling (  
    id_settling INTEGER PRIMARY KEY,  
    id_e VARCHAR(30) NOT NULL,  
    d_start DATE  
);
```




Table SETTLING created.

Теперь когда все таблицы созданы укажем все необходимые внешние ключи:

```
ALTER TABLE Residing  
ADD CONSTRAINT fk_residing_warrant  
FOREIGN KEY (id_warrant) REFERENCES Warrant(id_warrant);
```

```
ALTER TABLE Residing  
ADD CONSTRAINT fk_residing_premises  
FOREIGN KEY (id_premises) REFERENCES Premises(id_premises);
```

```
ALTER TABLE Warrant  
ADD CONSTRAINT fk_warrant_building  
FOREIGN KEY (id_building) REFERENCES Building(id_building);
```

```
ALTER TABLE Premises  
ADD CONSTRAINT fk_premises_building  
FOREIGN KEY (id_building) REFERENCES Building(id_building);
```

```

ALTER TABLE Residing
ADD CONSTRAINT fk_residing_warrant
FOREIGN KEY (id_warrant) REFERENCES Warrant(id_warrant);

ALTER TABLE Residing
ADD CONSTRAINT fk_residing_premises
FOREIGN KEY (id_premises) REFERENCES Premises(id_premises);

ALTER TABLE Warrant
ADD CONSTRAINT fk_warrant_building
FOREIGN KEY (id_building) REFERENCES Building(id_building);

ALTER TABLE Premises
ADD CONSTRAINT fk_premises_building
FOREIGN KEY (id_building) REFERENCES Building(id_building);

```




Table RESIDING altered.

Table RESIDING altered.

Table WARRANT altered.

Table PREMISES altered.

6 Указать для таблицы Warrant внешний ключ (id_settling) и задать ограничение –

```

ALTER TABLE Warrant
ADD CONSTRAINT fk_warrant_settling
FOREIGN KEY (id_settling) REFERENCES Settling(id_settling);
ALTER TABLE Warrant
ADD CONSTRAINT check_warrant_gt_settling
CHECK (id_warrant > id_settling);

```

```

ALTER TABLE Warrant
ADD CONSTRAINT fk_warrant_settling
FOREIGN KEY (id_settling) REFERENCES Settling(id_settling);

ALTER TABLE Warrant
ADD CONSTRAINT check_warrant_gt_settling
CHECK (id_warrant > id_settling);

```




Table WARRANT altered.

Table WARRANT altered.

7 Добавить в таблицу Building ограничение – наименование здания не должно быть пустым, по умолчанию «_».

```
ALTER TABLE Building
MODIFY b_name CHAR(10) DEFAULT '_' NOT NULL;
```




Table RESIDING altered.

Table RESIDING altered.

Table WARRANT altered.

Table PREMISES altered.

8 Вставить в таблицы следующие значения:

1. Building



id_building	b_name	b_note	b_start
11	K-1	Здание учебного корпуса № 1	01.01.2010
17	3O-1	Здание общежития № 1	01.01.2010
18	3O-2	Здание общежития № 2	01.01.2010

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
(11, 'K-1', 'Здание учебного корпуса № 1',
TO_DATE('01.01.2010', 'DD.MM.YYYY'));
```

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
(17, '3O-1', 'Здание общежития № 1', TO_DATE('01.01.2010', 'DD.MM.YYYY'));
```

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
(18, '3O-2', 'Здание общежития № 2', TO_DATE('01.01.2010', 'DD.MM.YYYY'));
```

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
(18, '3O-2', 'Здание общежития № 2', TO_DATE('01.01.2010', 'DD.MM.YYYY'));
```



1 row inserted.

1 row inserted.

```
SELECT * FROM Building;
```

		SELECT * FROM Building;
--	--	--------------------------------

Script Output x		Query Result x	
All Rows Fetched: 3 in 0,004 seconds			
ID_BUILDING	B_NAME	B_START	B_NOTE
1	11 K-1	01 ЯНВ 2010	Здание учебного корпуса № 1
2	17 30-1	01 ЯНВ 2010	Здание общежития № 1
3	18 30-2	01 ЯНВ 2010	Здание общежития № 2

2. Settling

id_settling	id_e	d_start
50	1	01.08.2011
51	2	01.09.2011
52	4	15.08.2011

```
INSERT INTO Settling (id_settling, id_e, d_start) VALUES
(50, '1', TO_DATE('01.08.2011', 'DD.MM.YYYY'));
```

```
INSERT INTO Settling (id_settling, id_e, d_start) VALUES
(51, '2', TO_DATE('01.09.2011', 'DD.MM.YYYY'));
```

```
INSERT INTO Settling (id_settling, id_e, d_start) VALUES
(52, '4', TO_DATE('15.08.2011', 'DD.MM.YYYY'));
```

		INSERT INTO Settling (id_settling, id_e, d_start) VALUES (52, '4', TO_DATE('15.08.2011', 'DD.MM.YYYY'));
--	--	---

Query Result x		Script Output x	
Task completed in 0,028 seconds			
1 row inserted.			
1 row inserted.			
1 row inserted.			

```
select * from Settling;
```

SELECT * FROM Settling;				
Script Output x Query Result x				
SQL All Rows Fetched: 3 in 0				
	ID_SETTLING	ID_E	D_START	
1	50	1	01 ABΓ 2011	
2	51	2	01 CEH 2011	
3	52	4	15 ABΓ 2011	

3. Premises

id_premises	name	p_d_start	p_area	id_building
1	110	22.06.2010	2	17
2	112	22.06.2010	5	18
4	115	22.06.2010	2	18
5	1110	22.06.2010	3	17
7	211	22.05.2010	4	17
8	1111	22.05.2010	50	11

```
ALTER TABLE Premises ADD p_area NUMBER;
```

ALTER TABLE Premises ADD p_area NUMBER;				
Query Result x Script Output x				
Task completed in 0,098 seconds				
Table PREMISES altered.				

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES
(1, '110', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 2, 17);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES
(2, '112', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 5, 18);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES
(4, '115', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 2, 18);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES
(5, '1110', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 3, 17);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES
(7, '211', TO_DATE('22.05.2010', 'DD.MM.YYYY'), 4, 17);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES
(8, '1111', TO_DATE('22.05.2010', 'DD.MM.YYYY'), 50, 11);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building) VALU
(8, '1111', TO_DATE('22.05.2010', 'DD.MM.YYYY'), 50, 11); |
```

Script Output x

Task completed in 0,055 seconds

1 row inserted.

1 row inserted.

```
SELECT * FROM Premises;
```

```
SELECT * FROM Premises;
```

Script Output x

Query Result x

All Rows Fetched: 6 in 0,066 seconds

	ID_PREMISES	P_NAME	P_D_START	ID_BUILDING	P_AREA
1	1 110	22 ИЮН 2010	17	2	
2	2 112	22 ИЮН 2010	18	5	
3	4 115	22 ИЮН 2010	18	2	
4	5 1110	22 ИЮН 2010	17	3	
5	7 211	22 МАЙ 2010	17	4	
6	8 1111	22 МАЙ 2010	11	50	

4. Warrant

id_warra nt	id_buildi ng	id_settling
400	17	50
404	17	52
404	18	52
406	17	51

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(400, 17, 50);
```

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(404, 17, 52);
```

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(406, 17, 51);
```

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(406, 17, 51);|
```

Query Result x Script Output x
Task completed in 0,047 seconds

1 row inserted.

1 row inserted.

1 row inserted.

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(404, 18, 52);
```

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(404, 17, 50);
```

Query Result x Script Output x
Task completed in 0,057 seconds

Error starting at line : 1 in command -

```
INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES  
(404, 17, 50)
```

Error report -

ORA-00001: уникальное ограничение (SYSTEM.SYS_C008535) нарушено в столбцах таблицы S
ORA-03301: (сведения ORA-00001) строка со значениями столбцов (ID_WARRANT:404) уже с

<https://docs.oracle.com/error-help/db/ora-00001/>

More Details :

<https://docs.oracle.com/error-help/db/ora-00001/>

<https://docs.oracle.com/error-help/db/ora-03301/>

```
select * from Warrant;
```

SELECT * FROM Warrant;

	ID_WARRANT	ID_BUILDING	ID_SETTLING
1	400	17	50
2	404	17	52
3	406	17	51

5. Residing

id_residing	id_warrant	id_premises	d_start	d_end	id_bas_sal
301	400	5	02.08.2011	30.09.2011	90
302	404	7	15.08.2011	15.09.2011	91
305	404	2	16.09.2011	30.09.2011	92
306	400	1	01.10.2011		93
307	406	1	01.08.2011		94

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
id_bas_sal_date)
VALUES (301, 400, 5, TO_DATE('02.08.2011', 'DD.MM.YYYY'),
TO_DATE('30.09.2011', 'DD.MM.YYYY'), 90);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
id_bas_sal_date)
VALUES (302, 404, 7, TO_DATE('15.08.2011', 'DD.MM.YYYY'),
TO_DATE('15.09.2011', 'DD.MM.YYYY'), 91);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
id_bas_sal_date)
VALUES (305, 404, 2, TO_DATE('16.09.2011', 'DD.MM.YYYY'),
TO_DATE('30.09.2011', 'DD.MM.YYYY'), 92);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
id_bas_sal_date)
VALUES (306, 400, 1, TO_DATE('01.10.2011', 'DD.MM.YYYY'), NULL, 93);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
id_bas_sal_date)
VALUES (307, 406, 1, TO_DATE('01.08.2011', 'DD.MM.YYYY'), NULL, 94);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
VALUES (307, 406, 1, TO_DATE('01.08.2011', 'DD.MM.YYYY'), NULL, 94);
```

Script Output x Query Result x

Task completed in 0,027 seconds

1 row inserted.

1 row inserted.

1 row inserted.

1 row inserted.

1 row inserted.

```
select * from Residing;
```

```
SELECT * FROM Residing;
```

Script Output x Query Result x

All Rows Fetched: 5 in 0,018 seconds

	ID_RESIDING	ID_WARRANT	ID_PREMISES	D_START	D_END	I...
1	301	400		5 02 ABГ 2011	30 CEH 2011	90
2	302	404		7 15 ABГ 2011	15 CEH 2011	91
3	305	404		2 16 CEH 2011	30 CEH 2011	92
4	306	400		1 01 OKT 2011	(null)	93
5	307	406		1 01 ABГ 2011	(null)	94

9 Изменить дату окончания проживания у id_warrant = 406 на «01.06.2012».

```
UPDATE Residing
SET d_end = TO_DATE('01.06.2012', 'DD.MM.YYYY')
WHERE id_warrant = 406;
```

```
UPDATE Residing
SET d_end = TO_DATE('01.06.2012', 'DD.MM.YYYY')
WHERE id_warrant = 406;
```

Script Output x

Task completed in 0,045 seconds

1 row updated.

```
select * from Residing where id_warrant=406;
```

```
SELECT * FROM Residing WHERE id_warrant = 406;
```

Script Output x Query Result x

SQL | All Rows Fetched: 1 in 0,009 seconds

ID_RESIDING	ID_WARRANT	ID_PREMISES	D_START	D_END	ID_BAS_SAL_DATE
1	307	406	101 ABT 2011 01	100H 2012	94

10 Создать пользователей user1, user2, user3, user4.

```
CREATE USER user1 IDENTIFIED BY password1;
CREATE USER user2 IDENTIFIED BY password2;
CREATE USER user3 IDENTIFIED BY password3;
CREATE USER user4 IDENTIFIED BY password4;
```

```
CREATE USER user1 IDENTIFIED BY password1;
CREATE USER user2 IDENTIFIED BY password2;
CREATE USER user3 IDENTIFIED BY password3;
CREATE USER user4 IDENTIFIED BY password4;
```

Script Output x Query Result x Query Result 1 x

Task completed in 0,07 seconds

User USER1 created.

User USER2 created.

User USER3 created.

User USER4 created.

```
SELECT *
FROM dba_users
WHERE username IN ('USER1', 'USER2', 'USER3', 'USER4');
```


13 Передать право user4 выполнять вставку и обновление таблицы Warrant, если у id_settling дата начала не равна пустоте.

```
GRANT CREATE SESSION TO user4;
```

```
CREATE OR REPLACE VIEW warrant_view AS
SELECT id_warrant, id_building, id_settling
FROM Warrant
WHERE id_settling IS NOT NULL
WITH CHECK OPTION;
```

```
CREATE OR REPLACE VIEW Warrant_View AS
SELECT id_warrant, id_building, id_settling
FROM Warrant
WHERE id_settling IS NOT NULL
WITH CHECK OPTION;
```

Script Output x Query Result x
Task completed in 0,035 seconds

View WARRANT_VIEW created.

```
GRANT INSERT, UPDATE ON warrant_view TO user4;
```

```
GRANT INSERT, UPDATE ON warrant_view TO user4;
```

Script Output x Query Result x Query Result 1 x
Task completed in 0,07 seconds

Grant succeeded.

lab_3_db.sql x user_2~1 x user_4.sql x user_1.sql x SETTling x

Worksheet Query Builder

```
--дата не пустое
INSERT INTO SYSTEM.Warrant_View (id_warrant, id_building, id_settling)
VALUES (409, 17, 50);

--дата пустое
INSERT INTO SYSTEM.Warrant_View (id_warrant, id_building, id_settling)
VALUES (410, 18, NULL);
```

Script Output x
Task completed in 0,071 seconds

1 row inserted.

Error starting at line : 6 in command -
INSERT INTO SYSTEM.Warrant_View (id_warrant, id_building, id_settling)
VALUES (410, 18, NULL)
Error at Command Line : 6 Column : 20
Error report -
SQL Error: ORA-01402: представление WITH CHECK OPTION не соответствует фразе WHERE

<https://docs.oracle.com/error-help/db/ora-01402/01402.00000-> "view WITH CHECK OPTION where-clause violation"

*Cause: An INSERT or UPDATE statement was attempted on a view created with the CHECK OPTION. This would have resulted in the creation of a row that would not satisfy the view's WHERE clause.

*Action: Examine the view's WHERE clause in the dictionary table VIEWS. If the current view does not have the CHECK OPTION, then its FROM clause must reference a second view that is defined using the CHECK OPTION. The second view's WHERE clause must also be satisfied by any INSERT or UPDATE statements. To insert the row, it may be necessary to insert it directly into the underlying table, rather than through the view.

More Details :
<https://docs.oracle.com/error-help/db/ora-01402/>

14 Разрешить user1 просматривать все Проживания кроме тех, которые не имеют даты

```
GRANT CREATE SESSION TO user1;
```

```
CREATE OR REPLACE VIEW Residing_With_EndDate AS  
SELECT * FROM Residing WHERE d_end IS NOT NULL;
```

```
GRANT SELECT ON Residing_With_EndDate TO user1;  
GRANT SELECT ON Settling TO user2 WITH GRANT OPTION;
```

```
GRANT CREATE SESSION TO user2;  
ALTER USER user2 IDENTIFIED BY password2;
```

```
REVOKE SELECT ON Settling FROM user2;
```

Script Output x Query Result x Query Result 1 x

Task completed in 0,07 seconds

Grant succeeded.

lab_3_db.sql x user_2~1 x user_4.sql x user_1.sql x SETTLING x

Query Builder

```
SELECT id_residing, d_start, d_end  
FROM SYSTEM.Residing_With_EndDate  
ORDER BY id_residing;
```

Query Result x

All Rows Fetched: 4 in 0,002 seconds

	ID_RESIDING	D_START	D_END
1	301	02.08.11	30.09.11
2	302	15.08.11	15.09.11
3	305	16.09.11	30.09.11
4	307	01.08.11	01.06.12

II. Вывод

В этой лабораторной работе я успешно создал базу данных для учета проживания в общежитиях.

Что было сделано:

1. Создал 5 связанных таблиц с данными о зданиях, помещениях, ордерах на проживание и самих проживающих.
2. Настроил защиту данных - создал 4 пользователей с разными правами:
 - User1 может только смотреть данные о проживании и менять даты
 - User2 и User3 могут просматривать информацию о заселениях
 - User4 может добавлять новые ордера, но только с заполненными данными

Результат: База данных надежно защищена, разные пользователи имеют доступ только к нужной им информации, а данные сохраняются в целости и сохранности.

--1--

```
CREATE OR REPLACE PROCEDURE settle_person(  
    p_id_warrant IN INTEGER,  
    p_id_premises IN INTEGER,  
    p_id_bas_sal_date IN INTEGER,  
    p_d_start IN DATE DEFAULT SYSDATE  
)  
IS  
    v_current_residing_id INTEGER;  
    v_free_premises_id INTEGER;  
    v_building_id INTEGER;  
BEGIN
```

```

-- Пробуем найти активное проживание
BEGIN
    SELECT id_residing INTO v_current_residing_id
    FROM Residing
    WHERE id_warrant = p_id_warrant
      AND d_end IS NULL
      AND ROWNUM = 1;

    -- Выделяем
    UPDATE Residing
    SET d_end = p_d_start
    WHERE id_residing = v_current_residing_id;

    -- Заселяем в новую
    INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start,
id_bas_sal_date)
    VALUES (
        (SELECT COALESCE(MAX(id_residing), 0) + 1 FROM Residing),
        p_id_warrant,
        p_id_premises,
        p_d_start,
        p_id_bas_sal_date
    );

EXCEPTION
    WHEN NO_DATA_FOUND THEN
        -- Если проживания нет, ищем здание по ордеру
        SELECT id_building INTO v_building_id
        FROM Warrant
        WHERE id_warrant = p_id_warrant;

        -- Ищем свободную комнату
        SELECT id_premises INTO v_free_premises_id
        FROM Premises p
        WHERE p.id_building = v_building_id
          AND NOT EXISTS (
              SELECT 1
              FROM Residing r
              WHERE r.id_premises = p.id_premises
                AND (r.d_end IS NULL OR r.d_end > p_d_start)
                AND r.d_start <= p_d_start
          )
          AND ROWNUM = 1;

```

```

        INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start,
id_bas_sal_date)
        VALUES (
            (SELECT COALESCE(MAX(id_residing), 0) + 1 FROM Residing),
            p_id_warrant,
            v_free_premises_id,
            p_d_start,
            p_id_bas_sal_date
        );
    END;
END settle_person;
/
--2--
CREATE OR REPLACE FUNCTION count_free_premises(
    p_id_building IN INTEGER,
    p_date IN DATE DEFAULT SYSDATE
) RETURN INTEGER
IS
    v_total_premises INTEGER;
    v_occupied_premises INTEGER;
BEGIN
    -- Общее количество комнат в здании
    SELECT COUNT(*) INTO v_total_premises
    FROM Premises
    WHERE id_building = p_id_building;

    -- Количество занятых комнат на дату
    SELECT COUNT(DISTINCT r.id_premises) INTO v_occupied_premises
    FROM Residing r
    JOIN Premises p ON r.id_premises = p.id_premises
    WHERE p.id_building = p_id_building
        AND r.d_start <= p_date
        AND (r.d_end IS NULL OR r.d_end > p_date);

    RETURN v_total_premises - v_occupied_premises;
END count_free_premises;

--3--
CREATE OR REPLACE TRIGGER trg_residing_bas_sal_date
BEFORE INSERT ON Residing
FOR EACH ROW
BEGIN
    IF :NEW.id_bas_sal_date IS NULL THEN
        :NEW.id_bas_sal_date := TO_NUMBER(TO_CHAR(SYSDATE,
'YYYYMMDD'));
    
```

```

    END IF;
END;

--4--
-- Создаем последовательность
CREATE SEQUENCE seq_settling_id
START WITH 53
INCREMENT BY 1
NOCACHE
NOMAXVALUE;

-- Триггер для автоматической установки id_settling
CREATE OR REPLACE TRIGGER trg_settling_id
BEFORE INSERT ON Settling
FOR EACH ROW
BEGIN
    IF :NEW.id_settling IS NULL THEN
        SELECT seq_settling_id.NEXTVAL INTO :NEW.id_settling FROM DUAL;
    END IF;
END;

--5--
ALTER TABLE Warrant ADD Kol_war NUMBER DEFAULT 0;

CREATE OR REPLACE TRIGGER trg_increment_kol_war
AFTER INSERT ON Settling
FOR EACH ROW
BEGIN
    UPDATE Warrant
    SET Kol_war = NVL(Kol_war, 0) + 1
    WHERE id_settling = :NEW.id_settling;
END;

--TEST--
--1--
-- Посмотрим, кто сейчас живет в комнате №1 по ордеру 400
SELECT * FROM Residing WHERE id_warrant = 400 AND d_end IS NULL;

-- Выполняем тест
BEGIN
    -- Переселяем ордер 400 в комнату 1
    -- 99 - это значение для id_bas_sal_date
    settle_person(400, 1, 99, SYSDATE);
    COMMIT;

```

```

END;
/

-- Смотрим результат
SELECT id_residing, id_warrant, id_premises, d_start, d_end, id_bas_sal_date
FROM Residing
WHERE id_warrant = 400
ORDER BY d_start DESC;

--2--
SELECT
    'On Date 01.01.2035' as test_case,
    count_free_premises(17, TO_DATE('01.01.2035', 'DD.MM.YYYY')) as
free_rooms
FROM DUAL;

--3--
--текущая дата по каденд
SELECT TO_CHAR(SYSDATE, 'YYYYMMDD') AS expected_value FROM
DUAL;

SELECT * FROM Residing;

-- Вставляем запись, "забыв" про поле с датой
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start)
VALUES (
    (SELECT MAX(id_residing) + 1 FROM Residing),
    400,
    1,
    SYSDATE
);
COMMIT;

SELECT * FROM Residing;

--4--
--Смотрим текущий максимум в таблице
SELECT MAX(id_settling) AS max_id_now FROM Settling;

INSERT INTO Settling (id_e, d_start)
VALUES ('999', SYSDATE);

-- Обязательно фиксируем, иначе данные не запишутся
COMMIT;

```

```
SELECT id_settling, id_e, d_start
FROM Settling
WHERE id_e = '999';
```

--5--

-----333333

```
CREATE TABLE Residing (
    id_residing INTEGER PRIMARY KEY,
    id_warrant INTEGER,
    id_premises INTEGER,
    d_start DATE NOT NULL,
    d_end DATE,
    id_bas_sal_date INTEGER NOT NULL
);
```

```
CREATE TABLE Warrant (
    id_warrant INTEGER PRIMARY KEY,
    id_building INTEGER,
    id_settling INTEGER
);
```

```
CREATE TABLE Building (
    id_building INTEGER PRIMARY KEY,
    b_name CHAR(100),
    b_start DATE NOT NULL,
```

```

        b_note CHAR(100)

    );

CREATE TABLE Premises (

    id_premises INTEGER PRIMARY KEY,

    p_name VARCHAR(30) NOT NULL,

    p_d_start DATE NOT NULL,

    id_building INTEGER

);

CREATE TABLE Settling (

    id_settling INTEGER PRIMARY KEY,

    id_e VARCHAR(30) NOT NULL,

    d_start DATE

);

ALTER TABLE Residing

ADD CONSTRAINT fk_residing_warrant

FOREIGN KEY (id_warrant) REFERENCES Warrant(id_warrant);

ALTER TABLE Residing

ADD CONSTRAINT fk_residing_premises

FOREIGN KEY (id_premises) REFERENCES Premises(id_premises);

ALTER TABLE Warrant

ADD CONSTRAINT fk_warrant_building

```

```
FOREIGN KEY (id_building) REFERENCES Building(id_building);
```

```
ALTER TABLE Premises
```

```
ADD CONSTRAINT fk_premises_building
```

```
FOREIGN KEY (id_building) REFERENCES Building(id_building);
```

```
ALTER TABLE Warrant
```

```
ADD CONSTRAINT fk_warrant_settling
```

```
FOREIGN KEY (id_settling) REFERENCES Settling(id_settling);
```

```
ALTER TABLE Warrant
```

```
ADD CONSTRAINT check_warrant_gt_settling
```

```
CHECK (id_warrant > id_settling);
```

```
ALTER TABLE Building
```

```
MODIFY b_name CHAR(10) DEFAULT '_' NOT NULL;
```

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
```

```
(11, 'К-1', 'Здание учебного корпуса № 1',  
TO_DATE('01.01.2010','DD.MM.YYYY'));
```

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
```

```
(17, 'ЗО-1', 'Здание общежития № 1', TO_DATE('01.01.2010',  
'DD.MM.YYYY'));
```

```
INSERT INTO Building (id_building, b_name, b_note, b_start) VALUES
```

```
(18, '3O-2', 'Здание общежития № 2', TO_DATE('01.01.2010',  
'DD.MM.YYYY'));
```

```
INSERT INTO Settling (id_settling, id_e, d_start) VALUES
```

```
(50, '1', TO_DATE('01.08.2011', 'DD.MM.YYYY'));
```

```
INSERT INTO Settling (id_settling, id_e, d_start) VALUES
```

```
(51, '2', TO_DATE('01.09.2011', 'DD.MM.YYYY'));
```

```
INSERT INTO Settling (id_settling, id_e, d_start) VALUES
```

```
(52, '4', TO_DATE('15.08.2011', 'DD.MM.YYYY'));
```

```
ALTER TABLE Premises ADD p_area NUMBER;
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)  
VALUES
```

```
(1, '110', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 2, 17);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)  
VALUES
```

```
(2, '112', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 5, 18);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)  
VALUES
```

```
(4, '115', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 2, 18);
```

```
INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)  
VALUES
```

(5, '1110', TO_DATE('22.06.2010', 'DD.MM.YYYY'), 3, 17);

INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES

(7, '211', TO_DATE('22.05.2010', 'DD.MM.YYYY'), 4, 17);

INSERT INTO Premises (id_premises, p_name, p_d_start, p_area, id_building)
VALUES

(8, '1111', TO_DATE('22.05.2010', 'DD.MM.YYYY'), 50, 11);

INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES

(400, 17, 50);

INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES

(404, 17, 52);

INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES

(406, 17, 51);

INSERT INTO Warrant (id_warrant, id_building, id_settling) VALUES

(404, 18, 52);

INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,
id_bas_sal_date)

VALUES (301, 400, 5, TO_DATE('02.08.2011', 'DD.MM.YYYY'),
TO_DATE('30.09.2011', 'DD.MM.YYYY'), 90);

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,  
id_bas_sal_date)
```

```
VALUES (302, 404, 7, TO_DATE('15.08.2011', 'DD.MM.YYYY'),  
TO_DATE('15.09.2011', 'DD.MM.YYYY'), 91);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,  
id_bas_sal_date)
```

```
VALUES (305, 404, 2, TO_DATE('16.09.2011', 'DD.MM.YYYY'),  
TO_DATE('30.09.2011', 'DD.MM.YYYY'), 92);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,  
id_bas_sal_date)
```

```
VALUES (306, 400, 1, TO_DATE('01.10.2011', 'DD.MM.YYYY'), NULL, 93);
```

```
INSERT INTO Residing (id_residing, id_warrant, id_premises, d_start, d_end,  
id_bas_sal_date)
```

```
VALUES (307, 406, 1, TO_DATE('01.08.2011', 'DD.MM.YYYY'), NULL, 94);
```

```
UPDATE Residing
```

```
SET d_end = TO_DATE('01.06.2012', 'DD.MM.YYYY')
```

```
WHERE id_warrant = 406;
```