

Team notebook

NCTU Daisengen

September 4, 2021



Contents

1 Algorithms	2
1.1 Mo's algorithm on trees	2
1.2 Mo's algorithm	3
1.3 sliding window	3
2 Basics	4
2.1 default code	4
3 Data structures	4
3.1 hash table	4
3.2 heavy light decomposition	4
3.3 persistent array	5
3.4 persistent seg tree	6
3.5 persistent trie	7
3.6 segment tree	8
3.7 sparse table	10
3.8 splay tree	10
3.9 STL order statistics tree II	11
3.10 STL order statistics tree	12
3.11 STL Treap	13

3.12 trie	13
3.13 wavelet tree	13
4 DP Optimizations	14
4.1 convex hull trick	14
4.2 divide and conquer	16
5 Geometry	16
6 Graphs	16
6.1 bridges	16
6.2 directed mst	17
6.3 karp min mean cycle	18
6.4 konig's theorem	19
6.5 minimum path cover in DAG	19
6.6 SCC kosaraju	19
6.7 tarjan scc	20
6.8 two sat (with kosaraju)	20
7 Math	22
7.1 fft	22
7.2 fibonacci properties	23
7.3 sigma function	24
7.4 triangles	24
8 Matrix	24
9 Misc	24

10 Number theory	24
10.1 convolution	24
10.2 diophantine equations	25
10.3 discrete logarithm	26
10.4 miller rabin	26
10.5 number theoretic transform	27
10.6 pollard rho factorize	27
11 Strings	28
11.1 Incremental Aho Corasick	28
11.2 minimal string rotation	29
11.3 suffix array	30
11.4 suffix automaton	31
11.5 z algorithm	31

1 Algorithms

1.1 Mo's algorithm on trees

```

/**
problems:
- https://codeforces.com/gym/101161 problem E
*/
void flat(vector<vector<edge>> &g, vector<int> &a,
vector<int> &le, vector<int> &ri, vector<int> &cost,
int node, int pi, int &ts, int w) {

    cost[node] = w;
    le[node] = ts;
    a[ts] = node;
    ts++;
    for (auto e : g[node]) {
        if (e.to == pi) continue;
        flat(g, a, le, ri, cost, e.to, node, ts, e.w);
    }
    ri[node] = ts;
    a[ts] = node;
    ts++;
}

/**

```

```

* Case when the cost is in the edges.
* */
void compute_queries(vector<vector<edge>> &g) {
    // g is undirected
    int n = g.size();

    lca_tree.init(g, 0);

    vector<int> a(2 * n), le(n), ri(n), cost(n);
    // a: nodes in the flatten array
    // le: left id of the given node
    // ri: right id of the given node
    // cost: cost of the edge from the node to the parent

    int ts = 0; // timestamp
    flat(g, a, le, ri, cost, 0, -1, ts, 0);

    int q; cin >> q;
    vector<query> queries(q);
    for (int i = 0; i < q; i++) {
        int u, v;
        cin >> u >> v;
        u--; v--;
        int lca = lca_tree.query(u, v);
        if (le[u] > le[v])
            swap(u, v);
        queries[i].id = i;
        queries[i].lca = lca;
        queries[i].u = u;
        queries[i].v = v;
        if (lca == u) {
            queries[i].a = le[u] + 1;
            queries[i].b = le[v];
        } else {
            queries[i].a = ri[u];
            queries[i].b = le[v];
        }
    }
    solve_mo(queries, a, le, cost); // this is the usual algorithm
}

```

1.2 Mo's algorithm

```

const int MN = 5 * 100000 + 1;
const int SN = 708;

struct Query {
    int a, b, id;
    Query() {}
    Query(int x, int y, int i) : a(x), b(y), id(i) {}

    bool operator<(const Query &o) const {
        if (a / SN != o.a / SN) return a < o.a;
        return a / SN & 1 ? b < o.b : b > o.b;
    }
};

struct DS {
    DS() : {}

    void Insert(int x) {}

    void Erase(int x) {}

    long long Query() {}
};

Query s[MN];
int ans[MN];
DS active;

int main() {
    int n;
    cin >> n;
    vector<int> a(n);
    for (auto &i : a) cin >> i;

    int q;
    cin >> q;
    for (int i = 0; i < q; ++i) {
        int b, e;
        cin >> b >> e;
        b--;
        e--;

```

```

        s[i] = Query(b, e, i);
    }

    sort(s, s + q);

    int i = 0;
    int j = -1;
    for (int k = 0; k < (int)q; ++k) {
        int L = s[k].a;
        int R = s[k].b;

        while (j < R) active.Insert(a[++j]);
        while (j > R) active.Erase(a[j--]);
        while (i < L) active.Erase(a[i++]);
        while (i > L) active.Insert(a[--i]);

        ans[s[k].id] = active.Query();
    }

    for (int i = 0; i < q; ++i) {
        cout << ans[i] << endl;
    }

    return 0;
};

```

1.3 sliding window

```

/*
 * Given an array ARR and an integer K, the problem boils down to computing
 *   for each index i: min(ARR[i], ARR[i-1], ..., ARR[i-K+1]).
 * if mx == true, returns the maximum.
 * http://people.cs.uct.ac.za/~ksmith/articles/sliding\_window\_minimum.html
 */

vector<int> sliding_window_minmax(vector<int> & ARR, int K, bool mx) {
    deque<pair<int, int> > window;
    vector<int> ans;
    for (int i = 0; i < ARR.size(); i++) {
        if (mx) {
            while (!window.empty() && window.back().first <= ARR[i])

```

```

        window.pop_back();
    } else {
        while (!window.empty() && window.back().first >= ARR[i])
            window.pop_back();
    }
    window.push_back(make_pair(ARR[i], i));

    while(window.front().second <= i - K)
        window.pop_front();

    ans.push_back(window.front().first);
}
return ans;
}

```

2 Basics

2.1 default code

```

#include<bits/stdc++.h>
using namespace std;

#define endl '\n'
#define pb emplace_back
#define X first
#define Y second
#define SZ(a) ((int)a.size())
#define ALL(x) x.begin(), x.end()
#define CLR(x, y) memset(x, y, sizeof(x))
#define IOS ios::sync_with_stdio(false); cin.tie(nullptr)
#define rep(i, begin, end) for (__typeof(end) i = (begin) - ((begin) > (end)); i != (end) - ((begin) > (end)); i += (begin > end ? -1 : 1))
#define debug(args...) { string _s = #args; replace(_s.begin(), _s.end(), ' ', ','); stringstream _ss(_s); istream_iterator<string> _it(_ss); err(_it, args); }
void err(istream_iterator<string> it) {}
template<typename T, typename... Args>
void err(istream_iterator<string> it, T a, Args... args) {
    cerr << *it << " = " << a << endl;
    err(++it, args...);
}

```

```

using ll = long long;
using vi = vector<int>;
using vii = vector<vi>;
using pii = pair<int, int>;
using pll = pair<ll, ll>;

```

```

const int MOD = 1000000007;
const int INF = INT_MAX;

```

```

signed main () {
    //    IOS;
    return 0;
}

```

3 Data structures

3.1 hash table

```

/*
 * Micro hash table, can be used as a set. Very efficient vs std::set
 */
const int MN = 1001;
struct ht {
    int _s[(MN + 10) >> 5];
    int len;
    void set(int id) {
        len++;
        _s[id >> 5] |= (1LL << (id & 31));
    }
    bool is_set(int id) {
        return _s[id >> 5] & (1LL << (id & 31));
    }
};

```

3.2 heavy light decomposition

```

// Heavy-Light Decomposition
struct TreeDecomposition {

```

```

vector<int> g[MAXN], c[MAXN];
int s[MAXN]; // subtree size
int p[MAXN]; // parent id
int r[MAXN]; // chain root id
int t[MAXN]; // index used in segtree/bit/...
int d[MAXN]; // depth
int ts;

void dfs(int v, int f) {
    p[v] = f;
    s[v] = 1;
    if (f != -1) d[v] = d[f] + 1;
    else d[v] = 0;

    for (int i = 0; i < g[v].size(); ++i) {
        int w = g[v][i];
        if (w != f) {
            dfs(w, v);
            s[v] += s[w];
        }
    }
}

void hld(int v, int f, int k) {
    t[v] = ts++;
    c[k].push_back(v);
    r[v] = k;

    int x = 0, y = -1;
    for (int i = 0; i < g[v].size(); ++i) {
        int w = g[v][i];
        if (w != f) {
            if (s[w] > x) {
                x = s[w];
                y = w;
            }
        }
    }
    if (y != -1) {
        hld(y, v, k);
    }

    for (int i = 0; i < g[v].size(); ++i) {
        int w = g[v][i];

```

```

        if (w != f && w != y) {
            hld(w, v, w);
        }
    }
}

void init(int n) {
    for (int i = 0; i < n; ++i) {
        g[i].clear();
    }
}

void add(int a, int b) {
    g[a].push_back(b);
    g[b].push_back(a);
}

void build() {
    ts = 0;
    dfs(0, -1);
    hld(0, 0, 0);
}
};

```

3.3 persistent array

```

struct node {
    node *l, *r;
    int val;

    node (int x) : l(NULL), r(NULL), val(x) {}
    node () : l(NULL), r(NULL), val(-1) {}
};

typedef node* pnode;

pnode update(pnode cur, int l, int r, int at, int what) {
    pnode ans = new node();

    if (cur != NULL) {
        *ans = *cur;
    }
}

```

```

if (l == r) {
    ans-> val = what;
    return ans;
}
int m = (l + r) >> 1;
if (at <= m) ans-> l = update(ans-> l, l, m, at, what);
else ans-> r = update(ans-> r, m + 1, r, at, what);
return ans;
}

int get(pnode cur, int l, int r, int at) {
    if (cur == NULL) return 0;
    if (l == r) return cur-> val;
    int m = (l + r) >> 1;
    if (at <= m) return get(cur-> l, l, m, at);
    else return get(cur-> r, m + 1, r, at);
}

```

3.4 persistent seg tree

```

/**
 * Important:
 * When using lazy propagation remember to create new
 * versions for each push_down operation!!!
 */
struct node {
    node *l, *r;
    long long acc;
    int flip;
    node (int x) : l(NULL), r(NULL), acc(x), flip(0) {}
    node () : l(NULL), r(NULL), acc(0), flip(0) {}
};

typedef node* pnode;

pnode create(int l, int r) {
    if (l == r) return new node();
    pnode cur = new node();
    int m = (l + r) >> 1;
    cur-> l = create(l, m);
    cur-> r = create(m + 1, r);
    return cur;
}

```

```

}

pnode copy_node(pnode cur) {
    pnode ans = new node();
    *ans = *cur;
    return ans;
}

void push_down(pnode cur, int l, int r) {
    assert(cur);
    if (cur-> flip) {
        int len = r - l + 1;
        cur-> acc = len - cur-> acc;
        if (cur-> l) {
            cur-> l = copy_node(cur-> l);
            cur-> l -> flip ^= 1;
        }
        if (cur-> r) {
            cur-> r = copy_node(cur-> r);
            cur-> r -> flip ^= 1;
        }
        cur-> flip = 0;
    }
}

int get_val(pnode cur) {
    assert(cur);
    assert((cur-> flip) == 0);
    if (cur) return cur-> acc;
    return 0;
}

pnode update(pnode cur, int l, int r, int at, int what) {
    pnode ans = copy_node(cur);
    if (l == r) {
        assert(l == at);
        ans-> acc = what;
        ans-> flip = 0;
        return ans;
    }
    int m = (l + r) >> 1;
    push_down(ans, l, r);
    if (at <= m) ans-> l = update(ans-> l, l, m, at, what);
    else ans-> r = update(ans-> r, m + 1, r, at, what);
}

```

```

push_down(ans->l, l, m);
push_down(ans->r, m + 1, r);
ans->acc = get_val(ans->l) + get_val(ans->r);
return ans;
}

pnode flip(pnode cur, int l, int r, int a, int b) {
    pnode ans = new node();

    if (cur != NULL) {
        *ans = *cur;
    }
    if (l > b || r < a)
        return ans;

    if (l >= a && r <= b) {
        ans->flip ^= 1;
        push_down(ans, l, r);
        return ans;
    }

    int m = (l + r) >> 1;
    ans->l = flip(ans->l, l, m, a, b);
    ans->r = flip(ans->r, m + 1, r, a, b);
    push_down(ans->l, l, m);
    push_down(ans->r, m + 1, r);
    ans->acc = get_val(ans->l) + get_val(ans->r);
    return ans;
}

long long get_all(pnode cur, int l, int r) {
    assert(cur);
    push_down(cur, l, r);
    return cur->acc;
}

void traverse(pnode cur, int l, int r) {
    if (!cur) return;
    cout << l << " - " << r << " : " << (cur->acc) << " " << (cur->flip) << endl;
    traverse(cur->l, l, (l + r) >> 1);
    traverse(cur->r, l + ((l + r) >> 1), r);
}

```

3.5 persistent trie

```

// Persistent binary trie (BST for integers)
const int MD = 31;

struct node_bin {
    node_bin *child[2];
    int val;

    node_bin() : val(0) {
        child[0] = child[1] = NULL;
    }
};

typedef node_bin* pnode_bin;

pnode_bin copy_node(pnode_bin cur) {
    pnode_bin ans = new node_bin();
    if (cur) *ans = *cur;
    return ans;
}

pnode_bin modify(pnode_bin cur, int key, int inc, int id = MD) {
    pnode_bin ans = copy_node(cur);
    ans->val += inc;
    if (id >= 0) {
        int to = (key >> id) & 1;
        ans->child[to] = modify(ans->child[to], key, inc, id - 1);
    }
    return ans;
}

int sum_smaller(pnode_bin cur, int key, int id = MD) {
    if (cur == NULL) return 0;
    if (id < 0) return 0; // strictly smaller
    // if (id == -1) return cur->val; // smaller or equal

    int ans = 0;
    int to = (key >> id) & 1;
    if (to) {

```

```

    if (cur->child[0]) ans += cur->child[0]->val;
    ans += sum_smaller(cur->child[1], key, id - 1);
} else {
    ans = sum_smaller(cur->child[0], key, id - 1);
}
return ans;
}

// Persistent trie for strings.
const int MAX_CHILD = 26;
struct node {
    node *child[MAX_CHILD];
    int val;
    node() : val(-1) {
        for (int i = 0; i < MAX_CHILD; i++) {
            child[i] = NULL;
        }
    }
};

typedef node* pnode;

pnode copy_node(pnode cur) {
    pnode ans = new node();
    if (cur) *ans = *cur;
    return ans;
}

pnode set_val(pnode cur, string &key, int val, int id = 0) {
    pnode ans = copy_node(cur);
    if (id >= int(key.size())) {
        ans->val = val;
    } else {
        int t = key[id] - 'a';
        ans->child[t] = set_val(ans->child[t], key, val, id + 1);
    }
    return ans;
}

pnode get(pnode cur, string &key, int id = 0) {
    if (id >= int(key.size()) || !cur)
        return cur;
    int t = key[id] - 'a';

```

```

    return get(cur->child[t], key, id + 1);
}

```

3.6 segment tree

```

const int MN = 1e5; // limit for array size

```

```

struct seg_tree {
    int n; // array size
    int t[2 * MN];

    seg_tree(int _n) : n(_n) {}

    void clear() {
        memset(t, 0, sizeof t);
    }

    void build() { // build the tree
        for (int i = n - 1; i > 0; --i) t[i] = t[i<<1] + t[i<<1|1];
    }

    // Single modification, range query.
    void modify(int p, int value) { // set value at position p
        for (t[p += n] = value; p > 1; p >>= 1) t[p>>1] = t[p] + t[p^1];
    }

    int query(int l, int r) { // sum on interval [l, r)
        int res = 0;
        for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
            if (l&1) res += t[l++];
            if (r&1) res += t[--r];
        }
        return res;
    }
};

// Range modification, single query.

void modify(int l, int r, int value) {
    for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
        if (l&1) t[l++] += value;
        if (r&1) t[--r] += value;
    }
}

```



```

    }
}

int query(int p) {
    int res = 0;
    for (p += n; p > 0; p >>= 1) res += t[p];
    return res;
}

/**
 * If at some point after modifications we need to inspect all the
 * elements in the array, we can push all the modifications to the
 * leaves using the following code. After that we can just traverse
 * elements starting with index n. This way we reduce the complexity
 * from  $O(n \log(n))$  to  $O(n)$  similarly to using build instead of n
 * modifications.
 */

void push() {
    for (int i = 1; i < n; ++i) {
        t[i<<1] += t[i];
        t[i<<1|1] += t[i];
        t[i] = 0;
    }
}

// Non commutative combiner functions.

void modify(int p, const S& value) {
    for (t[p += n] = value; p >>= 1; ) t[p] = combine(t[p<<1], t[p<<1|1]);
}

S query(int l, int r) {
    S resl, resr;
    for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
        if (l&1) resl = combine(resl, t[l++]);
        if (r&1) resr = combine(t[--r], resr);
    }
    return combine(resl, resr);
}

/**
 * segment tree for intervals

```

```

*
* */

const int MN = 100000 + 100;
struct seg_tree {
    int val[MN * 4 + 4];
    int pending[MN * 4 + 4];

    seg_tree() {
        memset(val, -1, sizeof val);
        memset(pending, -1, sizeof pending);
    }

    void propagate(int node, int b, int e) {
        if (pending[node] != -1) {
            val[node] = pending[node];
            if (b < e) {
                pending[node << 1] = pending[node];
                pending[node << 1 | 1] = pending[node];
            }
            pending[node] = -1;
        }
    }

    void set(int node, int b, int e, int from, int to, int v) {
        if (b > to || e < from) return;

        if (b >= from && e <= to) {
            pending[node] = v;
            propagate(node, b, e);
            return;
        }

        int mid = (b + e) >> 1;

        set(node << 1, b, mid, from, to, v);
        set(node << 1 | 1, mid + 1, e, from, to, v);
    }

    int query(int node, int b, int e, int pos) {
        propagate(node, b, e);

```

```

    if (b == e && b == pos) {
        return val[node];
    }

    int mid = (b + e) >> 1;
    if (pos <= mid)
        return query(node << 1, b, mid, pos);
    return query(node << 1 | 1, mid + 1, e, pos);
}

void set(int from, int to, int v) {
    return set(1, 0, MN - 1, from, to, v);
}

int query(int pos) {
    return query(1, 0, MN - 1, pos);
}
};

```

3.7 sparse table

```

// RMQ.
const int MN = 100000 + 10; // Max number of elements
const int ML = 18; // ceil(log2(MN));

struct st {
    int data[MN];
    int M[MN][ML];
    int n;

    void init(const vector<int> &d) {
        n = d.size();
        for (int i = 0; i < n; ++i)
            data[i] = d[i];

        build();
    }

    void build() {
        for (int i = 0; i < n; ++i)
            M[i][0] = data[i];
        for (int j = 1, p = 2, q = 1; p <= n; ++j, p <<= 1, q <<= 1)

```

```

        for (int i = 0; i + p - 1 < n; ++i)
            M[i][j] = max(M[i][j - 1], M[i + q][j - 1]);
    }
    int query(int b, int e) {
        int k = log2(e - b + 1);
        return max(M[b][k], M[e + 1 - (1 << k)][k]);
    }
};

```

3.8 splay tree

```

using namespace std;
#include<bits/stdc++.h>
#define D(x) cout<<x<<endl;

typedef int T;

struct node{
    node *left, *right, *parent;
    T key;
    node (T k) : key(k), left(0), right(0), parent(0) {}
};

struct splay_tree{

    node *root;

    void right_rot(node *x) {
        node *p = x->parent;
        if (x->parent = p->parent) {
            if (x->parent->left == p) x->parent->left = x;
            if (x->parent->right == p) x->parent->right = x;
        }
        if (p->left = x->right) p->left->parent = p;
        x->right = p;
        p->parent = x;
    }

    void left_rot(node *x) {
        node *p = x->parent;
        if (x->parent = p->parent) {

```

```

    if (x->parent->left == p) x->parent->left = x;
    if (x->parent->right == p) x->parent->right = x;
}
if (p->right = x->left) p->right->parent = p;
x->left = p;
p->parent = x;
}

```

```

void splay(node *x, node *fa = 0) {
    while( x->parent != fa and x->parent != 0) {
        node *p = x->parent;
        if (p->parent == fa)
            if (p->right == x)
                left_rot(x);
            else
                right_rot(x);
        else {
            node *gp = p->parent; //grand parent
            if (gp->left == p)
                if (p->left == x)
                    right_rot(x),right_rot(x);
                else
                    left_rot(x),right_rot(x);
            else
                if (p->left == x)
                    right_rot(x), left_rot(x);
                else
                    left_rot(x), left_rot(x);
        }
    }
    if (fa == 0) root = x;
}

```

```

void insert(T key) {
    node *cur = root;
    node *pcur = 0;
    while (cur) {
        pcur = cur;
        if (key > cur->key) cur = cur->right;
        else cur = cur->left;
    }
    cur = new node(key);
    cur->parent = pcur;
}

```

```

    if (!pcur) root = cur;
    else if (key > pcur->key ) pcur->right = cur;
    else pcur->left = cur;
    splay(cur);
}

node *find(T key) {
    node *cur = root;
    while (cur) {
        if (key > cur->key) cur = cur->right;
        else if(key < cur->key) cur = cur->left;
        else return cur;
    }
    return 0;
}

splay_tree(){ root = 0;};
};

```

3.9 STL order statistics tree II

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

using namespace std;
using namespace __gnu_pbds;

typedef tree<int,null_type,less<int>,rb_tree_tag,
tree_order_statistics_node_update> order_set;

order_set X;

int get(int y) {
    int l=0,r=1e9+1;
    while(l<r) {
        int m=l+((r-l)>>1);
        if(m-X.order_of_key(m+1)<y)
            l=m+1;
        else
            r=m;
    }
}

```

```

    return l;
}

main(){
    ios::sync_with_stdio(0);
    cin.tie(0);
    int n,m;
    cin>>n>>m;

    for(int i=0;i<m;i++) {
        char a;
        int b;
        cin>>a>>b;
        if(a=='L')
            cout<<get(b)<<endl;
        else
            X.insert(get(b));
    }
}

/**
Input
20 7
L 5
D 5
L 4
L 5
D 5
L 4
L 5

Output
5
4
6
4
7
***/

```

3.10 STL order statistics tree

```
#include <ext/pb_ds/assoc_container.hpp>
```

```

#include <ext/pb_ds/tree_policy.hpp>
#include <bits/stdc++.h>

using namespace __gnu_pbds;
using namespace std;

typedef
tree<
    pair<int,int>,
    null_type,
    less<pair<int,int>>,
    rb_tree_tag,
    tree_order_statistics_node_update>
ordered_set;

main()
{
    ios::sync_with_stdio(0);
    cin.tie(0);
    int n;
    int sz=0;
    cin>>n;
    vector<int> ans(n,0);

    ordered_set t;
    int x,y;
    for(int i=0;i<n;i++)
    {
        cin>>x>>y;
        ans[t.order_of_key({x,++sz})]++;
        t.insert({x,sz});
    }

    for(int i=0;i<n;i++)
        cout<<ans[i]<<'\\n';
}

/**
Input
5
1 1
5 1
7 1
3 3

```

5 5

Output

```
1
2
1
1
0
***/
```

3.11 STL Treap

```
#include <ext/rope> //header with rope
using namespace std;
using namespace __gnu_cxx; //namespace with rope and some additional stuff
int main()
{
    ios_base::sync_with_stdio(false);
    rope <int> v; //use as usual STL container
    int n, m;
    cin >> n >> m;
    for(int i = 1; i <= n; ++i)
        v.push_back(i); //initialization
    int l, r;
    for(int i = 0; i < m; ++i)
    {
        cin >> l >> r;
        --l, --r;
        rope <int> cur = v.substr(l, r - l + 1);
        v.erase(l, r - l + 1);
        v.insert(v.mutable_begin(), cur);
    }
    for(rope <int>::iterator it = v.mutable_begin(); it != v.mutable_end();
        ++it)
        cout << *it << " ";
    return 0;
}
```

3.12 trie

```
const int MN = 26; // size of alphabet
const int MS = 100010; // Number of states.

struct trie{
    struct node{
        int c;
        int a[MN];
    };

    node tree[MS];
    int nodes;

    void clear(){
        tree[nodes].c = 0;
        memset(tree[nodes].a, -1, sizeof tree[nodes].a);
        nodes++;
    }

    void init(){
        nodes = 0;
        clear();
    }

    int add(const string &s, bool query = 0){
        int cur_node = 0;
        for(int i = 0; i < s.size(); ++i){
            int id = gid(s[i]);
            if(tree[cur_node].a[id] == -1){
                if(query) return 0;
                tree[cur_node].a[id] = nodes;
                clear();
            }
            cur_node = tree[cur_node].a[id];
        }
        if(!query) tree[cur_node].c++;
        return tree[cur_node].c;
    }
};
```

3.13 wavelet tree

```
// this can be tested in the problem: http://www.spoj.com/problems/ILKQUERY/
```

```
struct wavelet {
    vector<int> values, ori;
    vector<int> map_left, map_right;
    int l, r, m;
    wavelet *left, *right;
    wavelet() : left(NULL), right(NULL) {}
    wavelet(int a, int b, int c) : l(a), r(b), m(c), left(NULL), right(NULL) {}
};
```

```
wavelet *init(vector<int> &data, vector<int> &ind, int lo, int hi) {
    if (lo > hi || (data.size() == 0)) return NULL;
    int mid = ((long long)(lo) + hi) / 2;
    if (lo + 1 == hi) mid = lo; // handle negative values
```

```
wavelet *node = new wavelet(lo, hi, mid);
```

```
vector<int> data_l, data_r, ind_l, ind_r;
int ls = 0, rs = 0;
for (int i = 0; i < int(data.size()); i++) {
    int value = data[i];
    if (value <= mid) {
        data_l.emplace_back(value);
        ind_l.emplace_back(ind[i]);
        ls++;
    } else {
        data_r.emplace_back(value);
        ind_r.emplace_back(ind[i]);
        rs++;
    }
    node->map_left.emplace_back(ls);
    node->map_right.emplace_back(rs);
    node->values.emplace_back(value);
    node->ori.emplace_back(ind[i]);
}
```

```
if (lo < hi) {
    node->left = init(data_l, ind_l, lo, mid);
    node->right = init(data_r, ind_r, mid + 1, hi);
}
return node;
}
```

```
int kth(wavelet *node, int to, int k) {
    // returns the kth element in the sorted version of (a[0], ..., a[to])
    if (node->l == node->r) return node->m;
    int c = node->map_left[to];
    if (k < c)
        return kth(node->left, c - 1, k);
    return kth(node->right, node->map_right[to] - 1, k - c);
}
```

```
int pos_kth_occurrence(wavelet *node, int val, int k) {
    // returns the position on the original array of the kth occurrence of the
    // value "val"
    if (!node) return -1;

    if (node->l == node->r) {
        if (int(node->ori.size()) <= k)
            return -1;
        return node->ori[k];
    }

    if (val <= node->m)
        return pos_kth_occurrence(node->left, val, k);
    return pos_kth_occurrence(node->right, val, k);
}
```

4 DP Optimizations

4.1 convex hull trick

```
/**
 * Problems:
 * http://codeforces.com/problemset/problem/319/C
 * http://codeforces.com/contest/311/problem/B
 * https://csacademy.com/contest/archive/task/squared-ends
 * http://codeforces.com/contest/932/problem/F
 */
```

```
struct line {
    long long m, b;
    line (long long a, long long c) : m(a), b(c) {}
```

```

    long long eval(long long x) {
        return m * x + b;
    }
};

long double inter(line a, line b) {
    long double den = a.m - b.m;
    long double num = b.b - a.b;
    return num / den;
}

/**
 * min m_i * x_j + b_i, for all i.
 *   x_j <= x_{j + 1}
 *   m_i >= m_{j + 1}
 */
struct ordered_cht {
    vector<line> ch;
    int idx; // id of last "best" in query
    ordered_cht() {
        idx = 0;
    }

    void insert_line(long long m, long long b) {
        line cur(m, b);
        // new line's slope is less than all the previous
        while (ch.size() > 1 &&
            (inter(cur, ch[ch.size() - 2]) >= inter(cur, ch[ch.size() - 1]))) {
            // f(x) is better in interval [inter(ch.back(), cur), inf)
            ch.pop_back();
        }

        ch.push_back(cur);
    }

    long long eval(long long x) { // minimum
        // current x is greater than all the previous x,
        // if that is not the case we can make binary search.
        idx = min<int>(idx, ch.size() - 1);
        while (idx + 1 < (int)ch.size() && ch[idx + 1].eval(x) <= ch[idx].eval(x))
            idx++;

        return ch[idx].eval(x);
    }
};

```

```

};

/**
 * Dynammic convex hull trick
 */

typedef long long int64;
typedef long double float128;

const int64 is_query = -(1LL<<62), inf = 1e18;

struct Line {
    int64 m, b;
    mutable function<const Line*> succ;
    bool operator<(const Line& rhs) const {
        if (rhs.b != is_query) return m < rhs.m;
        const Line* s = succ();
        if (!s) return 0;
        int64 x = rhs.m;
        return b - s->b < (s->m - m) * x;
    }
};

struct HullDynamic : public multiset<Line> { // will maintain upper hull for
    maximum
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y->m == z->m && y->b <= z->b;
        }
        auto x = prev(y);
        if (z == end()) return y->m == x->m && y->b <= x->b;
        return (float128)(x->b - y->b)*(z->m - y->m) >= (float128)(y->b -
            z->b)*(y->m - x->m);
    }

    void insert_line(int64 m, int64 b) {
        auto y = insert({ m, b });
        y->succ = [=] { return next(y) == end() ? 0 : &*next(y); };
        if (bad(y)) { erase(y); return; }
        while (next(y) != end() && bad(next(y))) erase(next(y));
        while (y != begin() && bad(prev(y))) erase(prev(y));
    }
};

```

```

int64 eval(int64 x) {
    auto l = *lower_bound((Line) { x, is_query });
    return l.m * x + l.b;
}
};

```

4.2 divide and conquer

```

/*
 * recurrence:
 *   dp[k][i] = min dp[k-1][j] + c[i][j - 1], for all j > i;
 *
 * "comp" computes dp[k][i] for all i in O(n log n) (k is fixed)
 */

void comp(int l, int r, int le, int re) {
    if (l > r) return;

    int mid = (l + r) >> 1;

    int best = max(mid + 1, le);
    dp[cur][mid] = dp[cur ^ 1][best] + cost(mid, best - 1);
    for (int i = best; i <= re; i++) {
        if (dp[cur][mid] > dp[cur ^ 1][i] + cost(mid, i - 1)) {
            best = i;
            dp[cur][mid] = dp[cur ^ 1][i] + cost(mid, i - 1);
        }
    }

    comp(l, mid - 1, le, best);
    comp(mid + 1, r, best, re);
}

```

5 Geometry

6 Graphs

6.1 bridges

```

struct Graph {
    vector<vector<Edge>> g;
    vector<int> vi, low, d, pi, is_b;
    int bridges_computed;

    int ticks, edges;

    Graph(int n, int m) {
        g.assign(n, vector<Edge>());
        is_b.assign(m, 0);
        vi.resize(n);
        low.resize(n);
        d.resize(n);
        pi.resize(n);
        edges = 0;
        bridges_computed = 0;
    }

    void AddEdge(int u, int v) {
        g[u].push_back(Edge(v, edges));
        g[v].push_back(Edge(u, edges));
        edges++;
    }

    void Dfs(int u) {
        vi[u] = true;
        d[u] = low[u] = ticks++;
        for (int i = 0; i < (int)g[u].size(); ++i) {
            int v = g[u][i].to;
            if (v == pi[u]) continue;
            if (!vi[v]) {
                pi[v] = u;
                Dfs(v);
                if (d[u] < low[v]) is_b[g[u][i].id] = true;

                low[u] = min(low[u], low[v]);
            }
        }
    }
}

```



```

    } else {
        low[u] = min(low[u], d[v]);
    }
}
}

// Multiple edges from a to b are not allowed.
// (they could be detected as a bridge).
// If you need to handle this, just count
// how many edges there are from a to b.
void CompBridges() {
    fill(pi.begin(), pi.end(), -1);
    fill(vi.begin(), vi.end(), 0);
    fill(low.begin(), low.end(), 0);
    fill(d.begin(), d.end(), 0);
    ticks = 0;
    for (int i = 0; i < (int)g.size(); ++i)
        if (!vi[i]) Dfs(i);
    bridges_computed = true;
}

map<int, vector<Edge>> BridgesTree() {
    if (!bridges_computed) CompBridges();
    int n = g.size();
    Dsu dsu(g.size());
    for (int i = 0; i < n; i++)
        for (auto e : g[i])
            if (!is_b[e.id]) dsu.Join(i, e.to);

    map<int, vector<Edge>> tree;
    for (int i = 0; i < n; i++)
        for (auto e : g[i])
            if (is_b[e.id])
                tree[dsu.Find(i)].emplace_back(dsu.Find(e.to), e.id);

    return tree;
}
};

```

6.2 directed mst

```
const int inf = 1000000 + 10;
```

```

struct edge {
    int u, v, w;
    edge() {}
    edge(int a, int b, int c) : u(a), v(b), w(c) {}
};

/**
 * Computes the minimum spanning tree for a directed graph
 * - edges : Graph description in the form of list of edges.
 *   each edge is: From node u to node v with cost w
 * - root : Id of the node to start the DMST.
 * - n : Number of nodes in the graph.
 */

int dmst(vector<edge> &edges, int root, int n) {
    int ans = 0;
    int cur_nodes = n;
    while (true) {
        vector<int> lo(cur_nodes, inf), pi(cur_nodes, inf);
        for (int i = 0; i < edges.size(); ++i) {
            int u = edges[i].u, v = edges[i].v, w = edges[i].w;
            if (w < lo[v] and u != v) {
                lo[v] = w;
                pi[v] = u;
            }
        }

        lo[root] = 0;
        for (int i = 0; i < lo.size(); ++i) {
            if (i == root) continue;
            if (lo[i] == inf) return -1;
        }

        int cur_id = 0;
        vector<int> id(cur_nodes, -1), mark(cur_nodes, -1);
        for (int i = 0; i < cur_nodes; ++i) {
            ans += lo[i];
            int u = i;
            while (u != root and id[u] < 0 and mark[u] != i) {
                mark[u] = i;
                u = pi[u];
            }
            if (u != root and id[u] < 0) { // Cycle
                for (int v = pi[u]; v != u; v = pi[v])

```

```

        id[v] = cur_id;
        id[u] = cur_id++;
    }
}

if (cur_id == 0)
    break;

for (int i = 0; i < cur_nodes; ++i)
    if (id[i] < 0) id[i] = cur_id++;

for (int i = 0; i < edges.size(); ++i) {
    int u = edges[i].u, v = edges[i].v, w = edges[i].w;
    edges[i].u = id[u];
    edges[i].v = id[v];
    if (id[u] != id[v])
        edges[i].w -= lo[v];
}
cur_nodes = cur_id;
root = id[root];
}

return ans;
}

```

6.3 karp min mean cycle

```

/**
 * Finds the min mean cycle, if you need the max mean cycle
 * just add all the edges with negative cost and print
 * ans * -1
 *
 * test: uva, 11090 - Going in Cycle!!
 * */

const int MN = 1000;
struct edge{
    int v;
    long long w;
    edge(){ } edge(int v, int w) : v(v), w(w) {}
};

```

```

long long d[MN][MN];
// This is a copy of g because increments the size
// pass as reference if this does not matter.
int karp(vector<vector<edge> > g) {
    int n = g.size();

    g.resize(n + 1); // this is important

    for (int i = 0; i < n; ++i)
        if (!g[i].empty())
            g[n].push_back(edge(i,0));
    ++n;

    for(int i = 0; i < n; ++i)
        fill(d[i], d[i] + (n+1), INT_MAX);

    d[n - 1][0] = 0;

    for (int k = 1; k <= n; ++k) for (int u = 0; u < n; ++u) {
        if (d[u][k - 1] == INT_MAX) continue;
        for (int i = g[u].size() - 1; i >= 0; --i)
            d[g[u][i].v][k] = min(d[g[u][i].v][k], d[u][k - 1] + g[u][i].w);
    }

    bool flag = true;

    for (int i = 0; i < n && flag; ++i)
        if (d[i][n] != INT_MAX)
            flag = false;

    if (flag) {
        return true; // return true if there is no a cycle.
    }

    double ans = 1e15;

    for (int u = 0; u + 1 < n; ++u) {
        if (d[u][n] == INT_MAX) continue;
        double W = -1e15;

        for (int k = 0; k < n; ++k)
            if (d[u][k] != INT_MAX)
                W = max(W, (double)(d[u][n] - d[u][k]) / (n - k));
    }
}

```

```

    ans = min(ans, W);
}

// printf("%.2lf\n", ans);
cout << fixed << setprecision(2) << ans << endl;

return false;
}

```

6.4 konig's theorem

In any bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover

6.5 minimum path cover in DAG

Given a directed acyclic graph $G = (V, E)$, we are to find the minimum number of vertex-disjoint paths to cover each vertex in V .

We can construct a bipartite graph $G' = (V_{out} \cup V_{in}, E')$ from G , where :

$$V_{out} = \{v \in V : v \text{ has positive out-degree}\}$$

$$V_{in} = \{v \in V : v \text{ has positive in-degree}\}$$

$$E' = \{(u, v) \in V_{out} \times V_{in} : (u, v) \in E\}$$

Then it can be shown, via König's theorem, that G' has a matching of size m if and only if there exists $n - m$ vertex-disjoint paths that cover each vertex in G , where n is the number of vertices in G and m is the maximum cardinality bipartite matching in G' .

Therefore, the problem can be solved by finding the maximum cardinality matching in G' instead.

NOTE: If the paths are not necessarily disjoint, find the transitive closure and solve the problem for disjoint paths.

6.6 SCC kosaraju

```

struct SCC {
    vector<vector<int> > g, gr;
    vector<bool> used;

```

```

    vector<int> order, component;
    int total_components;

    SCC(vector<vector<int> > &adj) {
        g = adj;
        int n = g.size();
        gr.resize(n);
        for (int i = 0; i < n; i++)
            for (auto to : g[i])
                gr[to].push_back(i);

        used.assign(n, false);
        for (int i = 0; i < n; i++)
            if (!used[i])
                GenTime(i);

        used.assign(n, false);
        component.assign(n, -1);
        total_components = 0;
        for (int i = n - 1; i >= 0; i--) {
            int v = order[i];
            if (!used[v]) {
                vector<int> cur_component;
                Dfs(cur_component, v);
                for (auto node : cur_component)
                    component[node] = total_components;
                total_components++;
            }
        }
    }

    void GenTime(int node) {
        used[node] = true;
        for (auto to : g[node])
            if (!used[to])
                GenTime(to);
        order.push_back(node);
    }

    void Dfs(vector<int> &cur, int node) {
        used[node] = true;
        cur.push_back(node);
        for (auto to : gr[node])
            if (!used[to])

```

```

        Dfs(cur, to);
    }

    vector<vector<int>> CondensedGraph() {
        vector<vector<int>> ans(total_components);
        for (int i = 0; i < int(g.size()); i++) {
            for (int to : g[i]) {
                int u = component[i], v = component[to];
                if (u != v)
                    ans[u].push_back(v);
            }
        }
        return ans;
    }
};

```

6.7 tarjan scc

```

const int MN = 20002;
struct tarjan_scc {
    int scc[MN], low[MN], d[MN], stacked[MN];
    int ticks, current_scc;
    deque<int> s; // used as stack.

    tarjan_scc() {}

    void init () {
        memset(scc, -1, sizeof scc);
        memset(d, -1, sizeof d);
        memset(stacked, 0, sizeof stacked);
        s.clear();
        ticks = current_scc = 0;
    }

    void compute(vector<vector<int>> &g, int u) {
        d[u] = low[u] = ticks++;
        s.push_back(u);
        stacked[u] = true;
        for (int i = 0; i < g[u].size(); ++i) {
            int v = g[u][i];
            if (d[v] == -1)
                compute(g, v);
        }
    }
};

```

```

        if (stacked[v]) {
            low[u] = min(low[u], low[v]);
        }
    }

    if (d[u] == low[u]) { // root
        int v;
        do {
            v = s.back(); s.pop_back();
            stacked[v] = false;
            scc[v] = current_scc;
        } while (u != v);
        current_scc++;
    }
}
};

```

6.8 two sat (with kosaraju)

```

/**
 * Given a set of clauses (a1 v a2)^(a2 v a3)....
 * this algorithm find a solution to it set of clauses.
 * test: http://lightoj.com/volume\_showproblem.php?problem=1251
 */

#include<bits/stdc++.h>
using namespace std;
#define MAX 100000
#define endl '\n'

vector<int> G[MAX];
vector<int> GT[MAX];
vector<int> Ftime;
vector<vector<int>> > SCC;
bool visited[MAX];
int n;

void dfs1(int n){
    visited[n] = 1;

    for (int i = 0; i < G[n].size(); ++i) {

```

```

    int curr = G[n][i];
    if (visited[curr]) continue;
    dfs1(curr);
}

Ftime.push_back(n);
}

void dfs2(int n, vector<int> &scc) {
    visited[n] = 1;
    scc.push_back(n);

    for (int i = 0; i < GT[n].size(); ++i) {
        int curr = GT[n][i];
        if (visited[curr]) continue;
        dfs2(curr, scc);
    }
}

void kosaraju() {
    memset(visited, 0, sizeof visited);

    for (int i = 0; i < 2 * n; ++i) {
        if (!visited[i]) dfs1(i);
    }

    memset(visited, 0, sizeof visited);
    for (int i = Ftime.size() - 1; i >= 0; i--) {
        if (visited[Ftime[i]]) continue;
        vector<int> _scc;
        dfs2(Ftime[i], _scc);
        SCC.push_back(_scc);
    }
}

/**
 * After having the SCC, we must traverse each scc, if in one SCC are -b y b,
 * there is not a solution.
 * Otherwise we build a solution, making the first "node" that we find truth
 * and its complement false.
 */

```

```

bool two_sat(vector<int> &val) {
    kosaraju();
    for (int i = 0; i < SCC.size(); ++i) {
        vector<bool> tmpvisited(2 * n, false);
        for (int j = 0; j < SCC[i].size(); ++j) {
            if (tmpvisited[SCC[i][j] ^ 1]) return 0;
            if (val[SCC[i][j]] != -1) continue;
            else {
                val[SCC[i][j]] = 0;
                val[SCC[i][j] ^ 1] = 1;
            }
            tmpvisited[SCC[i][j]] = 1;
        }
    }
    return 1;
}

// Example of use

int main() {

    int m, u, v, nc = 0, t; cin >> t;
    // n = "nodes" number, m = clauses number

    while (t--) {
        cin >> m >> n;
        Ftime.clear();
        SCC.clear();
        for (int i = 0; i < 2 * n; ++i) {
            G[i].clear();
            GT[i].clear();
        }

        // (a1 v a2) = (a1 -> a2) = (a2 -> a1)
        for (int i = 0; i < m; ++i) {
            cin >> u >> v;
            int t1 = abs(u) - 1;
            int t2 = abs(v) - 1;
            int p = t1 * 2 + ((u < 0)? 1 : 0);
            int q = t2 * 2 + ((v < 0)? 1 : 0);
            G[p ^ 1].push_back(q);
            G[q ^ 1].push_back(p);
            GT[p].push_back(q ^ 1);
            GT[q].push_back(p ^ 1);
        }
    }
}

```

```

}

vector<int> val(2 * n, -1);
cout << "Case " << ++nc << ": ";
if (two_sat(val)) {
    cout << "Yes" << endl;
    vector<int> sol;
    for (int i = 0; i < 2 * n; ++i)
        if (i % 2 == 0 and val[i] == 1)
            sol.push_back(i / 2 + 1);
    cout << sol.size() ;

    for (int i = 0; i < sol.size(); ++i) {
        cout << " " << sol[i];
    }
    cout << endl;
} else {
    cout << "No" << endl;
}
}
return 0;
}

```

7 Math

7.1 fft

```

/**
 * Fast Fourier Transform.
 * Useful to compute convolutions.
 * computes:
 *   C(f star g)[n] = sum_m(f[m] * g[n - m])
 * for all n.
 * test: icpc live archive, 6886 - Golf Bot
 */

```

```

using namespace std;
#include<bits/stdc++.h>
#define D(x) cout << #x " = " << (x) << endl
#define endl '\n'

```

```

const int MN = 262144 << 1;
int d[MN + 10], d2[MN + 10];

```

```

const double PI = acos(-1.0);

```

```

struct cpx {
    double real, image;
    cpx(double _real, double _image) {
        real = _real;
        image = _image;
    }
    cpx(){}
};

```

```

cpx operator + (const cpx &c1, const cpx &c2) {
    return cpx(c1.real + c2.real, c1.image + c2.image);
}

```

```

cpx operator - (const cpx &c1, const cpx &c2) {
    return cpx(c1.real - c2.real, c1.image - c2.image);
}

```

```

cpx operator * (const cpx &c1, const cpx &c2) {
    return cpx(c1.real*c2.real - c1.image*c2.image, c1.real*c2.image +
        c1.image*c2.real);
}

```

```

int rev(int id, int len) {
    int ret = 0;
    for (int i = 0; (1 << i) < len; i++) {
        ret <<= 1;
        if (id & (1 << i)) ret |= 1;
    }
    return ret;
}

```

```

cpx A[1 << 20];

```

```

void FFT(cpx *a, int len, int DFT) {
    for (int i = 0; i < len; i++)
        A[rev(i, len)] = a[i];
    for (int s = 1; (1 << s) <= len; s++) {

```

```

int m = (1 << s);
cpx wm = cpx(cos( DFT * 2 * PI / m), sin(DFT * 2 * PI / m));
for(int k = 0; k < len; k += m) {
    cpx w = cpx(1, 0);
    for(int j = 0; j < (m >> 1); j++) {
        cpx t = w * A[k + j + (m >> 1)];
        cpx u = A[k + j];
        A[k + j] = u + t;
        A[k + j + (m >> 1)] = u - t;
        w = w * wm;
    }
}
}
if (DFT == -1) for (int i = 0; i < len; i++) A[i].real /= len, A[i].image /=
    len;
for (int i = 0; i < len; i++) a[i] = A[i];
return;
}

```

```

cpx in[1 << 20];

```

```

void solve(int n) {
    memset(d, 0, sizeof d);
    int t;
    for (int i = 0; i < n; ++i) {
        cin >> t;
        d[t] = true;
    }
    int m;
    cin >> m;
    vector<int> q(m);
    for (int i = 0; i < m; ++i)
        cin >> q[i];

    for (int i = 0; i < MN; ++i) {
        if (d[i])
            in[i] = cpx(1, 0);
        else
            in[i] = cpx(0, 0);
    }
}

```

```

FFT(in, MN, 1);
for (int i = 0; i < MN; ++i) {
    in[i] = in[i] * in[i];
}

```

```

}
FFT(in, MN, -1);

int ans = 0;
for (int i = 0; i < q.size(); ++i) {
    if (in[q[i]].real > 0.5 || d[q[i]]) {
        ans++;
    }
}
cout << ans << endl;
}

int main() {
    ios_base::sync_with_stdio(false); cin.tie(NULL);
    int n;
    while (cin >> n)
        solve(n);
    return 0;
}

```

7.2 fibonacci properties

Let A, B and n be integer numbers.

$$k = A - B \quad (1)$$

$$F_A F_B = F_{k+1} F_A^2 + F_k F_A F_{A-1} \quad (2)$$

$$\sum_{i=0}^n F_i^2 = F_{n+1} F_n \quad (3)$$

$ev(n)$ = returns 1 if n is even.

$$\sum_{i=0}^n F_i F_{i+1} = F_{n+1}^2 - ev(n) \quad (4)$$

$$\sum_{i=0}^n F_i F_{i-1} = \sum_{i=0}^{n-1} F_i F_{i+1} \quad (5)$$

7.3 sigma function

the sigma function is defined as:

$$\sigma_x(n) = \sum_{d|n} d^x$$

when $x = 0$ is called the divisor function, that counts the number of positive divisors of n .

Now, we are interested in find

$$\sum_{d|n} \sigma_0(d)$$

if n is written as prime factorization:

$$n = \prod_{i=1}^k P_i^{e_k}$$

we can demonstrate that:

$$\sum_{d|n} \sigma_0(d) = \prod_{i=1}^k g(e_k + 1)$$

where $g(x)$ is the sum of the first x positive numbers:

$$g(x) = (x * (x + 1)) / 2$$

7.4 triangles

Let a , b , c be length of the three sides of a triangle.

$$p = (a + b + c) * 0.5$$

The inradius is defined by:

$$iR = \sqrt{\frac{(p-a)(p-b)(p-c)}{p}}$$

The radius of its circumcircle is given by the formula:

$$cR = \frac{abc}{\sqrt{(a+b+c)(a+b-c)(a+c-b)(b+c-a)}}$$

8 Matrix

9 Misc

10 Number theory

10.1 convolution

```
typedef long long int LL;
typedef pair<LL, LL> PLL;
```

```
inline bool is_pow2(LL x) {
    return (x & (x-1)) == 0;
}
```

```
inline int ceil_log2(LL x) {
    int ans = 0;
    --x;
    while (x != 0) {
        x >>= 1;
        ans++;
    }
    return ans;
}
```

```
/* Returns the convolution of the two given vectors in time proportional to
   n*log(n).
   * The number of roots of unity to use nroots_unity must be set so that the
   product of the first
   * nroots_unity primes of the vector nth_roots_unity is greater than the
   maximum value of the
```



```

* convolution. Never use sizes of vectors bigger than 2^24, if you need to
  change the values of
* the nth roots of unity to appropriate primes for those sizes.
*/
vector<LL> convolve(const vector<LL> &a, const vector<LL> &b, int nroots_unity
    = 2) {
    int N = 1 << ceil_log2(a.size() + b.size());
    vector<LL> ans(N,0), fA(N), fB(N), fC(N);
    LL modulo = 1;
    for (int times = 0; times < nroots_unity; times++) {
        fill(fA.begin(), fA.end(), 0);
        fill(fB.begin(), fB.end(), 0);
        for (int i = 0; i < a.size(); i++) fA[i] = a[i];
        for (int i = 0; i < b.size(); i++) fB[i] = b[i];
        LL prime = nth_roots_unity[times].first;
        LL inv_modulo = mod_inv(modulo % prime, prime);
        LL normalize = mod_inv(N, prime);
        ntfft(fA, 1, nth_roots_unity[times]);
        ntfft(fB, 1, nth_roots_unity[times]);
        for (int i = 0; i < N; i++) fC[i] = (fA[i] * fB[i]) % prime;
        ntfft(fC, -1, nth_roots_unity[times]);
        for (int i = 0; i < N; i++) {
            LL curr = (fC[i] * normalize) % prime;
            LL k = (curr - (ans[i] % prime) + prime) % prime;
            k = (k * inv_modulo) % prime;
            ans[i] += modulo * k;
        }
        modulo *= prime;
    }
    return ans;
}

```

10.2 diophantine equations

```

long long gcd(long long a, long long b, long long &x, long long &y) {
    if (a == 0) {
        x = 0;
        y = 1;
        return b;
    }
    long long x1, y1;
    long long d = gcd(b % a, a, x1, y1);

```

```

    x = y1 - (b / a) * x1;
    y = x1;
    return d;
}

bool find_any_solution(long long a, long long b, long long c, long long &x0,
    long long &y0, long long &g) {
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) {
        return false;
    }

    x0 *= c / g;
    y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}

void shift_solution(long long &x, long long &y, long long a, long long b,
    long long cnt) {
    x += cnt * b;
    y -= cnt * a;
}

long long find_all_solutions(long long a, long long b, long long c,
    long long minx, long long maxx, long long miny,
    long long maxy) {
    long long x, y, g;
    if (!find_any_solution(a, b, c, x, y, g)) return 0;
    a /= g;
    b /= g;

    long long sign_a = a > 0 ? +1 : -1;
    long long sign_b = b > 0 ? +1 : -1;

    shift_solution(x, y, a, b, (minx - x) / b);
    if (x < minx) shift_solution(x, y, a, b, sign_b);
    if (x > maxx) return 0;
    long long lx1 = x;

    shift_solution(x, y, a, b, (maxx - x) / b);
    if (x > maxx) shift_solution(x, y, a, b, -sign_b);
    long long rx1 = x;

```



```

    if (witness(a, n)) {
        return false;
    }
}
return true;
}

```

10.5 number theoretic transform

```

typedef long long int LL;
typedef pair<LL, LL> PLL;

/* The following vector of pairs contains pairs (prime, generator)
 * where the prime has an Nth root of unity for N being a power of two.
 * The generator is a number g s.t g^(p-1)=1 (mod p)
 * but is different from 1 for all smaller powers */
vector<PLL> nth_roots_unity {
    {1224736769,330732430},{1711276033,927759239},{167772161,167489322},
    {469762049,343261969},{754974721,643797295},{1107296257,883865065}};

```

```

PLL ext_euclid(LL a, LL b) {
    if (b == 0)
        return make_pair(1,0);
    pair<LL,LL> rc = ext_euclid(b, a % b);
    return make_pair(rc.second, rc.first - (a / b) * rc.second);
}

```

```

//returns -1 if there is no unique modular inverse
LL mod_inv(LL x, LL modulo) {
    PLL p = ext_euclid(x, modulo);
    if (p.first * x + p.second * modulo != 1)
        return -1;
    return (p.first+modulo) % modulo;
}

```

```

//Number theory fft. The size of a must be a power of 2
void ntfft(vector<LL> &a, int dir, const PLL &root_unity) {
    int n = a.size();
    LL prime = root_unity.first;
    LL basew = mod_pow(root_unity.second, (prime-1) / n, prime);
    if (dir < 0) basew = mod_inv(basew, prime);

```

```

for (int m = n; m >= 2; m >>= 1) {
    int mh = m >> 1;
    LL w = 1;
    for (int i = 0; i < mh; i++) {
        for (int j = i; j < n; j += m) {
            int k = j + mh;
            LL x = (a[j] - a[k] + prime) % prime;
            a[j] = (a[j] + a[k]) % prime;
            a[k] = (w * x) % prime;
        }
        w = (w * basew) % prime;
    }
    basew = (basew * basew) % prime;
}

int i = 0;
for (int j = 1; j < n - 1; j++) {
    for (int k = n >> 1; k > (i ^= k); k >>= 1);
    if (j < i) swap(a[i], a[j]);
}
}

```

10.6 pollard rho factorize

```

long long pollard_rho(long long n) {
    long long x, y, i = 1, k = 2, d;
    x = y = rand() % n;
    while (1) {
        ++i;
        x = mod_mul(x, x, n);
        x += 2;
        if (x >= n) x -= n;
        if (x == y) return 1;
        d = __gcd(abs(x - y), n);
        if (d != 1) return d;
        if (i == k) {
            y = x;
            k *= 2;
        }
    }
    return 1;
}

```

```
// Returns a list with the prime divisors of n
vector<long long> factorize(long long n) {
    vector<long long> ans;
    if (n == 1)
        return ans;
    if (miller_rabin(n)) {
        ans.push_back(n);
    } else {
        long long d = 1;
        while (d == 1)
            d = pollard_rho(n);
        vector<long long> dd = factorize(d);
        ans = factorize(n / d);
        for (int i = 0; i < dd.size(); ++i)
            ans.push_back(dd[i]);
    }
    return ans;
}
```

11 Strings

11.1 Incremental Aho Corasick

```
class IncrementalAhoCorasick {
    static const int Alphabets = 26;
    static const int AlphabetBase = 'a';
    struct Node {
        Node *fail;
        Node *next[Alphabets];
        int sum;
        Node() : fail(NULL), next{}, sum(0) {}
    };

    struct String {
        string str;
        int sign;
    };

public:
    //totalLen = sum of (len + 1)
```

```
void init(int totalLen) {
    nodes.resize(totalLen);
    nNodes = 0;
    strings.clear();
    roots.clear();
    sizes.clear();
    que.resize(totalLen);
}

void insert(const string &str, int sign) {
    strings.push_back(String{ str, sign });
    roots.push_back(nodes.data() + nNodes);
    sizes.push_back(1);
    nNodes += (int)str.size() + 1;
    auto check = [&]() { return sizes.size() > 1 && sizes.end()[-1] ==
        sizes.end()[-2]; };
    if(!check())
        makePMA(strings.end() - 1, strings.end(), roots.back(), que);
    while(check()) {
        int m = sizes.back();
        roots.pop_back();
        sizes.pop_back();
        sizes.back() += m;
        if(!check())
            makePMA(strings.end() - m * 2, strings.end(), roots.back(), que);
    }
}

int match(const string &str) const {
    int res = 0;
    for(const Node *t : roots)
        res += matchPMA(t, str);
    return res;
}

private:
    static void makePMA(vector<String>::const_iterator begin,
        vector<String>::const_iterator end, Node *nodes, vector<Node*> &que) {
        int nNodes = 0;
        Node *root = new(&nNodes[nNodes++]) Node();
        for(auto it = begin; it != end; ++it) {
            Node *t = root;
            for(char c : it->str) {
                Node *&n = t->next[c - AlphabetBase];
```

```

    if(n == nullptr)
        n = new(&nodes[nNodes ++]) Node();
    t = n;
}
t->sum += it->sign;
}
int qt = 0;
for(Node *n : root->next) {
    if(n != nullptr) {
        n->fail = root;
        que[qt ++] = n;
    } else {
        n = root;
    }
}
for(int qh = 0; qh != qt; ++ qh) {
    Node *t = que[qh];
    int a = 0;
    for(Node *n : t->next) {
        if(n != nullptr) {
            que[qt ++] = n;
            Node *r = t->fail;
            while(r->next[a] == nullptr)
                r = r->fail;
            n->fail = r->next[a];
            n->sum += r->next[a]->sum;
        }
        ++ a;
    }
}

static int matchPMA(const Node *t, const string &str) {
    int res = 0;
    for(char c : str) {
        int a = c - AlphabetBase;
        while(t->next[a] == nullptr)
            t = t->fail;
        t = t->next[a];
        res += t->sum;
    }
    return res;
}

```

```

vector<Node> nodes;
int nNodes;
vector<String> strings;
vector<Node*> roots;
vector<int> sizes;
vector<Node*> que;
};

int main() {
    int m;
    while(~scanf("%d", &m)) {
        IncrementalAhoCorasic iac;
        iac.init(600000);
        rep(i, m) {
            int ty;
            char s[300001];
            scanf("%d%s", &ty, s);
            if(ty == 1) {
                iac.insert(s, +1);
            } else if(ty == 2) {
                iac.insert(s, -1);
            } else if(ty == 3) {
                int ans = iac.match(s);
                printf("%d\n", ans);
                fflush(stdout);
            } else {
                abort();
            }
        }
    }
    return 0;
}

```

11.2 minimal string rotation

```

// Lexicographically minimal string rotation
int lmsr() {
    string s;
    cin >> s;
    int n = s.size();
    s += s;
}

```

```

vector<int> f(s.size(), -1);
int k = 0;
for (int j = 1; j < 2 * n; ++j) {
    int i = f[j - k - 1];
    while (i != -1 && s[j] != s[k + i + 1]) {
        if (s[j] < s[k + i + 1]) {
            k = j - i - 1;
            i = f[i];
        }
        if (i == -1 && s[j] != s[k + i + 1]) {
            if (s[j] < s[k + i + 1]) {
                k = j;
            }
            f[j - k] = -1;
        } else {
            f[j - k] = i + 1;
        }
    }
    return k;
}

```

11.3 suffix array

```

/**
 * O(n log^2(n))
 * See http://web.stanford.edu/class/cs97si/suffix-array.pdf for reference
 */

struct entry{
    int a, b, p;
    entry(){ }
    entry(int x, int y, int z): a(x), b(y), p(z){ }
    bool operator < (const entry &o) const {
        return (a == o.a) ? (b == o.b) ? (p < o.p) : (b < o.b) : (a < o.a);
    }
};

struct SuffixArray{
    const int N;
    string s;
    vector<vector<int>> > P;
    vector<entry> M;

```

```

SuffixArray(const string &s) : N(s.length()) , s(s), P(1, vector<int> (N, 0)), M(N) {
    for (int i = 0; i < N; ++i)
        P[0][i] = (int) s[i];

    for (int skip = 1, level = 1; skip < N; skip *= 2, level++) {
        P.push_back(vector<int>(N, 0));
        for (int i = 0; i < N; ++i) {
            int next = ((i + skip) < N) ? P[level - 1][i + skip] : -10000;
            M[i] = entry(P[level - 1][i], next, i);
        }
        sort(M.begin(), M.end());
        for (int i = 0; i < N; ++i)
            P[level][M[i].p] = (i > 0 and M[i].a == M[i - 1].a and M[i].b == M[i - 1].b) ? P[level][M[i - 1].p] : i;
    }
}

vector<int> getSuffixArray(){
    vector<int> &rank = P.back();
    vector<pair<int, int>> > inv(rank.size());
    for (int i = 0; i < rank.size(); ++i)
        inv[i] = make_pair(rank[i], i);
    sort(inv.begin(), inv.end());
    vector<int> sa(rank.size());
    for (int i = 0; i < rank.size(); ++i)
        sa[i] = inv[i].second;
    return sa;
}

// returns the length of the longest common prefix of s[i...L-1] and
// s[j...L-1]
int lcp(int i, int j) {
    int len = 0;
    if (i == j) return N - i;
    for (int k = P.size() - 1; k >= 0 && i < N && j < N; --k) {
        if (P[k][i] == P[k][j]) {
            i += 1 << k;
            j += 1 << k;
            len += 1 << k;
        }
    }
    return len;
}

```

```

}
};

```

11.4 suffix automaton

```

/*
 * Suffix automaton:
 * This implementation was extended to maintain (online) the
 * number of different substrings. This is equivalent to compute
 * the number of paths from the initial state to all the other
 * states.
 *
 * The overall complexity is O(n)
 * can be tested here:
 *   https://www.urionlinejudge.com.br/judge/en/problems/view/1530
 */

struct state {
    int len, link;
    long long num_paths;
    map<int, int> next;
};

const int MN = 200011;
state sa[MN << 1];
int sz, last;
long long tot_paths;

void sa_init() {
    sz = 1;
    last = 0;
    sa[0].len = 0;
    sa[0].link = -1;
    sa[0].next.clear();
    sa[0].num_paths = 1;
    tot_paths = 0;
}

void sa_extend(int c) {
    int cur = sz++;
    sa[cur].len = sa[last].len + 1;
    sa[cur].next.clear();

```

```

    sa[cur].num_paths = 0;
    int p;
    for (p = last; p != -1 && !sa[p].next.count(c); p = sa[p].link) {
        sa[p].next[c] = cur;
        sa[cur].num_paths += sa[p].num_paths;
        tot_paths += sa[p].num_paths;
    }

    if (p == -1) {
        sa[cur].link = 0;
    } else {
        int q = sa[p].next[c];
        if (sa[p].len + 1 == sa[q].len) {
            sa[cur].link = q;
        } else {
            int clone = sz++;
            sa[clone].len = sa[p].len + 1;
            sa[clone].next = sa[q].next;
            sa[clone].num_paths = 0;
            sa[clone].link = sa[q].link;
            for (; p != -1 && sa[p].next[c] == q; p = sa[p].link) {
                sa[p].next[c] = clone;
                sa[q].num_paths -= sa[p].num_paths;
                sa[clone].num_paths += sa[p].num_paths;
            }
            sa[q].link = sa[cur].link = clone;
        }
    }
    last = cur;
}

```

11.5 z algorithm

```

using namespace std;
#include<bits/stdc++.h>

vector<int> compute_z(const string &s){
    int n = s.size();
    vector<int> z(n,0);
    int l,r;
    r = l = 0;
    for(int i = 1; i < n; ++i){

```

```

if(i > r) {
    l = r = i;
    while(r < n and s[r - 1] == s[r])r++;
    z[i] = r - 1;r--;
}else{
    int k = i-1;
    if(z[k] < r - i +1) z[i] = z[k];
    else {
        l = i;
        while(r < n and s[r - 1] == s[r])r++;
        z[i] = r - 1;r--;
    }
}
}
return z;
}

```

```

int main(){

    //string line;cin>>line;
    string line = "alfalfa";
    vector<int> z = compute_z(line);

    for(int i = 0; i < z.size(); ++i ){
        if(i)cout<<" ";
        cout<<z[i];
    }
    cout<<endl;

    // must print "0 0 0 4 0 0 1"

    return 0;
}

```
