

1 Product Introduction

The RF detection device can detect UAV radio signals within the 400 MHz, 800 MHz, 900 MHz, 1.2 GHz, 1.4 GHz, 2.4 GHz, 5.2 GHz, and 5.8 GHz spectrum ranges, with a monitoring radius of 2 km. After being powered on, the device automatically and rapidly detects targets and provides sound and light alarms for UAV detection results.



Figure 1 Handheld RF Detection Device

2 Key Features

The system provides comprehensive UAV radio signal detection and warning functions. Main functions include:

- Passive Detection

Only passively receives signals and does not transmit any electromagnetic signals, with no impact on the environment.

- Full-Band Detection

Supports full-band detection from 400 MHz to 6 GHz.

- Detectable Models

Supports DJI series UAVs, Autel, Hubsan, and other mainstream UAVs on the market, as well as some frequency-hopping FPV drones.

- Target Warning

After a target is detected, vibration, sound, and screen light alarms can be provided.

- Power Detection

Supports full-band scanning power detection.

Basic Specifications	
Frequency Range	Supports 400 MHz-6 GHz custom scanning; default bands: 400 MHz, 800 MHz, 900 MHz, 1.2 GHz, 1.4 GHz, 2.4 GHz, 5.2 GHz, 5.8 GHz
Detection Range	≤ 2 km
Detection Response Time	≤ 3 s
Operating Principle	Spectrum recognition
Direction-Finding Mode	360° detection; no direction finding
Operation Mode	Button operation; supports adjusting sound and screen backlight and viewing UAV detection records
Battery	Battery capacity 1800 mAh; endurance ≤ 3 h Battery capacity 5000 mAh; endurance ≤ 8 h; supports battery replacement
Startup Time	15 s
Device Dimensions	135 mm × 69 mm × 50 mm (L×W×H)
Screen Size	1.77 inches
Antenna Dimensions	14.5 mm (Φ) × 58 mm (L)
Operating Temperature	-20°C to +50°C