

1 Product Overview

The portable RF detection device provides full-band detection capability from 300 MHz to 6000 MHz, enabling UAV detection, identification, positioning, tracking and audible/visual alarms within the detection range. After startup, the device automatically enters working mode. It is portable, mobile and suitable for rapid deployment.



Figure 1 Portable RF Detection Device

2 Key Features

- Passive Detection

It only passively receives signals and does not transmit any electromagnetic signals, causing no environmental impact.

- Multi-Mode Recognition

Supports spectrum recognition and protocol-message decoding recognition.

- Accurate Identification

Accurately identifies the serial number, model, position, speed, altitude, flight track and controller/pilot position of mainstream UAV brands.

- Blacklist and Whitelist

Supports one-click blacklist/whitelist marking. Whitelisted UAVs do not trigger alarms. It recognizes many models, including mainstream brands, Wi-Fi UAVs and DIY UAVs.

- Target Positioning

Accurately locates mainstream UAVs and their controllers/pilots.

- Full-Band Detection

Detects across the full 300 MHz to 6000 MHz frequency band.

- Network Reporting

Supports network connection to a back-end command platform.

- Trajectory Tracking

Supports multi-target trajectory tracking and displays flight tracks in different colors when multiple UAVs are detected simultaneously.

- Mobility

Meets mobile single-operator carry requirements.

Basic Specifications	
Operating Frequency	300MHz~6000MHz
Detection Mode	Passive detection, spectrum analysis, protocol-message decoding
Detection Angle	Horizontal 360°
Detection Radius	5 km
Direction-Finding Accuracy	$\leq 3^\circ$ (RMS)
Detection and Identification Time	$\leq 3s$
Screen Size	13.3 inches
Power Supply	Battery power / adapter power
Protection Rating	IP65
Maximum Power Consumption	80W
Battery Life	5h
Weight	16kg
Operating Temperature	-20℃~+55℃

