

1 Product Overview

The portable counter-UAS shield transmits radio signals to form electromagnetic shielding in a specific area, cutting off UAV control, video-transmission and navigation links so that UAVs cannot enter the controlled area, or are forced to land or return. It can also suppress the L1 band of navigation systems such as GPS, BDS, GLONASS and GALILEO.

The device covers a full range of jamming bands, supports multiple application scenarios, offers long suppression distance and supports external mains power. It supports backpack carry or tripod mounting and is supplied with a dedicated carrying case.



Figure 1 Portable Counter-UAS Shield

2 Key Features

- Multiple Jamming Types

The device can cut off the navigation, remote-control and video-transmission signals of common consumer-grade UAVs, industrial UAVs, model aircraft, FPV drones and DIY modified UAVs, causing UAVs to return or land.

- Long Suppression Distance

Up to 2 km in open environments (typical target: Mavic 2).

- Easy to Carry

It supports backpack carry or tripod mounting and is supplied with a dedicated carrying case.

- Easy Operation

The device is compact, lightweight and easy to deploy quickly. It can be operated by one person.

- Long Standby Time

Built-in high-capacity lithium battery provides long standby and operating time.

Basic Specifications	
Operating Frequency	800 MHz, 900 MHz, 1.5 GHz, 2.4 GHz, 5.8 GHz, 5.1-5.9 GHz
Jamming Distance	≥ 2 km (varies with RF environment and UAV model)
Interception Response Time	≤ 3 s
Total Power Consumption	≤ 400 W
Continuous Operating Time	≥ 30 min (all bands enabled)
Power Supply Method	Built-in high-capacity battery
External Power Interface	External 220 V power adapter; supports charging while in use
Screen Interaction	Built-in touchscreen design

Positioning Function	Supports GPS/BDS and reports longitude and latitude information
Antenna	Built-in
Operating Method	Handheld or tripod-mounted
Cooling Method	Fan cooling
Operating Temperature	-40°C ~ +65°C
Storage Temperature	-40°C ~ +75°C
Power Supply	AC220V
Device Dimensions	270mm*165mm*260mm
Device Weight	≤6.5kg