

1 Product Overview

The portable counter-UAS shield is mainly used to forcibly control flying UAVs or model aircraft by cutting off the communication signal between the UAV and the controller at long distance.

The device can jam GNSS satellite positioning signals, including GPS, BDS, GLONASS and GALILEO, and can also jam common UAV frequency bands, interrupting remote-control, video-transmission and positioning signals so that UAVs land, return or hover, thereby protecting low-altitude airspace in the area.

The device covers full jamming bands, supports multiple scenarios, provides long suppression distance, uses replaceable lithium batteries, supports backpack carry or tripod mounting, and comes with a dedicated carrying case.



Figure 1 Portable Counter-UAS Shield

2 Key Features

- Full Jamming Bands

Covers the frequency bands of mainstream brands and some DIY UAVs.

- Long Suppression Distance

Up to 3 km in open environments (typical target: Mavic 2).

- Easy to Carry

It supports backpack carry or tripod mounting and is supplied with a dedicated carrying case.

- Easy Operation

The device is compact, lightweight and easy to deploy quickly; one person can operate it.

- Long Standby Time

Built-in high-capacity lithium battery is replaceable and provides long standby and operating time.

- No Out-of-Band Interference

Uses digital signal-source technology with low spurious emissions and no out-of-band interference.

Basic Specifications	
Operating Frequency	800 MHz, 900 MHz, 1.2 GHz, 1.4 GHz, 1.5 GHz, 2.4 GHz, 5.8 GHz, 5.1-5.9 GHz
Jamming Distance	≥ 3 km (varies slightly with RF environment and UAV model)
Interception Response Time	≤ 3s
Continuous Operating Time	≥ 40 min (all bands enabled)
Power Supply Method	Lithium battery module; battery can be directly replaced
External Power	Can connect to an external 220 V power adapter

Interface	for direct power supply
Screen Interaction	Built-in touchscreen design
Battery Low-Voltage Alarm	Built-in battery level detection function
Positioning Function	GPS/ BDS
Device Dimensions	340mm*360mm*110mm
Device Weight	≤8.5kg
Operation Mode	Handheld or tripod-mounted
Cooling Method	Fan cooling
Antenna	Built-in
Operating Humidity	≤95%
Operating Temperature	-40℃~+60℃
Storage Temperature	-40℃~+75℃
Power Supply	AC220V