

1 Product Overview

The device uses satellite-navigation simulation technology to transmit navigation spoofing signals, causing UAVs to be driven away or forced to land. By deploying this navigation spoofing device, UAVs outside the controlled area cannot enter, and UAVs inside the controlled area cannot take off.



Figure 1 Fixed Counter-UAS RF Active Defense Device

2 Key Features

- Safe and Reliable

Low transmit power complies with national standards. The explosion-proof design can be applied in petrochemical and energy fields.

- Model Approval

Holds a radio transmitting equipment model approval certificate issued by the Ministry of Industry and Information Technology, complying with relevant national and industry standards and requirements.

- Comprehensive Coverage

Covers GPS, GLONASS, Galileo and other navigation signals, enabling response to multi-mode navigation UAVs.

- Multiple Jamming Effects

Directional drive-away, area denial and area no-fly control.

- Multi-Level Linkage

Can automatically link with low-altitude surveillance radar, RF detection devices and RF jamming devices.

- All-Weather Operation

Supports normal operation at night and in rain, snow, heavy fog and other conditions.

Basic Specifications	
Transmitting Frequency	GPS L1/ GLONASS L1/Galileo E1
Output Power	$\leq 10\text{dBm (mW)}$
Spoofing Response Time	$\leq 10\text{s}$
Synchronization Time Accuracy	$< 1\mu\text{s}$
Effective Operating Distance	Greater than 500 m and less than 1000 m; adjustable distance
Effective Drive-Away Angle	Horizontal 360°
Power Consumption	$\leq 30\text{W}$
Positioning	The device supports GPS positioning and displays longitude and latitude coordinates
Operating Temperature	-40°C ~ +65°C
Enclosure Protection Rating	IP65