

1 Product Introduction

The UAV navigation spoofing device transmits simulated satellite navigation signals to alter the positioning information of a target UAV navigation control system, inducing the target to make an erroneous response, move away from the alert zone in a specified direction, make a misjudgment and land nearby, or be guided to a designated area.

By deploying this device, a hemispherical control area centered on the equipment is formed. UAVs outside the controlled area cannot enter, and the system can counter UAV swarms.

The device can be used independently, or jointly with low-altitude surveillance radar, RF detection devices, and RF jamming devices. It supports mobile, vehicle-mounted, and fixed deployment.



Figure 1 UAV Navigation Spoofing Device

2 Key Features

- Multiple Jamming Modes

Directional drive-away, area denial, area no-fly control, navigation jamming, and fixed-point capture.

- Full Navigation Frequency Coverage

Covers GPS, GLONASS, BDS, GALILEO and other navigation signals, enabling response to UAVs using multi-mode navigation systems.

- Multi-Level Linkage

Can operate jointly with low-altitude surveillance radar, RF detection devices, and RF jamming devices.

- All-Weather Operation

Supports normal operation at night and under rain, snow, dense fog, and other conditions.

Basic Specifications	
Operating Frequency Point	GPS L1/L2, GLO L1/L2, BDS B1/B2 (frequency points customizable)
Spoofing Radius	1-30 km (adjustable range)
Navigation Jamming Radius	1-3 km (adjustable range)
Effective Operating Angle	Horizontal 360°
Spoofing Response Time	≤10s
Device Power Consumption	≤120 W
Device Startup Time	≤30 s
Device Positioning	The device has GNSS positioning and reports longitude and latitude coordinates.
Installation Method	Supports fixed-point, portable, and vehicle-mounted installation.
Power Supply	AC 90 V-260 V or DC 28-36 V
Operating Temperature	-41°C to +70°C
Enclosure Protection Rating	IP66
Dimensions	388mm*388mm*214mm
Weight	≤10 kg

