

1 Product Introduction

This device adopts satellite navigation simulation technology and transmits navigation spoofing signals to drive UAVs away. By deploying this device, UAVs outside the controlled area are prevented from entering the protected area, thereby maintaining low-altitude airspace security for key locations.



Figure 1 Portable Counter-UAS RF Active Defense Device

2 Key Features

- Safe and Reliable

Low transmit power; compliant with national standards.

- Type Approval

Holds a radio transmission equipment type approval certificate issued by the Ministry of Industry and Information Technology, meeting relevant national and industry standards and requirements.

- Comprehensive Coverage

Covers GPS, GLONASS, Galileo, and other navigation signals, enabling response to multi-mode navigation UAVs.

- Multiple Defense Effects

Directional drive-away and area no-fly control.

- Portable Operation

Lightweight and compact; can be used with a support bracket for easy carrying and operation.

Basic Specifications	
Transmit Frequency	GPS L1 / GLONASS L1 / Galileo E1
Output Power	≤10 dBm (mW)
Spoofing Response Time	≤10s
Synchronization Time Accuracy	<1 us
Effective Operating Range	More than 500 m and less than 1,000 m; adjustable range
Effective Drive-Away Angle	Horizontal 360°, vertical ±90°
Power Consumption	≤30 W
Positioning Function	The device supports GPS positioning and reports longitude and latitude information.
Device Weight	≤8 kg
Operating Temperature	-40°C to +65°C
Enclosure Protection Rating	IP65